

## Lab2

43. Copy the rm program to your home directory, naming it myrm, grant set-uid permission, what happens if one of the users starts your ~username/myrm to edit one of your own Files?

```
google-chrome-stable_current_amd64.deb myteam Public Videos
rahmasamy@rahmasamy-Vostro-3520:~$ cp usr/bin/rm /home/rahmasamy/myrm
cp: cannot stat 'usr/bin/rm': No such file or directory
rahmasamy@rahmasamy-Vostro-3520:~$ cp /bin/rm /home/rahmasamy/myrm
rahmasamy@rahmasamy-Vostro-3520:~$ ls -li
total 105220
4325485 drwxr-xr-x 2 rahmasamy rahmasamy 4096 00:58 22 م لي Desktop
4325489 drwxr-xr-x 3 rahmasamy rahmasamy 4096 13:58 8 يون Documents
4325486 drwxr-xr-x 3 rahmasamy rahmasamy 4096 11:38 10 يون Downloads
4333454 -rw-rw-r-- 1 rahmasamy rahmasamy 107630040 01:06 30 م لي google-chrome-st
able_current_amd64.deb
4325490 drwxr-xr-x 2 rahmasamy rahmasamy 4096 00:58 22 م لي Music
4329267 -rw--wx--x 1 rahmasamy rahmasamy 184 10:18 10 يون mycv3
4329242 -rwxr-xr-x 1 rahmasamy rahmasamy 59912 12:48 10 يون myrm
4606685 dr--rwxr-x 2 rahmasamy rahmasamy 4096 09:45 10 يون myteam
4606739 d----- 2 rahmasamy rahmasamy 4096 10:27 10 يون nonperm
4325453 -rw-r--r-- 1 rahmasamy rahmasamy 2955 13:32 8 يون odpasswd
4325491 drwxr-xr-x 3 rahmasamy rahmasamy 4096 22:28 1 يون Pictures
4325488 drwxr-xr-x 2 rahmasamy rahmasamy 4096 00:58 22 م لي Public
4329365 ----- 1 rahmasamy rahmasamy 0 10:27 10 يون rahma
4325382 drwx----- 7 rahmasamy rahmasamy 4096 10:55 6 يون snap
4325487 drwxr-xr-x 2 rahmasamy rahmasamy 4096 00:58 22 م لي Templates
4325492 drwxr-xr-x 2 rahmasamy rahmasamy 4096 00:58 22 م لي Videos
rahmasamy@rahmasamy-Vostro-3520:~$
rahmasamy@rahmasamy-Vostro-3520:~$ chmod u+s ~/myrm
rahmasamy@rahmasamy-Vostro-3520:~$
```

### 44. What is the difference between the set-uid and set-gid?

Uid :Set user editing or executing as owner of the file

set-gid: user to execute the file with the permissions of the file's group.

**45. Create a directory with sticky-bit and write permissions on, grant all the users to access the directory, will any user be able to create and delete files from the directory?**

```
newuser is not in the sudoers file. This incident will be reported.
newuser@rahmasamy-Vostro-3520:~$ mkdir mydir
newuser@rahmasamy-Vostro-3520:~$ chmod +wt mydir
newuser@rahmasamy-Vostro-3520:~$
```

Or

```
newuser@rahmasamy-Vostro-3520:~$ chmod 1777 mydir
newuser@rahmasamy-Vostro-3520:~$
```

```
rahmasamy@rahmasamy-Vostro-3520:~$ ls -l /home/newuser/mydir
total 0
-rw-rw-r-- 1 newuser newuser 0 13:59 10 يـن file1
rahmasamy@rahmasamy-Vostro-3520:~$ whoami
rahmasamy
rahmasamy@rahmasamy-Vostro-3520:~$ rm /home/newuser/mydir/file1
rm: remove write-protected regular empty file '/home/newuser/mydir/file1'? yes
rm: cannot remove '/home/newuser/mydir/file1': Operation not permitted
rahmasamy@rahmasamy-Vostro-3520:~$ ls -l /home/newuser/mydir
total 0
-rw-rw-r-- 1 newuser newuser 0 13:59 10 يـن file1
rahmasamy@rahmasamy-Vostro-3520:~$ sudo chmod o-t /home/newuser/mydir/
[sudo] password for rahmasamy:
rahmasamy@rahmasamy-Vostro-3520:~$ ls -ld /home/newuser/mydir
drwxrwxrwx 2 newuser newuser 4096 13:59 10 يـن /home/newuser/mydir
rahmasamy@rahmasamy-Vostro-3520:~$ rm /home/newuser/mydir/file1
rm: remove write-protected regular empty file '/home/newuser/mydir/file1'? yes
rahmasamy@rahmasamy-Vostro-3520:~$
```

After running these commands, any user will be able to create and delete files within the directory, but they'll only be able to delete their own files due to the sticky bit.

46. Create a directory with set-gid permission, what do you notice when you create a new file or a directory?

```
rahmasamy@rahmasamy-Vostro-3520:~$ mkdir my_dir
rahmasamy@rahmasamy-Vostro-3520:~$ chmod g+s my_dir
rahmasamy@rahmasamy-Vostro-3520:~$ ls -ld my_dir
drwxrwsr-x 2 rahmasamy rahmasamy 4096 13:28 10 يـن my_dir
rahmasamy@rahmasamy-Vostro-3520:~$ touch my_dir/3mo
rahmasamy@rahmasamy-Vostro-3520:~$ ls
3mo      Downloads      my_dir         odpasswd      snap
3momariam google-chrome-stable_current_and64.deb myrm         Pictures      Templates
Desktop  Music          myteam        Public        Videos
Documents mycv3          nonperm       rahma
```

## Lab3

1-List all available shell in your system

```
rahmasamy@rahmasamy-Vostro-3520:~$ cat /etc/shells
# /etc/shells: valid login shells
/bin/sh
/bin/bash
/usr/bin/bash
/bin/rbash
/usr/bin/rbash
/usr/bin/sh
/bin/dash
/usr/bin/dash
```

## 2- print all env in current shell

```
/usr/bin/bash
rahmasamy@rahmasamy-Vostro-3520:~$ printenv
SHELL=/bin/bash
SESSION_MANAGER=local/rahmasamy-Vostro-3520:@/tmp/.ICE-unix/2102,unix/rahmasamy-Vostro-3520:/tmp/.ICE-unix/2102
QT_ACCESSIBILITY=1
COLORTERM=truecolor
XDG_CONFIG_DIRS=/etc/xdg/xdg-ubuntu:/etc/xdg
SSH_AGENT_LAUNCHER=gnome-keyring
XDG_MENU_PREFIX=gnome-
GNOME_DESKTOP_SESSION_ID=this-is-deprecated
LC_ADDRESS=ar_EG.UTF-8
GNOME_SHELL_SESSION_MODE=ubuntu
LC_NAME=ar_EG.UTF-8
SSH_AUTH_SOCK=/run/user/1000/ssh-agent/ssh
```

## 3-man bash

executed, if one is present. Otherwise, it is set to the filename used to invoke **bash**, as given by argument zero.

### Shell Variables

The following variables are set by the shell:

- At shell startup, set to the pathname used to invoke the shell or shell script being executed as passed in the environment or argument list. Subsequently, expands to the last argument to the previous simple command executed in the foreground, after expansion. Also set to the full pathname used to invoke each command executed and placed in the environment exported to that command. When checking mail, this parameter holds the name of the mail file currently being checked.

**BASH** Expands to the full filename used to invoke this instance of **bash**.

#### BASHOPTS

A colon-separated list of enabled shell options. Each word in the list is a valid argument for the **-s** option to the **shopt** builtin command (see **SHELL BUILTIN COMMANDS** below). The options appearing in **BASHOPTS** are those reported as **on** by **shopt**. If this variable is in the environment when **bash** starts up, each shell option in the list will be enabled before reading any startup files. This variable is read-only.

#### BASHPID

Expands to the process ID of the current **bash** process. This differs from **\$\$** under certain circumstances, such as subshells that do not require **bash** to be re-initialized. Assignments to **BASHPID** have no effect. If **BASHPID** is unset, it loses its special properties, even if it is subsequently reset.

#### BASH\_ALIASES

An associative array variable whose members correspond to the internal list of aliases as maintained by the **alias** builtin. Elements added to this array appear in the alias list; however, unsetting array elements currently does not cause aliases to be removed from the alias list. If **BASH\_ALIASES** is unset, it loses its special properties, even if it is subsequently reset.

#### BASH\_ARGC

An array variable whose values are the number of parameters in each frame of the current **bash** execution call stack. The number of parameters to the current subroutine (shell function or script executed with **.** or **source**) is at the top of the stack. When a subroutine is executed, the number of parameters passed is pushed onto **BASH\_ARGC**. The shell sets **BASH\_ARGC** only when in extended debugging mode (see the description of the **extdebug** option to the **shopt** builtin below). Setting **extdebug** after the shell has started to execute a script, or referencing this variable when **extdebug** is not set, may result in inconsistent values.

#### BASH\_ARGV

An array variable containing all of the parameters in the current **bash** execution call stack. The final parameter of the last subroutine call is at the top of the stack; the first parameter of the initial call is at the bottom. When a subroutine is executed, the parameters supplied are pushed onto **BASH\_ARGV**. The shell sets

```

rahmasamy@rahmasamy-Vostro-3520:~$ set
BASH=/bin/bash
BASHOPTS=checkwinsize:cmdhist:complete_fullquote:expand_aliases:extglob:extquote:forc
e_ignore:globasciiranges:histappend:interactive_comments:login_shell:progcomp:prompt
vars:sourcpath
BASH_ALIASES=()
BASH_ARGC=([0]="0")
BASH_ARGV=()
BASH_CMDS=()
BASH_COMPLETION_VERSION=([0]="2" [1]="11")
BASH_LINENO=()
BASH_REMATCH=()
BASH_SOURCE=()
BASH_VERSION=([0]="5" [1]="1" [2]="16" [3]="1" [4]="release" [5]="x86_64-pc-linux-gn
u")
BASH_VERSION='5.1.16(1)-release'
COLUMNS=85
COMP_WORDBREAKS=$' \t\n\"\'>=<;|&(:'
DEFAULT_XDG_CONFIG_DIRS=/etc/xdg
DEFAULT_XDG_DATA_DIRS=/usr/local/share/:/usr/share/
DIRSTACK=()
EUID=1000
SESSION_MANAGER=local/rahmasamy-Vostro-3520:@/tmp/.ICE-unix/2102,unix/rahmasamy-
vostro-3520:/tmp/.ICE-unix/2102

```

5-

```

rahmasamy@rahmasamy-Vostro-3520:~$ var="rahma"
rahmasamy@rahmasamy-Vostro-3520:~$ echo $var
rahma
rahmasamy@rahmasamy-Vostro-3520:~$

```

6-

```

rahmasamy@rahmasamy-Vostro-3520:~$ sh
$ echo $SHELL
/bin/bash
$ echo $0
sh

```

7-

**Bash : .profile**

**Bourne Shell (sh):.profile**

**Korn Shell (ksh): .profile**

**C Shell (csh): .login**

8-

```

rahmasamy@rahmasamy-Vostro-3520:~$ nano ~/.bashrc
rahmasamy@rahmasamy-Vostro-3520:~$ bash
welcome rahma 10-6-2024
rahmasamy@rahmasamy-Vostro-3520:~$
exit
rahmasamy@rahmasamy-Vostro-3520:~$

```

9- when i press / the > shell will start (continous prompt)

```
_=/usr/bin/printf
rahmasamy@rahmasamy-Vostro-3520:~$ echo \
> export PS2=">>>"
export PS2=>>>
rahmasamy@rahmasamy-Vostro-3520:~$
```

10-

```
welcome rahma 10-0-2024
rahmasamy@rahmasamy-Vostro-3520:~$ ls
total 105228
drwxrwxr-x 2 rahmasamy rahmasamy 4096 3 13:23 10 يون mo
-rw-rw-r-- 1 rahmasamy rahmasamy 0 3 13:23 10 يون momariam
drwxr-xr-x 2 rahmasamy rahmasamy 4096 00:58 22 ملي Desktop
drwxr-xr-x 3 rahmasamy rahmasamy 4096 13:58 8 يون Documents
drwxr-xr-x 3 rahmasamy rahmasamy 4096 11:38 10 يون Downloads
-rw-rw-r-- 1 rahmasamy rahmasamy 107630040 01:06 30 ملي google-chrome-stable_current_
amd64.deb
drwxr-xr-x 2 rahmasamy rahmasamy 4096 00:58 22 ملي Music
-rw--wx--x 1 rahmasamy rahmasamy 184 10:18 10 يون mycv3
drwxrwsr-x 2 rahmasamy rahmasamy 4096 13:32 10 يون my_dir
-rwsr-xr-x 1 rahmasamy rahmasamy 59912 12:48 10 يون myrm
dr--rwxr-x 2 rahmasamy rahmasamy 4096 09:45 10 يون myteam
d----- 2 rahmasamy rahmasamy 4096 10:27 10 يون nonperm
-rw-r--r-- 1 rahmasamy rahmasamy 2955 13:32 8 يون odpasswd
drwxr-xr-x 3 rahmasamy rahmasamy 4096 22:28 1 يون Pictures
drwxr-xr-x 2 rahmasamy rahmasamy 4096 00:58 22 ملي Public
----- 1 rahmasamy rahmasamy 0 10:27 10 يون rahma
drwx----- 7 rahmasamy rahmasamy 4096 10:55 6 يون snap
drwxr-xr-x 2 rahmasamy rahmasamy 4096 00:58 22 ملي Templates
drwxr-xr-x 2 rahmasamy rahmasamy 4096 00:58 22 ملي Videos
rahmasamy@rahmasamy-Vostro-3520:~$
```