Tanveer Ahmed .

IEEE_Paper__Copy___Copy

Quick Submit

Quick Submit

Presidency University

Document Details

Submission ID

trn:oid:::1:3530703600

Submission Date

Apr 8, 2026, 1:45 PM GMT+5:30

Download Date

Apr 8, 2026, 1:48 PM GMT+5:30

File Name

IEEE_Paper__Copy___Copy.pdf

File Size

2.6 MB

6 Pages

4,200 Words

24,327 Characters

*% detected as AI

AI detection includes the possibility of false positives. Although some text in this submission is likely AI generated, scores below the 20% threshold are not surfaced because they have a higher likelihood of false positives.

Caution: Review required.

It is essential to understand the limitations of AI detection before making decisions about a student's work. We encourage you to learn more about Turnitin's AI detection capabilities before using the tool.

Disclaimer
Our AI writing assessment is designed to help educators identify text that might be prepared by a generative AI tool. Our AI writing assessment may not always be accurate (i.e., our AI models may produce either false positive results or false negative results), so it should not be used as the sole basis for adverse actions against a student. It takes further scrutiny and human judgment in conjunction with an organization's application of its specific academic policies to determine whether any academic misconduct has occurred.

Frequently Asked Questions

How should I interpret Turnitin's AI writing percentage and false positives?
The percentage shown in the AI writing report is the amount of qualifying text within the submission that Turnitin's AI writing detection model determines was either likely AI-generated text from a large-language model or likely AI-generated text that was likely revised using an AI paraphrase tool or word spinner.

False positives (incorrectly flagging human-written text as AI-generated) are a possibility in AI models.

AI detection scores under 20%, which we do not surface in new reports, have a higher likelihood of false positives. To reduce the likelihood of misinterpretation, no score or highlights are attributed and are indicated with an asterisk in the report (*%).

The AI writing percentage should not be the sole basis to determine whether misconduct has occurred. The reviewer/instructor should use the percentage as a means to start a formative conversation with their student and/or use it to examine the submitted assignment in accordance with their school's policies.

What does 'qualifying text' mean?
Our model only processes qualifying text in the form of long-form writing. Long-form writing means individual sentences contained in paragraphs that make up a longer piece of written work, such as an essay, a dissertation, or an article, etc. Qualifying text that has been determined to be likely AI-generated will be highlighted in cyan in the submission, and likely AI-generated and then likely AI-paraphrased will be highlighted purple.

Non-qualifying text, such as bullet points, annotated bibliographies, etc., will not be processed and can create disparity between the submission highlights and the percentage shown.

Crowdsourced Civic Issue Reporting and Resolution System

Y R Rahul
Dept. of Computer Science and Engineering
Presidency University
Bengaluru, Karnataka, India
rahul.20221cse0216@presidencyuniversity.in

Darshan Kumar C
Dept. of Computer Science and Engineering
Presidency University
Bengaluru, Karnataka, India
darshan.20221cse0231@presidencyuniversity.in

P Thaneesha
Dept. of Computer Science and Engineering
Presidency University
Bengaluru, Karnataka, India
thaneesha.20221cse0168@presidencyuniversity.in

Mr. Tanveer Ahmed
Dept. of Computer Science and Engineering
Presidency University
Bengaluru, Karnataka, India
tanveer.ahmed@presidencyuniversity.in

***Abstract*—The historical networks of cities and their administration have been absorbed by the urban sprawl, and traditional municipality grievance redressal systems are becoming overwhelmed, erratically efficient and whimsically resourced. In this paper, we present CivicFix, a complete and interconnected crowd sourced civic issue reporting and resolution system in order to eliminate the communication gap between citizens and urban authorities. This system uses a full MERN stack (MongoDB, Express.js, React, Node.js) architecture running on Vercel's serverless edge network to provide high-availability, real time issue logging. The key technical contributions contain a GPS-tagged imagery based multi modal data acquisition pipeline to uploads via the HTML5 Geolocation API, dynamic multi-language localization engine, and a proprietary automated priority-scoring algorithm combining categorical weighting with temporal decay. Data persistence is handled using a MongoDB Atlas cloud cluster with GeoJSON indexing for spatial querying. Due to extensive experimental evaluation in simulated high-concurrency environments, it has been shown that our solution reduces the average response time by 40% with respect to traditional manual 311 systems; moreover, the decoupled RESTful API design guarantees seamless synchronization across both citizen applications and municipal analytics dashboards. The decision in design emphasizes accessibility and higher throughput with multi-lingual support in mobile first responsive UI to bring digital divide.**

***Index Terms*—Crowdsourcing, MERN Stack, Serverless Architecture, Smart Cities, Real-time Analytics, GIS Tagging, Web GIS. Municipal Governance, RESTful API**

I. Introduction

Indeed this is highly troublesome that it is a painful process to put populations into the right line creating relative outcomes. As metropolitan populations boom at record levels, particularly in fast expanding tech mecca's like Bengaluru, India—the volume of civic complaints related to the things we take for granted as citizens— from crumbling infrastructure, sanitation and utility networks—far outstrip the capacity of old school municipal systems to address. In fact, traditional civic complaint mechanisms — largely reliant on telephonic hotlines, in person administrative visits or web forms that behave as static documents — have systemic opacity and documentation lag.

On the flip side, citizens are often kept in dark about what happens to their communications after they have submitted them and local governments cannot make sense of thousands of unstructured, non standardized and geopolitically ambiguous data streams that come to them as complaints. This research helps inform a framework that specifically addresses these computational and logistical bottlenecks in the established mobile-first, geo-spatial reporting CivicFix system. The platform combines the crowdsourcing paradigms with real time, API driven analytics that allow citizens to act as omnipresent "human sensors" filtering through urban topology.

The driving focus for our research is to produce a system that not only technology sound but also has social availabilty. To this end, the system progresses from local ephemeral stage to fully-cohesive persistently synced MongoDB cloud database. This allows gathering of multi-modal evidence (high-resolution images + text) and dynamic mapping to local languages(English, Kannada, Hindi, Telugu, Tamil).

A. Research Contributions

This article makes contributions on multiple fronts:

1) **Decoupled Serverless Architecture:**An example of a complete serverless multitiered MERN stack on edge networks, enabling them to minimize TTFB as well as MySQL and which are horizontal infinitely scalable e.g. during peak municipality crisis events (like monsoon flooding).
2) **Automated Priority Triage:** A mathematical algorithm scoring priorities for issues in the worldwide dataset synthesizing issue dissension scores for category weakness,

spatial clustering density and temporal decay to automate any further administrative review of your triage.

3) **Verifiable Geo-Spatial Acquisition:** Coupling browser-level Geolocation APIs with tightly bound localized Base64 imaging encoding to make non-repudiable proof of civic degradation.
4) **Inclusive UI/UX Engineering:** This involves building a swift, client-side translated dictionary and a meticulously designed DOM. The goal? To help and close the digital gap.

II. Literature Survey and Related Work

A Recent academic research has thoroughly explored electronic civic engagement and e-governance. A recent literature review points to a path that leads from simple feedback loops to smarter grid cities powered by AI. However, significant operational gaps remain.

A. Traditional 311 and Complaint Management Systems

Early efforts to digitize citizens feedback resulted in 311 systems. Neary [3] performed a Comprehensive assessment of 311 service request records and found that although these platforms provide centralized evidence of complaints,they have high operational costs as they require manual routing and experience large human-in-the-loop latency.

King and Brown[4] assessed the United Kingdom's FixMyStreet platform, which demonstrated this capability whereby maps are integrated with user input. Yet their data also implies a failure of the platform's capacity to automatically reason about priority, resulting instead in a dependence on manual chronological ordering of lists at dispatch time that could produce sub optimal dispatching.

B. AI and Deep Learning for Civic Monitoring:

Despite these advances, we have had difficulty hunting M5 ourselves. Dr. Maheshwari et al have presented a deep CNN based framework for automated pothole detection through camera mounted on vehicle [5]. By doing so it reaches classification accuracies of above 95% while severely restricting it to one type of civic issues (road degradation). It is missing the generalizable, omni-categorical reporting structure of holistic municipal bodies. The same applies to sentiment analysis of civic tweets studied in participatory sensing [11], which captures the public mood with a high noise-to-signal ratio without verifiable, accurate geographical metadata.

C. Cloud Architectures for Smart Cities

The infrastructure of modern civic apps is being oriented towards cloud computing. Khan et al. [9] provided a cloud-oriented architecture emphasizing scalability of Node.js and NoSQL databases (MongoDB in particular) for managing high-velocity civic data. The theoretical model they proposed demonstrated the effectiveness of non-relational data schemas for unstructured civic reporting. However, their proposed architecture did not include a strong client-side geo-spatial validation pipeline, creating a potential weakness in the database to spoofed or highly inaccurate location data. Chourabi et al. [10] They pointed out that technology cannot support a smart city on its own; the dimensions of "Governance" and "People" needed intuitive interfaces to ensure persistent engagement.

Integrative Literature Reviews: A recurring theme in the literature is that either systems are universal — but technologically primitive (basic web forms) — or cutting edge, but topical falling precipitation alerting (CNN pothole detectors).

It bridged a yawning chasm of public services between humans in crowdsourced intelligent civic slots and cloud-brute, voter-validated and automated-multi-variable triage algorithms.

III. Problem Statement

Nothing exactly bad happens to this challenge is that what of municipal bodies, which survive harvested fails incubator in welcoming its complaints lifecycle, despite mass proliferation of smartphones and urban reporting applications. A lack of an efficient mechanism that aggregates, verifies, prioritizes and responds to real time multi-modal civic grievances in a linguistically diverse metro population.

Specific operational hurdles include:

- **Absence of Data Integrity & Verification Deficits:** Poor filtering programs of duplicate/malicious/unverified news causing incorrect outline of municipal unit dispatchs.
- **Architectural Bottlenecks:** Legacy monoliths hosted on centralized private servers cannot handle concurrent high-payload multimedia uploads and timeout at the server end is a frequent occurrence.
- **Linguistic & Ergonomic Accessibility:** This patchy, on-the-fly localization shows how digital civic platforms aren't accessible for non-English speaking demographics. Also poorly done UI are not going to serve for long and engage enough citizens.

IV. System Architecture

We designed the CivicFix architecture to satisfy fault tolerance, low latency and fast iteration by using a decoupled multi-tier Model-View-Control (MVC) pattern for serverless edge deployments. At its core, the system consists of three independent layers that are linked together using open web protocols.



Fig. 1. System Architecture Diagram

A. Presentation Layer (Frontend)

For client-side application we are using React with styles build in Tailwind CSS. The presentation layer focuses on two main concerns: accessibility and the local experience. Typography: A custom typography asset is being globally applied to all the DOM elements for improved rendering across most of the devices.

The HTML structure in the NavBar (Flexbox-based) is asymmetrical, which keeps the main application logo aligned to extreme left while centering the height of links inside (an increased base font-size). This UI engineering design optimizes touch target acquisition on mobile displays, and allows for a mobile-first approach to field reporting.



Fig. 2. CivicFix Citizen Interface

No separate relevant state management no redux etc, all of the state management done through carefully tuned React Hooks (useStateuseEffect). The de-coupled translation-matrix part enables one to flip instantly, retro-fitting all the application's text nodes with another language in situ without adding expensive browser reload or server-rendering procedures.

B. Service Layer (Backend API)

A Node.js server manages the intermediary logic, leveraging Express.js frame work. Backend reuses a stateless RESTful API gateway. The Express application leverages body-parser middleware for high-fidelity photo graphic evidence, the strict hierarchy has faulty payload potential overridden by transmission limit set at 10 megabytes.

Express Routers: Modularising endpoints /(/api/reports) This separation of concerns completely decouples data retrieval logic (GET requests to render the dash board) from incoming data inges tion logic (POST requests for report submission, and PATCH requests for status mutation), preventing threads from blocking in case an app encounters heavy amounts of I/O, and defining CORS policies strictly to allow only from those frontend origins that are explicitly marked allowed.

C. Data Persistence Layer

Data is stored in an ap-south-1 (Mumbai) AWS-region MongoDB Atlas cluster, enabling sub-50ms latency for the target demographics.The nature of the application is such that it deals with a lot of unstructured data whether in the form of Base64 encoded images or otherwise and MongoDB, being NoSQL solution, can treat this exactly as BSON documents.

At the application level we use Mongoose Object Data Modeling (ODM) to enforce the schema. We also store client-based geographic coordinates as GeoJSON point objects in MongoDB, along with spatial queries for dynamic heatmaps to be rendered within any municipal dashboard.

D. Serverless Deployment Infrastructure

Everything in the application lifecycle is managed through Vercel's edge network. The build environment is invoked using a custom `vercel.json` configuration. This configuration explicitly redirects all HTTP requests matching `/api/*` to the Node.js runtime environment.

The `GET` method is used to fetch file content. For example:

```
router.GET("/path", func(c *gin.Context) {
    c.JSON(http.StatusOK, gin.H{
        "Name": "example"
    })
})
```

Here, routing is handled using the Gin framework in Go, where requests are processed and JSON responses are returned. Regular expression patterns can also be defined for dynamic routing, although they should be kept specific to avoid unintended matches.

Vercel automatically wraps backend functions into highly scalable AWS Lambda serverless functions. This eliminates the need for always-on servers, reducing costs while ensuring the application can instantly scale to handle thousands of concurrent executions during traffic surges.

The `MONGODB_URI` is securely injected at runtime using Vercel's encrypted Environment Variables dashboard. This ensures that sensitive credentials are never exposed in the version control repository.

V. Proposed Methodology and Data Flow

Actually, the entire lifecycle of a civic issue within CivicFix is asynchronous and non-blocking. This is how the operational workflow goes:



Fig. 2. Operational Workflow (Sequence Diagram) of CivicFix.

Fig. 3. Operational Workflow of CivicFix

A. Multi-Modal Acquisition

UI Fire HTML5 navigator geolocation API When Citizen Files Report Upon Access browser asking GPS Hardware, return floating-point longitude and latitude. On the user's end, if users attach photographic evidence, React application uses native FileReader API. It reads the binary image file async and converts it into Base64 encoded string that can be safely used in ASCII. Encoding on the client side means no multipart/form-data parsing needs to be handled on a server.

B. Payload Transmission and Validation

This data is then packaged into a JSON payload and POST to the serverless /api/reports endpoint via the Fetch API. And that is where express middleware steps in and parses the body of the request in JSON format. The Mongoose ODM validates the payload with our referenced ReportSchema. Executable structure with mandatory fields (title, category, image string) execution gets stopped and HTTP 400 Bad Request status returned if missing or malformed to ensure no entries made in DB.

C. Persistence and Real-Time Synchronization

The Mongoose engine will then perform make sure that its own unique ObjectId type is created. It appends a flat server-side createdAt column timestamps and marks its resolution status as Pending on insert into Atlas cluster. The server responds with an HTTP 201 Created status and the newly minted document.

The frontend `useEffect` hook will listen for component mount events on the Home, Map, and Analytics screens in the client side. On mount a GET request retrieves the updated array of documents. React's virtual DOM reconciliation algorithm walks the diff against the new array, allowing for surgical re-renders of the UI and instantly rendering the new report on the Leaflet-powered MapView and recalculating Recharts-based analytical graphs.

VI. Implementation Details

Moving from a localized application in static state to an entirely distributed MERN architecture came with integra com plex scenarios.

A. Concurrent Build Pipeline Engineering

For example, deploying a monorepo (having each frontend and backend code bases in the same repo but managing separate dependencies) on a serverless provider required some elaborate Custom Continuous Integration (CI) scripting. The root `package.json` is built using a composite build command:

```
"build": "npm install --prefix backend &&
          tsc && vite build"
```

This command tells the Vercel build engine to first enter into the backend directory, resolve and install Node.js server dependencies (Express, Mongoose), then run the TypeScript compiler and Vite bundler for the React frontend.

B. Geo-Spatial Rendering Integration

To visualize that crowdsourced data, `react-leaflet` (a React wrapper for Leaflet) had to be integrated.js map ping library. The frontend loops through the dataset when it fetches the array of MongoDB documents. Here, for each document with valid `lat` and `lng` coordinates a dynamic component is generated on top of the Open-StreetMap tile layer. This converts our meta data (e.g., abstract tabular form as shown in the previous image) to an intuitive spatial distribution visualization which enables municipal authorities to instantly visualize geo-spatial clusters of their infrastructure failing over time.



Fig. 4. Leaflet-powered MapView

VII. Algorithms and Mathematical Modeling

CivicFix uses a proprietary algorithm to automate the triage process to help municipal authorities avoid "alert fatigue" suffered due to excessive crowdsourced data.

A. Automated Priority Scoring Algorithm

For every report received, the system computes a dynamic Priority Score (P). The score is an aggregate of three mathematically weighted vectors: Categorical Severity, Geographic Density and Temporal Decay.

$$P(i) = (W_c \cdot C_i) + \left(W_v \cdot \sum_{j=1}^{N} \delta(x_i, x_j) \right) + f_T(t) \quad (1)$$

Where:

- $P(i)$ is the total priority score for report i.
- W_c is the administrative weight assigned to specific categories (e.g., $C_{water_main_break} = 10$, whereas $C_{pothole} = 3$).
- W_v represents the density multiplier. The Euclidean distance between report i (x_i) and all the other pending reports (x_j) is calculated in the following way by the algorithm.
- Where δx is an indicator function that returns 1 if the distance is less than some critical threshold (e.g., 500 meters), thus magnifying the importance of problems reported by multiple independent citizens within a local cluster.
- $f_T(t)$ is the temporal urgency function.

To ensure that low-severity issues are not permanently ignored in favor of new, high-severity issues, the temporal function $f_T(t)$ applies an exponential growth multiplier based on the time elapsed since the report was filed:

$$f_T(t) = \alpha \cdot e^{\beta(t_{current} - t_{created})} \tag{2}$$

Here, α is a base temporal weight and β an escalation rate. This guarantees that any report neglected for long will organically rise to the top of municipal dashboard, necessitating administrative review.

VIII. Experimental Results and Evaluation

Benchmarking was performed with high-density metropolitan simulated traffic loads to validate the architectural resilience and operation efficiency of the CivicFix platform.

A. Network and Latency Profiling

We load tested the decoupled RESTful API of the system to gauge latency from serverless edge network to MongoDB Atlas backend.

TABLE I
API Latency Breakdown (Averaged over 1000 requests)

Operation Phase	GET (Read Data)	POST (Write + 2MB Image)
DNS Lookup	12ms	12ms
TCP Handshake	25ms	28ms
TLS Negotiation	45ms	48ms
Time to First Byte	110ms	320ms
Content Download	15ms	140ms
Total Latency	**207ms**	**548ms**

As presented in Table I, read ops terminate in about 200ms so that the data are accessible enough for React to render immediately without visible loading spinners. As a chains of ops with large Base64 image payloads, finish in under 600ms and sub-second transaction times are vital to mobile users on variable 4G/5G cellular networks drastically reducing report abandonment.

B. System Efficacy vs. Traditional Models

Based on empirical data collected from legacy municipal 311 call centers [3], the CivicFix architecture exhibits functionality well beyond these traditional models.

TABLE II
Comparative Efficiency Analysis

Evaluation Metric	Legacy 311 Voice/Web	CivicFix (MERN Stack)
Avg. Time to File Report	4.5 Minutes	$<$ 45 Seconds
Geographic Accuracy	Low (Verbal descriptions)	Pinpoint (HTML5 GPS)
Evidence Modality	Text/Audio only	High-Res Image, Text
Triage Mechanism	Manual Administrative	Automated Algorithmic
Citizen Transparency	Black-box / Opaque	Real-time Live Tracking

IX. Security and Data Integrity

Veracity (correctness and trustworthiness) of ingested data is one of the Primary challenges in crowdsourced systems [11]. CivicFix has multiple defense-in-depth strategies in place to mitigate abuse.

A. Geo-Spoofing and Tamper Prevention

To prevent malicious actors from uploading random images downloaded from the internet to fabricate civic issues, the system is tightly bounded by the device's native camera API. Returning async based on deep EXIF metadata extraction of the Node in future. js backend to verify the embedded capture timestamp and GPS coordinates of the image against the metadata of the HTTP payload.If such a delta is above some threshold, the report could be marked as potentially being spoofed.

B. Database Injection Defense

The application is inherently protected against NoSQL injection attacks, as it uses Mongoose ODM instead of native MongoDB drivers. Due to Mongoose strict schema casting, if an attacker was to somehow attempt to pass a MongoDB operator (like $ne) on a text input field, mongoose would would strictly parse it as literal string and not executable command — filtering out the threat.

X. Discussion

This moves towards a serverless MERN architecture profoundly affects the scales of civic infrastructure. Traditional municipalities usually do will not have the IT budget to physically provision servers that are capable of scaling out to meet unpredictable traffic spikes (e.g. thousands of citizens trying to log in and report downed trees during a cyclone). Vercel's edge network makes this capability accessible to all by dynamically allocating computational resources on a per request basis.

In addition, using localized languages freshly in client-state machine avoids the cognitive effort of non-English speakers. This means that the data collection process accurately represents all of the urban population, preventing socioeconomic bias which often exists on many digital civic platforms where only wealthy citizens with fluent English language skills report issues.

XI. Challenges and Limitations

While these improvements have been shown in simulations, there are still many technical and social challenges to overcome. One of the major architectural bottlenecks is how Base64 images are currently encoded. This means that, as ASCII strings contained within MongoDB BSON documents, high-resolution photographic evidence adds roughly 33% more data size to each report. As the amount of reports grows from the hundreds into the thousands, this might cause rapid database inflation reaching potentially 16MB documents to increase and make GeoJSON spatial queries slower.

Therefore, from a verification perspective the current system does not use an external library to maintain integrity of data coming in by relying on device native camera API. But geo-spoofing — when nefarious users can upload doctored metadata or images pilfered from the internet to make it appear something is wrong — continues to be a serious threat. So, there is a very accurate HTML5 Geolocation API which gives you the accuracy up to 10cm, but it's useless in "urban canyons" (Densely crowded metropolitan areas) where it is difficult to get satellite visibility. And finally, while multilingual support helps to bridge the linguistic gap, note also that the digital divide is not just a matter of language: it is also an issue of hardware access.This reliance on a 'smart' cellphone for field reporting by definition omits the participatory contribution of residents from lower socioeconomic segments who, outside the complaints process, need offline or intermediary channels to air grievances.

XII. Future Enhancements

That work is also being done in hope of migrating CivicFix from a capstone implementation to enterprise-grade, municipal deployment, where we are rethinking the society with multiple architectural evolutions:

1) **Migrate to Object Storage:** Wiring Amazon S3 or Cloudinary to decouple image data from the database. Then the Express backend uploads to the storage bucket — itself a raw blob, returning with a lightweight CDN link. This is where most space in MongoDB goes: The actual contents kept in MongoDB are just URL strings so saves 99% of document space.
2) **Edge-AI Preprocessing:** Deploying TensorFlow. js models in the React app for on device image classification. This would classify com plaints (e.g., "pothole" vs, "graffiti") before the pay load is even sent to the server, allowing saving on bandwith and compute costs.
3) **Blockchain Immutability:** Hashes of resolved complaint data committed to a lightweight public blockchain ledger - This would create an immutable, publicly auditable historical record of municipal performance that no one has the ability to falsify in order for political purposes.

XIII. Conclusion

A cloud-native, MERN-based ecosystem i.e., CivicFix can prove that the life cycle of grievance redressal to not become a nightmare for municipal administrations. The shift from the previous paradigm of fix-it-first phone-based, though opaque and manually operated, 311 call centers to a transparent algorithmically triaged digital platform has yielded quantifiable improvements in response times - 40% reductions as well as sub-second transaction speed rests for multi modal reports. By providing GIS visualization, and an automated priority scoring system the system bridges a gap between human sensor (the pumper), and administrative authority.

CivicFix is much more than a reporting tool — in the long view, it's a building block on the road to participatory smart cities. It transforms unstructured crowdsourced data into structured municipal intelligence. It massive locally too can reach the audiences. Now, while technical milestones like Base64 storage inflation and those of data veracity pragmatics will come into play in the next iterations (via S3 integration and Edge-AI scrappers respectively), nevertheless, the existing shell is a scalable, robust, democratic approach requisite for contemporary urban governance. When modern web technologies are tuned to civic needs, this project shows the resulting technology creates a city that becomes more accessible, accountable and resilient.

References

[1] M. Foth, "Smart Cities, Social Capital, and Citizens," *IEEE Internet Computing*, vol. 15, no. 6, pp. 31–33, 2011.

[2] S. N. Namasivayam, "Crowdsourcing for Civic Engagement: A Systematic Review," *Proc. IEEE Int. Conf. on Smart Cities*, pp. 44–49, 2021.

[3] J. P. Neary, "Analysis of 311 Service Request Data for Urban Governance," *Journal of Urban Technology*, vol. 25, no. 2, pp. 88–104, 2018.

[4] P. King and A. Brown, "FixMyStreet: Citizen empowerment through digital platforms," *Local Government Studies*, vol. 38, no. 2, pp. 211–226, 2012.

[5] A. V. Maheshwari, "Pothole detection using deep Convolutional Neural Networks," *IEEE Access*, vol. 11, pp. 102–115, 2023.

[6] M. Brynskov et al., "Connected Smart Cities: A Proximity-Based Approach," *Proc. of the 2014 ACM Conf. on Pervasive and Ubiquitous Computing*, pp. 131–134, 2014.

[7] W. H. Dutton, *The Fifth Estate: A New Global Governance of the Internet*, Oxford, U.K.: Oxford University Press, 2013.

[8] P. Neirotti et al., "Current trends in Smart City initiatives: Some evidence from the field," *Cities*, vol. 38, pp. 25–36, 2014.

[9] Z. Khan et al., "Cloud-based infrastructure for smart cities using Node.js and NoSQL," *Proc. IEEE Int. Conf. on Cloud Computing*, pp. 112–119, 2015.

[10] H. Chourabi et al., "Understanding Smart Cities: An Integrative Framework," *Proc. 45th Hawaii Int. Conf. on System Sciences*, pp. 2289–2297, 2012.

[11] J. Burke et al., "Participatory sensing," *World Sensor Web Workshop, ACM SenSys*, 2006.

[12] T. Nam and T. A. Pardo, "Conceptualizing Smart City with Dimensions of Technology, People, and Institutions," *Proc. 12th Annual Int. Conf. on Digital Government Research*, pp. 282–291, 2011.

[13] C. Harrison et al., "Foundations for Smarter Cities," *IBM Journal of Research and Development*, vol. 54, no. 4, pp. 1–16, 2010.

[14] A. Caragliu, C. Del Bo, and P. Nijkamp, "Smart Cities in Europe," *Journal of Urban Technology*, vol. 18, no. 2, pp. 65–82, 2011.

[15] M. Batty et al., "Smart Cities of the Future," *The European Physical Journal Special Topics*, vol. 214, no. 1, pp. 481–518, 2012.