Appendix

This appendix lists all keywords and keyword-like words of the Java language. A “restricted keyword” is a keyword only in a module declaration, and otherwise an identifier. A “restricted identifier” is an identifier unless it is used in certain positions. For example, `var` is always an identifier unless it is used where a type is expected. The symbols `null`, `false`, and `true` are not keywords but literals.

Table : Java Keywords

Keyword	Meaning	Type	See Chapter
`abstract`	An abstract class or method	Keyword	5
`assert`	Used to locate internal program error	Keyword	7
`boolean`	The Boolean type	Keyword	3
`break`	Breaks out of a switch or loop	Keyword	3
`byte`	The 8-bit integer type	Keyword	3
`case`	A case of a `switch`	Keyword	3
`catch`	The clause of a `try` block catching an exception	Keyword	7
`char`	The type for UTF-16 code units	Keyword	3
`class`	Defines a class type	Keyword	4

Keyword	Meaning	Type	See Chapter
`const`	Not used	Keyword	
`continue`	Continues at the end of a loop	Keyword	3
`default`	The default clause of a `switch`, or a default method in an interface	Keyword	3, 6
`do`	The top of a `do`/`while` loop	Keyword	3
`double`	The double-precision floating-number type	Keyword	3
`else`	The `else` clause of an `if` statement	Keyword	3
`enum`	An enumerated type	Keyword	3
`exports`	Exports a package of a module	Restricted keyword	12
`extends`	Defines the parent class of a class, or an upper bound of a wildcard	Keyword	4
`false`	One of the two Boolean values	Literal	3
`final`	A constant, or a class or method that cannot be overridden	Keyword	5
`finally`	The part of a `try` block that is always executed	Keyword	7

Keyword	Meaning	Type	See Chapter
`float`	The single-precision floating-point type	Keyword	3
`for`	A loop type	Keyword	3
`goto`	Not used	Keyword	
`if`	A conditional statement	Keyword	3
`implements`	Defines the interface(s) that a class implements	Keyword	6
`import`	Imports a package	Keyword	4
`instanceof`	Tests if an object is an instance of a class	Keyword	5
`int`	The 32-bit integer type	Keyword	3
`interface`	An abstract type with methods that a class can implement	Keyword	6
`long`	The 64-bit long integer type	Keyword	3
`native`	A method implemented by the host system	Keyword	13 (Vol. II)
`new`	Allocates a new object or array	Keyword	3

Keyword	Meaning	Type	See Chapter
`non-sealed`	A subtype of a sealed type of which arbitrary subtypes may be formed	Keyword	5
`null`	A null reference	Literal	3
`module`	Declares a module	Restricted keyword	12
`open`	Modifies a `module` declaration	Restricted keyword	12
`opens`	Opens a package of a module	Restricted keyword	12
`package`	A package of classes	Keyword	4
`permits`	Introduces a list of permitted subtypes of a sealed type	Restricted identifier	3
`private`	A feature that is accessible only by methods of this class	Keyword	4
`protected`	A feature that is accessible only by methods of this class, its children, and other classes in the same package	Keyword	5
`provides`	Indicates that a module uses a service	Restricted keyword	12
`public`	A feature that is accessible by methods of all classes	Keyword	4

Keyword	Meaning	Type	See Chapter
`record`	Declares a class with a given set of final instance variables	Restricted identifier	4
`return`	Returns from a method	Keyword	3
`sealed`	A type with a controlled set of direct subtypes	Restricted identifier	5
`short`	The 16-bit integer type	Keyword	3
`static`	A feature that is unique to a class or interface, not to instances of a class	Keyword	3, 6
`strictfp`	Use strict rules for floating-point computations (obsolete)	Keyword	2
`super`	The superclass object or constructor, or a lower bound in a wildcard	Keyword	5
`switch`	A selection statement or expression	Keyword	3
`synchronized`	A method or code block that is atomic to a thread	Keyword	12
`this`	The implicit argument of a method, or a constructor of this class	Keyword	4
`throw`	Throws an exception	Keyword	7

Keyword	Meaning	Type	See Chapter
`throws`	The exceptions that a method can throw	Keyword	7
`to`	A part of an `exports` or `opens` declaration	Restricted keyword	12
`transient`	Marks data that should not be persistent	Keyword	2 (Vol. II)
`transitive`	Modifies a `requires` declaration	Restricted keyword	12
`true`	One of the two Boolean values	Literal	3
`try`	A block of code that traps exceptions	Keyword	7
`uses`	Indicates that a module uses a service	Restricted keyword	12
`var`	Declares a variable whose type is inferred	Restricted identifier	3
`void`	Denotes a method that returns no value	Keyword	3
`volatile`	Ensures that a field is coherently accessed by multiple threads	Keyword	12
`when`	Introduces a guard of a pattern	Restricted keyword	5

Keyword	Meaning	Type	See Chapter
`while`	A loop	Keyword	3
`with`	Defines the service class in a `provides` statement	Restricted keyword	12
`yield`	Yields the value of a `switch` expression	Restricted identifier	3
`_` (underscore)	An unnamed variable or pattern (preview)	Keyword	5

Previous chapter
< 12. The Java Platform Module System

Next chapter
Index >