Index

Symbols

`!` operator 3.5.7, 3.5.11
`!=` operator 3.5.7, 3.5.11, 3.8.4
`#` (number sign)
in JavaDoc hyperlinks 4.10.7
`printf` flag 3.7.2
`$` (dollar sign)
delimiter, for inner classes 6.3.3
in variable names 3.4.1
`printf` flag 3.7.2
`%` (percent sign)
arithmetic operator 3.5.1, 3.5.11
conversion character 3.7.2
🍺
🍺 3.3.4
“for each” loop 3.10.3
for array lists 5.3.2
for collections 9.1.3, 10.6.8
for multidimensional arrays 3.10.7
“Has–a” relationship 4.1.4
“Is–a” relationship 4.1.4, 5.1.5, 5.11
“Uses–a” relationship 4.1.4
`&` (ampersand)
bitwise operator 3.5.10, 3.5.11
in bounding types 8.1.5
in reference parameters (C++) 4.5
`&&` operator 3.5.7, 3.5.11
`>` (right angle bracket)
in shell syntax 7.6
relational operator 3.5.7, 3.5.11
`>&` (shell syntax) 7.6
`>>`, `>>>` operators 3.5.10, 3.5.11
`>=` operator 3.5.7, 3.5.11
`<` (left angle bracket)
`printf` flag 3.7.2
relational operator 3.5.7, 3.5.11
`<<` operator 3.5.10, 3.5.11
`<. . .>` (angle brackets) 5.3.1, 8.1.3
`<=` operator 3.5.7, 3.5.11
"""..." 3.6.10
"..." 3.1
`'`, `"` (single, double quote), escape sequences for 3.3.3
`(` (left parenthesis) 3.7.2
`printf` flag 3.7.2
`(. . .)` (parentheses)
empty, in method calls 3.1
for casts 3.5.4, 3.5.11, 5.1.8
for operator hierarchy 3.5.11
`*` (asterisk)
arithmetic operator 3.5.1, 3.5.11
for annotation processors 11.5.1
in class path 4.8.9
in imports 4.8.3
`+` (plus sign)
arithmetic operator 3.5.1, 3.5.3, 3.5.11
for objects and strings 3.6.1, 5.2.5
`printf` flag 3.7.2
`++` operator 3.5.6, 3.5.11
`,` (comma)
operator (C++) 3.5.11
`printf` flag 3.7.2
`-` (minus sign)
arithmetic operator 3.5.1, 3.5.11
`printf` flag 3.7.2
`->` operator
in lambda expressions 6.2.2
in `switch` expressions 3.8.5
`--` operator 3.5.6, 3.5.11
`.` (period) 4.8.9
`...` (ellipsis) 5.5

`.class` extension 3.1
`.exe` extension 4.9.3
`/` (slash) 3.5.1, 3.5.11
`/* . . . */` comments 3.2
`/** . . . */` (Javadoc comment delimiters) 3.2, 4.10, 4.10.1
`//` comments 3.2
`0`, `0b`, `0B`, `0x`, `0X` prefixes (in integers) 3.3.1
`0`, `printf` flag 3.7.2
`2>` (shell syntax) 7.6
`:` (colon)
in assertions 7.4.1
in class path (UNIX) 4.8.9
inheritance token (C++) 5.1.1
`::` (C++ operator) 6.2.5
`;` (semicolon)
in class path (Windows) 4.8.9
in statements 3.1, 3.4.1
`=` operator 3.4.2, 3.5.5
`==` operator 3.5.7, 3.5.11
for class objects 5.10.1
for enumerated types 5.7
for floating-point numbers 3.8.4
for identity hash maps 9.4.7
for strings 3.6.5
wrappers and 5.4
`?` (question mark)
for wildcard types 8.4.1
`?:` operator 3.5.8, 3.5.11
with pattern matching 5.1.9
`@` (at sign) 4.10.1
in `java` command-line options 12.10
`@author`
JavaDoc tag 4.10.8
`@Deprecated` annotation 11.3, 11.3.1
`@deprecated` JavaDoc tag 11.3.1
`@Documented` annotation 11.3, 11.3.2
`@FunctionalInterface` annotation 6.2.9, 11.3, 11.3.1, 11.3.2
`@Generated` annotation 11.3, 11.3.1
`@index`
JavaDoc tag 4.10.8
`@Inherited` annotation 11.3, 11.3.2
`@link`
JavaDoc tag 4.10.7
`@LogEntry` annotation 11.6.1
`@NonNull` annotation 11.1.4
`@Override` annotation 5.2.3, 11.3, 11.3.1
`@param`
JavaDoc tag 4.10.3
`@Persistent` annotation 11.3.2
`@Property` annotation 11.5.3
`@Repeatable` annotation 11.3, 11.3.2
`@RepeatedTest` annotation 11.1.1
`@Retention` annotation 11.2, 11.3
`@return`
JavaDoc tag 4.10.3
`@SafeVarargs` annotation 8.5.4, 11.3, 11.3.1
`@see`
JavaDoc tag 4.10.7
`@Serial` annotation 11.3, 11.3.1
`@since`
JavaDoc tag 4.10.8
`@SuppressWarnings` annotation 3.8.5, 5.3.3, 8.2.4, 8.5.4, 8.5.9, 11.3, 11.3.1, 11.3.2
`@Target` annotation 11.2, 11.3
`@Test` annotation 11.1, 11.2
`@throws`
JavaDoc tag 4.10.3
`@version`
JavaDoc tag 4.10.8, 4.10.10
`[. . .]` (brackets)
empty, in generics 8.1.4
for arrays 3.10.2
`\` (backslash)
escape sequence for 3.3.3
in text blocks 3.6.10
`\b` (backslash character literal) 3.3.3
`\f` (form feed character literal) 3.3.3
`\n` (newline character literal) 3.3.3, 3.6.10
`\r` (carriage return character literal) 3.3.3
`\s` (space character literal) 3.3.3, 3.6.10
`\t` (tab character literal) 3.3.3
`\u` (Unicode character literal) 3.3.3
`^` (caret) 3.5.10, 3.5.11, 6.2.2
`_` (underscore)
as a reserved word **Appendix**
delimiter, in number literals 3.3.1

`{. . .}` (braces)
double, in inner classes 6.3.6
for blocks 3.1, 3.8.1
for enumerated type 3.4.4
in annotation elements 11.1.1
in lambda expressions 6.2.2
`|` operator 3.5.10, 3.5.11
`||` operator 3.5.7, 3.5.11
`~` operator 3.5.10, 3.5.11

A

`A`, `a` conversion characters 3.7.2
Abstract classes 5.6
extending 5.6
interfaces and 6.1.1, 6.1.3
no instantiating for 5.6
object variables of 5.6
`abstract` keyword 5.6, **Appendix**
Abstract methods 5.6
in functional interfaces 6.2.3
`AbstractCollection` class 6.1.5, 9.1.4, 9.3.1
`AbstractProcessor` class 11.5.1
`acceptEither` method 10.7.2
Access modifiers
checking 5.10.4
`final` 3.4.3, 4.3.10, 5.1.7, 6.1.1, 6.3.5, 10.5.10
`private` 4.3.2, 4.8.8, 6.3.1
`protected` 5.1.10, 5.11, 6.1.9
`public` 3.1, 4.3.2, 4.8.8, 6.1.1
`public static final` 6.1.2
redundant 6.1.2
`static` 4.4
`accessFlags` method
of `Constructor` 5.11
of `Field` 5.11
of `Method` 5.11
`AccessibleObject` class 5.11
`canAccess` method 5.11
`setAccessible` method 5.10.5, 5.11
`trySetAccessible` method 5.11
Accessor methods 4.2.3, 4.3.7, 8.4.1
`accumulate` method
of `LongAccumulator` 10.5.11
`accumulateAndGet` method
of `AtomicXxx` 10.5.11
`ActionListener` interface
`actionPerformed` method 6.1.7, 6.2.1, 6.3.1, 6.3.3, 6.3.6
implementing 6.2.3
ActiveX 1.2.5
`add` method
of `ArrayList` 5.3.1, 5.11
of `BigDecimal` 3.10.8
of `BigInteger` 3.10.8
of `BlockingQueue` 10.6.1
of `Collection` 9.1.2, 9.1.4, 9.2, 9.7.6
of `GregorianCalendar` 4.2.3
of `HashSet` 9.3.3
of `List` 9.2, 9.7.6
of `ListIterator` 9.3.1, 9.7.6
of `LongAdder` 10.5.11
of `Queue` 9.7.6
of `Set` 9.2
`addAll` method
of `ArrayList` 8.1.2
of `Collection` 9.1.4, 9.7.6
of `Collections` 9.7.6
of `List` 9.7.6
`addExact` method 3.5.2
`addFirst` method
of `LinkedList` 9.7.6
of `SequencedCollection` 9.7.6
Addition 3.5.1, 3.5.11
for different numeric types 3.5.3
for objects and strings 3.6.1, 5.2.5
`addLast` method
of `LinkedList` 9.7.6
of `SequencedCollection` 9.7.6
`addSuppressed` method 7.2.5
of `Throwable` 7.6
Adobe Flash 1.3
Agent code 11.6.2
Aggregation 4.1.4
Algorithms 4.1
for binary search 9.6.3
for shuffling 9.6.2
for sorting 9.6.2
QuickSort 3.10.6, 9.6.2
simple, in the Java Collections Framework 9.6.4

writing 9.6.7
Algorithms + Data Structures = Programs (Wirth) 4.1
Algorithms in C++ (Sedgewick) 9.6.2
`allOf` method
of `CompletableFuture` 10.7.2
of `EnumSet` 9.7.6
`allProcesses` method 10.8.3
of `ProcessHandle` 10.8.3
Amazon 2.1
`and` method
of `BitSet` 9.7.6
`andNot` method
of `BitSet` 9.7.6
Andreessen, Mark 1.4
Android 1.5, 10.7.3
`AnnotatedConstruct` interface 11.5.2
`AnnotatedElement` interface 11.4, 11.6.2
`getAnnotation` method 11.6.2
`getAnnotation`, `getAnnotationsByType` methods 11.4
`getAnnotations` method 11.6.2
`getAnnotationsByType` method 11.6.2
`getDeclaredAnnotations` method 11.6.2
`isAnnotationPresent` method 11.6.2
`Annotation` interface 11.6.2
`annotationType` method 11.6.2
`equals` method 11.6.2
extending 11.2
`hashCode` method 11.6.2
`toString` method 11.6.2
Annotation interfaces 11.2
Annotation processors 11.5.1
at bytecode level 11.6
Annotations 8.2.4
accessing 11.2
applicability of 11.3
container 11.3.2, 11.4
declaration 11.1.3
documented 11.3, 11.3.2
generating source code with 11.5.3
inherited 11.3, 11.3.2, 11.4
key/value pairs in 11.1.1, 11.2
meta 11.2, 11.3.2
modifiers and 11.1.4
multiple 11.1.2
processing
at runtime 11.4
source-level 11.5
repeatable 11.1.2, 11.3, 11.3.2, 11.4
standard 11.3
type use 11.1.4
`annotationType` method
of `Annotation` 11.6.2
Anonymous arrays 3.10.1
Anonymous inner classes 6.3.6
Antisymmetry rule 6.1.1
`anyOf` method 10.7.2
of `CompletableFuture` 10.7.2
Apache
Commons CSV library 12.8
`append` method
of `StringBuilder` 3.6.9, 3.10.8
`appendCodePoint` method
of `StringBuilder` 3.10.8
Applets 1.3, 1.5
running in a browser 1.3
Application Programming Interfaces (APIs), online
documentation for 3.6.7, 3.6.8
Applications
compiling/launching from the command line 2.2, 3.1
debugging 2.2, 7.1
executing
without a separate Java runtime 12.15
extensible 5.1.6
for different Java releases 4.9.4
localizing 4.2.1, 5.10.3
managing in JVM 7.6
monitoring 11.6.2
responsive 10.7.3
terminating 4.3.5
testing 7.4
`applyToEither` method 10.7.2
Arguments 3.1
string 3.1
variable number of 5.5
`arguments` method
of `ProcessHandle.Info` 10.8.3
Arguments. See Parameters

Arithmetic operators 3.5.1
autoboxing with 5.4
combining with assignment 3.5.5
precedence of 3.5.11
`Array` class 5.10.6, 5.11
`get` method 5.11
`getLength` method 5.10.6, 5.11
`getXxx` method 5.11
`newInstance` method 5.10.6, 5.11
`set` method 5.11
`setXxx` method 5.11
Array lists 9.3.2
anonymous 6.3.6
capacity of 5.3.1
elements of
accessing 5.3.2
adding 5.3.1, 5.3.2
removing 5.3.2
traversing 5.3.2
generic 5.3
raw vs. typed 5.3.3
Array variables 3.10.1
`ArrayBlockingQueue` class 10.6.1, 10.8.3
Constructor 10.8.3
`ArrayDeque` class 9.3.5, 9.7.6
as a concrete collection type 9.3
Constructor 9.7.6
`ArrayIndexOutOfBoundsException` class 3.10.2, 7.1.1, 7.1.2
`ArrayList` class 3.10.3, 5.3, 5.11, 8.1, 9.3.1
`add` method 5.3.1, 5.11
`addAll` method 8.1.2
`ArrayList<E>` method 5.11
as a concrete collection type 9.3
declaring with `var` 5.3.1
`ensureCapacity` method 5.3.1, 5.11
`get` method 5.11
`get`, `set` methods 5.3.2
iterating over 9.1.3
`remove` method 5.3.2, 5.11
`removeIf` method 6.2.4
`set` method 5.11
`size` method 5.11
`size`, `trimToSize` methods 5.3.1
synchronized 10.6.8
`toArray` method 8.5.7
`trimToSize` method 5.11
`ArrayList<E>` method
of `ArrayList` 5.11
Arrays 3.10.2
annotating 11.1.4
anonymous 3.10.1
circular 9.1.1
cloning 6.1.9
converting to collections 9.6.6
copying 3.10.4
on write 10.6.6
creating 3.10.1
elements of
computing in parallel 10.6.7
numbering 3.10.2
remembering types of 5.1.5
removing from the middle 9.3.1
traversing 3.10.3, 3.10.7
equality testing for 5.2.3
generic methods for 5.10.6
hash codes of 5.2.4
in command-line arguments 3.10.5
initializing 3.10.1, 3.10.2
length of 3.10.2
equal to 0 3.10.1
increasing 3.10.4
multidimensional 3.10.7, 3.10.8, 5.2.3, 5.2.5
not of generic types 6.2.6, 8.3, 8.5.3, 8.5.7
of integers 5.2.5
of subclass/superclass references 5.1.5
of wildcard types 8.5.3
out-of-bounds access in 7.1.1
parallel operations on 10.6.7
printing 3.10.7, 5.2.5
ragged 3.10.8
size of 5.3.1, 5.10.6
setting at runtime 5.3
sorting 3.10.6, 6.1.1, 10.6.7
`Arrays` class 3.10.8, 5.11, 6.5.3, 9.7.6
`asList` method 9.7.6
`binarySearch` method 6.5.2, 9.7.6
`copyOf` method 3.10.4, 3.10.8, 5.10.6

`copyOfRange` method 3.10.8
`deepEquals` method 5.2.3
`deepToString` method 3.10.7, 5.2.5
`equals` method 3.10.8, 5.2.3, 5.11
`fill` method 3.10.8
`hashCode` method 5.2.4, 5.11
`parallelXxx` methods 10.6.7
`sort` method 3.10.6, 3.10.8, 6.1.1, 6.2.1, 6.2.3, 6.5.3
`toString` method 3.10.3, 3.10.8
`ArrayStoreException` class 5.1.5, 8.3, 8.5.3, 8.5.4
`arrayType` method 5.10.6
of `Class` 5.11
ASCII 3.3.4
`asIterator` method 9.7.2
of `Enumeration` 9.7.6
`asList` method
of `Arrays` 9.7.6
`assert` keyword 7.4, **Appendix**
Assertions 7.4
checking 11.1.4
checking parameters with 7.4.3
defined 7.4
documenting assumptions with 7.4.4
enabling/disabling 7.4.1, 7.4.2
Assignment 3.4.2, 3.5.5
Asynchronous computations 10.7
Asynchronous methods 10.4.1
`AsyncTask` class (Android) 10.7.3
`atan`, `atan2` methods
of `Math` 3.5.2
Atomic operations 10.5.11
client-side locking for 10.5.7
in concurrent hash maps 10.6.3
performance of 10.5.11
`Atomic`*`Type`* classes 10.5.11
@author 4.10.10
Autoboxing 5.4
`AutoCloseable` interface 7.2.5
`close` method 7.2.5
`await` method 10.2.3
of `Condition` 10.5.4, 10.8.3
`awaitTermination` method
of `ExecutorService` 10.8.3
Azul 2.1

B

`B`, `b` conversion characters 3.7.2
Base classes. See Superclasses
`BASE64Encoder` class 12.5
Basic multilingual planes 3.3.4
Batch files 4.8.10
`Beans` class 4.9.1
`beep` method
of `Toolkit` 6.5.3
`BiConsumer` interface 6.2.9
`BiFunction` interface 6.2.4, 6.2.9
BIG-5 3.3.4
`BigDecimal` class 3.9, 3.10.8
`add` method 3.10.8
`compareTo` method 3.10.8
Constructor 3.10.8
`divide` method 3.10.8
`multiply` method 3.10.8
`subtract` method 3.10.8
`BigInteger` class 3.9, 3.10.8
`add` method 3.10.8
`compareTo` method 3.10.8
`divide` method 3.10.8
`mod` method 3.10.8
`multiply` method 3.10.8
`pow` method 3.10.8
`sqrt` method 3.10.8
`subtract` method 3.10.8
`valueOf` method 3.9, 3.10.8
Binary search 9.6.3
`BinaryOperator` interface 6.2.9
`binarySearch` method
of `Arrays` 6.5.2, 9.7.6
of `Collections` 9.6.3, 9.7.6
`BiPredicate` interface 6.2.9
Bit masks 3.5.10
Bit sets 9.7.6
`BitSet` class 9.1, 9.7.6
`and` method 9.7.6
`andNot` method 9.7.6
`cardinality` method 9.7.6
`clear` method 9.7.6

Constructor 9.7.6
`get` method 9.7.6
`length` method 9.7.6
`or` method 9.7.6
`set` method 9.7.6
`size` method 9.7.6
`stream` method 9.7.6
`xor` method 9.7.6
Bitwise operators 3.5.10, 3.5.11
Blank lines, printing 3.1
Blocking queues 10.6.1
`BlockingDeque` interface 10.8.3
`offerFirst` method 10.8.3
`offerLast` method 10.8.3
`pollFirst` method 10.8.3
`pollLast` method 10.8.3
`putFirst` method 10.8.3
`putLast` method 10.8.3
`takeFirst` method 10.8.3
`takeLast` method 10.8.3
`BlockingQueue` interface 10.8.3
`add`, `element`, `peek`, `remove` methods 10.6.1
`offer` method 10.8.3
`offer`, `poll`, `put`, `take` methods 10.6.1
`poll` method 10.8.3
`put` method 10.8.3
`take` method 10.8.3
Blocks 3.1, 3.8.1
nested 3.8.1
synchronized 10.5.7
`Boolean` class 5.11, 9.7.6
converting from `boolean` 5.4
`getBoolean` method 9.7.6
`hashCode` method 5.11
`boolean` operators 3.5.7, 3.5.11
`boolean` type 3.3.5, **Appendix**
default initialization of 4.6.2
formatting output for 3.7.2
Bounded collections 9.1.1
Brace style
Kernighan and Ritchie 3.1
`break` keyword 3.8.5, 3.8.6, **Appendix**
labeled/unlabeled 3.8.6
not allowed in `switch` expressions 3.8.5
Bridge methods 8.2.3, 8.5.10
Buckets (of hash tables) 9.3.3
Bulk operations 9.6.5
`Byte` class 5.11
converting from `byte` 5.4
`hashCode` method 5.11
`toUnsignedInt` method 3.3.1
`byte` type 3.3.1, **Appendix**
Bytecode files 3.1
Bytecodes
engineering 11.6
at load time 11.6.2

C

C
`assert` macro in 7.4.1
function pointers in 5.10.7
integer types in 1.2.7, 3.3.1
C# 1.2.11
polymorphism in 5.1.7
useful features of 1.4
C++
`#include` in 4.8.3
`>>` operator in 3.5.10
`,` (comma) operator in 3.5.11
algorithms in 9.6.1
arrays in 3.10.4, 3.10.8
`boolean` values in 3.3.5
classes in 6.3
dynamic binding in 5.1.3
dynamic casts in 5.1.8
exceptions in 7.1.1, 7.1.2, 7.1.3
`for` loop in 3.8.4
function pointers in 5.10.7
inheritance in 5.1.1, 5.1.4, 6.1.3
integer types in 1.2.7, 3.3.1
iterators as parameters in 9.7.2
methods in
accessor 4.2.3
default 6.1.6
destructor 4.6.3
`namespace` directive in 4.8.3
`NULL` pointer in 4.2.1
object pointers in 4.2.1
operator overloading in 3.9

passing parameters in 4.5
performance of, compared to Java 9.7.6
polymorphism in 5.1.7
`protected` modifier in 5.1.10
pure virtual functions (`= 0`) in 5.6
range-based `for` loop in 3.8
references in 4.2.1
Standard Template Library in 9.1, 9.1.3
syntax of 1.2.1
templates in 1.4, 8.2.1
type parameters in 8.1.4
`using` directive in 4.8.3
variables in
redefining in nested blocks 3.8.1
`vector` template in 5.3.1
`C`, `c` conversion characters 3.7.2
`CachedRowSetImpl` class 12.5
`Calendar` class 4.2.2
`get/setTime` methods 5.1.7
Calendars
displaying 4.2.3
vs. time measurement 4.2.2
Call by reference 4.5
Call by value 4.5
`call` method
of `Callable` 10.8.3
of `ScopedValue.Carrier` 10.4.5
`Callable` interface 10.4.3, 10.8.3
`call` method 10.4.1, 10.8.3
wrapper for 10.4.1
Callables 10.4.1
Callbacks 6.1.7
CamelCase 3.1
`canAccess` method
of `AccessibleObject` 5.11
Cancel 10.4.2
`cancel` method 10.4.1
of `Future` 10.7.3, 10.8.3
`CancellationException` class 10.7.3
`cardinality` method
of `BitSet` 9.7.6
Carriage return character 3.3.3
`case` keyword 3.5.9, 3.8.5, Appendix
`cast` method
of `Class` 8.6.1, 8.6.4
Casts 3.5.4, 5.1.8
annotating 11.1.4
bad 7.1.1
checking before attempting 5.1.8
`catch` keyword 7.2, Appendix
annotating parameters of 11.1.3
`ceiling` method
of `NavigableSet` 9.7.6
`char` type 3.3.3, Appendix
`Character` class 5.11
converting from `char` 5.4
`hashCode` method 5.11
`isJavaIdentifier`Xxx methods 3.4.1
Characters
escape sequences for 3.3.3
exotic 3.3.4
formatting output for 3.7.2
`charAt` method 3.6.3
of `String` 3.10.8
`CharSequence` interface 3.6.7, 6.1.3
Checked exceptions 5.10.1, 5.10.2
applicability of 7.3
declaring 7.1.2
suppressing with generics 8.5.9
Checked views 9.5.6
`checkedCollection` method
of `Collections` 9.7.6
`checkedList` method
of `Collections` 9.7.6
`checkedMap` method
of `Collections` 9.7.6
`checkedNavigableMap` method
of `Collections` 9.7.6
`checkedNavigableSet` method
of `Collections` 9.7.6
`checkedQueue` method
of `Collections` 9.7.6
`checkedSet` method
of `Collections` 9.7.6
`checkedSortedMap` method
of `Collections` 9.7.6
`checkedSortedSet` method
of `Collections` 9.7.6

Checker Framework 11.1.4
checkFromIndexSize, checkFromToIndex, checkIndex methods
of Objects 7.3
Child classes. See Subclasses
children method
of ProcessHandle 10.8.3
ChronoLocalDate 8.4.2
Church, Alonzo 6.2.2
Circular arrays 9.1.1
Clark, Jim 1.4
Class class 5.10.1, 5.11, 8.6.4
arrayType method 5.10.6, 5.11
cast method 8.6.1, 8.6.4
forName method 5.10.1, 5.11
getClass method 5.10.1
getComponentType method 5.10.6, 5.11
getConstructor method 5.11, 8.6.4
getConstructors method 5.10.4, 5.11
getDeclaredConstructor method 8.6.4
getDeclaredConstructors method 5.10.4, 5.11
getDeclaredField method 5.11
getDeclaredFields method 5.11
getDeclaredMethods method 5.10.4, 5.10.7, 5.11
getEnumConstants method 8.6.1, 8.6.4
getField method 5.11
getFields method 5.11
getFields, getDeclaredFields methods 5.10.4, 5.10.5
getGenericInterfaces method 8.6.4
getGenericSuperclass method 8.6.4
getImage method 5.10.3
getMethod method 5.10.7
getMethods method 5.10.4, 5.11
getName method 5.10.1, 5.11
getPackageName method 5.11
getRecordComponents method 5.11
getResource method 5.11
getResource, getResourceAsStream methods 5.10.3
getResourceAsStream method 5.11, 12.7
getSuperclass method 5.11, 8.6.4
getTypeParameters method 8.6.4
isArray method 5.11
isEnum method 5.11
isInterface method 5.11
isRecord method 5.11
newInstance method 5.10.1, 8.6.1
Class constants 3.4.3
Class declarations
annotations in 11.1.3, 11.3.2
Class diagrams 4.1.4
Class file API 11.6
Class files 4.8.6, 4.8.9
compiling 3.1
format of 11.6
locating 4.8.9
modifying 11.6.1
transformers for 11.6.2
class keyword Appendix
implicitly declared 4.4.5
Class literals
no annotations for 11.1.4
Class loaders 6.5.2, 7.4.1, 7.4.2
Class path 4.8.9, 4.8.10
Class wins rule 6.1.6
Class<T> parameters 8.6.2
ClassCastException class 5.1.8, 5.10.6, 6.1.1, 8.3, 8.5.7, 8.6.1, 9.5.6
Classes 4.1.1, 5.1
abstract 5.6, 6.1.1, 6.1.3
access privileges for 4.3.8
adding to packages 4.8.6
capabilities of 5.10.4
companion 6.1.4, 6.1.5
constructors for 4.3.2
defining 4.3
at runtime 6.5.1
deprecated 11.3, 11.3.1
designing 4.1.3, 4.11
documentation comments for 4.10.1, 4.10.7
encapsulation of 4.1.1, 4.1.2, 4.3.7, 12
extending 4.1.1
final 5.1.7, 6.1.9
generic 5.3, 5.3.1, 8.1.3, 8.3, 8.5.6, 8.6.1, 8.6.3
immutable 4.3.10, 4.7.1, 5.11

implementing multiple interfaces 6.1.2, 6.1.3
importing 4.8.3
inner 6.3
instances of 4.1.1, 4.2.1
legacy 4.7.1
loading 7.6
names of 4.8.2, 4.11
full package 4.8.3
nested 11.1.4
number of basic types in 4.11
objects of, at runtime 5.10.5
package scope of 4.8.8
parameters in 4.3.6
predefined 4.2
private methods in 4.3.9
protected 5.1.10
public 4.8.3, 4.10.1
relationships between 4.1.4
sealed 5.8
sharing, among programs 4.8.9
wrapper 5.4
`ClassLoader` class 7.6
`clearAssertionStatus` method 7.6
`setClassAssertionStatus` method 7.6
`setDefaultAssertionStatus` method 7.6
`setPackageAssertionStatus` method 7.6
CLASSPATH 4.8.10
`clear` method
of `BitSet` 9.7.6
of `Collection` 9.1.4, 9.7.6
`clearAssertionStatus` method
of `ClassLoader` 7.6
Client-side locking 10.5.7
`clone` method
of array types 6.1.9
of `Object` 4.3.7, 6.1.9, 6.2.3
`Cloneable` interface 6.1.9
`CloneNotSupportedException` class 6.1.9
`close` method
of `AutoCloseable` 7.2.5
of `Closeable` 7.2.5
of `ExecutorService` 10.8.3
of `Handler` 7.6
Closures 6.2.7
Code errors 7.1
Code generator tools 11.3.1
Code planes 3.3.4
Code points, code units 3.3.4, 3.6.3
`Collection` interface 9.1.2, 9.2, 9.3.1, 9.7.6
`add` method 9.1.2, 9.1.4, 9.2, 9.7.6
`addAll` method 9.1.4, 9.7.6
`clear` method 9.1.4, 9.7.6
`contains` method 9.7.6
`contains`, `containsAll` methods 9.1.4, 9.3.1
`containsAll` method 9.7.6
`equals` method 9.1.4
generic 9.1.4
implementing 6.1.5
`isEmpty` method 6.1.5, 9.1.4, 9.7.6
`iterator` method 9.1.2, 9.7.6
`remove` method 9.1.4, 9.7.6
`removeAll` method 9.1.4, 9.7.6
`removeIf` method 9.7.6
`retain` method 9.1.4
`retainAll` method 9.7.6
`size` method 9.1.4, 9.7.6
`stream` method 6.1.5
`toArray` method 5.3.2, 9.1.4, 9.6.6, 9.7.6
`Collections` class 9, 9.6.2, 9.7.6, 10.8.3
`addAll` method 9.7.6
algorithms for 9.6.1
`binarySearch` method 9.6.3, 9.7.6
bounded 9.1.1
bulk operations in 9.6.5
`checkedCollection` method 9.7.6
`checkedList` method 9.7.6
`checkedMap` method 9.7.6
`checkedNavigableMap` method 9.7.6
`checkedNavigableSet` method 9.7.6
`checkedQueue` method 9.7.6
`checkedSet` method 9.7.6
`checkedSortedMap` method 9.7.6
`checkedSortedSet` method 9.7.6
concrete 9.3
concurrent modifications of 9.3.1
converting to arrays 9.6.6
`copy` method 9.7.6
debugging 9.3.1

`disjoint` method 9.7.6
elements of
inserting 9.2
maximum 9.6.1
removing 9.1.3
traversing 9.1.3
`emptyEnumeration` method 9.7.6
`emptyIterator` method 9.7.6
`emptyList` method 9.7.6
`emptyListIterator` method 9.7.6
`emptyMap` method 9.7.6
`emptyNavigableMap` method 9.7.6
`emptyNavigableSet` method 9.7.6
`emptySet` method 9.7.6
`emptySortedMap` method 9.7.6
`emptySortedSet` method 9.7.6
`enumeration` method 9.7.2, 9.7.6
`fill` method 9.7.6
`frequency` method 9.7.6
`indexOfSubList` method 9.7.6
interfaces for 9.1
`lastIndexOfSubList` method 9.7.6
legacy 9.7
`list` method 9.7.6
`max` method 9.7.6
`min` method 9.7.6
mutable 9.5.1
`nCopies` method 9.5.1, 9.7.6
`newSetFromMap` method 9.7.6
ordered 9.2, 9.3.1
performance of 9.2, 9.3.3
`replaceAll` method 9.7.6
`reverse` method 9.7.6
`rotate` method 9.7.6
searching in 9.6.3
`shuffle` method 9.6.2, 9.7.6
`singleton` method 9.7.6
`singletonList` method 9.7.6
`sort` method 9.6.2, 9.7.6
sorted 9.3.4
`swap` method 9.7.6
`synchronizedCollection` method 9.7.6, 10.8.3
`synchronized`Collection methods 9.5.7
`synchronizedList` method 9.7.6, 10.8.3
`synchronizedMap` method 9.7.6, 10.8.3
`synchronizedNavigableMap` method 9.7.6
`synchronizedNavigableSet` method 9.7.6
`synchronizedSet` method 9.7.6, 10.8.3
`synchronizedSortedMap` method 9.7.6, 10.8.3
`synchronizedSortedSet` method 9.7.6, 10.8.3
thread-safe 9.5.7, 10.6
`unmodifiableCollection` method 9.7.6
`unmodifiable`Collection methods 9.5.2
`unmodifiableList` method 9.7.6
`unmodifiableMap` method 9.7.6
`unmodifiableNavigableMap` method 9.7.6
`unmodifiableNavigableSet` method 9.7.6
`unmodifiableSequencedCollection` method 9.7.6
`unmodifiableSequencedMap` method 9.7.6
`unmodifiableSequencedSet` method 9.7.6
`unmodifiableSet` method 9.7.6
`unmodifiableSortedMap` method 9.7.6
`unmodifiableSortedSet` method 9.7.6
using for method parameters 9.6.7
Command line
arguments in 3.10.5
compiling/launching from 2.2, 3.1
`command` method
of `ProcessHandle.Info` 10.8.3
`commandLine` method
of `ProcessHandle.Info` 10.8.3
Comments 3.2
automatic documentation and 3.2, 4.10
blocks of 3.2
not nesting 3.2
to the end of line 3.2
Commons CSV library 12.8
Compact compilation unit 4.4.5
Compact source file 4.8.4
Companion classes 6.1.4, 6.1.5
`Comparable` interface 6.1.1, 6.5.2, 6.5.3, 8.1.5, 9.3.3, 9.6.2
`compareTo` method 6.1.1, 6.5.3, 8.1.5, 8.4.2
`Comparator` interface 6.1.8, 6.2.1, 6.2.10, 9.6.2, 9.7.6
chaining comparators in 6.2.10
`comparing` method 6.2.10

lambda expressions and 6.2.3
`naturalOrder` method 6.2.10
`nullFirst/Last` methods 6.2.10
`reversed` method 9.7.6
`reversed`, `reverseOrder` methods 6.2.10, 9.6.2
`reverseOrder` method 9.7.6
`thenComparing` method 6.2.10
`comparator` method
of `SortedMap` 9.7.6
of `SortedSet` 9.7.6
`compare` method
of `Double` 6.5.3
of `Integer` 6.5.3
`compare` method (integer types) 6.2.3
`compareAndSet` method 10.5.11
`compareTo` method
in subclasses 6.1.1
of `BigDecimal` 3.10.8
of `BigInteger` 3.10.8
of `Comparable` 6.1.1, 6.5.3, 8.1.5, 8.4.2
of `Enum` 5.11
of `String` 3.10.8
Compilation unit
compact 4.4.5
Compiler
autoboxing in 5.4
bridge methods in 8.2.3
command-line options of 7.6
creating bytecode files in 3.1
deducting method types in 8.1.4
enforcing `throws` specifiers in 7.2.1
error messages in 7.1.2
just-in-time 1.2.6, 1.2.8, 1.5, 5.1.7, 9.7.6
launching 2.2
optimizing method calls in 1.2.9, 5.1.7
overloading resolution in 5.1.6
shared strings in 3.6.4, 3.6.5
translating typed array lists in 5.3.3
type parameters in 8.1.1
warnings in 3.8.5, 5.3.3
whitespace in 3.1
`CompletableFuture` class 10.7.2
`acceptEither` method 10.7.2
`allOf`, `anyOf` methods 10.7.2
`applyToEither` method 10.7.2
`exceptionally`, `exceptionallyCompose` methods 10.7.2
`handle` method 10.7.2
`orTimeout` method 10.7.2
`runAfterXxx` methods 10.7.2
`thenAccept`, `thenAcceptBoth`, `thenCombine`, `thenRun` methods 10.7.2
`thenApply`, `thenApplyAsync`, `thenCompose` methods 10.7.2
`whenComplete` method 10.7.2
`CompletionStage` interface 10.7.2
Components (of records) 4.7.1
Computations
asynchronous 10.7
performance of 3.5.2
`compute` method
of `Map` 9.7.6
`compute`, `computeIfXxx` methods
of `ConcurrentHashMap` 10.6.3
`computeIfAbsent` method
of `Map` 9.7.6
`computeIfPresent` method
of `Map` 9.7.6
Concrete collections 9.3
Concrete methods 5.6
Concurrent hash maps
atomic updates in 10.6.3
bulk operations on 10.6.4
efficiency of 10.6.2
size of 10.6.2
vs. synchronization wrappers 10.6.8
Concurrent modification detection 9.3.1
Concurrent programming 1.2.10, 10, 10.8.2
records in 4.7.1
synchronization in 10.5
Concurrent sets 10.6.5
`ConcurrentHashMap` class 10.6.2, 10.8.3
atomic updates in 10.6.3
`compute`, `computeIfXxx` methods 10.6.3
`forEach` method 10.6.4
`forEach`, `forEachXxx` methods 10.6.4
`get` method 10.6.3

keySet, newKeySet methods 10.6.5
mappingCount method 10.6.2
merge method 10.6.3
organizing buckets as trees in 10.6.2
put, putIfAbsent methods 10.6.3
reduce, reduceXxx methods 10.6.4
replace method 10.6.3
search, searchXxx methods 10.6.4
V> method 10.8.3
ConcurrentLinkedQueue class 10.6.2, 10.8.3
ConcurrentLinkedQueue<E> method 10.8.3
ConcurrentLinkedQueue<E> method
of ConcurrentLinkedQueue 10.8.3
ConcurrentModificationException class 9.3.1, 10.6.2, 10.6.8
ConcurrentSkipListMap class 10.8.3
V> method 10.8.3
ConcurrentSkipListMap/Set classes 10.6.2
ConcurrentSkipListSet class 10.8.3
ConcurrentSkipListSet<E> method 10.8.3
ConcurrentSkipListSet<E> method
of ConcurrentSkipListSet 10.8.3
Condition interface 10.5.6, 10.8.3
await method 10.2.3, 10.8.3
signal method 10.8.3
signal, signalAll methods 10.5.5
signalAll method 10.8.3
vs. synchronization methods 10.5.6
Condition objects 10.5.4
Condition variables 10.5.4
Conditional operator 3.5.8
with pattern matching 5.1.9
Conditional statements 3.8.2
Configuration files
editing 7.5.4
Console class 3.7.1, 3.10.8
printing output to 3.1, 3.7.2
reading input from 3.7.1
readLine method 3.10.8
readPassword method 3.10.8
console method
of System 3.10.8
ConsoleHandler class 7.5.5, 7.5.6, 7.6
Constructor 7.6
const keyword 3.4.3, Appendix
Constants 3.4.3
documentation comments for 4.10.4
names of 3.4.3
public 4.4.2
static 4.4.2
Constructor class 5.10.4, 5.11
accessFlags method 5.11
getDeclaringClass method 5.11
getExceptionTypes method 5.11
getModifiers method 5.11
getModifiers, getName methods 5.10.4
getName method 5.11
getParameterTypes method 5.11
getReturnType method 5.11
newInstance method 5.11
Constructor expressions 8.5.6
Constructor references 6.2.6
annotating 11.1.4
Constructors 4.3.2, 4.3.3, 4.6
annotating 11.1.3, 11.1.4
calling another constructor in 4.6.6
canonical, compact, custom 4.7.2
defined 4.2.1
documentation comments for 4.10.1
field initialization in 4.6.2, 4.6.4
final 5.10.4
initialization blocks in 4.6.7
names of 4.2.1, 4.3.3
no-argument 4.6.3, 5.1.3, 6.4
overloading 4.6.1
parameter names in 4.6.5
private 5.10.4
protected 4.10.1
public 4.10.1, 5.10.4
with super keyword 5.1.3
Consumer interface 6.2.9
Consumer threads 10.6.1
contains method
of Collection 9.1.4, 9.3.1, 9.7.6
of HashSet 9.3.3
containsAll method 9.1.4, 9.3.1
of Collection 9.7.6
containsKey method

of `Map` 9.7.6
`containsValue` method
of `Map` 9.7.6
Context
early execution 4.6.6
`continue` keyword 3.8.6, Appendix
not allowed in `switch` expressions 3.8.5
Control flow 3.8
block scope 3.8.1
breaking 3.8.6
conditional statements 3.8.2
loops 3.8.3
"for each" 3.10.3
determinate 3.8.4
multiple selections 3.8.5
Conversion characters 3.7.2
Coordinated Universal Time (UTC) 4.2.2
Copies 9.5
unmodifiable 9.5.2
`copy` method
of `Collections` 9.7.6
`copyOf` method
of `Arrays` 3.10.4, 3.10.8, 5.10.6
of `EnumSet` 9.7.6
of `List` 9.7.6
of `List`, `Map`, `Set` 9.5.2
of `Map` 9.7.6
of `Map.Entry` 9.7.6
of `Set` 9.7.6
`copyOfRange` method
of `Arrays` 3.10.8
`CopyOnWriteArrayList` class 10.6.6, 10.6.8
`CopyOnWriteArraySet` class 10.6.6
CORBA 12.1
Cornell, Gary 1.1
Corruption of data 10.5.1, 10.5.2
`cos` method
of `Math` 3.5.2
Count of Monte Cristo, The (Dumas) 10.7.3
Covariant return types 8.2.3
CSV files 12.8
Ctrl+\, for thread dump 10.5.5
Ctrl+C, for program termination 10.5.1, 10.5.4
`current` method
of `ProcessHandle` 10.8.3
of `ThreadLocalRandom` 10.8.3
`currentThread` method 10.3.2
of `Thread` 10.8.3

D

`d` conversion character 3.7.2
`D`, `d` suffixes (for `double` numbers) 3.3.2
`daemon` method
of `Thread.Builder.OfPlatform` 10.8.3
Daemon threads 10.3.3
Data types 3.3
`boolean` type 3.3.5
casting between 3.5.4
`char` type 3.3.3
conversions between 3.5.3, 5.1.8
floating-point 3.3.2
integer 3.3.1
Databases 11
`DataFlavor` class 12.1
Date and time
formatting output for 3.7.2
hash codes for 5.2.4
no built-in types for 4.2.1
`Date` class 4.2.2
`getDay/Month/Year` methods (deprecated) 4.2.2
`toString` method 4.2.1
Deadlocks 10.5.4, 10.5.5
Debugging 1.2.11, 7.6
collections 9.3.1
debuggers for 7.6
generic types 9.5.6
GUI programs 7.2.1
including class names in 6.3.6
messages for 7.1.4
reflection for 5.10.5
trapping program errors in a file for 7.6
when running applications in terminal window 2.2
Decrement operators 3.5.6
`decrementExact` method 3.5.2
Deep copies 6.1.9
`deepEquals` method 5.2.3
`deepToString` method 3.10.7, 5.2.5
Default for annotation element 11.2
`default` keyword 3.8.5, 6.1.5, Appendix

sealed classes and 5.8
Default methods 6.1.5
conflicts in 6.1.6
Deferred execution 6.2.9
`delete` method
of `StringBuilder` 3.10.8
Dependence 4.1.4
Deprecated methods 4.2.2, 4.2.3
`Deque` interface 9.3.5, 9.7.6
`offerFirst` method 9.7.6
`offerLast` method 9.7.6
`peekFirst` method 9.7.6
`peekLast` method 9.7.6
`pollFirst` method 9.7.6
`pollLast` method 9.7.6
Deques 9.3.5
Derived classes. See Subclasses
`descendants` method
of `ProcessHandle` 10.8.3
`destroy` method
of `Process` 10.8.3
`destroy`, `destroyForcibly` methods
of `Process` 10.8.2
`destroyForcibly` method
of `Process` 10.8.3
Determinate loops 3.8.4
Development environments
choosing 2.2
in terminal window 2.2
integrated 2.3
Device errors 7.1
Diamond syntax 5.3.1
Digital signatures 1.2.5
Directories
working, for a process 10.8.1
`directory` method
of `ProcessBuilder` 10.8.1, 10.8.3
`disjoint` method
of `Collections` 9.7.6
`divide` method
of `BigDecimal` 3.10.8
of `BigInteger` 3.10.8
Division 3.5.1
`do`/`while` loop 3.8.3, Appendix
Documentation comments 3.2, 4.10
extracting 4.10.10
for fields 4.10.4
for methods 4.10.3
for packages 4.10.5
general 4.10.8
HTML markup in 4.10.6
hyperlinks in 4.10.7
inserting 4.10.1
links to other files in 4.10.7
overview 4.10.10
`doInBackground` method 10.7.3
of `SwingWorker` 10.8.3
Double brace initialization 6.3.6
`Double` class 5.11, 6.5.3
`compare` method 6.5.3
converting from `double` 5.4
`hashCode` method 5.11
`parseDouble` method 3.7.1
`POSITIVE_INFINITY`, `NEGATIVE_INFINITY`, `NaN` constants 3.3.2
`double` type 3.3.2, Appendix
arithmetic computations with 3.5.1
converting to other numeric types 3.5.3
Double-precision numbers 3.3.2
`DoubleAccumulator`, `DoubleAdder` classes 10.5.11
Doubly linked lists 9.3.1
Dynamic binding 5.1.3, 5.1.6
Dynamic languages 1.2.11

E

`E`
of `Math` 3.5.2
`E`, `e` conversion characters 3.3.2, 3.7.2
Early construction context 4.6.6
Eclipse 2.3, 7.6
Adoptium 2.1
configuring projects in 2.3
IDE 12.5
imports in 4.8.3
running source files in 2.3
Yasson framework 12.7
Effectively final variables 7.2.5
Eiffel programming language 6.1.3

`Element` interface 11.5.2
`element` method
of `BlockingQueue` 10.6.1
of `Queue` 9.7.6
Elements 11.1.1
`else if` 3.8.2
`else` keyword 3.8.2, Appendix
Emoji characters 3.3.4
`emptyEnumeration` method
of `Collections` 9.7.6
`emptyIterator` method
of `Collections` 9.7.6
`emptyList` method
of `Collections` 9.7.6
`emptyListIterator` method
of `Collections` 9.7.6
`emptyMap` method
of `Collections` 9.7.6
`emptyNavigableMap` method
of `Collections` 9.7.6
`emptyNavigableSet` method
of `Collections` 9.7.6
`emptySet` method
of `Collections` 9.7.6
`emptySortedMap` method
of `Collections` 9.7.6
`emptySortedSet` method
of `Collections` 9.7.6
`EmptyStackException` class 7.3
Encapsulation 4.1.1, 4.1.2, 12
benefits of 4.3.7
compile-time 12.10
protected instance fields and 5.11
`endsWith` method
of `String` 3.10.8
`ensureCapacity` method 5.3.1
of `ArrayList` 5.11
Enterprise Edition 1.4
`entry` method
of `Map` 9.5.1, 9.7.6
EntryLogger 11.6.2
EntryLoggingAgent.mf 11.6.2
`entrySet` method 9.4.3
of `Map` 9.7.6
`Enum` class 5.7, 5.11
`compareTo` method 5.11
`name` method 5.11
`ordinal` method 5.11
`toString`, `valueOf` methods 5.7
`valueOf` method 5.11
`enum` keyword 3.4.4, Appendix
Enumerated types 3.4.4
equality testing for 5.7
in `switch` statement 3.5.9
`Enumeration` interface 9.1, 9.7.2, 9.7.6
`asIterator` method 9.7.2, 9.7.6
`hasMoreElements` method 9.7.6
`hasMoreElements`, `nextElement` methods
9.1.3, 9.7.2
`nextElement` method 9.7.6
Enumeration maps/sets 9.4.6
`enumeration` method
of `Collections` 9.7.6
Enumerations 5.7
always final 5.1.7
annotating 11.1.3
declared inside a class 6.3.8
implementing interfaces 6.1.2
legacy 9.7.2
`EnumMap` class 9.4.6, 9.7.6
as a concrete collection type 9.3
Constructor 9.7.6
`EnumSet` class 9.4.6, 9.7.6
`allOf` method 9.7.6
as a concrete collection type 9.3
`copyOf` method 9.7.6
`noneOf` method 9.7.6
`of` method 9.7.6
`range` method 9.7.6
`environment` method
of `ProcessBuilder` 10.8.3
Environment variables, modifying 10.8.1
`EOFException` class 7.1.3
Epoch 4.2.2
Equals 6.1.6
`hashCode` method and 5.2.4
implementing 5.2.3
inheritance and 5.2.3

of proxy classes 6.5.3
of records 4.7.1, 5.2.2
redefining 5.2.4
wrappers and 5.4
`equals` method
of `Annotation` 11.6.2
of `Arrays` 3.10.8, 5.2.3, 5.11
of `Collection` 9.1.4
of `Object` 5.2.2, 5.11, 9.5.2
of `Objects` 5.11
of `Set` 9.2
of `String` 3.6.5, 3.10.8
`equalsIgnoreCase` method 3.6.5
of `String` 3.10.8
`Error` class 7.1.1
Errors
checking, in mutator methods 4.3.7
code 7.1
device 7.1
internal 7.1.1, 7.1.2, 7.4.3
messages for 7.2.2
physical limitations 7.1
user input 7.1
Escape sequences 3.3.3
`Exception` class 7.1.1, 7.6
Constructor 7.6
Exception handlers 5.10.2, 7.1
Exception specification 7.1.2
`exceptionally`, `exceptionallyCompose` methods
of `CompletableFuture` 10.7.2
`exceptionally`, `exceptionallyCompose` methods (`CompletableFuture`) 10.7.2
`exceptionNow` method
of `Future` 10.8.3
Exceptions 7.1.1
"throw early, catch late" 7.3
annotating 11.1.4
`ArrayIndexOutOfBoundsException` 3.10.2, 7.1.1, 7.1.2
`ArrayStoreException` 5.1.5, 8.3, 8.5.3, 8.5.4
`CancellationException` 10.7.3
catching 4.3.5, 5.10.2, 6.1.9, 7.1.2, 7.2
changing type of 7.2.3
checked 5.10.1, 5.10.2, 7.1.1, 7.1.2, 7.3
`ClassCastException` 5.1.8, 5.10.6, 6.1.1, 8.3, 8.5.7, 8.6.1, 9.5.6
`CloneNotSupportedException` 6.1.9
`ConcurrentModificationException` 9.3.1, 10.6.2, 10.6.8
creating classes for 7.1.3, 7.1.4
documentation comments for 4.10.3
`EmptyStackException` 7.3
`EOFException` 7.1.3
`FileNotFoundException` 7.1.2
`finally` clause in 7.2.4
generics in 8.5.9
hierarchy of 7.1.1, 7.3
`IllegalAccessException` 5.10.5
`IllegalStateException` 9.1.3, 10.6.1
`InaccessibleObjectException` 5.10.5
`InterruptedException` 10.1, 10.3.2, 10.4.1
`InvocationTargetException` 5.10.1
`IOException` 7.1.2, 7.1.3, 7.2.1, 7.2.5
logging 7.5.7
micromanaging 7.3
`NoSuchElementException` 9.1.3
`NullPointerException` 4.3.5, 5.4, 6.2.5, 7.1.1, 7.3
`NumberFormatException` 7.3
out-of-bounds 7.3
propagating 7.2.1, 7.3
rethrowing and chaining 7.2.3, 7.6
`RuntimeException` 7.1.1, 7.3
`ServletException` 7.2.3
squelching 7.3
stack trace for 7.2.6
throwing 5.10.2, 7.1.3
`TimeoutException` 10.4.1
tips for using 7.3
type variables in 8.1.6
uncaught 7.6, 10.2.4, 10.3.5
unchecked 5.10.2, 7.1.1, 7.1.2, 7.3
unexpected 7.5.7
`UnsupportedOperationException` 9.4.3, 9.5.2, 9.5.8
variables for, implicitly `final` 7.2.2
vs. simple tests 7.3

wrapping 7.2.3
exec method
of Runtime 10.8
Executable class 5.10.7
Executable JAR files 4.9.3
ExecutableElement interface 11.5.2
Execute 10.7.3
execute method
of SwingWorker 10.8.3
ExecutorCompletionService class 10.4.3, 10.8.3
Constructor 10.8.3
poll method 10.8.3
submit method 10.8.3
take method 10.8.3
Executors class 10.4.2, 10.8.3
groups of tasks, controlling 10.4.3
newCachedThreadPool method 10.8.3
newFixedThreadPool method 10.8.3
newSingleThreadExecutor method 10.8.3
newThreadPerTaskExecutor method 10.8.3
newVirtualThreadPerTaskExecutor method 10.8.3
Executors class, newXxx methods 10.4.2
ExecutorService interface 10.8.3
awaitTermination method 10.8.3
close method 10.8.3
invokeAll method 10.8.3
invokeAny method 10.8.3
invokeAny/All methods 10.4.3
shutdown method 10.4.2, 10.8.3
shutdownNow method 10.4.2, 10.8.3
submit method 10.4.2, 10.8.3
exitValue method 10.8.2
of Process 10.8.3
exp method
of Math 3.5.2
Explicit parameters 4.3.6
Exploratory programming 1.2.8
exports keyword 12.5, 12.13, Appendix
Expressions 3.5.5
extends keyword 5.1, 8.1.5, Appendix

F

F, f conversion characters 3.7.2
F, f suffixes (for float numbers) 3.3.2
factory method
of Thread.Builder 10.8.3
Factory methods 4.4.4
Fair locks 10.5.3
Fallthrough behavior 3.8.5
false literal Appendix
fdlibm library 3.5.2
Field class 5.10.4, 5.11
accessFlags method 5.11
get method 5.10.5, 5.11
getDeclaringClass method 5.11
getExceptionTypes method 5.11
getModifiers method 5.11
getModifiers, getName methods 5.10.4
getName method 5.11
getParameterTypes method 5.11
getReturnType method 5.11
getType method 5.10.4
set method 5.11
Fields
adding, in subclasses 5.1.2
annotating 11.1.3
default initialization of 4.6.2
documentation comments for 4.10.1, 4.10.4
final 4.4.2, 5.1.7
instance 4.1.1, 4.3.2, 4.3.7, 4.3.10, 4.6.4, 4.11
private 4.11, 5.1.1, 5.1.2
protected 4.10.1, 5.1.10, 5.11
public 4.10.1, 4.10.4
public static final 6.1.2
static 4.4.1, 4.6.8, 4.8.5, 8.5.8
volatile 10.5.9
with the null value 4.3.5
File handlers 7.5.5
FileHandler class 7.5.5, 7.5.6, 7.6
Constructor 7.6
FileNotFoundException class 7.1.2
Files class
reading
all words from 7.2.5
in a separate thread 10.7.3
fill method
of Arrays 3.10.8

of `Collections` 9.7.6
`Filter` class 7.5.6
`Filter` interface 7.6
`isLoggable` method 7.6
`final` keyword 3.4.3, 5.1.7, Appendix
checking 5.10.4
for fields in interfaces 6.1.2
for instance fields 4.3.10
for methods in superclass 6.1.1
for shared fields 10.5.10
inner classes and 6.3.5
`finalize` method
of `Object` 4.6.3
`finally` keyword 7.2.4, Appendix
`return` statements in 7.2.4
`unlock` operation in 10.5.3
without `catch` 7.2.4
Financial calculations 3.3.2
`findFirst` method
of `ServiceLoader` 6.5.3
`first` method
of `SortedSet` 9.7.6
First Person, Inc. 1.4
`firstKey` method
of `SortedMap` 9.7.6
Flags, for formatted output 3.7.2
`Float` class 5.11
converting from `float` 5.4
`hashCode` method 5.11
`POSITIVE_INFINITY`, `NEGATIVE_INFINITY`, `NaN` constants 3.3.2
`float` type 3.3.2, Appendix
converting to other numeric types 3.5.3
Floating-point numbers 3.3.2
arithmetic computations with 3.5.1
converting from/to integers 5.1.8
equality of 3.8.4
formatting output for 3.7.2
rounding 3.3.2, 3.5.4
`floor` method
of `NavigableSet` 9.7.6
`floorMod` method 3.5.1
`flush` method
of `Handler` 7.6
`for` keyword 3.8.4, Appendix
comma-separated expressions in 3.5.11
defining variables inside 3.8.4
for collections 9.1.3
`forEach` method
of `ConcurrentHashMap` 10.6.4
of `Map` 9.7.6
of `StackWalker` 7.6
`forEach`, `forEachXxx` methods
of `ConcurrentHashMap` 10.6.4
`forEachRemaining` method 9.1.3
of `Iterator` 9.7.6
Fork-join framework 10.4.6
Form feed character 3.3.3
`format` method
of `Formatter` 7.6
Format specifiers 3.7.2
`formatMessage` method
of `Formatter` 7.6
`Formattable` interface 3.7.2
`formatted` method
of `String` 3.7.2
`Formatter` class 7.5.6, 7.6
`format` method 7.6
`formatMessage` method 7.6
`getHead` method 7.6
`getTail` method 7.6
`forName` method 5.10.1
of `Class` 5.11
`frequency` method
of `Collections` 9.7.6
`from` method
of `Random` 4.11
`Function` interface 6.2.9
Functional interfaces 6.2.3, 11.3, 11.3.1
abstract methods in 6.2.3
annotating 6.2.9
conversion to 6.2.3
generic 6.2.4
using supertype bounds in 8.4.2
Functions. See Methods
`Future` interface 10.4.3, 10.8.3
`cancel` method 10.8.3
`cancel`, `get` methods 10.4.1, 10.4.2, 10.7.3

`exceptionNow` method 10.8.3
`get` method 10.8.3
`isCancelled` method 10.8.3
`isCancelled`, `isDone` methods 10.4.1, 10.4.2
`isDone` method 10.8.3
`resultNow` method 10.8.3
`state` method 10.8.3
Futures 10.4.1
combining 10.7.2
completable 10.7.2
`FutureTask` class 10.4.1, 10.8.3
Constructor 10.8.3

G

`G`, `g` conversion characters 3.7.2
Garbage collection 4.2.1
hash maps and 9.4.4
GB18030 3.3.4
General Public License (GPL) 1.5
Generic programming 8
arrays and 6.2.6, 8.5.7
classes in 5.3, 5.3.1, 8.1.3
extending/implementing other generic classes 8.3
no throwing or catching instances of 8.1.6
collection interfaces in 9.6.6
converting to raw types 8.3
debugging 9.5.6
expressions in 8.2.2
in JVM 8.2, 8.6.3
inheritance rules for 8.3
legacy code and 8.2.4
methods in 8.1.4, 8.2.3, 9.1.4
reflection and 8.6
required skill levels for 8.1.1
static fields or methods and 8.5.8
type erasure in 8.2.1, 8.5.1, 8.5.7
clashes after 8.5.10
type matching in 8.6.2
vs. inheritance 8.1
wildcard types in 8.4
Generic types
annotating 11.1.4
`GenericArrayType` interface 8.6.3, 8.6.4
`getGenericComponentType` method 8.6.4
`get` method
of `Array` 5.11
of `ArrayList` 5.3.2, 5.11
of `BitSet` 9.7.6
of `ConcurrentHashMap` 10.6.3
of `Field` 5.10.5, 5.11
of `Future` 10.4.1, 10.4.2, 10.7.3, 10.8.3
of `LinkedList` 9.3.1
of `List` 9.2, 9.7.6
of `LongAccumulator` 10.5.11
of `Map` 9.2, 9.4.1, 9.7.6
of `Paths` 6.1.4
of `ScopedValue` 10.8.3
of `ServiceLoader.Provider` 6.4, 6.5.3
of `ThreadLocal` 10.8.3
of `Vector` 10.5.7
`getAccessor` method
of `RecordComponent` 5.11
`getActualTypeArguments` method
of `ParameterizedType` 8.6.4
`getAndUpdate`, `getAndAccumulate` methods
of `AtomicXxx` 10.5.11
`getAnnotation` method
of `AnnotatedElement` 11.6.2
`getAnnotation`, `getAnnotationsByType` methods
of `AnnotatedConstruct` 11.5.2
of `AnnotatedElement` 11.4
`getAnnotations` method
of `AnnotatedElement` 11.6.2
`getAnnotationsByType` method
of `AnnotatedElement` 11.6.2
`getBoolean` method
of `Boolean` 9.7.6
`getBounds` method
of `TypeVariable` 8.6.4
`getCause` method
of `Throwable` 7.6
`getClass` method
of `Class` 5.10.1
of `Object` 5.11
`getClassName` method
of `StackTraceElement` 7.6
of `StackWalker.StackFrame` 7.6
`getComponentType` method 5.10.6

of `Class` 5.11
`getConstructor` method
of `Class` 5.11, 8.6.4
`getConstructors` method 5.10.4
of `Class` 5.11
`getDay` method
of `Date` 4.2.2
`getDayOfMonth` method
of `LocalDate` 4.2.2, 4.11
`getDayOfWeek` method
of `LocalDate` 4.11
`getDeclaredAnnotations` method
of `AnnotatedElement` 11.6.2
`getDeclaredAnnotation`*`Xxx`* methods
of `AnnotatedElement` 11.4
`getDeclaredConstructor` method
of `Class` 8.6.4
`getDeclaredConstructors` method 5.10.4
of `Class` 5.11
`getDeclaredField` method
of `Class` 5.11
`getDeclaredFields` method 5.10.4, 5.10.5
of `Class` 5.11
`getDeclaredMethods` method 5.10.4, 5.10.7
of `Class` 5.11
`getDeclaringClass` method
of `Constructor` 5.11
of `Field` 5.11
of `Method` 5.11
of `StackWalker.StackFrame` 7.6
`getDefault` method
of `RandomGenerator` 4.11
`getDefaultToolkit` method
of `Toolkit` 6.5.3
`getDefaultUncaughtExceptionHandler` method
of `Thread` 10.8.3
`getElementsAnnotatedWith` method 11.5.2
`getEnclosedElements` method 11.5.2
`getEnumConstants` method 8.6.1
of `Class` 8.6.4
`getErrorStream` method 10.8.1
of `Process` 10.8.3
`getExceptionTypes` method
of `Constructor` 5.11
of `Field` 5.11
of `Method` 5.11
`getField` method
of `Class` 5.11
`getFields` method 5.10.4
of `Class` 5.11
`getFileName` method
of `StackTraceElement` 7.6
of `StackWalker.StackFrame` 7.6
`getFilter` method
of `Handler` 7.6
`getFirst` method
of `LinkedList` 9.7.6
of `SequencedCollection` 9.7.6
`getFormatter` method
of `Handler` 7.6
`getGenericComponentType` method
of `GenericArrayType` 8.6.4
`getGenericInterfaces` method
of `Class` 8.6.4
`getGenericParameterTypes` method
of `Method` 8.6.4
`getGenericReturnType` method
of `Method` 8.6.4
`getGenericSuperclass` method
of `Class` 8.6.4
`getGlobal` method 7.6
`getHead` method 7.5.6
of `Formatter` 7.6
`getImage` method
of `Class` 5.10.3
`getInputStream` method 10.8.1
of `Process` 10.8.3
`getInstance` method 7.2.6
of `StackWalker` 7.6
`getInstant` method
of `LogRecord` 7.6
`getInteger` method
of `Integer` 9.7.6
`getKey` method
of `Map.Entry` 9.7.6
`getLast` method
of `LinkedList` 9.7.6
of `SequencedCollection` 9.7.6

`getLength` method 5.10.6
of `Array` 5.11
`getLevel` method
of `Handler` 7.6
of `LogRecord` 7.6
`getLineNumber` method
of `StackTraceElement` 7.6
of `StackWalker.StackFrame` 7.6
`getLogger` method 7.5.3
of `System` 7.5.2
`getLoggerName` method
of `LogRecord` 7.6
`getLong` method
of `Long` 9.7.6
`getLongThreadID` method
of `LogRecord` 7.6
`getLowerBounds` method
of `WildcardType` 8.6.4
`getMessage` method
of `LogRecord` 7.6
of `Throwable` 7.6
`getMethod` method 5.10.7
`getMethodName` method
of `StackTraceElement` 7.6
of `StackWalker.StackFrame` 7.6
`getMethods` method 5.10.4
of `Class` 5.11
`getMillis` method
of `LogRecord` 7.6
`getModifiers` method
of `Constructor` 5.11
of `Field` 5.11
of `java.lang.reflect.Member` 5.10.4
of `Method` 5.11
`getMonth` method
of `Date` 4.2.2
`getMonthValue` method
of `LocalDate` 4.2.2, 4.11
`getName` method
of `Class` 5.10.1, 5.11
of `Constructor` 5.11
of `Field` 5.11
of `java.lang.reflect.Member` 5.10.4
of `Method` 5.11
of `RecordComponent` 5.11
of `System.Logger` 7.6
of `Thread` 10.8.3
of `TypeVariable` 8.6.4
`getOrDefault` method
of `Map` 9.7.6
`getOutputStream` method 10.8.1
of `Process` 10.8.3
`getOwnerType` method
of `ParameterizedType` 8.6.4
`getPackageName` method
of `Class` 5.11
`getParameters` method
of `LogRecord` 7.6
`getParameterTypes` method
of `Constructor` 5.11
of `Field` 5.11
of `Method` 5.11
`getProperties` method 9.7.4
of `System` 9.7.6
`getProperty` method
of `Properties` 9.7.3, 9.7.6
of `System` 9.7.6
`getProxyClass` method 6.5.3
of `Proxy` 6.5.3
`getQualifiedName` method 11.5.2
`getRawType` method
of `ParameterizedType` 8.6.4
`getRecordComponents` method
of `Class` 5.11
`getResource` method
of `Class` 5.11
`getResource`, `getResourceAsStream` methods
of `Class` 5.10.3
`getResourceAsStream` method
of `Class` 5.11, 12.7
of `Module` 12.7
`getResourceBundle` method
of `LogRecord` 7.6
`getResourceBundleName` method
of `LogRecord` 7.6
`getReturnType` method
of `Constructor` 5.11
of `Field` 5.11

of `Method` 5.11
`getSequenceNumber` method
of `LogRecord` 7.6
`getSimpleName` method
of `Element` 11.5.2
`getSourceClassName` method
of `LogRecord` 7.6
`getSourceMethodName` method
of `LogRecord` 7.6
`getStackTrace` method 7.2.6
of `Throwable` 7.6
`getState` method
of `SwingWorker` 10.8.3
of `Thread` 10.8.3
`getSuperclass` method
of `Class` 5.11, 8.6.4
`getSuppressed` method 7.2.5
of `Throwable` 7.6
`getTail` method 7.5.6
of `Formatter` 7.6
Getters/setters, generated automatically 11.5.3
`getThrown` method
of `LogRecord` 7.6
`getTime` method 5.1.7
`getType` method
of `Field` 5.10.4
of `RecordComponent` 5.11
`getTypeParameters` method
of `Class` 8.6.4
of `Method` 8.6.4
`getUncaughtExceptionHandler` method
of `Thread` 10.8.3
`getUpperBounds` method
of `WildcardType` 8.6.4
`getValue` method
of `Map.Entry` 9.7.6
`getXxx` method
of `Array` 5.11
`getYear` method
of `Date` 4.2.2
of `LocalDate` 4.2.2, 4.11
GMT (Greenwich Mean Time) 4.2.2
Goetz, Brian 10, 10.5.9
Gosling, James 1.4
`goto` keyword 3.8, 3.8.6, Appendix
Graphical User Interface
debugging 7.2.1
long-running tasks in 10.7.3
Green project 1.4
`GregorianCalendar` class 4.2.3
`add` method 4.2.3
constructors for 4.2.2, 4.6.1
`group` method
of `Thread.Builder.OfPlatform` 10.8.3
GUI. See Graphical User Interface

H

`H`, `h` conversion characters 3.7.2
`handle` method
of `CompletableFuture` 10.7.2
`Handler` class 7.6
`close` method 7.6
`flush` method 7.6
`getFilter` method 7.6
`getFormatter` method 7.6
`getLevel` method 7.6
`publish` method 7.6
`setFilter` method 7.6
`setFormatter` method 7.6
`setLevel` method 7.6
Hansen, Per Brinch 10.5.8
Hash codes 5.2.4, 9.3.3
default 5.2.4
formatting output for 3.7.2
Hash collisions 5.2.4, 9.3.3
Hash maps 9.4.1
concurrent 10.6.2
identity 9.4.7
linked 9.4.5
setting 9.4.1
vs. tree maps 9.4.1
weak 9.4.4
`hash` method
of `Objects` 5.2.4, 5.11
Hash sets 9.3.3
linked 9.4.5
Hash tables 9.3.3
legacy 9.7.1
load factor of 9.3.3

rehashing 9.3.3
`hashCode` method 5.2.4
`equals` method and 5.2.4
null-safe 5.2.4
of `Annotation` 11.6.2
of `Arrays` 5.2.4, 5.11
of `Boolean` 5.11
of `Byte` 5.11
of `Character` 5.11
of `Double` 5.11
of `Float` 5.11
of `Integer` 5.11
of `LocalDate` 5.2.4
of `Long` 5.11
of `Object` 5.11, 9.7.6
of `Objects` 5.2.4, 5.11
of proxy classes 6.5.3
of records 4.7.1, 5.2.4
of `Set` 9.2
of `Short` 5.11
of `String` 9.3.3
`HashMap` class 9.4.1, 9.7.6
as a concrete collection type 9.3
Constructor 9.7.6
`newHashMap` method 9.7.6
`HashSet` class 9.3.3, 9.7.6
`add`, `contains` methods 9.3.3
as a concrete collection type 9.3
Constructor 9.7.6
iterating over 9.1.3
`newHashSet` method 9.7.6
`Hashtable` class 9.1, 9.7, 9.7.1, 10.6.8
as a concrete collection type 9.3
synchronized methods 9.7.1
`hasMoreElements` method 9.1.3, 9.7.2
of `Enumeration` 9.7.6
`hasNext` method
of `Iterator` 9.1.3, 9.7.6
of `Scanner` 3.10.8
`hasNextDouble` method
of `Scanner` 3.10.8
`hasNextInt` method
of `Scanner` 3.10.8
`hasPrevious` method 9.3.1
of `ListIterator` 9.7.6
`headMap` method
of `NavigableMap` 9.7.6
of `SortedMap` 9.5.3, 9.7.6
`headSet` method
of `NavigableSet` 9.5.3, 9.7.6
of `SortedSet` 9.5.3, 9.7.6
Heap 9.3.6
Helper methods 4.3.9, 6.1.4, 8.4.4
Hexadecimal numbers
formatting output for 3.7.2
prefix for 3.3.1
`HexFormat` class 3.7.2
`higher` method
of `NavigableSet` 9.7.6
Hoare, Tony 10.5.8
Hold count 10.5.3
HotJava browser 1.4
Hotspot just-in-time compiler 2.1.1, 9.7.6
HTML 1.4, 1.5
generating documentation in 11.5.3
in JavaDoc comments 4.10.6

I

Identifiers Appendix
Identity hash maps 9.4.7
`identityHashCode` method 9.4.7
of `System` 5.11, 9.7.6
`IdentityHashMap` class 9.4.7, 9.7.6
as a concrete collection type 9.3
Constructor 9.7.6
`identityToString` method
of `Objects` 5.11
IEEE 754 specification 3.3.2, 3.5.2
`if` keyword 3.8.2, Appendix
`IllegalAccessException` class 5.10.5
`IllegalStateException` class 9.1.3, 10.6.1
Immutable classes 4.3.10, 5.11
Implementations 9.1.1
`implements` keyword 6.1.1, Appendix
Implicit parameters 4.3.6
none, in static methods 4.4.3
state of 7.6
Implicitly declared class 4.4.5
`import` keyword 4.8.3, Appendix

no annotations for 11.1.4
`InaccessibleObjectException` class 5.10.5
`increment` method
of `LongAdder` 10.5.11
Increment operators 3.5.6
Incremental linking 1.2.8
`incrementAndGet` method 10.5.11
`incrementExact` method 3.5.2
Indentation, in text blocks 3.6.10
`Index` class 3.10.2
`indexOf` method
of `List` 9.7.6
of `String` 3.10.8
`indexOfSubList` method
of `Collections` 9.7.6
Inferred types 6.2.2
`info` method
of `ProcessHandle` 10.8.3
Information hiding. See Encapsulation
Inheritance 4.1.4, 5
design hints for 5.11
equality testing and 5.2.3
hierarchies of 5.1.4
multiple 5.1.4, 6.1.3
preventing 5.1.7
private fields and 5.1.1
vs. type parameters 8.1, 8.3
`inheritIO` method
of `ProcessBuilder` 10.8.3
`initCause` method
of `Throwable` 7.6
Initialization blocks 4.6.7
static 4.6.8
Inlining 1.2.9, 5.1.7
Inner classes 6.3
accessing object state with 6.3.1
anonymous 6.3.6
applicability of 6.3.3
defined 6.3
local 6.3.4
private 6.3.1
static 6.3, 6.3.7
syntax of 6.3.2
translated into regular classes 6.3.3
vs. lambda expressions 6.2.3
Input, reading 3.7.1
`insert` method
of `StringBuilder` 3.10.8
Instance field
declared with prefix 4.6.5
Instance fields 4.1.1
final 4.3.10
initializing 4.6.7, 4.11
explicit 4.6.4
names of 4.7.1
not present in interfaces 6.1.1, 6.1.2
private 4.3.2, 4.11
protected 5.11
shadowing 4.3.3, 4.6.5
values of 4.3.7
volatile 10.5.9
vs. local variables 4.3.3, 4.3.6, 4.6.2
Instance method 3.6.2
`instanceof` keyword 3.5.11, 5.1.8, 5.2.3, 6.1.2, **Appendix**
annotating 11.1.4
pattern matching for 5.1.9
Instances 4.1.1
creating on the fly 5.10.1
Instrumentation API 11.6.2
`int` type 3.3.1, **Appendix**
converting to other numeric types 3.5.3
fixed size for 1.2.7
platform-independent 3.3.1
`Integer` class 5.11, 6.5.3, 9.7.6
`compare` method 6.2.3, 6.5.3
converting from `int` 5.4
`getInteger` method 9.7.6
`hashCode` method 5.11
`intValue` method 5.11
`parseInt` method 3.7.1, 5.4, 5.11
`toString` method 5.11
`valueOf` method 5.11
Integer types 3.3.1
arithmetic computations with 3.5.1
arrays of 5.2.5
computations of 3.5.2
converting from/to floating-point 5.1.8

formatting output for 3.7.2
no unsigned types in Java 3.3.1
Integrated Development Environment (IDE) 2.3
IntelliJ IDEA 2.3
@interface 11.2
`interface` keyword 6.1.1, Appendix
Interface types 9.1.1
Interface variables 6.1.2
Interfaces 6.1
abstract classes and 6.1.3
annotating 11.1.3, 11.1.4
binary- vs. source-compatible 6.1.5
callbacks and 6.1.7
constants in 6.1.2
declared inside a class 6.3.8
documentation comments for 4.10.1
evolution of 6.1.5
extending 6.1.2
for custom algorithms 9.6.7
functional 6.2.3, 11.3, 11.3.1
implementing 6.1.1, 6.1.2, 6.1.4
methods in
clashes between 6.1.6
nonabstract 6.2.3
private 6.1.4
static 6.1.4
no instance fields in 6.1.1, 6.1.2
properties of 6.1.2
public 4.10.1
sealed 6.1.2
tagging 6.1.9, 9.2
vs. implementations 9.1.1
Internal errors 7.1.1, 7.1.2, 7.4.3
Internationalization. See Localization
Internet Explorer 1.3
Interpreted languages 1.5
Interpreter 1.2.8
`interrupt` method
of `Thread` 10.3.2, 10.8.3
`interrupted` method
of `Thread` 10.3.2, 10.8.3
`InterruptedException` class 10.1, 10.3.2, 10.4.1
Intrinsic locks 10.5.6, 10.5.8, 10.5.9
Introduction to Algorithms (Cormen et al.) 9.3.4
`intValue` method
of `Integer` 5.11
Invocation handlers 6.5.1
`InvocationHandler` interface 6.5.1, 6.5.3
`invoke` method 6.5.3
`invokeDefault` method 6.5.3
`InvocationTargetException` class 5.10.1
`invoke` method
of `InvocationHandler` 6.5.1, 6.5.3
of `Method` 5.10.7, 5.11
`invokeAll` method
of `ExecutorService` 10.8.3
`invokeAny` method
of `ExecutorService` 10.8.3
`invokeAny/All` methods (`ExecutorService`) 10.4.3
`invokeDefault` method
of `InvocationHandler` 6.5.3
`IO` 3.1
`print` method 3.7.2
`readln` method 3.7.1
`IO` class 3.7.1, 3.10.8
`print` method 3.10.8
`println` method 3.10.8
`readln` method 3.10.8
`IOException` class 7.1.2, 7.1.3, 7.2.1, 7.2.5
`isAbstract` method
of `Modifier` 5.11
`isAlive` method 10.8.2
of `Process` 10.8.3
`isAnnotationPresent` method
of `AnnotatedElement` 11.6.2
`isArray` method
of `Class` 5.11
`isBound` method
of `ScopedValue` 10.8.3
`isCancelled` method
of `Future` 10.8.3
`isCancelled`, `isDone` methods
of `Future` 10.4.1
`isCancelled`, `isDone` methods (`Future`) 10.4.2
`isDone` method
of `Future` 10.8.3
`isEmpty` method

of `Collection` 6.1.5, 9.1.4, 9.7.6
of `String` 3.10.8
`isEnum` method
of `Class` 5.11
`isFinal` method 5.10.4
of `Modifier` 5.11
`isInterface` method
of `Class` 5.11
of `Modifier` 5.11
`isInterrupted` method 10.3.2
of `Thread` 10.8.3
`isJavaIdentifierXxx` methods
of `Character` 3.4.1
`isLoggable` method
of `Filter` 7.5.6, 7.6
of `System.Logger` 7.6
`isNaN` method 3.3.2
`isNative` method
of `Modifier` 5.11
`isNativeMethod` method
of `StackTraceElement` 7.6
of `StackWalker.StackFrame` 7.6
ISO 8601 format 11.3.1
ISO 8859-1 3.3.4, 9.7.3
`isPrivate` method
of `Modifier` 5.11
`isPrivate`, `isProtected`, `isPublic` methods
of `Modifier` 5.10.4
`isProtected` method
of `Modifier` 5.11
`isProxyClass` method 6.5.3
of `Proxy` 6.5.3
`isPublic` method
of `Modifier` 5.11
`isRecord` method
of `Class` 5.11
`isStatic` method
of `Modifier` 5.11
`isStrict` method
of `Modifier` 5.11
`isSynchronized` method
of `Modifier` 5.11
`isVirtual` method
of `Thread` 10.8.3
`isVolatile` method
of `Modifier` 5.11
`Iterable` interface 3.10.3
`Iterator` interface 9.1.3, 9.7.6
“for each” loop 9.1.3
`forEachRemaining` method 9.1.3, 9.7.6
generic 9.1.4
`hasNext` method 9.1.3, 9.7.6
`next` method 9.1.3, 9.7.6
`remove` method 9.1.3, 9.7.6
`iterator` method
of `Collection` 9.1.2, 9.7.6
of `ServiceLoader` 6.5.3
Iterators 9.1.3
being between elements 9.1.3
weakly consistent 10.6.2
IzPack 4.9.3

J

J#, J++ programming languages 1.2.11
Jar 4.9.1, 12.6
command-line options of 4.9.1, 4.9.3, 4.9.5
Jar Bundler 4.9.3
JAR files 4.8.9, 4.9
analyzing dependencies of 12.15
creating 4.9.1
executable 4.9.3
file resources in 12.7
in `jre/lib/ext` directory 4.8.10
manifest of 4.9.2, 12.8
`META-INF/services` directory 12.14
modular 12.6, 12.8
multi-release 4.9.4
resources and 5.10.3
scanning for deprecated elements 11.3.1
Java 2.2
`--add-exports` option 12.10
`--add-opens` option 12.10
`--illegal-access` option 12.10
`--module`, `--module-path` options 12.3
`-javaagent` option 11.6.2
architecture-neutral object file format of 1.2.6
as a programming platform 1.1
available under GPL 1.5
backward compatibility of 4.9.4, 5.1.9, 6.2.9, 8

basic syntax of 3.1, 4.3.1
case-sensitiveness of 3.1, 3.4.1, 9.7.1
command-line options of 4.9.5, 7.4.2
design of 1.2
documentation for 2.1.3
dynamic 1.2.11
history of 1.4
interpreter in 1.2.8
libraries in 1.2.1, 1.4, 1.5
installing 2.1.3
misconceptions about 1.5
networking capabilities of 1.2.3
no multiple inheritance in 6.1.3
no operator overloading in 3.9
no unsigned types in 3.3.1
reliability of 1.2.4
security of 1.2.5, 1.5
simplicity of 1.2.1, 6.2.1
strongly typed 3.3, 6.1.1
versions of 1.4
vs. C++ 1.2.1, 9.7.6
Java bug parade 3.1
Java Collections Framework 9
algorithms in 9.6.1
converting to/from arrays in 9.6.6
copies and views in 9.5
interfaces in 9.2
vs. implementations 9.1.1
legacy classes in 9.7
operations in
bulk 9.6.5
optional 9.5.8
vs. traditional collections libraries 9.1.3
Java Concurrency in Practice (Goetz) 10
Java Development Kit (JDK) 1.2.6, 2
documentation in 3.6.8
downloading 2.1.1
installation of 2.1
default 4.9.1
obsolete features in 12.1
setting up 2.1.2
Java Language Specification 3.1
Java Memory Model and Thread Specification 10.5.9
Java Persistence Architecture 11
Java Platform Module System 12, 12.15
migration to 12.8, 12.10
Java Runtime Environment (JRE) 2.1.1
Java Virtual Machine (JVM) 1.2.6
generics in 8.2, 8.6.3
launching 2.2
managing applications in 7.6
method tables in 5.1.6
thread priority levels in 10.3.6
watching class loading in 7.6
Java Virtual Machine Specification 3.1, 11.6
`java.awt` package 12.1
`java.desktop` module 12.11
`java.lang.annotation` package 11.3
`java.lang.Object` class 4.1.1
`java.lang.reflect` package 5.10.4, 5.10.6
`java.logging` module 12.11
`java.se` module 12.11
`java.util.Collections` class 9.6.2
`java.util.concurrent` package 10.5.3
efficient collections in 10.6.2
`java.util.concurrent.atomic` package 10.5.11
`java.util.function` package 6.2.4
`java.util.logging` package 7.5.1, 7.5.4
`java.util.Timer` class 6.1.7
Javac 2.2
`-processor` option 11.5.1
`-XprintRounds` option 11.5.3
current directory in 4.8.9
JavaDoc 4.10
command-line options of 4.10.10
comments in 4.10.1, 4.10.5
extracting 4.10.10
overview 4.10.10
redeclaring `Object` methods for 6.2.3
HTML markup in 4.10.6
including annotations in 11.3.2
links in 4.10.7
online documentation of 4.10.10
JavaFX 10.7.3
`javafx.css.CssParser` class 4.9.4
`javan.log` files 7.5.5
Javap 4.9.4, 6.3.3

JavaScript 1.5
`for of` loop in 3.8
`javax.annotation` package 11.3
`javax.swing.Timer` class 6.1.7
JAXB 12.7
JCommander 11
Jconsole 7.5.4, 7.6, 10.5.5
Jdeprscan 11.3.1
Jdeps 12.15
JEP 264 (platform logging API) 7.5.1
Jimage 12.15
Jlink 12.15
Jmod 12.15
JMOD files 12.15
Jmol applet 1.3
`join` method
of `String` 3.10.8
of `Thread` 10.2.3, 10.8.3
`JOptionPane` class 6.5.3
`showMessageDialog` method 6.5.3
JShell 1.2.8, 2.4
JShell, loading modules into 12.6
`JSlider` class
`setLabelTable` method 8.2.4
JSON 5.8
JSON-B 12.7
JUnit 11, 11.1
JUnit framework 7.6
Just-in-time compiler 1.2.6, 1.2.8, 1.5, 5.1.7, 9.7.6
JVM
specification for 11.6

K

Key/value pairs
in annotations 11.1.1, 11.2
`keySet` method
of `ConcurrentHashMap` 10.6.5
of `Map` 9.4.3, 9.7.6
Keywords Appendix
hyphenated 5.8
not used 3.4.3
redundant 6.1.2
reserved 3.4.1
restricted Appendix
Knuth, Donald 3.8.6
KOI-8 3.3.4

L

`L`, `l` suffixes (for `long` integers) 3.3.1
Lambda expressions 6.2
accessing variables in 6.2.7
annotating targets for 11.3.1
atomic updates with 10.5.11
capturing values by 6.2.7
for loggers 7.5.3
functional interfaces and 6.2.3
method references and 6.2.5
not for variables of type `Object` 6.2.3
parameter types of 6.2.2
processing 6.2.9
result type of 6.2.2
scope of 6.2.7
syntax of 6.2.2
`this` keyword in 6.2.8
vs. inner classes 6.2.3
vs. method references 6.2.5
Language model API 11.5.2
`last` method
of `SortedSet` 9.7.6
`lastIndexOf` method
of `List` 9.7.6
of `String` 3.10.8
`lastIndexOfSubList` method
of `Collections` 9.7.6
`lastKey` method
of `SortedMap` 9.7.6
Launch4J 4.9.3
Legacy classes 4.7.1
generics and 8.2.4
Legacy collections 9.7
bit sets 9.7.6
enumerations 9.7.2
hash tables 9.7.1
property maps 9.7.3
stacks 9.7.5
Length
of arrays 3.10.2
`length` method
of `BitSet` 9.7.6
of `String` 3.6.3, 3.6.6, 3.10.8

of `StringBuilder` 3.10.8
Line feed character
escape sequence for 3.3.3
in output 3.1, 3.6.10
in text blocks 3.6.10
Linked hash maps/sets 9.4.5
Linked lists 9.3.1
concurrent modifications of 9.3.1
doubly linked 9.3.1
printing 9.3.1
random access in 9.3.1, 9.6.1
removing elements from 9.3.1
`LinkedBlockingDeque` class 10.8.3
Constructor 10.8.3
`LinkedBlockingQueue` method 10.8.3
`LinkedBlockingDeque` method
of `LinkedBlockingQueue` 10.8.3
`LinkedBlockingQueue` class 10.6.1, 10.8.3
Constructor 10.8.3
`LinkedBlockingDeque` method 10.8.3
`LinkedBlockingQueue` method
of `LinkedBlockingDeque` 10.8.3
`LinkedHashMap` class 9.4.5, 9.7.6
access vs. insertion order in 9.4.5
as a concrete collection type 9.3
Constructor 9.7.6
`removeEldestEntry` method 9.4.5, 9.7.6
`LinkedHashSet` class 9.4.5, 9.7.6
as a concrete collection type 9.3
Constructor 9.7.6
`LinkedList` class 9.3.1, 9.3.5, 9.7.6
`addFirst` method 9.7.6
`addLast` method 9.7.6
as a concrete collection type 9.3
Constructor 9.7.6
`get` method 9.3.1
`getFirst` method 9.7.6
`getLast` method 9.7.6
`listIterator` method 9.3.1
`next/previousIndex` methods 9.3.1
`removeAll` method 9.3.1
`removeFirst` method 9.7.6
`removeLast` method 9.7.6
Linux
IDEs for 2.3
JDK in 2.1
no thread priorities in OpenJDK VM for 10.3.6
paths in 4.8.9, 4.8.10
troubleshooting Java programs in 2.2
`List` class 9.2
`add` method 9.2
`copyOf` method 9.5.2
`get` method 9.2
`of` method 9.5.1, 9.6.6
`remove` method 9.2
`set` method 9.2
`subList` method 9.5.3
`List` interface 9.7.6
`add` method 9.7.6
`addAll` method 9.7.6
`copyOf` method 9.7.6
`get` method 9.7.6
`indexOf` method 9.7.6
`lastIndexOf` method 9.7.6
`listIterator` method 9.7.6
`of` method 9.7.6
`remove` method 9.7.6
`replaceAll` method 9.7.6
`set` method 9.7.6
`sort` method 9.7.6
`subList` method 9.7.6
`list` method
of `Collections` 9.7.6
`ListIterator` interface 9.3.1, 9.7.6
`add` method 9.3.1, 9.7.6
`hasPrevious` method 9.3.1, 9.7.6
`nextIndex` method 9.7.6
`previous` method 9.3.1, 9.7.6
`previousIndex` method 9.7.6
`remove` method 9.3.1
`set` method 9.3.1, 9.7.6
`listIterator` method
of `LinkedList` 9.3.1
of `List` 9.7.6
Lists 9.2
modifiable/resizable 9.6.2
with given elements 9.5.1
`load` method

of `Properties` 9.7.3, 9.7.6
of `ServiceLoader` 6.5.3
Load time 11.6.2
Local inner classes 6.3.4
accessing variables from outer methods in 6.3.5
Local variables
annotating 8.2.4, 11.1.3
vs. instance fields 4.3.3, 4.3.6, 4.6.2
`LocalDate` class 4.2.2, 4.11
`getDayOfMonth` method 4.11
`getDayOfWeek` method 4.11
`getMonthValue` method 4.11
`getYear` method 4.11
`hashCode` method 5.2.4
`minusDays` method 4.11
`now` method 4.11
`now`, `of` methods 4.2.2
`of` method 4.11
`plusDays` method 4.2.2, 4.11
processing arrays of 8.4.2
Locales 3.7.2
Localization 4.2.1, 5.10.3
`Lock` interface 10.5.6, 10.8.3
`await` method 10.5.4
`lock` method 10.8.3
`newCondition` method 10.5.4, 10.8.3
`signal` method 10.5.4
`signalAll` method 10.5.4
`tryLock` method 10.2.3
`unlock` method 10.5.3, 10.8.3
vs. synchronization methods 10.5.6
`lock` method
of `Lock` 10.8.3
Locks 10.5.3
client-side 10.5.7
condition objects for 10.5.4
deadlocks 10.5.4, 10.5.5
fair 10.5.3
hold count for 10.5.3
in synchronized blocks 10.5.7
intrinsic 10.5.6, 10.5.8, 10.5.9
not with `try`-with-resources statement 10.5.3
not wrapper objects for 5.4
reentrant 10.5.3
Log file pattern variables 7.5.5
Log handlers 7.5.5
filtering/formatting 7.5.6
Log messages, adding to classes 11.6.1
`log` method
of `System.Logger` 7.6
`log`, `log10` methods
of `Math` 3.5.2
Log4j 7.5.1
Logback 7.5.1
`Logger` class
`getGlobal` method 7.6
Loggers
filtering/formatting 7.5.6
hierarchy of 7.5.4
naming 7.5.2
Logging 7.5
configuring 7.5.4
including class names in 6.3.6
levels of 7.5.3, 7.5.4
messages for 5.2.5
recipe for 7.5.7
Logging proxy 7.6
Logical “and”, “or” 3.5.7
Logical conditions 3.3.5
`LogRecord` class 7.6
`getInstant` method 7.6
`getLevel` method 7.6
`getLoggerName` method 7.6
`getLongThreadID` method 7.6
`getMessage` method 7.6
`getMillis` method 7.6
`getParameters` method 7.6
`getResourceBundle` method 7.6
`getResourceBundleName` method 7.6
`getSequenceNumber` method 7.6
`getSourceClassName` method 7.6
`getSourceMethodName` method 7.6
`getThrown` method 7.6
`Long` class 5.11, 9.7.6
converting from `long` 5.4
`getLong` method 9.7.6
`hashCode` method 5.11
Long Term Support (LTS) 2.1.1

`long` type 3.3.1, Appendix
platform-independent 3.3.1
`LongAccumulator` class, methods of 10.5.11
`LongAdder` class 10.5.11, 10.6.3
`add`, `increment`, `sum` methods 10.5.11
Loops
"for each" 3.10.3
`break` statements in 3.8.6
`continue` statements in 3.8.6
determinate (`for`) 3.8.4
`while` 3.8.3
`lower` method
of `NavigableSet` 9.7.6

M

Mac OS X
executing JARs in 4.9.3
IDEs for 2.3
JDK in 2.1
`main` ,method
launching 3.1
`main` method 4.4.5
body of 3.1
not defined 4.6.8
separate for each class 7.6
`String[] args` parameter of 3.10.5
MANIFEST.MF 4.9.2
editing 4.9.2
newline characters in 4.9.3
`Map` interface 9.2, 9.7.6
`compute` method 9.7.6
`computeIfAbsent` method 9.7.6
`computeIfPresent` method 9.7.6
`containsKey` method 9.7.6
`containsValue` method 9.7.6
`copyOf` method 9.5.2, 9.7.6
`entry` method 9.5.1, 9.7.6
`entrySet` method 9.4.3, 9.7.6
`forEach` method 9.7.6
`get` method 9.2, 9.4.1, 9.7.6
`getOrDefault` method 9.7.6
`keySet` method 9.4.3, 9.7.6
`merge` method 9.7.6
`of` method 9.5.1, 9.7.6
`ofEntries` method 9.5.1, 9.7.6
`put` method 9.2, 9.4.1, 9.7.6
`putAll` method 9.7.6
`putIfAbsent` method 9.7.6
`remove` method 9.4.1
`replaceAll` method 9.7.6
`values` method 9.4.3, 9.7.6
`Map.Entry` interface 9.4.3, 9.7.6
`copyOf` method 9.7.6
`getKey` method 9.7.6
`getValue` method 9.7.6
`setValue` method 9.7.6
`mappingCount` method 10.6.2
Maps 9.4
adding/retrieving objects to/from 9.4.1
concurrent 10.6.2
garbage collecting 9.4.4
hash vs. tree 9.4.1
implementations for 9.4.1
keys for 9.4.1
enumerating 9.4.3
subranges of 9.5.3
with given key/value pairs 9.5.1
Marker interfaces 6.1.9
`Math` class 2.4, 3.5.2
`E`, `PI` static constants 3.5.2
`floorMod` method 3.5.1
`log`, `log10` methods 3.5.2
`pow` method 3.5.2, 4.4.3
`round` method 3.5.4
`sqrt` method 3.5.2, 5.10.7
trigonometric functions 3.5.2
xxx`Exact` methods 3.5.2
`max` method
of `Collections` 9.7.6
`MAX_PRIORITY` field
of `Thread` 10.8.3
Maximum value, computing 8.1.3
`merge` method
of `ConcurrentHashMap` 10.6.3
of `Map` 9.7.6
Merge sort algorithm 9.6.2
Meta-annotations 11.2, 11.3.2
META-INF 4.9.2
`META-INF/versions` directory 4.9.4

`Method` class 5.10.4, 5.11, 8.6.4
`accessFlags` method 5.11
`getDeclaringClass` method 5.11
`getExceptionTypes` method 5.11
`getGenericParameterTypes` method 8.6.4
`getGenericReturnType` method 8.6.4
`getModifiers` method 5.11
`getModifiers`, `getName` methods 5.10.4
`getName` method 5.11
`getParameterTypes` method 5.11
`getReturnType` method 5.11
`getTypeParameters` method 8.6.4
instance 3.6.2
`invoke` method 5.10.7, 5.11
static 3.6.2
`toString` method 5.10.4
Method parameters. See Parameters
Method pointers 5.10.7
Method references 6.2.5
annotating 11.1.4
`this`, `super` parameters in 6.2.5
vs. lambda expressions 6.2.5
Method tables 5.1.6
`MethodHandles` class 12.7
Methods 4.1.1
abstract 5.6
in functional interfaces 6.2.3
accessor 4.2.3, 4.3.7, 8.4.1
adding logging messages to 11.6.1
adding, in subclasses 5.1.2
annotating 11.1.3
applying to objects 4.2.1
asynchronous 10.4.1
body of 3.1
bridge 8.2.3, 8.5.10
calling by reference vs. by value 4.5
casting 5.1.8
chaining calls of 6.2.9
concrete 5.6
conflicts in 6.1.6
consistent 5.2.3
default 6.1.5
deprecated 4.2.2, 4.2.3, 11.3, 11.3.1
destructor 4.6.3
documentation comments for 4.10.1, 4.10.7
dynamic binding for 5.1.3, 5.1.6
error checking in 4.3.7
exception specification in 7.1.2
factory 4.4.4
final 5.1.6, 5.1.7, 5.10.4, 6.1.1
generic 8.1.4, 8.2.3, 9.1.4
getters/setters, generated automatically 11.5.3
helper 4.3.9, 8.4.4
inlining 1.2.9, 5.1.7
invoking 3.1, 5.10.7
mutator 4.2.3, 4.3.7, 8.4.1
names of 4.7.1, 4.11
overloading 4.6.1
overriding 5.1.2, 5.2.3, 5.11, 11.3, 11.3.1
exceptions and 7.1.2
return type and 8.2.3
package scope of 4.8.8
passing objects to 4.2.1
private 4.3.9, 5.1.6, 5.10.4, 6.1.4
protected 4.10.1, 5.1.10, 5.11, 6.1.9
public 4.10.1, 5.10.4, 6.1.1
reflexive 5.2.3
return type of 4.6.1, 5.1.6
signature of 4.6.1, 5.1.6
static 4.4.3, 4.8.5, 5.1.6, 8.5.8, 10.5.6
adding to interfaces 6.1.4
symmetric 5.2.3
tracing 6.5.2
transitive 5.2.3
used for serialization 11.3, 11.3.1
utility 6.1.4
varargs 5.5, 8.5.4
visibility of, in subclasses 5.1.6
Micro Edition 1.4
Microsoft
ActiveX 1.2.5
C# 1.2.11, 1.4, 5.1.7
Internet Explorer 1.3
J#, J++ 1.2.11
JDK in 2.1
.NET platform 1.2.6
Visual Basic 1.2.1, 4.2.1
Visual Studio 2.2

Microsoft Windows. See Windows operating system
`min` method
of `Collections` 9.7.6
`MIN_PRIORITY` field
of `Thread` 10.8.3
Minimum value, computing 8.1.3
`minusDays` method
of `LocalDate` 4.11
`mod` method
of `BigInteger` 3.10.8
`Modifier` class 5.11
`isAbstract` method 5.11
`isFinal` method 5.11
`isInterface` method 5.11
`isNative` method 5.11
`isPrivate` method 5.11
`isProtected` method 5.11
`isPublic` method 5.11
`isStatic` method 5.11
`isStrict` method 5.11
`isSynchronized` method 5.11
`isVolatile` method 5.11
`isXxx` methods 5.10.4
`toString` method 5.11
`Module` class
`getResourceAsStream` method 12.7
`module` keyword 12.3, **Appendix**
Module path 4.8.10
Module-info.class 12.6, 12.8
Module-info.java 12.3, 12.8
Modules 1.4, 4.8.8, 12, 12.15
accessing 12.7, 12.10
automatic 12.8, 12.9
declaration of 12.3
explicit 12.9
exporting packages 12.5
loading into JShell 12.6
migration to 12.8, 12.10
naming 12.2, 12.8
not passing access rights 12.4
open 12.7
opening packages in 12.7
packages with the same names in 12.5
qualified exports of 12.13
reading other modules 12.4
requiring 12.4
service implementations and 12.14
tools for 12.15
unnamed 5.10.5, 12.9
versioning 12.1, 12.3
Modulus 3.5.1
Monitor concept 10.5.8
Mosaic 1.4
Multi-release JARs 4.9.4
Multidimensional arrays 3.10.7, 3.10.8
printing 5.2.5
ragged 3.10.8
Multiple inheritance 6.1.3
not supported in Java 5.1.4
Multiple selections 3.8.5
Multiplication 3.5.1
`multiply` method
of `BigDecimal` 3.10.8
of `BigInteger` 3.10.8
`multiplyExact` method 3.5.2
Multitasking 10
Multithreading 1.2.10, 10
deadlocks in 10.5.4, 10.5.5
deferred execution in 6.2.9
performance and 10.5.11, 10.6.1
synchronization in 10.5
using pools for 10.4.2
Mutator methods 4.2.3, 8.4.1
error checking in 4.3.7

N

`n` conversion character 3.7.2
Name
qualified 4.8.2, 4.8.3, 6.4
simple 4.8.3
of enumeration 5.7
`name` method
of `Enum` 5.11
of `Thread.Builder` 10.8.3
NaN 3.3.2
`native` keyword **Appendix**
`naturalOrder` method 6.2.10
Naughton, Patrick 1.4
`NavigableMap` interface 9.2, 9.7.6

`headMap` method 9.7.6
`subMap` method 9.7.6
`tailMap` method 9.7.6
`NavigableSet` interface 9.2, 9.3.4, 9.7.6
`ceiling` method 9.7.6
`floor` method 9.7.6
`headSet` method 9.7.6
`headSet`, `subSet`, `tailSet` methods 9.5.3
`higher` method 9.7.6
`lower` method 9.7.6
`pollFirst` method 9.7.6
`pollLast` method 9.7.6
`subSet` method 9.7.6
`tailSet` method 9.7.6
`nCopies` method 9.5.1
of `Collections` 9.7.6
`negateExact` method 3.5.2
Negation operator 3.5.7
Negative infinity 3.3.2
Nested classes
annotating 11.1.4
.NET platform 1.2.6
NetBeans 2.3, 7.6
Netscape 1.4
LiveScript/JavaScript 1.5
Navigator browser 1.3
Networking 1.2.3
`new` keyword 3.5.11, 4.2.1, 4.3.3, Appendix
in constructor references 6.2.6
not for interfaces 6.1.2
return value of 4.2.1
with arrays 3.10.1
with generic classes 5.3.1
with threads 10.2.1
`newCachedThreadPool` method 10.4.2
of `Executors` 10.8.3
`newCondition` method 10.5.4
of `Lock` 10.8.3
`newFixedThreadPool` method 10.4.2
of `Executors` 10.8.3
`newHashMap` method
of `HashMap` 9.7.6
`newHashSet` method
of `HashSet` 9.7.6
`newInstance` method
of `Array` 5.10.6, 5.11
of `Class` 5.10.1, 8.6.1
of `Constructor` 5.11
of `ScopedValue` 10.8.3
`newKeySet` method 10.6.5
Newline. See Line feed character
`newProxyInstance` method 6.5.2, 6.5.3
of `Proxy` 6.5.3
`newSetFromMap` method
of `Collections` 9.7.6
`newSingleThreadExecutor` method
of `Executors` 10.8.3
`newSingleThreadXxx` methods
of `Executors` 10.4.2
`newThread` method
of `ThreadFactory` 10.8.3
`newThreadPerTaskExecutor` method
of `Executors` 10.8.3
`newVirtualThreadPerTaskExecutor` method
of `Executors` 10.8.3
`next` method
of `Iterator` 9.1.3, 9.7.6
of `Scanner` 3.10.8
`nextDouble` method 3.7.1
of `Scanner` 3.10.8
`nextElement` method 9.1.3, 9.7.2
of `Enumeration` 9.7.6
`nextIndex` method
of `LinkedList` 9.3.1
of `ListIterator` 9.7.6
`nextInt` method
of `RandomGenerator` 4.6.8, 4.11
of `Scanner` 3.7.1, 3.10.8
`nextLine` method 3.7.1
of `Scanner` 3.10.8
No-argument constructors 4.6.3, 5.1.3, 6.4
`non-sealed` keyword 5.8, Appendix
`noneOf` method
of `EnumSet` 9.7.6
`NORM_PRIORITY` field
of `Thread` 10.8.3
`NoSuchElementException` class 9.1.3
Notepad 2.2

`notify` method
of `Object` 10.8.3
`notify`, `notifyAll` methods
of `Object` 10.5.6
`notifyAll` method
of `Object` 10.8.3
`now` method
of `LocalDate` 4.2.2, 4.11
`null` literal 4.2.1, Appendix
as a reference 4.3.5
equality testing to 5.2.3
`nullFirst/Last` methods
of `Comparator` 6.2.10
`NullPointerException` class 3.5.9, 4.3.5, 5.4, 6.2.5, 7.1.1, 7.3
`Number` class 5.4
`NumberFormat` class 5.11
factory methods 4.4.4
`parse` method 5.11
`NumberFormatException` class 7.3
Numbers
floating-point 3.3.2, 3.5.4, 3.7.2, 3.8.4, 5.1.8
Java Virtual Machine (JVM)truncating computations in 3.5.1
generated random 10.5.14
hexadecimal 3.3.1, 3.7.2
octal 3.3.1, 3.7.2
prime 9.7.6
rounding 3.3.2, 3.5.4
unsigned 3.3.1
Numeric types
casting 3.5.4
comparing 3.5.7, 6.2.10
converting
to other numeric types 3.5.3, 5.1.8
to strings 5.4
default initialization of 4.6.2
fixed sizes for 1.2.7
precision of 3.7.2, 3.9
printing 3.7.2

O

`o` conversion character 3.7.2
Oak 1.4, 7.1.1
`Object` class 4.1.1, 5.2, 5.11, 9.7.6, 10.8.3
`clone` method 4.3.7, 6.1.9, 6.2.3
`equals` method 5.2.2, 5.11, 6.1.6, 9.5.2
`getClass` method 5.11
`hashCode` method 5.2.4, 5.11, 9.7.6
no redefining for methods of 6.1.6
`notify` method 10.8.3
`notify`, `notifyAll` methods 10.5.6
`notifyAll` method 10.8.3
`toString` method 5.2.5, 5.11, 6.1.6, 6.2.3
`wait` method 10.2.3, 10.5.6, 10.8.3
Object references
as method parameters 4.5
converting 5.1.8
default initialization of 4.6.2
modifying 4.5
Object traversal algorithms 9.4.7
Object variables 5.6
in predefined classes 4.2.1
initializing 4.2.1
setting to `null` 4.2.1
vs. C++ object pointers 4.2.1
vs. objects 4.2.1
Object-oriented programming (OOP) 1.2.2, 4.1, 5
passing objects in 6.1.7
time measurement in 4.2.2
vs. procedural 4.1
Object-relational mappers 12.7
Objects 4.1, 4.1.2
analyzing at runtime 5.10.5
applying methods to 4.2.1
behavior of 4.1.2
cloning 6.1.9
comparing 6.1.1
concatenating with strings 5.2.5
constructing 4.1.1, 4.6
default hash codes of 5.2.4
destruction of 4.6.3
equality testing for 5.2.2, 5.10.1
`finalize` method of 4.6.3
identity of 4.1.2
implementing an interface 6.1.2
in predefined classes 4.2.1
initializing 4.2.1
intrinsic locks of 10.5.6

passing to methods 4.2.1
references to 4.2.1
runtime type identification of 5.10.1
serializing 9.4.7
sorting 6.1.1
state of 4.1.1, 4.1.2, 6.3.1
vs. object variables 4.2.1
`Objects` class 4.11, 5.11
`checkXxx` methods 7.3
`equals` method 5.11
`hash` method 5.11
`hash`, `hashCode` methods 5.2.4
`hashCode` method 5.11
`identityToString` method 5.11
`requireNonNull` method 4.3.5, 4.11, 7.3
`requireNonNullElse` method 4.3.5, 4.11
`requireNonNullElseGet` method 4.11
Octal numbers
formatting output for 3.7.2
prefix for 3.3.1
`of` method
of `EnumSet` 9.7.6
of `List` 9.7.6
of `List`, `Map`, `Set` 9.5.1, 9.6.6
of `LocalDate` 4.2.2, 4.11
of `Map` 9.7.6
of `Path` 6.1.4
of `ProcessHandle` 10.8.3
of `RandomGenerator` 4.11
of `Set` 9.7.6
`ofEntries` method
of `Map` 9.5.1, 9.7.6
`offer` method
of `BlockingQueue` 10.6.1, 10.8.3
of `Queue` 9.7.6
`offerFirst` method
of `BlockingDeque` 10.8.3
of `Deque` 9.7.6
`offerLast` method
of `BlockingDeque` 10.8.3
of `Deque` 9.7.6
`ofPlatform` method
of `Thread` 10.8.3
`ofVirtual` method
of `Thread` 10.8.3
On-demand initialization 10.5.12
`onExit` method
of `Process` 10.8.3
Online documentation 3.6.7, 3.6.8, 4.10, 4.10.10
`open` keyword 12.7, **Appendix**
OpenJ9 just-in-time compiler 2.1.1
OpenJDK 2.1, 2.1.1
`opens` keyword 12.7, 12.13, **Appendix**
Operators
arithmetic 3.5.1
bitwise 3.5.10, 3.5.11
`boolean` 3.5.7
hierarchy of 3.5.11
increment/decrement 3.5.6
no overloading for 3.9
relational 3.5.7
Optional operations 9.5.8
`or` method
of `BitSet` 9.7.6
Oracle 1.4
Ordered collections 9.2, 9.3.1
`ordinal` method
of `Enum` 5.11
`orElse` method
of `ScopedValue` 10.8.3
`org.omg.corba` package 12.1
`orTimeout` method 10.7.2
OSGi platform 6.4
Out-of-bounds exceptions 7.3
Output
formatting 3.7.2
statements in 3.6.1
Overloading resolution 4.6.1, 5.1.6
`overview.html` file 4.10.10

P

`p` (hexadecimal floating-point literals) 3.3.2
`package` keyword 4.8.3, 4.8.6, **Appendix**
Package-info.java 4.10.5, 11.1.3
`package.html` file 4.10.5
Packages 4.8, 12.1
accessing 4.8.8
adding classes into 4.8.6
annotating 11.1.3

documentation comments for 4.10.1, 4.10.5
exporting 12.5
hidden 12.5
importing 4.8.3
names of 4.8.2, 5.10.1
opening 12.7
split 12.6
unnamed 4.8.6, 4.8.8, 4.10.10, 7.4.2
Parallelism threshold 10.6.4
`parallelXxx` methods
of `Arrays` 10.6.7
Parameter variables
annotating 11.1.3
Parameterized types. See Type parameters
`ParameterizedType` interface 8.6.3, 8.6.4
`getActualTypeArguments` method 8.6.4
`getOwnerType` method 8.6.4
`getRawType` method 8.6.4
Parameters 4.5
checking, with assertions 7.4.3
documentation comments for 4.10.3
explicit 4.3.6
implicit 4.3.6, 4.4.3, 7.6
modifying 4.5
names of 4.6.5
using collection interfaces in 9.6.7
variable number of
passing generic types to 8.5.4
Parent classes. See Superclasses
`parse` method
of `NumberFormat` 5.11
`parseDouble` method
of `Double` 3.7.1
`parseInt` method 5.4
of `Integer` 3.7.1, 5.11
Pascal 1.4
compiled code in 1.2.6
passing parameters in 4.5
Passwords
reading from console 3.7.1
`Path` interface, `of` method 6.1.4
`Paths` class, `get` method 6.1.4
Pattern matching 5.1.9
Payne, Jonathan 1.4
`peek` method
of `BlockingQueue` 10.6.1
of `Queue` 9.7.6
of `Stack` 9.7.6
`peekFirst` method
of `Deque` 9.7.6
`peekLast` method
of `Deque` 9.7.6
Performance 1.2.9
computations and 3.5.2
JAR files and 4.8.9
measuring 9.7.6
multithreading and 10.5.11, 10.6.1
of collections 9.2, 9.3.3, 10.6.2
of Java vs. C++ 9.7.6
of simple tests vs. catching exceptions 7.3
`permits` keyword 5.8, 6.1.2, **Appendix**
Physical limitations 7.1
`PI`
of `Math` 3.5.2, 4.4.2
Picocli 11
`pid` method
of `ProcessHandle` 10.8.3
Platform logging API 7.5.1, 7.5.4
`plusDays` method
of `LocalDate` 4.2.2, 4.11
`Point` class 4.7, 4.7.1
`poll` method
of `BlockingQueue` 10.6.1, 10.8.3
of `ExecutorCompletionService` 10.8.3
of `Queue` 9.7.6
`pollFirst` method
of `BlockingDeque` 10.8.3
of `Deque` 9.7.6
of `NavigableSet` 9.7.6
`pollLast` method
of `BlockingDeque` 10.8.3
of `Deque` 9.7.6
of `NavigableSet` 9.7.6
Polymorphism 5.1.3, 5.1.5, 5.8, 5.11
`pop` method
of `Stack` 9.7.6
Portability 1.2.7, 1.5, 3.5.1
Positive infinity 3.3.2

`pow` method
of `BigInteger` 3.10.8
of `Math` 3.5.2, 4.4.3
`powExact` method 3.5.2
Precision, of numbers 3.7.2
Preconditions 7.4.3
Predefined classes 4.2
mutator and accessor methods in 4.2.3
objects, object variables in 4.2.1
`Predicate` interface 6.2.4, 6.2.9
Prefix
of instance field name 4.6.5
`premain` method (Instrumentation API) 11.6.2
`previous` method
of `ListIterator` 9.3.1, 9.7.6
`previousIndex` method
of `LinkedList` 9.3.1
of `ListIterator` 9.7.6
Prime numbers 9.7.6
Primitive types 3.3
as method parameters 4.5
comparing 6.2.10
converting to objects 5.4
final fields of 4.3.10
not for type parameters 8.5.1
transforming hash map values to 10.6.4
values of, not object 5.2.1
Princeton University 1.2.5
`print` method
of `IO` 3.1, 3.7.2, 3.10.8
Print statements
for logging 7.5
Printf
arguments of 5.5
conversion characters for 3.7.2
flags for 3.7.2
`println` method
of `IO` 3.1, 3.10.8
`printStackTrace` method 7.2.6, 7.6
of `Throwable` 5.11
`priority` method
of `Thread.Builder.OfPlatform` 10.8.3
Priority queues 9.3.6
`PriorityBlockingQueue` class 10.6.1, 10.8.3
Constructor 10.8.3
`PriorityQueue` class 9.7.6
as a concrete collection type 9.3
Constructor 9.7.6
`private` keyword 4.3.2, 4.8.8, 6.3.1, **Appendix**
checking 5.10.4
for fields, in superclasses 5.1.2
for methods 4.3.9
Procedures 4.1
`Process` class 10.8, 10.8.3
`destroy` method 10.8.3
`destroy`, `destroyForcibly` methods 10.8.2
`destroyForcibly` method 10.8.3
`exitValue` method 10.8.2, 10.8.3
`getErrorStream` method 10.8.3
`getInputStream` method 10.8.3
`getOutputStream` method 10.8.3
`get`*`Xxx`*`Stream` methods 10.8.1
`isAlive` method 10.8.2, 10.8.3
`onExit` method 10.8.3
`supportsNormalTermination` method 10.8.3
`toHandle` method 10.8.3
`waitFor` method 10.8.2, 10.8.3
`process` method
of `SwingWorker` 10.7.3, 10.8.3
`ProcessBuilder` class 10.8, 10.8.3
Constructor 10.8.3
`directory` method 10.8.1, 10.8.3
`environment` method 10.8.3
`inheritIO` method 10.8.3
`redirectError` method 10.8.3
`redirectErrorStream` method 10.8.3
`redirectInput` method 10.8.3
`redirectOutput` method 10.8.3
`redirect`*`Xxx`* methods 10.8.1
`start` method 10.8.2, 10.8.3
`startPipeline` method 10.8.1, 10.8.3
Processes 10.8
building 10.8.1
killing 10.8.2
running 10.8.2
`ProcessHandle` interface 10.8.3
`allProcesses` method 10.8.3
`children` method 10.8.3

`children`, `descendants` methods 10.8.3
`current` method 10.8.3
`descendants` method 10.8.3
`info` method 10.8.3
`of` method 10.8.3
`pid` method 10.8.3
`ProcessHandle.Info` interface 10.8.3
`arguments` method 10.8.3
`command` method 10.8.3
`commandLine` method 10.8.3
`startInstant` method 10.8.3
`totalCpuDuration` method 10.8.3
`user` method 10.8.3
`Processor` interface 11.5.1
Producer threads 10.6.1
Programs. See Applications
Prompt
`readln` method 3.7.1
`Properties` class 9.7, 9.7.6
Constructor 9.7.6
`getProperty` method 9.7.3, 9.7.6
`load` method 9.7.3, 9.7.6
`setProperty` method 9.7.6
`store` method 9.7.3, 9.7.6
`stringPropertyNames` method 9.7.6
Property files
generating 11.5.3
Property maps 9.7.3
reading/writing 9.7.3
`protected` keyword 5.1.10, 5.11, 6.1.9, Appendix
`provides` keyword 12.14, Appendix
Proxies 6.5
properties of 6.5.3
purposes of 6.5.2
`Proxy` class 6.5.3
`get/isProxyClass` methods 6.5.3
`getProxyClass` method 6.5.3
`isProxyClass` method 6.5.3
`newProxyInstance` method 6.5.2, 6.5.3
`public` keyword 4.3.2, 4.8.8, 6.1.1, Appendix
checking 5.10.4
for fields in interfaces 6.1.2
for `main` method 3.1
not specified for interfaces 6.1.1
`publish` method
of `Handler` 7.6
of `SwingWorker` 10.7.3, 10.8.3
Pure virtual functions (C++) 5.6
`push` method
of `Stack` 9.7.6
`put` method
of `BlockingQueue` 10.6.1, 10.8.3
of `ConcurrentHashMap` 10.6.3
of `Map` 9.2, 9.4.1, 9.7.6
`putAll` method
of `Map` 9.7.6
`putFirst` method
of `BlockingDeque` 10.8.3
`putIfAbsent` method
of `ConcurrentHashMap` 10.6.3
of `Map` 9.7.6
`putLast` method
of `BlockingDeque` 10.8.3

Q

Qualified exports 12.13
Qualified name 4.8.2, 4.8.3, 6.4
`Queue` class 9.3.5
implementing 9.1.1
`Queue` interface 9.7.6
`add` method 9.7.6
`element` method 9.7.6
`offer` method 9.7.6
`peek` method 9.7.6
`poll` method 9.7.6
`remove` method 9.7.6
Queues 9.1.1, 9.3.5
blocking 10.6.1
concurrent 10.6.2
QuickSort algorithm 3.10.6, 9.6.2

R

Race conditions 10.5.1, 10.5.2
and atomic operations 10.5.11
Ragged arrays 3.10.8
`Random` class 4.11
`from` method 4.11
thread-safe 10.5.14
`RandomAccess` interface 9.2, 9.6.2
`RandomGenerator` interface 4.11

`getDefault` method 4.11
`nextInt` method 4.6.8, 4.11
`of` method 4.11
`range` method
of `EnumSet` 9.7.6
Raw types 8.2.1
converting type parameters to 8.3
type inquiring at runtime 8.5.2
`readLine` method
of `Console` 3.10.8
`readln` method
of `IO` 3.7.1, 3.10.8
`readPassword` method
of `Console` 3.10.8
Receiver parameter 11.1.5
`record` keyword Appendix
`RecordComponent` class 5.11
`getAccessor` method 5.11
`getName` method 5.11
`getType` method 5.11
Records 4.7, 5.1.1
adding methods to 4.7.1
always final 5.1.7
declared inside a class 6.3.8
`equals` method of 5.2.2
`hashCode` method of 5.2.4
implementing interfaces 6.1.2
instance fields of 4.7.1
`toString` method of 5.2.5
`Rectangle` class 9.3.4
Rectangles
comparing 9.3.4
Recursive computations 10.4.6
`RecursiveAction`, `RecursiveTask` classes 10.4.6
Red Hat 2.1
Red-black trees 9.3.4
`redirectError` method
of `ProcessBuilder` 10.8.3
`redirectErrorStream` method
of `ProcessBuilder` 10.8.3
`redirectInput` method
of `ProcessBuilder` 10.8.3
`redirectOutput` method
of `ProcessBuilder` 10.8.3
`redirectXxx` methods
of `ProcessBuilder` 10.8.1
`reduce`, `reduceXxx` methods
of `ConcurrentHashMap` 10.6.4
Reentrant locks 10.5.3
`ReentrantLock` class 10.5.3, 10.8.3
Constructor 10.8.3
Reflection 5.1, 5.10
accessing
private members 12.7, 12.10
analyzing
classes 5.10.4
objects, at runtime 5.10.5
generics and 5.10.6, 8.6
overusing 5.11
processing annotations with 11.4
Reinhold, Mark 1.4
Relational operators 3.5.7, 3.5.11
Relative resource names 5.10.3
`remove` method
of `ArrayList` 5.3.2, 5.11
of `BlockingQueue` 10.6.1
of `Collection` 9.1.4, 9.7.6
of `Iterator` 9.1.3, 9.7.6
of `List` 9.2, 9.7.6
of `ListIterator` 9.3.1
of `Map` 9.4.1
of `Queue` 9.7.6
of `ThreadLocal` 10.8.3
`removeAll` method
of `Collection` 9.1.4, 9.7.6
of `LinkedList` 9.3.1
`removeEldestEntry` method 9.4.5
of `LinkedHashMap` 9.7.6
`removeFirst` method
of `LinkedList` 9.7.6
of `SequencedCollection` 9.7.6
`removeIf` method
of `ArrayList` 6.2.4
of `Collection` 9.7.6
`removeLast` method
of `LinkedList` 9.7.6
of `SequencedCollection` 9.7.6

`repeat` method
of `String` 3.6.1, 3.10.8
of `StringBuilder` 3.10.8
REPL 2.4
`replace` method
of `ConcurrentHashMap` 10.6.3
of `String` 3.10.8
`replaceAll` method
of `Collections` 9.7.6
of `List` 9.7.6
of `Map` 9.7.6
`requireNonNull` method 4.3.5, 7.3
of `Objects` 4.11
`requireNonNullElse` method 4.3.5
of `Objects` 4.11
`requireNonNullElseGet` method
of `Objects` 4.11
`requires` keyword 12.4, 12.5, 12.8, 12.11
Reserved words. See Keywords
Resources 5.10.3
exhaustion of 7.1.1
in JAR files 12.7
localizing 5.10.3
names of 5.10.3
Restricted views 9.5.8
`resultNow` method
of `Future` 10.8.3
`resume` method
of `Thread` 10.8.3
`retain` method
of `Collection` 9.1.4
`retainAll` method
of `Collection` 9.7.6
`return` keyword **Appendix**
in `finally` blocks 7.2.4
in lambda expressions 6.2.2
not allowed in `switch` expressions 3.8.5
Return types 5.1.6
covariant 8.2.3
documentation comments for 4.10.3
for overridden methods 8.2.3
Return values 4.2.1
`reverse` method
of `Collections` 9.7.6
of `StringBuilder` 3.10.8
`reversed` method
of `Comparator` 9.7.6
of `SequencedCollection` 9.7.6
of `SequencedMap` 9.7.6
of `SequencedSet` 9.7.6
`reversed`, `reverseOrder` methods
of `Comparator` 9.6.2
`reversed`, `reverseOrder` methods
of `Comparator` 6.2.10
`reverseOrder` method
of `Comparator` 9.7.6
`rotate` method
of `Collections` 9.7.6
`round` method
of `Math` 3.5.4
`RoundEnvironment` interface 11.5.2
`rt.jar` file
no longer present 12.15
`run` method
of `Runnable` 10.8.3
of `ScopedValue.Carrier` 10.4.5
of `Thread` 10.1, 10.8.3
`runAfter`*`Xxx`* methods
of `CompletableFuture` 10.7.2
`Runnable` interface 6.2.9, 10.1, 10.8.3
lambda expressions and 6.2.3
`run` method 6.2.9, 10.8.3
`Runtime` class
analyzing objects at 5.10.5
creating classes at 6.5.1
`exec` method 10.8
setting the size of an array at 5.3
type identification at 5.1.8, 5.10.1, 8.5.2
Runtime image file 12.15
`RuntimeException` class 7.1.1, 7.3, 7.6
Constructor 7.6

S

`S`, `s` conversion characters 3.7.2
Scala programming language 6.1.6
`Scanner` class 3.10.8
Constructor 3.10.8
`hasNext` method 3.10.8
`hasNextDouble` method 3.10.8

`hasNextInt` method 3.10.8
`next` method 3.10.8
`nextDouble` method 3.10.8
`nextInt` method 3.10.8
`nextLine` method 3.10.8
`nextXxx` methods 3.7.1
`ScopedValue` class 10.8.3
`get` method 10.8.3
`isBound` method 10.8.3
`newInstance` method 10.8.3
`orElse` method 10.8.3
`where` method 10.8.3
`ScopedValue.Carrier` class 10.4.5
`ScopedValue.Carrier` class, methods of 10.4.5
`sealed` keyword 5.8, 6.1.2, **Appendix**
`search`, `searchXxx` methods
of `ConcurrentHashMap` 10.6.4
`Security` class 1.2.5, 1.5
`SequencedCollection` interface 9.7.6
`addFirst` method 9.7.6
`addLast` method 9.7.6
`getFirst` method 9.7.6
`getLast` method 9.7.6
`removeFirst` method 9.7.6
`removeLast` method 9.7.6
`reversed` method 9.7.6
`SequencedMap` interface 9.7.6
`reversed` method 9.7.6
`SequencedSet` interface 9.7.6
`reversed` method 9.7.6
Serialization 9.4.7
Service loaders 6.4, 12.14
`ServiceLoader` class 6.4, 6.5.3, 12.14
`findFirst` method 6.5.3
`iterator` method 6.5.3
`load` method 6.5.3
`stream` method 6.4, 6.5.3
`ServiceLoader.Provider` interface 6.5.3
`get` method 6.5.3
`type` method 6.5.3
`ServiceLoader.Provider` interface, methods of 6.4
Services 6.4
ServletException 7.2.3
Servlets 7.2.3
`Set` interface 9.7.6
`add`, `equals`, `hashCode`, methods of 9.2
`copyOf` method 9.5.2, 9.7.6
`of` method 9.5.1, 9.7.6
`set` method
of `Array` 5.11
of `ArrayList` 5.3.2, 5.11
of `BitSet` 9.7.6
of `Field` 5.11
of `List` 9.2, 9.7.6
of `ListIterator` 9.3.1, 9.7.6
of `ThreadLocal` 10.8.3
of `Vector` 10.5.7
`setAccessible` method 5.10.5
of `AccessibleObject` 5.11
`setClassAssertionStatus` method
of `ClassLoader` 7.6
`setDaemon` method 10.3.3
of `Thread` 10.8.3
`setDefaultAssertionStatus` method
of `ClassLoader` 7.6
`setDefaultUncaughtExceptionHandler` method 7.6, 10.3.5
of `Thread` 10.8.3
`setFilter` method
of `Handler` 7.6
`setFormatter` method
of `Handler` 7.6
`setLabelTable` method 8.2.4
`setLevel` method
of `Handler` 7.6
`setName` method
of `Thread` 10.8.3
`setOut` method 4.4.2
`setPackageAssertionStatus` method
of `ClassLoader` 7.6
`setPriority` method
of `Thread` 10.8.3
`setProperty` method 7.5.4
of `Properties` 9.7.6
Sets 9.3.3
concurrent 10.6.2
intersecting 9.6.5

mutating elements of 9.3.3
subranges of 9.5.3
thread-safe 10.6.5
with given elements 9.5.1
`setTime` method 5.1.7
`setUncaughtExceptionHandler` method
of `Thread` 10.8.3
`setValue` method
of `Map.Entry` 9.7.6
`setXxx` method
of `Array` 5.11
Shallow copies 6.1.9
Shell
scripts for, generating 11.5.3
scripts in 4.8.10
Shift operators 3.5.10
`Short` class 5.11
converting from `short` 5.4
`hashCode` method 5.11
`short` type 3.3.1, Appendix
`showMessageDialog` method
of `JOptionPane` 6.5.3
`shuffle` method
of `Collections` 9.6.2, 9.7.6
Shuffling 9.6.2
`shutdown` method
of `ExecutorService` 10.4.2, 10.8.3
`shutdownNow` method 10.4.2
of `ExecutorService` 10.8.3
Sieve of Eratosthenes benchmark 9.7.6
`signal` method
of `Condition` 10.5.4, 10.5.5, 10.8.3
`signalAll` method 10.5.4, 10.5.5
of `Condition` 10.8.3
Signatures (of methods) 4.6.1, 5.1.6
Signatures. See Digital signatures
Simple name 4.8.3
of enumeration 5.7
`sin` method
of `Math` 3.5.2
`singleton` method
of `Collections` 9.7.6
`singletonList` method
of `Collections` 9.7.6
Size
of concurrent collections 10.6.2
`size` method
of `ArrayList` 5.3.1, 5.11
of `BitSet` 9.7.6
of `Collection` 9.1.4, 9.7.6
`sleep` method
of `Thread` 10.1, 10.3.2, 10.8.3
SLF4J 7.5.1
Smart cards 1.2.1
SOAP 12.1
`SocketHandler` class 7.5.5
`sort` method
of `Arrays` 3.10.6, 3.10.8, 6.1.1, 6.2.1, 6.2.3, 6.5.3
of `Collections` 9.6.2, 9.7.6
of `List` 9.7.6
`SortedMap` interface 9.2, 9.7.6
`comparator` method 9.7.6
`firstKey` method 9.7.6
`headMap` method 9.7.6
`headMap`, `subMap`, `tailMap` methods 9.5.3
`lastKey` method 9.7.6
`subMap` method 9.7.6
`tailMap` method 9.7.6
`SortedSet` interface 9.2, 9.7.6
`comparator` method 9.7.6
`first` method 9.7.6
`headSet` method 9.7.6
`headSet`, `subSet`, `tailSet` methods 9.5.3
`last` method 9.7.6
`subSet` method 9.7.6
`tailSet` method 9.7.6
Sorting
algorithms for 3.10.6, 9.6.2
arrays 3.10.6, 6.1.1
assertions for 7.4.3
order of 9.6.2
people, by name 6.2.10
strings by length 6.1.8, 6.2.1, 6.2.2
Source code, generating 11.3, 11.3.1, 11.5.3
Source file
compact 4.8.4
Source files 4.8.9
installing 2.1.3

running in Eclipse 2.3
Space. See Whitespace
Special characters 3.3.3
Split packages 12.6
`sqrt` method
of `BigInteger` 3.10.8
of `Math` 3.5.2, 5.10.7
`src.zip` file 2.1.3
`Stack` class 9.1, 9.7, 9.7.5, 9.7.6
`peek` method 9.7.6
`pop` method 9.7.6
`push` method 9.7.6
Stack trace 7.2.6, 10.5.5
no displaying to users 7.3
StackFrame
`toString` method 7.2.6
Stacks 9.7.5
`stackSize` method
of `Thread.Builder.OfPlatform` 10.8.3
`StackTraceElement` class 7.6
`getClassName` method 7.6
`getFileName` method 7.6
`getLineNumber` method 7.6
`getMethodName` method 7.6
`isNativeMethod` method 7.6
`toString` method 7.6
`StackWalker` class 7.2.6, 7.6
`forEach` method 7.6
`getInstance` method 7.2.6, 7.6
`walk` method 7.2.6, 7.6
`StackWalker.StackFrame` interface 7.6
`getClassName` method 7.6
`getDeclaringClass` method 7.6
`getFileName` method 7.6
`getLineNumber` method 7.6
`getMethodName` method 7.6
`isNativeMethod` method 7.6
`toString` method 7.6
Standard Edition 1.4, 2.1.1
Standard Java library
companion classes in 6.1.4
online API documentation for 3.6.7, 3.6.8, 4.10, 4.10.10
Standard Template Library (STL) 9.1, 9.1.3
`start` method
of `ProcessBuilder` 10.8.2, 10.8.3
of `Thread` 10.1, 10.2.2, 10.8.3
of `Thread.Builder` 10.8.3
of `Timer` 6.5.3
`startInstant` method
of `ProcessHandle.Info` 10.8.3
`startPipeline` method 10.8.1
of `ProcessBuilder` 10.8.3
`startsWith` method
of `String` 3.10.8
`startVirtualThread` method
of `Thread` 10.8.3
`state` method
of `Future` 10.8.3
Statements 3.1
conditional 3.8.2
in output 3.6.1
Static binding 5.1.6
Static constants 4.4.2
documentation comments for 4.10.4
Static fields 4.4.1
accessing, in static methods 4.4.3
importing 4.8.5
initializing 4.6.8
no type variables in 8.5.8
Static imports 4.8.5
`static` keyword 4.4, 12.11, **Appendix**
for fields in interfaces 6.1.2
Static method 3.6.2
Static methods 4.4.3
accessing static fields in 4.4.3
adding to interfaces 6.1.4
importing 4.8.5
no type variables in 8.5.8
Static nested classes 6.3, 6.3.7
Static variables 4.4.2
`stop` method
of `Thread` 10.3.2, 10.8.3
of `Timer` 6.5.3
`store` method
of `Properties` 9.7.3, 9.7.6
`Stream` interface, `toArray` method 6.2.6
`stream` method

of `BitSet` 9.7.6
of `Collection` 6.1.5
of `ServiceLoader` 6.4, 6.5.3
`strictfp` keyword Appendix
`StrictMath` class 3.5.2
`String`
`formatted` method 5.5
`String` class 3.6, 3.10.8
`charAt` method 3.6.3, 3.10.8
`compareTo` method 3.10.8
`endsWith` method 3.10.8
`equals` method 3.10.8
`equals`, `equalsIgnoreCase` methods 3.6.5
`equalsIgnoreCase` method 3.10.8
`hashCode` method 5.2.4, 9.3.3
immutability of 3.6.4, 4.3.10, 5.1.7
implementing `CharSequence` 6.1.3
`indexOf` method 3.10.8, 4.6.1
`isEmpty` method 3.10.8
`join` method 3.10.8
`lastIndexOf` method 3.10.8
`length` method 3.6.3, 3.6.6, 3.10.8
`repeat` method 3.6.1, 3.10.8
`replace` method 3.10.8
`startsWith` method 3.10.8
`strip` method 3.10.8
`substring` method 3.6.3, 3.10.8, 9.5.3
`toLowerCase` method 3.10.8
`toUpperCase` method 3.10.8
`transform` method 6.2.9
`StringBuffer` class 3.6.9
`StringBuilder` class 3.6.9, 3.10.8
`append` method 3.6.9, 3.10.8
`appendCodePoint` method 3.10.8
Constructor 3.10.8
`delete` method 3.10.8
implementing `CharSequence` 6.1.3
`insert` method 3.10.8
`length` method 3.10.8
`repeat` method 3.10.8
`reverse` method 3.10.8
`toString` method 3.6.9, 3.10.8
`stringPropertyNames` method
of `Properties` 9.7.6
Strings 3.6
building 3.6.9
code points/code units of 3.6.3
comparing 6.1.8
concatenating 3.6.1
with objects 5.2.5
converting to numbers 5.4
empty 3.6.6
equality of 3.6.5
formatting output for 3.7.2
immutability of 3.6.4
length of 3.6.3, 3.6.6
null 3.6.6
shared, in compiler 3.6.4, 3.6.5
sorting by length 6.1.8, 6.2.1, 6.2.2
spanning multiple lines 3.6.10
substrings of 3.6.3
using `". . ."` for 3.1
`strip` method
of `String` 3.10.8
Strongly typed languages 3.3, 6.1.1
Subclasses 5.1
adding fields/methods to 5.1.2
anonymous 6.3.6
cloning 6.1.9
comparing objects from 6.1.1
constructors for 5.1.3
defining 5.1.1
forbidding 5.8
inheriting annotations 11.3
method visibility in 5.1.6
no access to private fields of superclass 5.1.10
non-sealed 5.8
overriding superclass methods in 5.1.2
`subList` method
of `List` 9.5.3, 9.7.6
`subMap` method
of `NavigableMap` 9.7.6
of `SortedMap` 9.5.3, 9.7.6
`submit` method
of `ExecutorCompletionService` 10.8.3
of `ExecutorService` 10.4.2, 10.8.3
Subranges 9.5.3
`subSet` method

of `NavigableSet` 9.5.3, 9.7.6
of `SortedSet` 9.5.3, 9.7.6
Substitution principle 5.1.5
`substring` method
of `String` 3.6.3, 3.10.8, 9.5.3
`subtract` method
of `BigDecimal` 3.10.8
of `BigInteger` 3.10.8
`subtractExact` method 3.5.2
Subtraction 3.5.1
`sum` method
of `LongAdder` 10.5.11
Sun Microsystems 1.1, 1.2.5, 1.4, 1.5
HotJava browser 1.4
`super` keyword 5.1.2, 8.4.2, Appendix
in method references 6.2.5
vs. `this` 5.1.2, 5.1.3
Superclass wins rule 6.1.6
Superclasses 5.1
accessing private fields of 5.1.2
annotating 11.1.4
common fields and methods in 5.6, 5.11
overriding methods of 5.2.3
`throws` specifiers in 7.1.2, 7.2.1
Supertype bounds 8.4.2
`Supplier` interface 6.2.9
`supportsNormalTermination` method
of `Process` 10.8.3
Surrogates area (Unicode) 3.3.4
`suspend` method
of `Thread` 10.8.3
`swap` method
of `Collections` 9.7.6
Swing 10.7.3
`SwingWorker` class 10.7.3, 10.8.3
`doInBackground` method 10.7.3, 10.8.3
`execute` method 10.7.3, 10.8.3
`getState` method 10.8.3
`process` method 10.8.3
`process`, `publish` methods 10.7.3
`publish` method 10.8.3
`switch` keyword 3.5.9, 3.8.5, Appendix
enumerated constants in 3.5.9
throwing exceptions in 3.8.5
value of 3.5.9
with fallthrough 3.8.5
with pattern matching 5.8
Synchronization 10.5
condition objects for 10.5.4
final fields and 10.5.10
in `Vector` 9.3.2
lock objects for 10.5.3
monitor concept for 10.5.8
race conditions in 10.5.1, 10.5.2, 10.5.11
volatile fields and 10.5.9
Synchronization wrappers 10.6.8
Synchronized blocks 10.5.7
`synchronized` keyword 10.5.3, 10.5.6, 10.5.8, Appendix
Synchronized views 9.5.7
`synchronizedCollection` method
of `Collections` 9.7.6, 10.8.3
`synchronized`Collection methods (`Collections`) 9.5.7
`synchronizedList` method
of `Collections` 9.7.6, 10.8.3
`synchronizedMap` method
of `Collections` 9.7.6, 10.8.3
`synchronizedNavigableMap` method
of `Collections` 9.7.6
`synchronizedNavigableSet` method
of `Collections` 9.7.6
`synchronizedSet` method
of `Collections` 9.7.6, 10.8.3
`synchronizedSortedMap` method
of `Collections` 9.7.6, 10.8.3
`synchronizedSortedSet` method
of `Collections` 9.7.6, 10.8.3
`System` class 3.10.8, 5.11, 9.7.6
`console` method 3.10.8
`getLogger` method 7.5.2, 7.5.3
`getProperties` method 9.7.4, 9.7.6
`getProperty` method 9.7.4, 9.7.6
`identityHashCode` method 5.11, 9.4.7, 9.7.6
`setOut` method 4.4.2
`setProperty` method 7.5.4
`System.err` 7.5.5, 7.6
`System.in` 3.7.1

`System.Logger` interface 7.5.2, 7.6
`getName` method 7.6
`isLoggable` method 7.6
`log` method 7.6
`System.Logger.Level` enumeration 7.5.3
`System.Logger log` method
`log` method
`log` methodof `System.Logger` 7.5.2
`System.out` 4.4.2

T

`T`, `t` conversion characters 3.7.2
Tab completion 2.4
Tabs, in text blocks 3.6.10
Tagging interfaces 6.1.9, 9.2
`tailMap` method
of `NavigableMap` 9.7.6
of `SortedMap` 9.5.3, 9.7.6
`tailSet` method
of `NavigableSet` 9.5.3, 9.7.6
of `SortedSet` 9.5.3, 9.7.6
`take` method
of `BlockingQueue` 10.6.1, 10.8.3
of `ExecutorCompletionService` 10.8.3
`takeFirst` method
of `BlockingDeque` 10.8.3
`takeLast` method
of `BlockingDeque` 10.8.3
`tan` method
of `Math` 3.5.2
`tar` command 4.9.1
Tasks
asynchronously running 10.4.1
controlling groups of 10.4.3
decoupling from mechanism of running 10.1
long-running 10.7.3
multiple 10
work stealing for 10.4.6
`TAU`
of `Math` 3.5.2
Terminal window 2.2
Text blocks 3.6.10
`thenAccept`, `thenAcceptBoth`, `thenCombine` methods
of `CompletableFuture` 10.7.2
`thenApply`, `thenApplyAsync` methods
of `CompletableFuture` 10.7.2
`thenComparing` method 6.2.10
`thenCompose` method 10.7.2
`thenRun` method 10.7.2
`this` keyword 4.3.6, 4.6.5, **Appendix**
annotating 11.1.5
in body of constructor 4.6.6
in inner classes 6.3.2
in lambda expressions 6.2.8
in method references 6.2.5
vs. `super` 5.1.2, 5.1.3
`Thread` class 10.8.3
Constructor 10.8.3
`currentThread` method 10.3.2, 10.8.3
extending 10.1
`getDefaultUncaughtExceptionHandler` method 10.8.3
`getName` method 10.8.3
`getState` method 10.8.3
`getUncaughtExceptionHandler` method 10.8.3
`interrupt` method 10.8.3
`interrupt`, `isInterrupted` methods 10.3.2
`interrupted` method 10.3.2, 10.8.3
`isInterrupted` method 10.8.3
`isVirtual` method 10.8.3
`join` method 10.2.3, 10.8.3
`MAX_PRIORITY` field 10.8.3
methods with timeout 10.2.3
`MIN_PRIORITY` field 10.8.3
`NORM_PRIORITY` field 10.8.3
`ofPlatform` method 10.8.3
`ofVirtual` method 10.8.3
`resume` method 10.8.3
`run` method 10.1, 10.8.3
`setDaemon` method 10.3.3, 10.8.3
`setDefaultUncaughtExceptionHandler` method 7.6, 10.3.5, 10.8.3
`setName` method 10.8.3
`setPriority` method 10.8.3
`setUncaughtExceptionHandler` method 10.8.3
`sleep` method 10.1, 10.3.2, 10.8.3

`start` method 10.1, 10.2.2, 10.8.3
`startVirtualThread` method 10.3.1, 10.8.3
`stop` method 10.3.2, 10.8.3
`suspend` method 10.8.3
`threadId` method 10.8.3
`yield` method 10.8.3
Thread dump 10.5.5
Thread groups 10.3.5
Thread pools 10.4.2
Thread-safe collections 10.6
callables and futures 10.4.1
concurrent 10.6.2
copy on write arrays 10.6.6
synchronization wrappers 10.6.8
`Thread.Builder` interface 10.8.3
`factory` method 10.8.3
`name` method 10.8.3
`start` method 10.8.3
`uncaughtExceptionHandler` method 10.8.3
`unstarted` method 10.8.3
`Thread.Builder.OfPlatform` interface 10.8.3
`daemon` method 10.8.3
`group` method 10.8.3
`priority` method 10.8.3
`stackSize` method 10.8.3
`Thread.UncaughtExceptionHandler` interface 10.3.5, 10.8.3
`uncaughtException` method 10.8.3
`ThreadFactory` interface 10.8.3
`newThread` method 10.8.3
`ThreadGroup` class 10.8.3
`uncaughtException` method 10.8.3
`threadId` method
of `Thread` 10.8.3
`ThreadLocal` class 10.8.3
`get` method 10.8.3
`remove` method 10.8.3
`set` method 10.8.3
`withInitial` method 10.8.3
`ThreadLocalRandom` class 10.8.3
`current` method 10.8.3
`ThreadPoolExecutor` class 10.4.2
Threads
accessing collections from 9.5.7, 10.6
blocked 10.2.3, 10.3.2
condition objects for 10.5.4
daemon 10.3.3
executing code in 6.2.9
idle 10.4.6
interrupting 10.3.2
listing all 10.5.5
locking 10.5.7
new 10.2.1
priorities of 10.3.6
producer/customer 10.6.1
runnable 10.2.2
states of 10.2
synchronizing 10.5
terminated 10.1, 10.2.4, 10.3.2
thread-local variables in 10.5.14
timed waiting 10.2.3
unblocking 10.5.4
uncaught exceptions in 10.3.5
waiting 10.2.3, 10.5.4
work stealing for 10.4.6
worker 10.7.3
`throw` keyword 7.1.3, **Appendix**
`Throwable` class 5.11, 7.1.1, 7.3, 7.6
`add/getSuppressed` methods 7.2.5
`addSuppressed` method 7.6
Constructor 7.6
`getCause` method 7.6
`getMessage` method 7.6
`getStackTrace` method 7.2.6, 7.6
`getSuppressed` method 7.6
`initCause` method 7.6
`printStackTrace` method 5.11, 7.2.6, 7.6
`toString` method 7.1.4
`throws` keyword 5.10.2, 7.1.2, **Appendix**
Time measurement vs. calendars 4.2.2
Timed waiting threads 10.2.3
`TimeoutException` class 10.4.1, 10.7.2
`Timer` class 6.1.7, 6.2.1, 6.5.3
Constructor 6.5.3
`start` method 6.5.3
`stop` method 6.5.3
`to` keyword **Appendix**
`toArray` method

of `ArrayList` 8.5.7
of `Collection` 5.3.2, 9.1.4, 9.6.6, 9.7.6
of `Stream` 6.2.6
`toHandle` method 10.8.3
of `Process` 10.8.3
`toLowerCase` method
of `String` 3.10.8
`Toolkit` class 6.5.3
`beep` method 6.5.3
`getDefaultToolkit` method 6.5.3
`toString` method
adding to all classes 5.2.5
`Formattable` and 3.7.2
of `Annotation` 11.6.2
of `Arrays` 3.10.3, 3.10.8
of `Date` 4.2.1
of `Enum` 5.7
of `Integer` 5.11
of `Modifier` 5.10.4, 5.11
of `Object` 5.2.5, 5.11, 6.1.6
of proxy classes 6.5.3
of records 4.7.1, 5.2.5
of `StackFrame` 7.2.6
of `StackTraceElement` 7.6
of `StackWalker.StackFrame` 7.6
of `StringBuilder` 3.6.9, 3.10.8
of `Throwable` 7.1.4
redeclaring 6.2.3
working with any class 5.10.5
Total ordering 9.3.4
`totalCpuDuration` method
of `ProcessHandle.Info` 10.8.3
`toUnsignedInt` method 3.3.1
`toUpperCase` method
of `String` 3.10.8
TraceHandler 6.5.2
`transfer` method
of `TransferQueue` 10.8.3
`TransferQueue` interface 10.6.1, 10.8.3
`transfer` method 10.8.3
`tryTransfer` method 10.8.3
Transform 6.2.9
`transform` method
of `String` 6.2.9
`transient` keyword Appendix
`transitive` keyword 12.11, Appendix
Tree maps 9.4.1
Tree sets 9.3.4
red-black 9.3.4
total ordering of 9.3.4
vs. priority queues 9.3.6
`TreeMap` class 9.2, 9.4.1, 9.7.6
as a concrete collection type 9.3
Constructor 9.7.6
vs. `HashMap` 9.4.1
`TreeSet` class 9.2, 9.3.4, 9.7.6
as a concrete collection type 9.3
Constructor 9.7.6
Trigonometric functions 3.5.2
`trimToSize` method 5.3.1
of `ArrayList` 5.11
Troubleshooting. See Debugging
`true` literal Appendix
`try` keyword Appendix
`try`-with-resources statement 7.2.5
effectively final variables in 7.2.5
no locks with 10.5.3
`try`/`catch` 7.2.1, 7.2.3
generics and 8.1.6
wrapping entire task in `try` block 7.3
`try`/`finally` 7.2.4
`tryLock` method 10.2.3
`trySetAccessible` method
of `AccessibleObject` 5.11
`tryTransfer` method
of `TransferQueue` 10.8.3
Two-dimensional arrays 3.10.7, 3.10.8
Type bounds
annotating 11.1.4
Type erasure 8.2.1, 8.5.1
clashes after 8.5.10
`Type` interface 8.6.3
`type` method
of `ServiceLoader.Provider` 6.4, 6.5.3
Type parameters 5.3
annotating 11.1.3
converting to raw types 8.3
not for arrays 8.3, 8.5.3

not instantiated with primitive types 8.5.1
vs. inheritance 8.1
Type variables
bounds for 8.1.5
common names of 8.1.3
in exceptions 8.1.6
in static fields or methods 8.5.8
matching in generic methods 8.6.2
no instantiating for 8.5.6
replacing with bound types 8.2.1
`TypeElement` interface 11.5.2
Types. See Data types
`TypeVariable` interface 8.6.3, 8.6.4
`getBounds` method 8.6.4
`getName` method 8.6.4

U

UCSD Pascal system 1.2.6
UML (Unified Modeling Language) notation 4.1.4
`UnaryOperator` interface 6.2.9
`uncaughtException` method
of `Thread.UncaughtExceptionHandler` 10.8.3
of `ThreadGroup` 10.8.3
`uncaughtExceptionHandler` method
of `Thread.Builder` 10.8.3
Unchecked exceptions 5.10.2, 7.1.1, 7.1.2
applicability of 7.3
Unequality operator 3.5.7
Unicode 1.2.7, 3.3.3, 3.3.4, 3.6
Unit tests 11
University of Illinois 1.4
UNIX 4.8.9, 4.8.10
`unlock` method
of `Lock` 10.5.3, 10.8.3
Unmodifiable copies 9.5.2
Unmodifiable views 9.5.2
`unmodifiableCollection` method
of `Collections` 9.7.6
`unmodifiable`Collection methods (`Collections`) 9.5.2
`unmodifiableList` method
of `Collections` 9.7.6
`unmodifiableMap` method
of `Collections` 9.7.6
`unmodifiableNavigableMap` method
of `Collections` 9.7.6
`unmodifiableNavigableSet` method
of `Collections` 9.7.6
`unmodifiableSequencedCollection` method
of `Collections` 9.7.6
`unmodifiableSequencedMap` method
of `Collections` 9.7.6
`unmodifiableSequencedSet` method
of `Collections` 9.7.6
`unmodifiableSet` method
of `Collections` 9.7.6
`unmodifiableSortedMap` method
of `Collections` 9.7.6
`unmodifiableSortedSet` method
of `Collections` 9.7.6
Unnamed modules 5.10.5
Unnamed packages 4.8.6, 4.8.8, 4.10.10, 7.4.2
`unstarted` method
of `Thread.Builder` 10.8.3
`UnsupportedOperationException` class 9.4.3, 9.5.1, 9.5.2, 9.5.8
`updateAndGet` method
of `AtomicXxx` 10.5.11
User input 7.1
User Interface. See Graphical User Interface
`user` method
of `ProcessHandle.Info` 10.8.3
User-defined types 5.4
`uses` keyword 12.14, **Appendix**
UTC (Coordinated Universal Time) 4.2.2
Utility classes/methods 6.1.4, 6.1.5

V

`V>` method
of `ConcurrentHashMap` 10.8.3
of `ConcurrentSkipListMap` 10.8.3
`valueOf` method
of `BigInteger` 3.9, 3.10.8
of `Enum` 5.7, 5.11
of `Integer` 5.11
`values` method
of `Map` 9.4.3, 9.7.6
`var` keyword 4.3.4, 6.2.2, 6.3.6, **Appendix**
diamond syntax and 5.3.1

Varargs methods 5.5
passing generic types to 8.5.4
Varargs parameters
safety of 11.3, 11.3.1
`VarHandle` class 5.10.5, 12.7
Variable handles 5.10.5, 12.7
`VariableElement` interface 11.5.2
Variables 3.4.1
accessing
from outer methods 6.3.5
in lambda expressions 6.2.7
annotating 8.2.4
copying 6.1.9
declarations of 3.4.1, 5.1.9
deprecated 11.3, 11.3.1
effectively final 6.2.7, 7.2.5
initializing 3.4.2, 4.11
local 4.3.4, 5.1.9, 8.2.4
mutating in lambda expressions 6.2.7
names of 3.4.1
package scope of 4.8.8
printing/logging values of 7.6
static 4.4.2
thread-local 10.5.14
`Vector` class 9.1, 9.7, 9.7.2, 10.5.7, 10.6.8
for dynamic arrays 5.3.1
`get`, `set` methods 10.5.7
synchronization in 9.3.2
Views 9.5
bulk operations for 9.6.5
checked 9.5.6
restricted 9.5.8
subranges of 9.5.3
synchronized 9.5.7
unmodifiable 9.5.2
Visual Basic
built-in date type in 4.2.1
syntax of 1.2.1
Visual Studio 2.2
`void` keyword Appendix
Volatile fields 10.5.9
`volatile` keyword 10.5.9, 10.5.11, Appendix
Von der Ahé, Peter 8.1.4

W

`wait` method
of `Object` 10.2.3, 10.5.6, 10.8.3
Wait sets 10.5.4
`waitFor` method 10.8.2
of `Process` 10.8.3
`walk` method
of `StackWalker` 7.2.6, 7.6
Warning messages 11.3
Warning messages, suppressing 11.3.1
Warnings
fallthrough behavior and 3.8.5
generic 5.3.3, 8.2.4, 8.5.4, 8.5.9
suppressing 8.5.4, 8.5.9
Weak hash maps 9.4.4
Weak references 9.4.4
`WeakHashMap` class 9.4.4, 9.7.6
as a concrete collection type 9.3
Constructor 9.7.6
Weakly consistent iterators 10.6.2
`WeakReference` class 9.4.4
Web pages
dynamic 1.3
extracting links from 10.7.2
reading 10.7.3
`whenComplete` method
of `CompletableFuture` 10.7.2
`where` method
of `ScopedValue` 10.4.5, 10.8.3
`while` keyword 3.8.3, Appendix
Whitespace
escape sequence for 3.3.3, 3.6.10
in text blocks 3.6.10
irrelevant to compiler 3.1
leading/trailing 3.6.10
Wildcard types 8.1.2, 8.4
annotating 11.1.4
arrays of 8.5.3
capturing 8.4.4
supertype bounds for 8.4.2
unbounded 8.4.3
`WildcardType` interface 8.6.3, 8.6.4
`getLowerBounds` method 8.6.4
`getUpperBounds` method 8.6.4

Windows
changing warning string in 4.8.8
Windows operating system
executing JARs in 4.9.3
IDEs for 2.3
JDK in 2.1
paths in 4.8.9, 4.8.10
thread priority levels in 10.3.6
Wirth, Niklaus 1.2.6, 1.4, 4.1
`with` keyword Appendix
`withInitial` method
of `ThreadLocal` 10.8.3
Work stealing 10.4.6
Worker threads 10.7.3
Working directory, for a process 10.8.1
Wrappers 5.4
class constructors for 5.4
equality testing for 5.4
immutability of 5.4
locks and 5.4, 10.5.7

X

`X`, `x` conversion characters 3.7.2
XML 1.4, 1.5
XML descriptors, generating 11.5.3
XML/JSON binding 12.7
`xor` method
of `BitSet` 9.7.6

Y

Yasson 12.7
`yield` keyword 3.8.5, Appendix
`yield` method
of `Thread` 10.8.3

Z

ZIP archives
for JMOD files 12.15
ZIP format 4.8.9, 4.9

Previous chapter
‹ Appendix

Next chapter
Core Java, Vol. I: Fundamentals, 14th Edition ›