Chapter 1. Streams

In this chapter

- 1.1 From Iterating to Stream Operations
- 1.2 Stream Creation
- 1.3 The `filter`, `map`, and `flatMap` Methods
- 1.4 Extracting Substreams and Combining Streams
- 1.5 Other Stream Transformations
- 1.6 Simple Reductions
- 1.7 The Optional Type
- 1.8 Collecting Results
- 1.9 Collecting into Maps
- 1.10 Grouping and Partitioning
- 1.11 Downstream Collectors
- 1.12 Reduction Operations
- 1.13 Primitive Type Streams
- 1.14 Parallel Streams

Compared to collections, streams provide a view of data that lets you specify computations at a higher conceptual level. With a stream, you specify what you want to have done, not how to do it. You leave the scheduling of operations to the implementation. For example, suppose you want to compute the average of a certain property. You specify the source of data and the property, and the stream library can then optimize the computation, for example by using multiple threads for computing sums and counts and combining the results.

In this chapter, you will learn how to use the Java stream library, which was introduced in Java 8, to process collections in a "what, not how" style.

1.1 From Iterating to Stream Operations

When you process a collection, you usually iterate over its elements and do some work with each of them. For example, suppose we want to count all long words in a book. First, let's put them into a list:

Click here to view code image

```
var contents =  Files.readString(Path.of("alice.txt")); // Read file into string
List<String> words = List.of(contents.split("\\PL+"));
  // Split into words; nonletters are delimiters
```

Now we are ready to iterate:

Click here to view code image

```
int count = 0;
for (String w : words)
{
  if (w.length() > 12) count++;
}
```

With streams, the same operation looks like this:

Click here to view code image

```
long count = words.stream()
  .filter(w -> w.length() > 12)
  .count();
```

Now you don't have to scan the loop for evidence of filtering and counting. The method names tell you right away what the code intends to do. Moreover, where the loop prescribes the order of operations in complete detail, a stream is able to schedule the operations any way it wants, as long as the result is correct.

Simply changing `stream` to `parallelStream` allows the stream library to do the filtering and counting in parallel.

Click here to view code image

```
long count = words.parallelStream()
  .filter(w -> w.length() > 12)
  .count();
```

Streams follow the "what, not how" principle. In our stream example, we describe what needs to be done: get the long words and count them. We don't specify in which order, or in which thread, this should happen. In contrast, the loop at the beginning of this section specifies exactly how the computation should work, and thereby forgoes any chances of optimization.

A stream seems superficially similar to a collection, allowing you to transform and retrieve data. But there are significant differences:

1. A stream does not store its elements. They may be stored in an underlying collection or generated on demand.
2. Stream operations don't mutate their source. For example, the `filter` method does not remove elements from a stream but yields a new stream in which they are not present.
3. Stream operations are *lazy* when possible. This means they are not executed until their result is needed. For example, if you only ask for the first five long words instead of all, the `filter` method will stop filtering after the fifth match. As a conse-

quence, you can even have infinite streams!

Let us have another look at the example. The `stream` and `parallelStream` methods yield a *stream* for the `words` list. The `filter` method returns another stream that contains only the words of length greater than 12. The `count` method reduces that stream to a result.

This workflow is typical when you work with streams. You set up a pipeline of operations in three stages:

1. Create a stream.
2. Specify *intermediate operations* for transforming the initial stream into others, possibly in multiple steps.
3. Apply a *terminal operation* to produce a result. This operation forces the execution of the lazy operations that precede it. Afterwards, the stream can no longer be used.

In the example in **Listing 1.1**, the stream is created with the `stream` or `parallelStream` methods. The `filter` method transforms it, and `count` is the terminal operation.

In the next section, you will see how to create a stream. The subsequent three sections deal with stream transformations. They are followed by five sections on terminal operations.

Listing 1.1 streams/CountLongWords.java

Click here to view code image

```
1  package streams;
2
3  import java.io.*;
4  import java.nio.file.*;
5  import java.util.*;
6
7  /**
```

```
 8   * @version 1.02 2019-08-28
 9   * @author Cay Horstmann
10   */
11  public class CountLongWords
12  {
13     public static void main(String[] args) throws IOException
14     {
15        var contents = Files.readString(
16           Path.of("../gutenberg/alice30.txt"));
17        List<String> words = List.of(contents.split("\\PL+"));
18
19        long count = 0;
20        for (String w : words)
21        {
22           if (w.length() > 12) count++;
23        }
24        System.out.println(count);
25
26        count = words.stream().filter(w -> w.length() > 12).count();
27        System.out.println(count);
28
29        count = words.parallelStream().filter(w -> w.length() > 12).count();
30        System.out.println(count);
31     }
32  }
```

java.util.stream.Stream<T> 8

- `Stream<T> filter(Predicate<? super T> p)`
  yields a stream containing all elements of this stream fulfilling `p`.
- `long count()`

yields the number of elements of this stream. This is a terminal operation.

---

java.util.Collection<E> 1.2

- `default Stream<E> stream()`
- `default Stream<E> parallelStream()`

  yield a sequential or parallel stream of the elements in this collection.

1.2 Stream Creation

You have already seen that you can turn any collection into a stream with the `stream` method of the `Collection` interface. If you have an array, use the static `Stream.of` method instead.

Click here to view code image

```
Stream<String> words = Stream.of(contents.split("\\PL+"));
  // split returns a String[] array
```

The `of` method has a varargs parameter, so you can construct a stream from any number of arguments:

Click here to view code image

```
Stream<String> song = Stream.of("gently", "down", "the", "stream");
```

Use `Arrays.stream(array, from, to)` to make a stream from a part of an array.

To make a stream with no elements, use the static `Stream.empty` method:

Click here to view code image

```
Stream<String> silence = Stream.empty();
  // Generic type <String> is inferred; same as Stream.<String>empty()
```

The `Stream` interface has two static methods for making infinite streams. The `generate` method takes a function with no arguments (or, technically, an object of the `Supplier<T>` interface). Whenever a stream value is needed, that function is called to produce a value. You can get a stream of constant values as

Click here to view code image

```
Stream<String> echos = Stream.generate(() -> "Echo");
```

or a stream of random numbers as

Click here to view code image

```
Stream<Double> randoms = Stream.generate(Math::random);
```

To produce sequences such as `0 1 2 3 . . .`, use the `iterate` method instead. It takes a "seed" value and a function (technically, a `UnaryOperator<T>`) and repeatedly applies the function to the previous result. For example,

Click here to view code image

```
Stream<BigInteger> integers
  = Stream.iterate(BigInteger.ZERO, n -> n.add(BigInteger.ONE));
```

The first element in the sequence is the seed `BigInteger.ZERO`. The second element is `f(seed)` which yields `1` (as a big integer). The next element is `f(f(seed))` which yields `2`, and so on.

To produce a finite stream instead, add a predicate that specifies when the iteration should finish:

Click here to view code image

```
var limit = new BigInteger("10000000");
Stream<BigInteger> integers
  = Stream.iterate(BigInteger.ZERO,
    n -> n.compareTo(limit) < 0,
    n -> n.add(BigInteger.ONE));
```

As soon as the predicate rejects an iteratively generated value, the stream ends.

Finally, the `Stream.ofNullable` method makes a really short stream from an object. The stream has length 0 if the object is `null` or length 1 otherwise, containing just the object. This is mostly useful in conjunction with `flatMap`—see Section 1.7.7, "Turning an Optional into a Stream," on p. 23 for an example.



Note

A number of methods in the Java API yield streams. For example, the `String` class has a `lines` method that yields a stream of the lines contained in the string:

Click here to view code image

```
Stream<String> greetings = "Hello\nGuten Tag\nBonjour".lines()
```

The `Pattern` class has a method `splitAsStream` that splits a `CharSequence` by a regular expression. You can use the following statement to split a string into words:

Click here to view code image

```
Stream<String> words = Pattern.compile("\\PL+").splitAsStream(contents);
```

The `Scanner.tokens` method yields a stream of tokens of a scanner. Another way to get a stream of words from a string is

Click here to view code image

```
Stream<String> words = new Scanner(contents).tokens();
```

The static `Files.lines` method returns a `Stream` of all lines in a file:

Click here to view code image

```
try (Stream<String> lines = Files.lines(path))
{
  Process lines
}
```

To view the contents of one of the streams introduced in this section, use the `toList` method, which collects the stream's elements in a list. Like `count`, `toList` is a terminal operation. If the stream is infinite, first truncate it with the `limit` method:

Click here to view code image

```
System.out.println(Stream.generate(Math::random).limit(10).toList());
```



Note

If you have an `Iterable` that is not a collection, you can turn it into a stream by calling

Click here to view code image

```
StreamSupport.stream(iterable.spliterator(), false);
```

If you have an `Iterator` and want a stream of its results, use

Click here to view code image

```
StreamSupport.stream(Spliterators.spliteratorUnknownSize(
  iterator, Spliterator.ORDERED), false);
```



Caution

It is very important that you don't modify the collection backing a stream while carrying out a stream operation. Remember that streams don't collect their data—the data is always in a separate collection. If you modify that collection, the outcome of the stream operations becomes undefined. The JDK documentation refers to this requirement as *noninterference*.

To be exact, since intermediate stream operations are lazy, it is possible to mutate the collection up to the point where the terminal operation executes. For example, the following, while certainly not recommended, will work:

Click here to view code image

```
List<String> wordList = . . .;
Stream<String> words = wordList.stream();
wordList.add("END");
long n = words.distinct().count();
```

But this code is wrong:

Click here to view code image

```
Stream<String> words = wordList.stream();
words.forEach(s -> {if (s.length() < 12) wordList.remove(s);});
  // ERROR--interference
```

The example program in **Listing 1.2** shows the various ways of creating a stream.

Listing 1.2 streams/CreatingStreams.java

Click here to view code image

```
 1  package streams;
 2
 3  import java.io.*;
 4  import java.math.*;
 5  import java.nio.file.*;
 6  import java.util.*;
 7  import java.util.regex.Pattern;
 8  import java.util.stream.*;
 9
10 /**
11  * @version 1.03  2021-09-06
12  * @author Cay Horstmann
13  */
14 public class CreatingStreams
15 {
16     public static <T> void show(String title, Stream<T> stream)
17     {
18        final int SIZE = 10;
19        List<T> firstElements = stream
20           .limit(SIZE + 1)
21           .toList();
22        System.out.print(title + ": ");
23        for (int i = 0; i < firstElements.size(); i++)
24        {
25           if (i > 0) System.out.print(", ");
26           if (i < SIZE) System.out.print(firstElements.get(i));
27           else System.out.print("...");
28        }
29        System.out.println();
30     }
```

```
31
32      public static void main(String[] args) throws IOException
33      {
34         Path path = Path.of("../gutenberg/alice30.txt");
35         var contents = Files.readString(path);
36
37         Stream<String> words = Stream.of(contents.split("\\PL+"));
38         show("words", words);
39         Stream<String> song = Stream.of("gently", "down", "the", "stream");
40         show("song", song);
41         Stream<String> silence = Stream.empty();
42         show("silence", silence);
43
44         Stream<String> echos = Stream.generate(() -> "Echo");
45         show("echos", echos);
46
47         Stream<Double> randoms = Stream.generate(Math::random);
48         show("randoms", randoms);
49
50         Stream<BigInteger> integers = Stream.iterate(BigInteger.ONE,
51            n -> n.add(BigInteger.ONE));
52         show("integers", integers);
53
54         Stream<String> greetings = "Hello\nGuten Tag\nBonjour".lines();
55         show("greetings", greetings);
56
57         Stream<String> wordsAnotherWay = Pattern.compile("\\PL+").splitAsStream(contents);
58         show("wordsAnotherWay", wordsAnotherWay);
59
60         try (Stream<String> lines = Files.lines(path))
61         {
62            show("lines", lines);
63         }
```

```
64
65          Iterable<Path> iterable = FileSystems.getDefault().getRootDirectories();
66          Stream<Path> rootDirectories = StreamSupport.stream(iterable.spliterator(), false);
67          show("rootDirectories", rootDirectories);
68
69          Iterator<Path> iterator = Path.of("/usr/share/dict/words").iterator();
70          Stream<Path> pathComponents = StreamSupport.stream(Spliterators.spliteratorUnknownSize(
71             iterator, Spliterator.ORDERED), false);
72          show("pathComponents", pathComponents);
73       }
74    }
```

java.util.stream.Stream 8

- `static <T> Stream<T> of(T... values)`
  yields a stream whose elements are the given values.
- `static <T> Stream<T> empty()`
  yields a stream with no elements.
- `static <T> Stream<T> generate(Supplier<T> s)`
  yields an infinite stream whose elements are constructed by repeatedly invoking the function `s`.
- `static <T> Stream<T> iterate(T seed, UnaryOperator<T> f)`
- `static <T> Stream<T> iterate(T seed, Predicate<? super T> hasNext, UnaryOperator<T> f)`
  yield a stream whose elements are `seed`, `f` invoked on `seed`, `f` invoked on the preceding element, and so on. The first method yields an infinite stream. The stream of the second method comes to an end before the first element that doesn't fulfill the `hasNext` predicate.
- `static <T> Stream<T> ofNullable(T t)` 9
  returns an empty stream if `t` is `null` or a stream containing `t` otherwise.

java.util.Spliterators 8

- `static <T> Spliterator<T> spliteratorUnknownSize(Iterator<? extends T> iterator, int characteristics)`
  turns an iterator into a splittable iterator of unknown size with the given characteristics (a bit pattern containing constants such as `Spliterator.ORDERED`).

---

java.util.Arrays 1.2

- `static <T> Stream<T> stream(T[] array, int startInclusive, int endExclusive)` 8
  yields a stream whose elements are the specified range of the array.

---

java.lang.String

- `static Stream<String> lines()` 11
  yields a stream whose elements are the lines of this string.

---

java.util.regex.Pattern 1.4

- `Stream<String> splitAsStream(CharSequence input)` 8
  yields a stream whose elements are the parts of the input that are delimited by this pattern.

---

java.nio.file.Files 7

- `static Stream<String> lines(Path path)` 8
- `static Stream<String> lines(Path path, Charset cs)` 8

  yield a stream whose elements are the lines of the specified file, with the UTF-8 charset or the given charset.

---

java.util.stream.StreamSupport 8

- `static <T> Stream<T> stream(Spliterator<T> spliterator, boolean parallel)`

  yields a stream containing the values produced by the given splittable iterator.

---

java.lang.Iterable 5

- `Spliterator<T> spliterator()` 8

  yields a splittable iterator for this `Iterable`. The default implementation does not split and does not report a size.

---

java.util.Scanner 5

- `public Stream<String> tokens()` 9

  yields a stream of strings returned by calling the `next` method of this scanner.

---

java.util.function.Supplier<T> 8

- `T get()`
  supplies a value.

1.3 The `filter`, `map`, and `flatMap` Methods

A stream transformation produces a stream whose elements are derived from those of another stream. You have already seen the `filter` transformation that yields a new stream with those elements that match a certain condition. Here, we transform a stream of strings into another stream containing only long words:

Click here to view code image

```
List<String> words = . . .;
Stream<String> longWords = words.stream().filter(w -> w.length() > 12);
```

The argument of `filter` is a `Predicate<T>`—that is, a function from `T` to `boolean`.

Often, you want to transform the values in a stream in some way. Use the `map` method and pass the function that carries out the transformation. For example, you can transform all words to lowercase like this:

Click here to view code image

```
Stream<String> lowercaseWords = words.stream().map(String::toLowerCase);
```

Here, we used `map` with a method reference. Often, you will use a lambda expression instead:

Click here to view code image

```
Stream<String> firstLetters = words.stream().map(s -> s.substring(0, 1));
```

The resulting stream contains the first letter of each word.

When you use `map`, a function is applied to each element, and the result is a new stream with the results. Occasionally, you are faced with a mapping function that generates an optional result, or more than one result. As an example, consider a method `codePoints` that yields all code points of a string. For example, `codePoints("Hello 🌐")` would consist of `"H"`, `"e"`, `"l"`, `"l"`, `"o"`, `" "`, `"🌐"`. Note that the globe symbol (U+1F310) consists of two `char` values, so the `codePoints` method has to do some heavy lifting to make this happen. We will look at a couple of implementations momentarily.

How should `codePoints` collect its multiple results? For the stream API, it is most natural if the method returns a `Stream<String>`.

Now let's map such a `codePoints` method on a stream of strings:

Click here to view code image

```
Stream<Stream<String>> result = words.stream().map(w -> codePoints(w));
```

You will get a stream of streams, like `[. . . ["y", "o", "u", "r"], ["b", "o", "a", "t"], . . .]`. To flatten it out to a single stream `[. . . "y", "o", "u", "r", "b", "o", "a", "t", . . .]`, use the `flatMap` method instead of `map`:

Click here to view code image

```
Stream<String> flatResult = words.stream().flatMap(w -> codePoints(w));
```

```
// Calls codePoints on each word and flattens the results
```

Now that you have seen how to use the `codePoints` method, how do you write it? The `String` class has a `codePoints` method that yields a stream of *integer* code points:

Click here to view code image

```
"Hello 🌐".codePoints() // A stream of integers 72, 101, 108, 108, 111, 32, 127760
```

Next, we need to transform each of the integers to a string containing the Unicode character with the given code point. Unfortunately, there is a technical difficulty. The `codePoints` method produces an `IntStream`, which is a little different from a `Stream<Integer>`, as you will see in Section 1.13, "Primitive Type Streams," on p. 43. Instead of `map`, you use the `mapToObj` method to transform the elements. Perhaps surprisingly, there is no convenient method for turning an integer codepoint into a string. Here is the best I could come up with:

Click here to view code image

```
public static Stream<String> codePoints(String s)
{
  return s.codePoints().mapToObj(cp -> new String(new int [] { cp }, 0, 1));
}
```

When using `flatMap`, you provide a method that produces a new stream for every stream element. As you have seen, that can be tedious. It can also be a little inefficient. The `mapMulti` method offers an alternative. Instead of producing a stream of results, you generate the results and pass them to a collector—an object of a class implementing the functional interface `Consumer`. For each result, invoke the collector's `accept` method.

Let's do this with an example. The following loop produces the code points of a string `s`:

Click here to view code image

```
int i = 0;
while (i < s.length())
{
  int cp = sentence.codePointAt(i);
  // Do something with cp
  if (Character.isSupplementaryCodePoint(cp)) i += 2;
  else i++;
}
```

When calling `mapMulti`, you provide a function that is invoked with the stream element and the collector. In your function, pass your results to the collector.

Click here to view code image

```
Stream<String> result = words.stream().mapMulti((s, collector) ->
  {
    int i = 0;
    while (i < s.length())
    {
      int cp = sentence.codePointAt(i);
      collector.accept(cp);
      if (Character.isSupplementaryCodePoint(cp)) i += 2;
      else i++;
    }
  });
```

java.util.stream.Stream 8

- `Stream<T> filter(Predicate<? super T> predicate)`
  yields a stream containing the elements of this stream that fulfill the predicate.
- `<R> Stream<R> map(Function<? super T,? extends R> mapper)`
  yields a stream containing the results of applying `mapper` to the elements of this stream.
- `<R> Stream<R> flatMap(Function<? super T,? extends Stream<? extends R>> mapper)`
  yields a stream obtained by concatenating the results of applying `mapper` to the elements of this stream. (Note that each `mapper` result is a stream.)
- `<R> Stream<R> mapMulti(BiConsumer<? super T,? super Consumer<R>> mapper)` 16
  For each stream element, the `mapper` is invoked, and all elements passed to the `Consumer` during invocation are added to the result stream.

1.4 Extracting Substreams and Combining Streams

The call *stream*.limit(n) returns a new stream that ends after `n` elements (or when the original stream ends if it is shorter). This method is particularly useful for cutting infinite streams down to size. For example,

Click here to view code image

```
Stream<Double> randoms = Stream.generate(Math::random).limit(100);
```

yields a stream with 100 random numbers.

The call *stream*.skip(n) does the exact opposite. It discards the first `n` elements. This is handy in our book reading example where, due to the way the `split` method works, the first element is an unwanted empty string. We can make it go away by calling

`skip`:

Click here to view code image

```
Stream<String> words = Stream.of(contents.split("\\PL+")).skip(1);
```

The *stream*.takeWhile(*predicate*) call takes all elements from the stream while the predicate is `true`, and then stops.

For example, suppose we use the `codePoints` method of the preceding section to split a string into characters, and we want to collect all initial digits. The `takeWhile` method can do this:

Click here to view code image

```
Stream<String> initialDigits = codePoints(str).takeWhile(
  s -> "0123456789".contains(s));
```

The `dropWhile` method does the opposite, dropping elements while a condition is `true` and yielding a stream of all elements starting with the first one for which the condition was `false`. For example,

Click here to view code image

```
Stream<String> withoutInitialWhiteSpace = codePoints(str).dropWhile(
  s -> s.strip().length() == 0);
```

You can concatenate two streams with the static `concat` method of the `Stream` class:

Click here to view code image

```
Stream<String> combined = Stream.concat(
  codePoints("Hello"), codePoints("World"));
  // Yields the stream ["H", "e", "l", "l", "o", "W", "o", "r", "l", "d"]
```

Of course, the first stream should not be infinite—otherwise the second one wouldn't ever get a chance.

---

java.util.stream.Stream 8

- `Stream<T> limit(long maxSize)`
  yields a stream with up to `maxSize` of the initial elements from this stream.
- `Stream<T> skip(long n)`
  yields a stream whose elements are all but the initial `n` elements of this stream.
- `Stream<T> takeWhile(Predicate<? super T> predicate)` 9
  yields a stream whose elements are the initial elements of this stream that fulfill the predicate.
- `Stream<T> dropWhile(Predicate<? super T> predicate)` 9
  yields a stream whose elements are the elements of this stream except for the initial ones that do not fulfill the predicate.
- `static <T> Stream<T> concat(Stream<? extends T> a, Stream<? extends T> b)`
  yields a stream whose elements are the elements of `a` followed by the elements of `b`.

1.5 Other Stream Transformations

The `distinct` method returns a stream that yields elements from the original stream, in the same order, except that duplicates are suppressed. The duplicates need not be adjacent.

Click here to view code image

```
Stream<String> uniqueWords
  = Stream.of("merrily", "merrily", "merrily", "gently").distinct();
  // Only one "merrily" is retained
```

For sorting a stream, there are several variations of the `sorted` method. One works for streams of `Comparable` elements, and another accepts a `Comparator`. Here, we sort strings so that the longest ones come first:

Click here to view code image

```
Stream<String> longestFirst
  = words.stream().sorted(Comparator.comparing(String::length).reversed());
```

As with all stream transformations, the `sorted` method yields a new stream whose elements are the elements of the original stream in sorted order.

Of course, you can sort a collection without using streams. The `sorted` method is useful when the sorting process is part of a stream pipeline.

Finally, the `peek` method yields another stream with the same elements as the original, but a function is invoked every time an element is retrieved. That is handy for debugging:

Click here to view code image

```
Object[] powers = Stream.iterate(1.0, p -> p * 2)
  .peek(e -> System.out.println("Fetching " + e))
  .limit(20).toArray();
```

When an element is actually accessed, a message is printed. This way you can verify that the infinite stream returned by `iterate` is processed lazily.

 **Tip**

When you use a debugger to debug a stream computation, you can set a breakpoint in a method that is called from one of the transformations. With most IDEs, you can also set breakpoints in lambda expressions. If you just want to know what happens at a particular point in the stream pipeline, add

Click here to view code image

```
.peek(x ->
  {
    return;
  })
```

and set a breakpoint on the second line.

---

java.util.stream.Stream 8

- `Stream<T> distinct()`
  yields a stream of the distinct elements of this stream.
- `Stream<T> sorted()`
- `Stream<T> sorted(Comparator<? super T> comparator)`

yield a stream whose elements are the elements of this stream in sorted order. The first method requires that the elements are instances of a class implementing `Comparable`.

- `Stream<T> peek(Consumer<? super T> action)`
  yields a stream with the same elements as this stream, passing each element to `action` as it is consumed.

1.6 Simple Reductions

Now that you have seen how to create and transform streams, we will finally get to the most important point—getting answers from the stream data. The methods covered in this section are called *reductions*. Reductions are *terminal operations*. They reduce the stream to a nonstream value that can be used in your program.

You have already seen a simple reduction: the `count` method that returns the number of elements of a stream.

Other simple reductions are `max` and `min` that return the largest or smallest value. There is a twist—these methods return an `Optional<T>` value that either wraps the answer or indicates that there is none (because the stream happened to be empty). In the olden days, it was common to return `null` in such a situation. But that can lead to null pointer exceptions when it happens in an incompletely tested program. The `Optional` type is a better way of indicating a missing return value. We discuss the `Optional` type in detail in the next section. Here is how you can get the maximum of a stream:

Click here to view code image

```
Optional<String> largest = words.max(String::compareToIgnoreCase);
System.out.println("largest: " + largest.orElse(""));
```

The `findFirst` returns the first value in a nonempty collection. It is often useful when combined with `filter`. For example, here we find the first word that starts with the letter Q, if it exists:

Click here to view code image

```
Optional<String> startsWithQ
  = words.filter(s -> s.startsWith("Q")).findFirst();
```

If you are OK with any match, not just the first one, use the `findAny` method. This is effective when you parallelize the stream, since the stream can report any match that it finds instead of being constrained to the first one.

Click here to view code image

```
Optional<String> startsWithQ
  = words.parallel().filter(s -> s.startsWith("Q")).findAny();
```

If you just want to know if there is a match, use `anyMatch`. That method takes a predicate argument, so you won't need to use `filter`.

Click here to view code image

```
boolean aWordStartsWithQ
  = words.parallel().anyMatch(s -> s.startsWith("Q"));
```

There are methods `allMatch` and `noneMatch` that return `true` if all or no elements match a predicate. These methods also benefit from being run in parallel.

---

java.util.stream.Stream 8

- `Optional<T> max(Comparator<? super T> comparator)`

- `Optional<T> min(Comparator<? super T> comparator)`
  yield a maximum or minimum element of this stream, using the ordering defined by the given comparator, or an empty `Optional` if this stream is empty. These are terminal operations.
- `Optional<T> findFirst()`
- `Optional<T> findAny()`
  yield the first, or any, element of this stream, or an empty `Optional` if this stream is empty. These are terminal operations.
- `boolean anyMatch(Predicate<? super T> predicate)`
- `boolean allMatch(Predicate<? super T> predicate)`
- `boolean noneMatch(Predicate<? super T> predicate)`
  return `true` if any, all, or none of the elements of this stream match the given predicate. These are terminal operations.

1.7 The Optional Type

An `Optional<T>` object is a wrapper for either an object of type `T` or no object. In the former case, we say that the value is *present*. The `Optional<T>` type is intended as a safer alternative for a reference of type `T` that either refers to an object or is `null`. But it is only safer if you use it right. The next three sections shows you how.

1.7.1 Getting an Optional Value

The key to using `Optional` effectively is to use a method that either *produces an alternative* if the value is not present, or *consumes the value* only if it is present.

In this section, we look at the first strategy. Often, there is a default that you want to use when there was no match, perhaps the empty string:

Click here to view code image

```
String result = optionalString.orElse("");
  // The wrapped string, or "" if none
```

You can also invoke code to compute the default:

Click here to view code image

```
String result = optionalString.orElseGet(() -> System.getProperty("myapp.default"));
  // The function is only called when needed
```

Or you can throw an exception if there is no value:

Click here to view code image

```
String result = optionalString.orElseThrow(IllegalStateException::new);
  // Supply a method that yields an exception object
```

java.util.Optional 8

- `T orElse(T other)`
  yields the value of this `Optional`, or `other` if this `Optional` is empty.
- `T orElseGet(Supplier<? extends T> other)`
  yields the value of this `Optional`, or the result of invoking `other` if this `Optional` is empty.
- `<X extends Throwable> T orElseThrow(Supplier<? extends X> exceptionSupplier)`
  yields the value of this `Optional`, or throws the result of invoking `exceptionSupplier` if this `Optional` is empty.

1.7.2 Consuming an Optional Value

In the preceding section, you saw how to produce an alternative if no value is present. The other strategy for working with optional values is to consume the value only if it is present.

The `ifPresent` method accepts a function. If the optional value exists, it is passed to that function. Otherwise, nothing happens.

Click here to view code image

```
optionalValue.ifPresent(v -> Process v);
```

For example, if you want to add the value to a set if it is present, call

Click here to view code image

```
optionalValue.ifPresent(v -> results.add(v));
```

or simply

Click here to view code image

```
optionalValue.ifPresent(results::add);
```

If you want to take one action if the `Optional` has a value and another action if it doesn't, use `ifPresentOrElse`:

Click here to view code image

```
optionalValue.ifPresentOrElse(
  v -> System.out.println("Found " + v),
  () -> logger.warning("No match"));
```

java.util.Optional 8

- `void ifPresent(Consumer<? super T> action)`
  If this `Optional` is nonempty, passes its value to `action`.
- `void ifPresentOrElse(Consumer<? super T> action, Runnable emptyAction)` 9
  If this `Optional` is nonempty, passes its value to `action`, else invokes `emptyAction`.

1.7.3 Pipelining Optional Values

In the preceding sections, you saw how to get a value out of an `Optional` object. Another useful strategy is to keep the `Optional` intact. You can transform the value inside an `Optional` by using the `map` method:

Click here to view code image

```
Optional<String> transformed = optionalString.map(String::toUpperCase);
```

If `optionalString` is empty, then `transformed` is also empty.

Here is another example. We add a result to a list if it is present:

Click here to view code image

```
optionalValue.map(results::add);
```

If `optionalValue` is empty, nothing happens.



Note

This `map` method is the analog of the `map` method of the `Stream` interface that you have seen in **Section 1.3**, "**The `filter`, `map`, and `flatMap` Methods**," on p. **11**. Simply imagine an optional value as a stream of size zero or one. The result again has size zero or one, and in the latter case, the function has been applied.

Similarly, you can use the `filter` method to only consider `Optional` values that fulfill a certain property before or after transforming it. If the property is not fulfilled, the pipeline yields an empty result:

Click here to view code image

```
Optional<String> transformed = optionalString
   .filter(s -> s.length() >= 8)
   .map(String::toUpperCase);
```

You can substitute an alternative `Optional` for an empty `Optional` with the `or` method. The alternative is computed lazily.

Click here to view code image

```
Optional<String> result = optionalString.or(() -> // Supply an Optional
   alternatives.stream().findFirst());
```

If `optionalString` has a value, then `result` is `optionalString`. If not, the lambda expression is evaluated, and its result is used.

`java.util.Optional` 8

- `<U> Optional<U> map(Function<? super T,? extends U> mapper)`
  yields an `Optional` whose value is obtained by applying the given function to the value of this `Optional` if present, or an empty `Optional` otherwise.
- `Optional<T> filter(Predicate<? super T> predicate)`
  yields an `Optional` with the value of this `Optional` if it fulfills the given predicate, or an empty `Optional` otherwise.
- `Optional<T> or(Supplier<? extends Optional<? extends T>> supplier)` 9
  yields this `Optional` if it is nonempty, or the one produced by the supplier otherwise.

1.7.4 How Not to Work with Optional Values

If you don't use `Optional` values correctly, you have no benefit over the "something or `null`" approach of the past.

The `get` method gets the wrapped element of an `Optional` value if it exists, or throws a `NoSuchElementException` if it doesn't. Therefore,

Click here to view code image

```
Optional<T> optionalValue = . . .;
optionalValue.get().someMethod()
```

is no safer than

Click here to view code image

```
T value = . . .;
value.someMethod();
```

The `isPresent` and `isEmpty` methods report whether or not an `Optional<T>` object has a value. But

Click here to view code image

```
if (optionalValue.isPresent()) optionalValue.get().someMethod();
```

is no easier than

Click here to view code image

```
if (value != null) value.someMethod();
```



Note

Java 10 introduced `orElseThrow`, a scarier-sounding synonym for the `get` method. When you call `optionalValue.orElseThrow().someMethod()`, it becomes explicit that an exception will occur if the `optionalValue` is empty. The hope is that programmers will only use `orElseThrow` when it is absolutely clear that this cannot happen.

Here are a few more tips for the proper use of the `Optional` type:

- A variable of type `Optional` should *never* be `null`.

- Don't use fields of type `Optional`. The cost is an additional object. Inside a class, use `null` for an absent field. To discourage `Optional` fields, the class is not serializable.
- Method parameters of type `Optional` are questionable. They make the call unpleasant in the common case where the requested value is present. Instead, consider two overloaded versions of the method, with and without the parameter. (On the other hand, returning an `Optional` is fine. It is the proper way to indicate that a function may not have a result.)
- Don't put `Optional` objects in a set, and don't use them as keys for a map. Collect the values instead.

`java.util.Optional` 8

- `T get()`
- `T orElseThrow()` 10
  yield the value of this `Optional`, or throw a `NoSuchElementException` if it is empty.
- `boolean isEmpty()` 11
- `boolean isPresent()`
  return `true` if this `Optional` is empty or not empty.

1.7.5 Creating Optional Values

So far, we have discussed how to consume an `Optional` object someone else created. If you want to write a method that creates an `Optional` object, there are several static methods for that purpose, including `Optional.of(result)` and `Optional.empty()`. For example,

Click here to view code image

```
public static Optional<Double> inverse(Double x)
{
```

```
  return x == 0 ? Optional.empty() : Optional.of(1 / x);
}
```

The `ofNullable` method is intended as a bridge from possibly `null` values to optional values. `Optional.ofNullable(obj)` returns `Optional.of(obj)` if `obj` is not `null` and `Optional.empty()` otherwise.

`java.util.Optional` 8

- `static <T> Optional<T> of(T value)`
- `static <T> Optional<T> ofNullable(T value)`
  yield an `Optional` with the given value. If `value` is `null`, the first method throws a `NullPointerException` and the second method yields an empty `Optional`.
- `static <T> Optional<T> empty()`
  yields an empty `Optional`.

1.7.6 Composing Optional Value Functions with `flatMap`

Suppose you have a method `f` yielding an `Optional<T>`, and the target type `T` has a method `g` yielding an `Optional<U>`. If they were normal methods, you could compose them by calling `s.f().g()`. But that composition doesn't work since `s.f()` has type `Optional<T>`, not `T`. Instead, call

Click here to view code image

```
Optional<U> result = s.f().flatMap(T::g);
```

If `s.f()` is present, then `g` is applied to it. Otherwise, an empty `Optional<U>` is returned.

Clearly, you can repeat that process if you have more methods or lambdas that yield `Optional` values. You can then build a pipeline of steps, simply by chaining calls to `flatMap`, that will succeed only when all parts do.

For example, consider the safe `inverse` method of the preceding section. Suppose we also have a safe square root:

Click here to view code image

```
public static Optional<Double> squareRoot(Double x)
{
  return x < 0 ? Optional.empty() : Optional.of(Math.sqrt(x));
}
```

Then you can compute the square root of the `inverse` as

Click here to view code image

```
Optional<Double> result = inverse(x).flatMap(MyMath::squareRoot);
```

or, if you prefer,

Click here to view code image

```
Optional<Double> result
  = Optional.of(-4.0).flatMap(Demo::inverse).flatMap(Demo::squareRoot);
```

If either the `inverse` method or the `squareRoot` returns `Optional.empty()`, the result is empty.



Note

You have already seen a `flatMap` method in the `Stream` interface (see **Section 1.3**, "**The** `filter`, `map`, **and** `flatMap` **Methods**," on p. **11**). That method maps a stream-yielding method to all elements of a stream, and then flattens out the resulting stream of streams. The `Optional.flatMap` method works in the same way. By mapping an optional-yielding method to an optional, you get an optional of optional, which is then flattened out.

`java.util.Optional` 8

- `<U> Optional<U> flatMap(Function<? super T,? extends Optional<? extends U>> mapper)`
  yields the result of applying `mapper` to the value in this `Optional` if present, or an empty optional otherwise.

1.7.7 Turning an Optional into a Stream

The `stream` method turns an `Optional<T>` into a `Stream<T>` with zero or one element. Sure, why not, but why would you ever want that?

This becomes useful with methods that return an `Optional` result. Suppose you have a stream of user IDs and a method

Click here to view code image

```
Optional<User> lookup(String id)
```

How do you get a stream of users, skipping those IDs that are invalid?

Of course, you can filter out the invalid IDs and then apply `get` to the remaining ones:

Click here to view code image

```
Stream<String> ids = . . .;
Stream<User> users = ids.map(Users::lookup)
  .filter(Optional::isPresent)
  .map(Optional::get);
```

But that uses the `isPresent` and `get` methods that we warned about. It is more elegant to call

Click here to view code image

```
Stream<User> users = ids.map(Users::lookup)
  .flatMap(Optional::stream);
```

Each call to `stream` returns a stream with zero or one element. The `flatMap` method combines them all. That means the nonexistent users are simply dropped.



Note

In this section, we consider the happy scenario in which we have a method that returns an `Optional` value. These days, many methods return `null` when there is no valid result. Suppose `Users.classicLookup(id)` returns a `User` object or `null`, not an `Optional<User>`. Then you can of course filter out the `null` values:

Click here to view code image

```
Stream<User> users = ids.map(Users::classicLookup)
  .filter(Objects::nonNull);
```

But if you prefer the `flatMap` approach, you can use

Click here to view code image

```
Stream<User> users = ids.flatMap(
  id -> Stream.ofNullable(Users.classicLookup(id)));
```

or

Click here to view code image

```
Stream<User> users = ids.map(Users::classicLookup)
  .flatMap(Stream::ofNullable);
```

The call `Stream.ofNullable(obj)` yields an empty stream if `obj` is `null` or a stream just containing `obj` otherwise.

The example program in **Listing 1.3** demonstrates the `Optional` API.

Listing 1.3 optional/OptionalTest.java

Click here to view code image

```
 1  package optional;
 2
 3  import java.io.*;
 4  import java.nio.file.*;
 5  import java.util.*;
 6
 7  /**
 8   * @version 1.02 2019-08-28
 9   * @author Cay Horstmann
10   */
11  public class OptionalTest
12  {
13     public static void main(String[] args) throws IOException
14     {
15        var contents = Files.readString(
16          Path.of("../gutenberg/alice30.txt"));
17        List<String> wordList = List.of(contents.split("\\PL+"));
18
19       Optional<String> optionalValue = wordList.stream()
20          .filter(s -> s.contains("fred"))
21          .findFirst();
22       System.out.println(optionalValue.orElse("No word") + " contains fred");
23
24       Optional<String> optionalString = Optional.empty();
25       String result = optionalString.orElse("N/A");
26       System.out.println("result: " + result);
27       result = optionalString.orElseGet(() -> Locale.getDefault().getDisplayName());
28       System.out.println("result: " + result);
29       try
30       {
31          result = optionalString.orElseThrow(IllegalStateException::new);
32          System.out.println("result: " + result);
```

```
33       }
34       catch (Throwable t)
35       {
36          t.printStackTrace();
37       }
38
39       optionalValue = wordList.stream()
40          .filter(s -> s.contains("red"))
41          .findFirst();
42       optionalValue.ifPresent(s -> System.out.println(s + " contains red"));
43
44       var results = new HashSet<String>();
45       optionalValue.ifPresent(results::add);
46       Optional<Boolean> added = optionalValue.map(results::add);
47       System.out.println(added);
48
49       System.out.println(inverse(4.0).flatMap(OptionalTest::squareRoot));
50       System.out.println(inverse(-1.0).flatMap(OptionalTest::squareRoot));
51       System.out.println(inverse(0.0).flatMap(OptionalTest::squareRoot));
52       Optional<Double> result2 = Optional.of(-4.0)
53          .flatMap(OptionalTest::inverse).flatMap(OptionalTest::squareRoot);
54       System.out.println(result2);
55    }
56
57    public static Optional<Double> inverse(Double x)
58    {
59        return x == 0 ? Optional.empty() : Optional.of(1 / x);
60    }
61
62    public static Optional<Double> squareRoot(Double x)
63    {
64        return x < 0 ? Optional.empty() : Optional.of(Math.sqrt(x));
```

```
65     }
66   }
```

java.util.Optional 8

- <U> Optional<U> flatMap(Function<? super T,Optional<U>> mapper) 9
  yields the result of applying mapper to the value of this Optional, or an empty Optional if this Optional is empty.

1.8 Collecting Results

When you are done with a stream, you will often want to look at the results. You can call the iterator method, which yields an old-fashioned iterator that you can use to visit the elements.

Alternatively, you can call the forEach method to apply a function to each element:

Click here to view code image

```
stream.forEach(System.out::println);
```

On a parallel stream, the forEach method traverses elements in arbitrary order. If you want to process them in stream order, call forEachOrdered instead. Of course, you might then give up some or all of the benefits of parallelism.

But more often than not, you will want to collect the result in a data structure. You have already seen the toList method that yields a list of the stream elements.

Call toArray to get an array of the stream elements.

Since it is not possible to create a generic array at runtime, the expression `stream.toArray()` returns an `Object[]` array. If you want an array of the correct type, pass in the array constructor:

Click here to view code image

```
String[] result = stream.toArray(String[]::new);
  // stream.toArray() has type Object[]
```

For collecting stream elements to another target, there is a convenient `collect` method that takes an instance of the `Collector` interface. A *collector* is an object that accumulates elements and produces a result. The `Collectors` class provides a large number of factory methods for common collectors. Before the `toList` method was added in Java 16, you had to use the collector produced by `Collectors.toList()`:

Click here to view code image

```
List<String> result = stream.collect(Collectors.toList());
```

Similarly, here is how you can collect stream elements into a set:

Click here to view code image

```
Set<String> result = stream.collect(Collectors.toSet());
```

These calls give you a list or set, but you cannot make any further assumptions. The collection might not be mutable, serializable, or thread-safe. If you want to control which kind of collection you get, use the following call instead:

Click here to view code image

```
TreeSet<String> result = stream.collect(Collectors.toCollection(TreeSet::new));
```

Suppose you want to collect all strings in a stream by concatenating them. You can call

Click here to view code image

```
String result = stream.collect(Collectors.joining());
```

If you want a delimiter between elements, pass it to the `joining` method:

Click here to view code image

```
String result = stream.collect(Collectors.joining(", "));
```

If your stream contains objects other than strings, you need to first convert them to strings, like this:

Click here to view code image

```
String result = stream.map(Object::toString).collect(Collectors.joining(", "));
```

If you want to reduce the stream results to a sum, count, average, maximum, or minimum, use one of the `summarizing(Int|Long|Double)` methods. These methods take a function that maps the stream objects to numbers and yield a result of type `(Int|Long|Double)SummaryStatistics`, simultaneously computing the sum, count, average, maximum, and minimum.

Click here to view code image

```
IntSummaryStatistics summary = stream.collect(
  Collectors.summarizingInt(String::length));
double averageWordLength = summary.getAverage();
double maxWordLength = summary.getMax();
```

The example program in **Listing 1.4** shows how to collect elements from a stream.

Listing 1.4 collecting/CollectingResults.java

Click here to view code image

```
 1  package collecting;
 2
 3  import java.io.*;
 4  import java.nio.file.*;
 5  import java.util.*;
 6  import java.util.stream.*;
 7
 8  /**
 9   * @version 1.02 2019-08-28
10   * @author Cay Horstmann
11   */
12  public class CollectingResults
13  {
14     public static Stream<String> noVowels() throws IOException
15     {
16        var contents = Files.readString(
17           Path.of("../gutenberg/alice30.txt"));
18
19        List<String> wordList = List.of(contents.split("\\PL+"));
```

```
20          Stream<String> words = wordList.stream();
21          return words.map(s -> s.replaceAll("[aeiouAEIOU]", ""));
22      }
23
24      public static <T> void show(String label, Set<T> set)
25      {
26          System.out.print(label + ": " + set.getClass().getName());
27          System.out.println("["
28             + set.stream().limit(10).map(Object::toString).collect(Collectors.joining(", "))
29             + "]");
30      }
31
32      public static void main(String[] args) throws IOException
33      {
34         Iterator<Integer> iter = Stream.iterate(0, n -> n + 1).limit(10).iterator();
35         while (iter.hasNext())
36            System.out.println(iter.next());
37
38         Object[] numbers = Stream.iterate(0, n -> n + 1).limit(10).toArray();
39         System.out.println("Object array:" + numbers);
40            // Note it's an Object[] array
41
42         try
43         {
44            var number = (Integer) numbers[0]; // OK
45            System.out.println("number: " + number);
46            System.out.println("The following statement throws an exception:");
47            var numbers2  = (Integer[]) numbers; // Throws exception
48         }
49         catch (ClassCastException e)
50         {
51            System.out.println(e);
52         }
```

```
53
54        Integer[] numbers3 = Stream.iterate(0, n -> n + 1)
55           .limit(10)
56           .toArray(Integer[]::new);
57        System.out.println("Integer array: " + numbers3);
58           // Note it's an Integer[] array
59
60        Set<String> noVowelSet = noVowels().collect(Collectors.toSet());
61        show("noVowelSet", noVowelSet);
62
63        TreeSet<String> noVowelTreeSet = noVowels().collect(
64           Collectors.toCollection(TreeSet::new));
65        show("noVowelTreeSet", noVowelTreeSet);
66
67        String result = noVowels().limit(10).collect(Collectors.joining());
68        System.out.println("Joining: " + result);
69        result = noVowels().limit(10)
70           .collect(Collectors.joining(", "));
71        System.out.println("Joining with commas: " + result);
72
73        IntSummaryStatistics summary = noVowels().collect(
74           Collectors.summarizingInt(String::length));
75        double averageWordLength = summary.getAverage();
76        double maxWordLength = summary.getMax();
77        System.out.println("Average word length: " + averageWordLength);
78        System.out.println("Max word length: " + maxWordLength);
79        System.out.println("forEach:");
80        noVowels().limit(10).forEach(System.out::println);
81     }
82  }
```

java.util.stream.BaseStream 8

- `Iterator<T> iterator()`
  yields an iterator for obtaining the elements of this stream. This is a terminal operation.

---

java.util.stream.Stream 8

- `List<T> toList()` 16
  yields a list of the elements in this stream.
- `void forEach(Consumer<? super T> action)`
  invokes `action` on each element of the stream.
- `Object[] toArray()`
- `<A> A[] toArray(IntFunction<A[]> generator)`
  yield an array of objects, or of type `A` when passed a constructor reference `A[]::new`. These are terminal operations.
- `<R,A> R collect(Collector<? super T,A,R> collector)`
  collects the elements in this stream, using the given collector. The `Collectors` class has factory methods for many collectors.

---

java.util.stream.Collectors 8

- `static <T> Collector<T,?,List<T>> toList()`
- `static <T> Collector<T,?,List<T>> toUnmodifiableList()` 10
- `static <T> Collector<T,?,Set<T>> toSet()`
- `static <T> Collector<T,?,Set<T>> toUnmodifiableSet()` 10
  yield collectors that collect elements in a list or set.
- `static <T,C extends Collection<T>> Collector<T,?,C> toCollection(Supplier<C> collectionFactory)`

yields a collector that collects elements into an arbitrary collection. Pass a constructor reference such as `TreeSet::new`.

- `static Collector<CharSequence,?,String> joining()`
- `static Collector<CharSequence,?,String> joining(CharSequence delimiter)`
- `static Collector<CharSequence,?,String> joining(CharSequence delimiter, CharSequence prefix, CharSequence suffix)`
  yield a collector that joins strings. The delimiter is placed between strings, and the prefix and suffix before the first and after the last string. When not specified, these are empty.
- `static <T> Collector<T,?,IntSummaryStatistics> summarizingInt(ToIntFunction<? super T> mapper)`
- `static <T> Collector<T,?,LongSummaryStatistics> summarizingLong(ToLongFunction<? super T> mapper)`
- `static <T> Collector<T,?,DoubleSummaryStatistics> summarizingDouble(ToDoubleFunction<? super T> mapper)`
  yield collectors that produce an (`Int` | `Long` | `Double`) `SummaryStatistics` object, from which you can obtain the count, sum, average, maximum, and minimum of the results of applying `mapper` to each element.

`IntSummaryStatistics` 8
`LongSummaryStatistics` 8
`DoubleSummaryStatistics` 8

- `long getCount()`
  yields the count of the summarized elements.
- (`int` | `long` | `double`) `getSum()`
- `double getAverage()`
  yield the sum or average of the summarized elements, or zero if there are no elements.
- (`int` | `long` | `double`) `getMax()`
- (`int` | `long` | `double`) `getMin()`
  yield the maximum or minimum of the summarized elements, or (`Integer` | `Long` | `Double`) . (`MAX` | `MIN`) `_VALUE` if there are no elements.

1.9 Collecting into Maps

Suppose you have a `Stream<Person>` and want to collect the elements into a map so that later you can look up people by their ID. The `Collectors.toMap` method has two function arguments that produce the map's keys and values. For example,

Click here to view code image

```
public record Person(int id, String name) {}
. . .
Map<Integer, String> idToName = people.collect(
  Collectors.toMap(Person::id, Person::name));
```

In the common case when the values should be the actual elements, use `Function.identity()` for the second function.

Click here to view code image

```
Map<Integer, Person> idToPerson = people.collect(
  Collectors.toMap(Person::id, Function.identity()));
```

If there is more than one element with the same key, there is a conflict, and the collector will throw an `IllegalStateException`. You can override that behavior by supplying a third function argument that resolves the conflict and determines the value for the key, given the existing and the new value. Your function could return the existing value, the new value, or a combination of them.

Here, we construct a map that contains, for each language in the available locales, as key its name in your default locale (such as `"German"`), and as value its localized name (such as `"Deutsch"`).

Click here to view code image

```
Stream<Locale> locales = Stream.of(Locale.getAvailableLocales());
Map<String, String> languageNames = locales.collect(
  Collectors.toMap(
    Locale::getDisplayLanguage,
    loc -> loc.getDisplayLanguage(loc),
    (existingValue, newValue) -> existingValue));
```

We don't care that the same language might occur twice (for example, German in Germany and in Switzerland), so we just keep the first entry.



Note

In this chapter, I use the `Locale` class as a source of an interesting data set. See **Chapter 7** for more information on working with locales.

Now suppose we want to know all languages in a given country. Then we need a `Map<String, Set<String>>`. For example, the value for `"Switzerland"` is the set `[French, German, Italian]`. At first, we store a singleton set for each language. Whenever a new language is found for a given country, we form the union of the existing and the new set.

Click here to view code image

```
Map<String, Set<String>> countryLanguageSets = locales.collect(
  Collectors.toMap(
    Locale::getDisplayCountry,
    l -> Collections.singleton(l.getDisplayLanguage()),
    (a, b) ->
      { // Union of a and b
        var union = new HashSet<String>(a);
```

```
        union.addAll(b);
        return union;
      }));
```

You will see a simpler way of obtaining this map in the next section.

If you want a `TreeMap`, supply the constructor as the fourth argument. You must provide a merge function. Here is one of the examples from the beginning of the section, now yielding a `TreeMap`:

Click here to view code image

```
Map<Integer, Person> idToPerson = people.collect(
  Collectors.toMap(
    Person::id,
    Function.identity(),
    (existingValue, newValue) -> { throw new IllegalStateException(); },
    TreeMap::new));
```



Note

For each of the `toMap` methods, there is an equivalent `toConcurrentMap` method that yields a concurrent map. A single concurrent map is used in the parallel collection process. When used with a parallel stream, a shared map is more efficient than merging maps. Note that elements are no longer collected in stream order, but that doesn't usually make a difference.

The program in Listing 1.5 gives examples of collecting stream results into maps.

Listing 1.5 collecting/CollectingIntoMaps.java

Click here to view code image

```
 1  package collecting;
 2
 3  import java.io.*;
 4  import java.util.*;
 5  import java.util.function.*;
 6  import java.util.stream.*;
 7
 8  /**
 9   * @version 1.01 2021-09-06
10   * @author Cay Horstmann
11   */
12  public class CollectingIntoMaps
13  {
14
15     public record Person(int id, String name) {}
16
17     public static Stream<Person> people()
18     {
19        return Stream.of(new Person(1001, "Peter"), new Person(1002, "Paul"),
20           new Person(1003, "Mary"));
21     }
22
23     public static void main(String[] args) throws IOException
24     {
25        Map<Integer, String> idToName = people().collect(
26           Collectors.toMap(Person::id, Person::name));
27        System.out.println("idToName: " + idToName);
28
```

```
      Map<Integer, Person> idToPerson = people().collect(
         Collectors.toMap(Person::id, Function.identity()));
      System.out.println("idToPerson: " + idToPerson.getClass().getName()
         + idToPerson);

      idToPerson = people().collect(
         Collectors.toMap(Person::id, Function.identity(),
            (existingValue, newValue) -> { throw new IllegalStateException(); },
            TreeMap::new));
      System.out.println("idToPerson: " + idToPerson.getClass().getName()
         + idToPerson);

      Stream<Locale> locales = Stream.of(Locale.getAvailableLocales());
      Map<String, String> languageNames = locales.collect(
         Collectors.toMap(
            Locale::getDisplayLanguage,
            l -> l.getDisplayLanguage(l),
            (existingValue, newValue) -> existingValue));
      System.out.println("languageNames: " + languageNames);

      locales = Stream.of(Locale.getAvailableLocales());
      Map<String, Set<String>> countryLanguageSets = locales.collect(
         Collectors.toMap(
            Locale::getDisplayCountry,
            l -> Set.of(l.getDisplayLanguage()),
            (a, b) ->
               { // union of a and b
               Set<String> union = new HashSet<>(a);
               union.addAll(b);
               return union;
            }));
      System.out.println("countryLanguageSets: " + countryLanguageSets);
```

```
61      }
62  }
```

java.util.stream.Collectors 8

- static <T,K,U> Collector<T,?,Map<K,U>> toMap(Function<? super T,? extends K> keyMapper, Function<? super T,? extends U> valueMapper)
- static <T,K,U> Collector<T,?,Map<K,U>> toMap(Function<? super T,? extends K> keyMapper, Function<? super T,? extends U> valueMapper, BinaryOperator<U> mergeFunction)
- static <T,K,U,M extends Map<K,U>> Collector<T,?,M> toMap(Function<? super T,? extends K> keyMapper, Function<? super T,? extends U> valueMapper, BinaryOperator<U> mergeFunction, Supplier<M> mapSupplier)
- static <T,K,U> Collector<T,?,Map<K,U>> toUnmodifiableMap(Function<? super T,? extends K> keyMapper, Function<? super T,? extends U> valueMapper) 10
- static <T,K,U> Collector<T,?,Map<K,U>> toUnmodifiableMap(Function<? super T,? extends K> keyMapper, Function<? super T,? extends U> valueMapper, BinaryOperator<U> mergeFunction) 10
- static <T,K,U> Collector<T,?,ConcurrentMap<K,U>> toConcurrentMap(Function<? super T,? extends K> keyMapper, Function<? super T,? extends U> valueMapper)
- static <T,K,U> Collector<T,?,ConcurrentMap<K,U>> toConcurrentMap(Function<? super T,? extends K> keyMapper, Function<? super T,? extends U> valueMapper, BinaryOperator<U> mergeFunction)
- static <T,K,U,M extends ConcurrentMap<K,U>> Collector<T,?,M> toConcurrentMap(Function<? super T,? extends K> keyMapper, Function<? super T,? extends U> valueMapper, BinaryOperator<U> mergeFunction, Supplier<M> mapSupplier)
  yield a collector that produces a map, unmodifiable map, or concurrent map. The `keyMapper` and `valueMapper` functions are applied to each collected element, yielding a key/value entry of the resulting map. By default, an `IllegalStateException` is thrown when two elements give rise to the same key. You can instead supply a `mergeFunction` that merges values with the same key. By default, the result is a `HashMap` or `ConcurrentHashMap`. You can instead supply a `mapSupplier` that yields the desired map instance.

1.10 Grouping and Partitioning

In the preceding section, you saw how to collect all languages in a given country. But the process was a bit tedious. You had to generate a singleton set for each map value and then specify how to merge the existing and new values. Forming groups of values with the same characteristic is very common, so the `groupingBy` method supports it directly.

Let's look at the problem of grouping locales by country. First, form this map:

Click here to view code image

```
Map<String, List<Locale>> countryToLocales = locales.collect(
  Collectors.groupingBy(Locale::getCountry));
```

The function `Locale::getCountry` is the *classifier function* of the grouping. You can now look up all locales for a given country code, for example

Click here to view code image

```
List<Locale> swissLocales = countryToLocales.get("CH");
  // Yields locales de_CH, fr_CH, it_CH, and maybe more
```



Note

A quick refresher on locales: Each locale has a language code (such as `en` for English) and a country code (such as `US` for the United States). The locale `en_US` describes English in the United States, and `en_IE` is English in

Ireland. Some countries have multiple locales. For example, `ga_IE` is Gaelic in Ireland, and, as the preceding example shows, the JDK knows at least three locales in Switzerland.

When the classifier function is a predicate function (that is, a function returning a `boolean` value), the stream elements are partitioned into two lists: those where the function returns `true` and the complement. In this case, it is more efficient to use `partitioningBy` instead of `groupingBy`. For example, here we split all locales into those that use English and all others:

Click here to view code image

```
Map<Boolean, List<Locale>> englishAndOtherLocales = locales.collect(
  Collectors.partitioningBy(l -> l.getLanguage().equals("en")));
List<Locale> englishLocales = englishAndOtherLocales.get(true);
```



Note

If you call the `groupingByConcurrent` method, you get a concurrent map that, when used with a parallel stream, is concurrently populated. This is entirely analogous to the `toConcurrentMap` method.

`java.util.stream.Collectors` 8

- `static <T,K> Collector<T,?,Map<K,List<T>>> groupingBy(Function<? super T,? extends K> classifier)`
- `static <T,K> Collector<T,?,ConcurrentMap<K,List<T>>> groupingByConcurrent(Function<? super T,? extends K> classifier)`

yield a collector that produces a map or concurrent map whose keys are the results of applying `classifier` to all collected elements, and whose values are lists of elements with the same key.

- `static <T> Collector<T,?,Map<Boolean,List<T>>> partitioningBy(Predicate<? super T> predicate)`

yields a collector that produces a map whose keys are `true` / `false`, and whose values are lists of the elements that fulfill/do not fulfill the predicate.

1.11 Downstream Collectors

The `groupingBy` method yields a map whose values are lists. If you want to process those lists in some way, supply a *downstream collector*. For example, if you want sets instead of lists, you can use the `Collectors.toSet` collector that you saw in the preceding section:

Click here to view code image

```
Map<String, Set<Locale>> countryToLocaleSet = locales.collect(
  groupingBy(Locale::getCountry, toSet()));
```



Note

In this example, as well as the remaining examples of this section, I assume a static import of `java.util.stream.Collectors.*` to make the expressions easier to read.

Several collectors are provided for reducing collected elements to numbers:

- `counting` produces a count of the collected elements. For example,
  Click here to view code image

```
Map<String, Long> countryToLocaleCounts = locales.collect(
```

```
  groupingBy(Locale::getCountry, counting()));
```

counts how many locales there are for each country.

- `summing(Int|Long|Double)` and `averaging(Int|Long|Double)` take a function argument, apply the function to the downstream elements, and produce their sum or average. For example,

  Click here to view code image

  ```
  public record City(String name, String state, int population) {}
  . . .
  Map<String, Integer> stateToCityPopulation = cities.collect(
    groupingBy(City::state, averagingInt(City::population)));
  ```

  computes the average of populations per state in a stream of cities.

- `maxBy` and `minBy` take a comparator and produce maximum and minimum of the downstream elements. For example,

  Click here to view code image

  ```
  Map<String, Optional<City>> stateToLargestCity = cities.collect(
    groupingBy(City::state,
      maxBy(Comparator.comparing(City::population))));
  ```

  produces the largest city per state.

The `collectingAndThen` collector adds a final processing step behind a collector. For example, if you want to know how many distinct results there are, collect them into a set and then compute the size:

Click here to view code image

```
Map<Character, Integer> stringCountsByStartingLetter = strings.collect(
  groupingBy(s -> s.charAt(0),
    collectingAndThen(toSet(), Set::size)));
```

The `mapping` collector does the opposite. It applies a function to each collected element and passes the results to a downstream collector.

Click here to view code image

```
Map<Character, Set<Integer>> stringLengthsByStartingLetter = strings.collect(
  groupingBy(s -> s.charAt(0),
    mapping(String::length, toSet())));
```

Here, we group strings by their first character. Within each group, we produce the lengths and collect them in a set.

The `mapping` method also yields a nicer solution to a problem from the preceding section—gathering a set of all languages in a country.

Click here to view code image

```
Map<String, Set<String>> countryToLanguages = locales.collect(
  groupingBy(Locale::getDisplayCountry,
    mapping(Locale::getDisplayLanguage,
      toSet())));
```

There is a `flatMapping` method as well, for use with functions that return streams.

If the grouping or mapping function has return type `int`, `long`, or `double`, you can collect elements into a summary statistics object, as discussed in Section 1.8, "Collecting Results," on p. 26. For example,

Click here to view code image

```
Map<String, IntSummaryStatistics> stateToCityPopulationSummary = cities.collect(
  groupingBy(City::state,
    summarizingInt(City::population)));
```

Then you can get the sum, count, average, minimum, and maximum of the function values from the summary statistics objects of each group.

The `filtering` collector applies a filter to each group, for example:

Click here to view code image

```
Map<String, Set<City>> largeCitiesByState
  = cities.collect(
    groupingBy(City::state,
      filtering(c -> c.population() > 500000,
        toSet()))); // States without large cities have empty sets
```

Finally, you can use the `teeing` collector to branch into two parallel downstream collections. This is useful whenever you need to compute more than one result from a stream. Suppose you want to collect city names and also compute their average population. You can't read a stream twice, but `teeing` lets you carry out two computations. Specify two downstream collectors and a function that combines the results.

Click here to view code image

```
record Pair<S, T>(S first, T second) {}
Pair<List<String>, Double> result = cities.filter(c -> c.state().equals("NV"))
  .collect(teeing(
    mapping(City::name, toList()), // First downstream collector
    averagingDouble(City::population), // Second downstream collector
    (list, avg) -> new Result(list,  avg))); // Combining function
```



Note

There are also three versions of a `reducing` method that apply general reductions, as described in the next section.

Composing collectors is powerful, but it can lead to very convoluted expressions. The best use is with `groupingBy` or `partitioningBy` to process the "downstream" map values. Otherwise, simply apply methods such as `map`, `reduce`, `count`, `max`, or `min` directly on streams.

The example program in **Listing 1.6** demonstrates downstream collectors.

Listing 1.6 collecting/DownstreamCollectors.java

Click here to view code image

```
1  package collecting;
2
3  import static java.util.stream.Collectors.*;
4
5  import java.io.*;
6  import java.nio.file.*;
```

```
import java.util.*;
import java.util.stream.*;

/**
 * @version 1.01 2021-09-06
 * @author Cay Horstmann
 */
public class DownstreamCollectors
{
   public record City(String name, String state, int population) {}

   public static Stream<City> readCities(String filename) throws IOException
   {
      return Files.lines(Path.of(filename))
         .map(l -> l.split(", "))
         .map(a -> new City(a[0], a[1], Integer.parseInt(a[2])));
   }

public static void main(String[] args) throws IOException
{
   Stream<Locale> locales = Stream.of(Locale.getAvailableLocales());
   Map<String, Set<Locale>> countryToLocaleSet = locales.collect(groupingBy(
      Locale::getCountry, toSet()));
   System.out.println("countryToLocaleSet: " + countryToLocaleSet);

   locales = Stream.of(Locale.getAvailableLocales());
   Map<String, Long> countryToLocaleCounts = locales.collect(groupingBy(
      Locale::getCountry, counting()));
   System.out.println("countryToLocaleCounts: " + countryToLocaleCounts);

   Stream<City> cities = readCities("cities.txt");
   Map<String, Integer> stateToCityPopulation = cities.collect(groupingBy(
      City::state, summingInt(City::population)));
```

```
40    System.out.println("stateToCityPopulation: " + stateToCityPopulation);
41
42    cities = readCities("cities.txt");
43    Map<String, Optional<String>> stateToLongestCityName = cities
44       .collect(groupingBy(City::state,
45          mapping(City::name, maxBy(Comparator.comparing(String::length)))));
46    System.out.println("stateToLongestCityName: " + stateToLongestCityName);
47
48    locales = Stream.of(Locale.getAvailableLocales());
49    Map<String, Set<String>> countryToLanguages = locales.collect(groupingBy(
50       Locale::getDisplayCountry, mapping(Locale::getDisplayLanguage, toSet())));
51    System.out.println("countryToLanguages: " + countryToLanguages);
52
53    cities = readCities("cities.txt");
54    Map<String, IntSummaryStatistics> stateToCityPopulationSummary = cities
55       .collect(groupingBy(City::state, summarizingInt(City::population)));
56    System.out.println(stateToCityPopulationSummary.get("NY"));
57
58    cities = readCities("cities.txt");
59    Map<String, String> stateToCityNames = cities.collect(groupingBy(
60       City::state,
61       reducing("", City::name, (s, t) -> s.length() == 0 ? t : s + ", " + t)));
62
63    cities = readCities("cities.txt");
64    stateToCityNames = cities.collect(groupingBy(City::state,
65       mapping(City::name, joining(", "))));
66    System.out.println("stateToCityNames: " + stateToCityNames);
67
68    cities = readCities("cities.txt");
69    record Pair<S, T>(S first, T second) {}
70    Pair<List<String>, Double> result = cities.filter(c -> c.state().equals("NV"))
71       .collect(teeing(
72          mapping(City::name, toList()),
```

```
73          averagingDouble(City::population),
74          (names, avg) -> new Pair<>(names, avg)));
75     System.out.println(result);
76   }
77  }
```

java.util.stream.Collectors 8

- `public static <T,K,A,D> Collector<T,?,Map<K,D>> groupingBy(Function<? super T,? extends K> classifier, Collector<? super T,A,D> downstream)`
  yields a collector that produces a map. The keys are the results of applying `classifier` to all collected elements. The values are the results of collecting elements with the same key, using the downstream collector.
- `static <T> Collector<T,?,Long> counting()`
  yields a collector that counts the collected elements.
- `static <T> Collector<T,?,Integer> summingInt(ToIntFunction<? super T> mapper)`
- `static <T> Collector<T,?,Long> summingLong(ToLongFunction<? super T> mapper)`
- `static <T> Collector<T,?,Double> summingDouble(ToDoubleFunction<? super T> mapper)`
  yield a collector that computes the sum of the results of applying `mapper` to the collected elements.
- `static <T> Collector<T,?,Optional<T>> maxBy(Comparator<? super T> comparator)`
- `static <T> Collector<T,?,Optional<T>> minBy(Comparator<? super T> comparator)`
  yield a collector that computes the maximum or minimum of the collected elements, using the ordering specified by `comparator` .
- `static <T,A,R,RR> Collector<T,A,RR> collectingAndThen(Collector<T,A,R> downstream, Function<R,RR> finisher)`
  yields a collector that sends elements to the downstream collector and then applies the finisher function to its result.
- `static <T,U,A,R> Collector<T,?,R> mapping(Function<? super T,? extends U> mapper, Collector<? super U,A,R> downstream)`
  yields a collector that calls `mapper` on each element and passes the results to the downstream collector.
- `static <T,U,A,R> Collector<T,?,R> flatMapping(Function<? super T,? extends Stream<? extends U>> mapper, Collector<? super U,A,R> downstream)`

yields a collector that calls `mapper` on each element and passes the elements of the results to the downstream collector.

- `static <T,A,R> Collector<T,?,R> filtering(Predicate<? super T> predicate, Collector<? super T,A,R> downstream)`
  yields a collector that passes the elements fulfilling the predicate to the downstream collector.

1.12 Reduction Operations

The `reduce` method is a general mechanism for computing a value from a stream. The simplest form takes a binary function and keeps applying it, starting with the first two elements. It's easy to explain this if the function is the sum:

Click here to view code image

```
List<Integer> values = . . .;
Optional<Integer> sum = values.stream().reduce((x, y) -> x + y);
```

In this case, the `reduce` method computes $v_0 + v_1 + v_2 + \ldots$, where v_i are the stream elements. The method returns an `Optional` because there is no valid result if the stream is empty.



Note

In this case, you can write `reduce(Integer::sum)` instead of `reduce((x, y) -> x + y)`.

More generally, you can use any operation that combines a partial result `x` with the next value `y` to yield a new partial result.

Here is another way of looking at reductions. Given a reduction operation *op*, the reduction yields v_0 *op* v_1 *op* v_2 *op*..., where v_i *op* v_{i+1} denotes the function call $op(v_i, v_{i+1})$. There are many operations that might be useful in practice—such as sum, product, string concatenation, maximum and minimum, set union or intersection.

If you want to use reduction with parallel streams, the operation must be *associative*: It shouldn't matter in which order you combine the elements. In math notation, (*x op y*) *op z* must be equal to *x op* (*y op z*). An example of an operation that is not associative is subtraction. For example, (6 − 3) − 2 ≠ 6 − (3 − 2).

Often, there is an *identity e* such that *e op x* = *x*, and that element can be used as the start of the computation. For example, 0 is the identity for addition, and you can use the second form of `reduce`:

Click here to view code image

```
List<Integer> values = . . .;
Integer sum = values.stream().reduce(0, (x, y) -> x + y);
  // Computes 0 + v0 + v1 + v2 + . . .
```

The identity value is returned if the stream is empty, and you no longer need to deal with the `Optional` class.

Now suppose you have a stream of objects and want to form the sum of some property, such as lengths in a stream of strings. You can't use the simple form of `reduce`. It requires a function `(T, T) -> T`, with the same types for the arguments and the result, but in this situation you have two types: The stream elements have type `String`, and the accumulated result is an integer. There is a form of `reduce` that can deal with this situation.

First, you supply an "accumulator" function `(total, word) -> total + word.length()`. That function is called repeatedly, forming the cumulative total. But when the computation is parallelized, there will be multiple computations of this kind, and you need to combine their results. You supply a second function for that purpose. The complete call is

Click here to view code image

```
int result = words.reduce(0,
  (total, word) -> total + word.length(),
```

```
(total1, total2) -> total1 + total2);
```



Note

In practice, you probably won't use the `reduce` method a lot. It is usually easier to map to a stream of numbers and use one of its methods to compute sum, maximum, or minimum. (We discuss streams of numbers in **Section 1.13**, "**Primitive Type Streams**," on p. **43**.) In this particular example, you could have called `words.mapToInt(String::length).sum()`, which is both simpler and more efficient since it doesn't involve boxing.



Note

There are times when `reduce` is not general enough. For example, suppose you want to collect the results in a `BitSet`. If the collection is parallelized, you can't put the elements directly into a single `BitSet` because a `BitSet` object is not thread-safe. For that reason, you can't use `reduce`. Each segment needs to start out with its own empty set, and `reduce` only lets you supply one identity value. Instead, use the three-argument form of `collect`. Its arguments are:

1. A *supplier* to construct new instances of the target object
2. An *accumulator* that adds an element to the target
3. A *combiner* that merges two target objects into one

Here is how the `collect` method works for a bit set:

Click here to view code image

```
BitSet result = stream.collect(BitSet::new, BitSet::set, BitSet::or);
```

---

java.util.Stream 8

- `Optional<T> reduce(BinaryOperator<T> accumulator)`
- `T reduce(T identity, BinaryOperator<T> accumulator)`
- `<U> U reduce(U identity, BiFunction<U,? super T,U> accumulator, BinaryOperator<U> combiner)`
  form a cumulative total of the stream elements with the given `accumulator` function. If `identity` is provided, then it is the first value to be accumulated. If `combiner` is provided, it can be used to combine totals of segments that are accumulated separately.
- `<R> R collect(Supplier<R> supplier, BiConsumer<R,? super T> accumulator, BiConsumer<R,R> combiner)`
  collects elements in a result of type `R`. On each segment, `supplier` is called to provide an initial result, `accumulator` is called to mutably add elements to it, and `combiner` is called to combine two results.

1.13 Primitive Type Streams

So far, we have collected integers in a `Stream<Integer>`, even though it is clearly inefficient to wrap each integer into a wrapper object. The same is true for the other primitive types—`double`, `float`, `long`, `short`, `char`, `byte`, and `boolean`. The stream library has specialized types `IntStream`, `LongStream`, and `DoubleStream` that store primitive values directly, without using wrappers. If you want to store `short`, `char`, `byte`, and `boolean`, use an `IntStream`; for `float`, use a `DoubleStream`.

To create an `IntStream`, call the `IntStream.of` and `Arrays.stream` methods:

Click here to view code image

```
IntStream stream = IntStream.of(1, 1, 2, 3, 5);
stream = Arrays.stream(values, from, to); // values is an int[] array
```

As with object streams, you can also use the static `generate` and `iterate` methods. In addition, `IntStream` and `LongStream` have static methods `range` and `rangeClosed` that generate integer ranges with step size one:

Click here to view code image

```
IntStream zeroToNinetyNine = IntStream.range(0, 100); // Upper bound is excluded
IntStream zeroToHundred = IntStream.rangeClosed(0, 100); // Upper bound is included
```

The `CharSequence` interface has methods `codePoints` and `chars` that yield an `IntStream` of the Unicode codes of the characters or of the code units in the UTF-16 encoding. (See **Chapter 2** for the sordid details.)

Click here to view code image

```
String sentence = "\uD835\uDD46 is the set of octonions.";
  // \uD835\uDD46 is the UTF-16 encoding of the letter 𝕆, unicode U+1D546

IntStream codes = sentence.codePoints();
  // The stream with hex values 1D546 20 69 73 20 . . .
```

When you have a stream of objects, you can transform it to a primitive type stream with the `mapToInt`, `mapToLong`, or `mapToDouble` methods. For example, if you have a stream of strings and want to process their lengths as integers, you might as well do it in an `IntStream`:

Click here to view code image

```
Stream<String> words = . . .;
IntStream lengths = words.mapToInt(String::length);
```

To convert a primitive type stream to an object stream, use the `boxed` method:

Click here to view code image

```
Stream<Integer> integers = IntStream.range(0, 100).boxed();
```

Generally, the methods on primitive type streams are analogous to those on object streams. Here are the most notable differences:

- The `toArray` methods return primitive type arrays.
- Methods that yield an optional result return an `OptionalInt`, `OptionalLong`, or `OptionalDouble`. These classes are analogous to the `Optional` class, but they have methods `getAsInt`, `getAsLong`, and `getAsDouble` instead of the `get` method.
- There are methods `sum`, `average`, `max`, and `min` that return the sum, count, average, maximum, and minimum. These methods are not defined for object streams.
- The `summaryStatistics` method yields an object of type `IntSummaryStatistics`, `LongSummaryStatistics`, or `DoubleSummaryStatistics` that can simultaneously report the sum, count, average, maximum, and minimum of the stream.



Note

The `Random` class has methods `ints`, `longs`, and `doubles` that return primitive type streams of random numbers. If you need random numbers in parallel streams, use the `SplittableRandom` class instead.

The program in Listing 1.7 gives examples for the API of primitive type streams.

Listing 1.7 streams/PrimitiveTypeStreams.java

Click here to view code image

```
 1  package streams;
 2
 3  import java.io.*;
 4  import java.nio.file.*;
 5  import java.util.stream.*;
 6
 7  /**
 8   * @version 1.02 2021-09-09
 9   * @author Cay Horstmann
10   */
11  public class PrimitiveTypeStreams
12  {
13     public static void show(String title, IntStream stream)
14     {
15        final int SIZE = 10;
16        int[] firstElements = stream.limit(SIZE + 1).toArray();
17        System.out.print(title + ": ");
18        for (int i = 0; i < firstElements.length; i++)
19        {
20           if (i > 0) System.out.print(", ");
21           if (i < SIZE) System.out.print(firstElements[i]);
22           else System.out.print("...");
23        }
24        System.out.println();
25     }
26
27     public static void main(String[] args) throws IOException
28     {
```

```
29        IntStream is1 = IntStream.generate(() -> (int) (Math.random() * 100));
30        show("is1", is1);
31        IntStream is2 = IntStream.range(5, 10);
32        show("is2", is2);
33        IntStream is3 = IntStream.rangeClosed(5, 10);
34        show("is3", is3);
35
36        Path path = Path.of("../gutenberg/alice30.txt");
37        var contents = Files.readString(path);
38
39        Stream<String> words = Stream.of(contents.split("\\PL+"));
40        IntStream is4 = words.mapToInt(String::length);
41        show("is4", is4);
42        String sentence = "\uD835\uDD46 is the set of octonions.";
43        System.out.println(sentence);
44        IntStream codes = sentence.codePoints();
45        System.out.println(codes.mapToObj(c -> "%X ".formatted(c)).collect(
46           Collectors.joining()));
47
48        Stream<Integer> integers = IntStream.range(0, 100).boxed();
49        IntStream is5 = integers.mapToInt(Integer::intValue);
50        show("is5", is5);
51     }
52  }
```

java.util.stream.IntStream 8

- `static IntStream range(int startInclusive, int endExclusive)`
- `static IntStream rangeClosed(int startInclusive, int endInclusive)`

yield an `IntStream` with the integers in the given range.

- `static IntStream of(int... values)`
  yields an `IntStream` with the given elements.
- `int[] toArray()`
  yields an array with the elements of this stream.
- `int sum()`
- `OptionalDouble average()`
- `OptionalInt max()`
- `OptionalInt min()`
- `IntSummaryStatistics summaryStatistics()`
  yield the sum, count, average, maximum, or minimum of the elements in this stream, or an object from which all four of these values can be obtained.
- `Stream<Integer> boxed()`
  yields a stream of wrapper objects for the elements in this stream.

---

java.util.stream.LongStream 8

- `static LongStream range(long startInclusive, long endExclusive)`
- `static LongStream rangeClosed(long startInclusive, long endInclusive)`
  yield a `LongStream` with the integers in the given range.
- `static LongStream of(long... values)`
  yields a `LongStream` with the given elements.
- `long[] toArray()`
  yields an array with the elements of this stream.
- `long sum()`
- `OptionalDouble average()`
- `OptionalLong max()`
- `OptionalLong min()`

- `LongSummaryStatistics summaryStatistics()`
  yield the sum, count, average, maximum, or minimum of the elements in this stream, or an object from which all four of these values can be obtained.
- `Stream<Long> boxed()`
  yields a stream of wrapper objects for the elements in this stream.

---

java.util.stream.DoubleStream 8

- `static DoubleStream of(double... values)`
  yields a `DoubleStream` with the given elements.
- `double[] toArray()`
  yields an array with the elements of this stream.
- `double sum()`
- `OptionalDouble average()`
- `OptionalDouble max()`
- `OptionalDouble min()`
- `DoubleSummaryStatistics summaryStatistics()`
  yield the sum, count, average, maximum, or minimum of the elements in this stream, or an object from which all four of these values can be obtained.
- `Stream<Double> boxed()`
  yields a stream of wrapper objects for the elements in this stream.

---

java.lang.CharSequence 1.0

- `IntStream codePoints()` 8

yields a stream of all Unicode code points of this string.

---

java.util.random.RandomGenerator 17

- `IntStream ints()`
- `IntStream ints(int randomNumberOrigin, int randomNumberBound)`
- `IntStream ints(long streamSize)`
- `IntStream ints(long streamSize, int randomNumberOrigin, int randomNumberBound)`
- `LongStream longs()`
- `LongStream longs(long randomNumberOrigin, long randomNumberBound)`
- `LongStream longs(long streamSize)`
- `LongStream longs(long streamSize, long randomNumberOrigin, long randomNumberBound)`
- `DoubleStream doubles()`
- `DoubleStream doubles(double randomNumberOrigin, double randomNumberBound)`
- `DoubleStream doubles(long streamSize)`
- `DoubleStream doubles(long streamSize, double randomNumberOrigin, double randomNumberBound)`

  yield streams of random numbers. If `streamSize` is provided, the stream is finite with the given number of elements. When bounds are provided, the elements are between `randomNumberOrigin` (inclusive) and `randomNumberBound` (exclusive).

---

java.util.Optional (Int | Long | Double) 8

- `static Optional ( Int | Long | Double ) of( ( int | long | double ) value)`

  yields an optional object with the supplied primitive type value.
- `( int | long | double ) getAs ( Int | Long | Double ) ()`

  yields the value of this optional object, or throws a `NoSuchElementException` if it is empty.

- `( int | long | double ) orElse( ( int | long | double ) other)`
- `( int | long | double ) orElseGet( ( Int | Long | Double ) Supplier other)`
  yield the value of this optional object, or the alternative value if this object is empty.
- `void ifPresent( ( Int | Long | Double ) Consumer consumer)`
  If this optional object is not empty, passes its value to `consumer`.

`java.util. ( Int | Long | Double ) SummaryStatistics 8`

- `long getCount()`
- `( int | long | double ) getSum()`
- `double getAverage()`
- `( int | long | double ) getMax()`
- `( int | long | double ) getMin()`
  yield the count, sum, average, maximum, and minimum of the collected elements.

1.14 Parallel Streams

Streams make it easy to parallelize bulk operations. The process is mostly automatic, but you need to follow a few rules. First of all, you must have a parallel stream. You can get a parallel stream from any collection with the `Collection.parallelStream()` method:

Click here to view code image

```
Stream<String> parallelWords = words.parallelStream();
```

Moreover, the `parallel` method converts any sequential stream into a parallel one.

Click here to view code image

```
Stream<String> parallelWords = Stream.of(wordArray).parallel();
```

As long as the stream is in parallel mode when the terminal method executes, all intermediate stream operations will be parallelized.

When stream operations run in parallel, the intent is that the same result is returned as if they had run serially. It is important that the operations are *stateless* and can be executed in an arbitrary order.

Here is an example of something you cannot do. Suppose you want to count all short words in a stream of strings:

Click here to view code image

```
var shortWords = new int[12];
words.parallelStream().forEach(
  s -> { if (s.length() < 12) shortWords[s.length()]++; });
    // ERROR--race condition!
System.out.println(Arrays.toString(shortWords));
```

This is very, very bad code. The function passed to `forEach` runs concurrently in multiple threads, each updating a shared array. As you saw in **Chapter 12** of Volume I, that's a classic *race condition*. If you run this program multiple times, you are quite likely to get a different sequence of counts in each run—each of them wrong.

It is your responsibility to ensure that any functions you pass to parallel stream operations are safe to execute in parallel. The best way to do that is to stay away from mutable state. In this example, you can safely parallelize the computation if you group strings

by length and count them:

Click here to view code image

```
Map<Integer, Long> shortWordCounts
  = words.parallelStream()
    .filter(s -> s.length() < 12)
    .collect(groupingBy(
      String::length,
      counting()));
```

By default, streams that arise from ordered collections (arrays and lists), from ranges, generators, and iterators, or from calling `Stream.sorted`, are *ordered*. Results are accumulated in the order of the original elements, and are entirely predictable. If you run the same operations twice, you will get exactly the same results.

Ordering does not preclude efficient parallelization. For example, when computing `stream.map(fun)`, the stream can be partitioned into *n* segments, each of which is concurrently processed. Then the results are reassembled in order.

Some operations can be more effectively parallelized when the ordering requirement is dropped. By calling the `Stream.unordered` method, you indicate that you are not interested in ordering. One operation that can benefit from this is `Stream.distinct`. On an ordered stream, `distinct` retains the first of all equal elements. That impedes parallelization—the thread processing a segment can't know which elements to discard until the preceding segment has been processed. If it is acceptable to retain *any* of the unique elements, all segments can be processed concurrently (using a shared set to track duplicates).

You can also speed up the `limit` method by dropping ordering. If you just want any `n` elements from a stream and you don't care which ones you get, call

Click here to view code image

```
Stream<String> sample = words.parallelStream().unordered().limit(n);
```

As discussed in **Section 1.9**, "**Collecting into Maps**," on p. **31**, merging maps is expensive. For that reason, the `Collectors.groupingByConcurrent` method uses a shared concurrent map. To benefit from parallelism, the order of the map values will not be the same as the stream order.

Click here to view code image

```
Map<Integer, List<String>> result = words.parallelStream().collect(
  Collectors.groupingByConcurrent(String::length));
  // Values aren't collected in stream order
```

Of course, you won't care if you use a downstream collector that is independent of the ordering, such as

Click here to view code image

```
Map<Integer, Long> wordCounts
  = words.parallelStream()
    .collect(
      groupingByConcurrent(
        String::length,
        counting()));
```

Don't turn all your streams into parallel streams in the hope of speeding up operations. Keep these issues in mind:

- There is a substantial overhead to parallelization that will only pay off for very large data sets.
- Parallelizing a stream is only a win if the underlying data source can be effectively split into multiple parts.

- The thread pool that is used by parallel streams can be starved by blocking operations such as file I/O or network access.

Parallel streams work best with huge in-memory collections of data and computationally intensive processing.



Tip

Prior to Java 9, parallelizing the stream returned by the `Files.lines` method made no sense. The data was not splittable—you had to read the first half of the file before the second half. Now the method uses a memory-mapped file, and splitting is effective. If you process the lines of a huge file, parallelizing the stream may improve performance.



Note

By default, parallel streams use the global fork-join pool returned by `ForkJoinPool.commonPool`. That is fine if your operations don't block and you don't share the pool with other tasks. There is a trick to substitute a different pool. Place your operations inside the `submit` method of a custom pool:

Click here to view code image

```
ForkJoinPool customPool = . . .;
result = customPool.submit(() ->
  stream.parallel().map(. . .).collect(. . .)).get();
```

Or, asynchronously:

Click here to view code image

```
CompletableFuture.supplyAsync(() ->
  stream.parallel().map(. . .).collect(. . .),
  customPool).thenAccept(result -> . . .);
```



Note

If you want to parallelize stream computations based on random numbers, don't start out with a stream obtained from the `Random.ints`, `Random.longs`, or `Random.doubles` methods. Those streams don't split. Instead, use the `ints`, `longs`, or `doubles` methods of the `SplittableRandom` class.

The example program in **Listing 1.8** demonstrates how to work with parallel streams.

Listing 1.8 parallel/ParallelStreams.java

Click here to view code image

```
 1  package parallel;
 2
 3  import static java.util.stream.Collectors.*;
 4
 5  import java.io.*;
 6  import java.nio.file.*;
 7  import java.util.*;
 8  import java.util.stream.*;
 9
10  /**
11   * @version 1.02 2019-08-28
```

```
 * @author Cay Horstmann
 */
public class ParallelStreams
{
   public static void main(String[] args) throws IOException
   {
    var contents = Files.readString(
       Path.of("../gutenberg/alice30.txt"));
    List<String> wordList = List.of(contents.split("\\PL+"));

    // Very bad code ahead
    var shortWords = new int[10];
    wordList.parallelStream().forEach(s ->
       {
          if (s.length() < 10) shortWords[s.length()]++;
       });
    System.out.println(Arrays.toString(shortWords));

    // Try again--the result will likely be different (and also wrong)
    Arrays.fill(shortWords, 0);
    wordList.parallelStream().forEach(s ->
       {
          if (s.length() < 10) shortWords[s.length()]++;
       });
    System.out.println(Arrays.toString(shortWords));

    // Remedy: Group and count
    Map<Integer, Long> shortWordCounts = wordList.parallelStream()
       .filter(s -> s.length() < 10)
       .collect(groupingBy(String::length, counting()));

    System.out.println(shortWordCounts);

```

```
45      // Downstream order not deterministic
46      Map<Integer, List<String>> result = wordList.parallelStream().collect(
47         Collectors.groupingByConcurrent(String::length));
48
49      System.out.println(result.get(14));
50
51      result = wordList.parallelStream().collect(
52         Collectors.groupingByConcurrent(String::length));
53
54      System.out.println(result.get(14));
55
56      Map<Integer, Long> wordCounts = wordList.parallelStream().collect(
57         groupingByConcurrent(String::length, counting()));
58
59      System.out.println(wordCounts);
60    }
61  }
```

java.util.stream.BaseStream<T,S extends BaseStream<T,S>> 8

- `S parallel()`
  yields a parallel stream with the same elements as this stream.
- `S unordered()`
  yields an unordered stream with the same elements as this stream.

java.util.Collection<E> 1.2

- `Stream<E> parallelStream()` 8

yields a parallel stream with the elements of this collection.

In this chapter, you have learned how to put the stream library of Java 8 to use. The next chapter covers another important topic: processing input and output.

Previous chapter
< Acknowledgments

Next chapter
Chapter 2. Input and Output >