Index

umbers

-

(minus sign)

in regular expressions, 144

in URLs, 271

_

(underscore)

in native method names, 787–788

in SQL, 299, 329

in URLs, 271

,

(comma)

decimal, 388, 395, 402

in DTDs, 178–179

;

(semicolon)

in classpath, 302

in decimal formatting, 400

in method signatures, 807

in SQL, 303

not needed, in annotations, 468

:

(colon)

in classpath, 302

in text files, 72

in URLs, 260–261

!=

operator (SQL), 299

?

(question mark)

in DTDs, 178–180

in glob patterns, 127

in prepared queries, 319

in regular expressions, 144–145, 147

in URLs, 270

/

(slash)

in method signatures, 807

in paths, 64, 115

in URLs, 260

.

(period)

decimal, 388, 395, 402

in method signatures, 807

in regular expressions, 144–145, 156

in URLs, 271

..

, in paths, 116

^

(caret), in regular expressions, 144–147, 156

~

(tilde), in URLs, 271

'

(apostrophe), entity reference for, 164

'. . .'

, in SQL, 299

". . ."

, in XML, 162

(. . .)

(parentheses)

in annotations, 477

in method signatures, 807

in regular expressions, 144–147, 151–154

[

(array), type code, 96, 806

[. . .]

(square brackets)

in
`DOCTYPE`
declaration, 177

in glob patterns, 127

in regular expressions, 144–146

in XPath, 195

`{. . .}`
(curly brackets)

in annotations, 478

in glob patterns, 127

in message formatting, 413–418

in regular expressions, 144–147, 155

`@`
(at)

in annotations, 468, 477

in
`java`
command-line options, 522

in URIs, 261

in XPath, 195

`¤`
(currency sign), 401

`$`
(dollar sign), 403

in native method names, 787

in regular expressions, 144–145, 147, 155–157

```
€
```

(euro sign), 402, 419

```
*
```

(asterisk)

in DTDs, 178–180

in glob patterns, 127

in regular expressions, 144–147, 152

```
\
```

(backslash)

in glob patterns, 127

in paths, 64, 115

in regular expressions, 144–145, 155, 157

```
\\|
```

, in regular expressions, 73

```
&
```

(ampersand)

in CDATA sections, 165

in entity references, 164

parsing, 179

```
&&
```

, in regular expressions, 146

```
&#
```

,

&#x

, in character references, 164

#

(number sign)

in decimal formatting, 400

in message formatting, 416–417

in URLs, 260

%

(percent sign)

in locales, 395

in SQL, 299, 329

in URLs, 271

+

(plus sign)

in DTDs, 178–179

in regular expressions, 144–147

in URLs, 271

operator, identity for, 42

<

(left angle bracket)

in CDATA sections, 165

in message formatting, 417

parsing, 179

<!--. . .-->

,

<?. . .?>

,

<![CDATA[. . .]]>

, in XML, 165

<. . .>

(angle brackets), in regular

expressions, 147

<>

operator (SQL), 299

>

(right angle bracket), in XML, 165

≤

operator, 417

=

operator (SQL), 299

==

operator, in enumerations, 105

|

(vertical bar)

in DTDs, 178–180

in message formatting, 416

in regular expressions, 144–146

in text files, 72

\0

, in regular expressions, 145

1931 CIE XYZ color specification, 734

2D graphics. *See* **Java 2D API**

\a
,
\A
, in regular expressions, 145, 148

abort
method (
LoginModule
), 562

absolute
method (
ResultSet
), 333, 337

AbstractCellEditor
class, 621–623

isCellEditable
method, 622

AbstractProcessor
class, 488

AbstractTableModel
class, 596

getColumnName
method, 597–598

isCellEditable

method, 619

accept
method (
ServerSocket
), 244, 247–248

acceptChanges
method (
CachedRowSet
), 340, 342

Accumulator functions, 42

Action listeners

annotating, 469–475

installing, 470

action.properties
file, 461

ActionListener
interface

actionPerformed
method, 452, 470

@ActionListenerFor
annotation, 469, 485

ActionListenerInstaller
class

processAnnotations
method, 470

add

method

of
`Area`
, 691–692

of
`AttributeSet`
, 779, 783

of
`DefaultMutableTreeNode`
, 633, 641

`addActionListener`
method (
`ButtonFrame`
), 469–470

`addAttribute`
method (
`AttributesImpl`
), 233

`addBatch`
method (
`Statement`
), 355–356

`addCellEditorListener`
method (
`CellEditor`
), 630

`addColumn`
method (
`JTable`
), 608, 614

addRecipient
method (
MimeMessage
), 288

addTreeModelListener
method (
TreeModel
), 663, 671

addTreeSelectionListener
method (
JTree
), 655

addURLs
method (
URLClassLoader
), 537

Adleman, Leonard, 568, 587

AES (Advanced Encryption Standard), 579

generating keys in, 580–585

aes/AESTest.java
, 582

aes/Util.java
, 583

Affine transformations, 706, 740

AffineTransform
class, 706–709

constructor, 707–708

get
Xxx
Instance
methods, 706–709, 711

setTo
Xxx methods, 707, 709

AffineTransformOp
class, 740

constructor, 747

TYPE_
XXX fields, 741, 747

afterLast
method (
ResultSet
), 333, 337

Agent code, 499–500

Aliases, for namespaces, 185, 201

allMatch
method (
Stream
), 17

allocate
method (
ByteBuffer
), 138, 140

Alpha channel, 712–716

Alpha composites, 721

AlphaComposite
class, 715

getInstance
method, 715, 721

&
, entity reference, 164

Anchor rectangles, 702

andFilter
method (
RowFilter
), 607, 616

AnnotatedConstruct
interface, 489

AnnotatedElement
interface

getAnnotation
method, 470, 474, 488–489

getAnnotations
method, 474

getAnnotationsByType
method, 474, 488–489

getDeclaredAnnotations
method, 475

isAnnotationPresent
method, 474

Annotation

interface

extending, 475

methods of, 476

Annotation interfaces, 469, 475–476

predefined, 482–488

Annotation processors, 488–489

at bytecode level, 470, 493

at runtime, 470

Annotations, 467–475

applicability of, 484–485

documented, 485–486

elements of, 468, 476

evaluating, 478

for compilation, 483

for local variables, 480

for packages, 479

generating source code with, 490–493

inherited, 487

marker, 477

meta, 469, 483–488

never set to

null

, 478

no annotations for, 481

no circular dependencies in, 479

processing tools for, 467

repeatable, 488

retaining, 485

single value, 477

source-level, 488–493

standard, 482–488

syntax of, 475–482

transient, 486

vs. Javadoc comments, 468

`ANY`
element content (DTD), 178

`anyMatch`
method (
Stream
), 17

Apache, 159

Commons CSV library, 519–520

Derby, 302

connecting to, 305

drivers for, 302–304

populating, 315-318

starting, 303

DOM parser, 166

Tomcat, 359

Apollo 11, launch of, 366, 375

`'`
, entity reference, 164

`append`
method

of
Appendable
, 62-63

of
`Path2D`
, 681, 691, 711

Appendable
interface, 61-63

`appendChild`
method (
Node
), 213, 215

Applets

executing, 562, 577

security mechanisms in, 533

Application servers, 359

Applications

business logic vs. visual representation of, 294–295

client/server, 295

configuring, 160–161

enterprise, 358–360

executing:

loading classes for, 534

without a separate Java runtime, 530

localizing, 421–423

monitoring, 499–500

paid, 541

server-side, 269–278

signing, 577

web, 358–360

`applyPattern` method (`MessageFormat`), 415

`apply-templates` element (XSLT), 225

`Arc2D` class, 674–675, 678

`Arc2D.Double` class, 675, 677, 690

Arc2D.Float
class, 675, 677

ArcMaker
class, 682

Arcs

bounding rectangles of, 675, 678

closure types of, 678

computing angles of, 678

Area
class

add
method, 691–692

exclusiveOr
method, 692

intersect
method, 692

subtract
method, 692

ARGB (Alpha, Red, Green, Blue), 716, 735

ARRAY
data type (SQL), 357–358

ArrayIndexOutOfBoundsException
, 820

Arrays

converting to/from streams, 5, 26, 50

getting from a database, 358

in annotation elements, 478

in native code, 816–819

of primitive types, 818

of strings, 154

type code for, 96, 806

type use annotations in, 480

`Arrays`
class

`stream`
method, 5, 9, 44

`ArrayStoreException`
, 820

`asCharBuffer`
method (
`ByteBuffer`
), 138

ASCII encoding, 76, 155

in property files, 423

native code and, 795

ASM library, 493–501

`asMatchPredicate`
method (
`Pattern`
), 149

ASP (Active Server Pages), 269

asPredicate
method (
Pattern
), 149

Associative operations, 42

Atomic operations, 121

ATTLIST
declaration (DTD), 180

attribute
element (XML Schema), 187

Attribute
interface, 776

getCategory
method, 778, 783

getName
method, 783

implementing, 778

Attribute sets, 778

Attributes (XML)

enumerating, 170

in XML Schema, 187

legal, 180

names of, 162

namespace of, 201

values of, 162

accessing in XPath, 195

copying with XSLT, 226

default (DTDs), 181

normalizing, 181

vs. elements, 163–164, 181, 223

Attributes

interface

get

Xxx methods, 208

AttributeSet

interface, 777

add

method, 779, 783

get

method, 779, 783

remove

method, 784

toArray

method, 784

AttributesImpl

class

addAttribute

method, 233

clear
method, 233

atZone
method (
LocalDateTime
), 375

auth/AuthTest.java
, 551

auth/jaas.config
, 552

Authentication, 549–562, 572–574

role-based, 553

through a trusted intermediary, 572–573

Autoboxing, 593

AutoCloseable
interface

close
method, 62

Autocommit mode (databases), 353–355

Autoflushing, 69

Auxiliary files, generated, 467

available
method (
InputStream
), 57–58

availableCharsets
method (
Charset
), 77

average
method (primitive streams), 44, 46–47

averaging
Xxx methods (
Collectors
), 36

AWT (Abstract Window Toolkit), 671–721

B
(
byte
), type code, 96, 806

\b
,
\B
, in regular expressions, 148

Banding, 751

Banner
class

getPageCount
method, 760

layoutPages
method, 760

Banners, printing, 759–769

BASE64Encoder
class, 510

BaseStream
interface

iterator
method, 29

parallel
method, 53

unordered
method, 53

BasicFileAttributes
interface, 123

methods of, 124

BasicStroke
class, 693–701

constructor, 701

Batch updates (databases), 354–357

BCP 47 memo, 390, 393

Bean info classes, generated, 467

beforeFirst
method (
ResultSet
), 333, 337

between
method (
Duration

), 363, 365

Bevel join, 694

Bézier curves, 680

Bicubic, bilinear interpolations, 741, 747

BIG_ENDIAN
constant (
ByteOrder
), 138

Big5 encoding, 418, 421

BigDecimal
class, 103

Big-endian order, 76, 79, 420

Binary data

converting to Unicode code units, 68

reading/writing, 78–79

vs. text, 68

Bindings
interface, 446

get
,
put
methods, 447

Birthdays, calculating, 367

BitSet
interface, 43

BLOB

data type (SQL), 301, 357

Blob

interface, 326

getBinaryStream

method, 326–327

getBytes

method, 326–327

length

method, 327

setBinaryStream

method, 327

BLOBs (binary large objects), 326

creating empty, 328

placing in database, 326

Blocking

by I/O methods, 57

by network connections, 236, 240, 252–259

Blur filter, 742

BMP format, 722

body

method (

HttpResponse

), 280, 286

BodyHandlers

class

discarding

method, 281

ofString

method, 280–281

BodyPublishers

class

ofString

method, 280

Book

class, 759

book/Banner.java

, 763

book/BookTestFrame.java

, 761

book/PrintPreviewCanvas.java

, 767

book/PrintPreviewDialog.java

, 766

BOOLEAN

data type (SQL), 301, 357

boolean

type

printing, 69

streams of, 43–49

type code for, 96, 806

vs. C types, 793

writing in binary format, 78

Bootstrap class loader, 535–536

Bounding rectangles, 675

`boxed`
method (primitive streams), 44, 46–47

Bray, Tim, 161

Breadth-first enumerations, 649–650

`breadthFirstEnumeration`
method

(
`DefaultMutableTreeNode`
), 649, 654

Browsers

forms in, 269–278

response pages in, 269

`Buffer`
class, 139–141

`capacity`
method, 141

`clear`
method, 140

`flip`

method, 140

hasRemaining

method, 137

limit

method, 137

mark

method, 140–141

position

method, 141

remaining

method, 140–141

reset

method, 140–141

rewind

method, 140–141

BufferedImage

class, 702, 732

constructor, 733, 738

getColorModel

method, 735, 738

getRaster

method, 733, 738

TYPE_BYTE_GRAY

field, 736, 738

TYPE_BYTE_INDEXED

field, 738

TYPE_INT_ARGB
field, 733–734, 738

BufferedImageOp
interface, 732

filter
method, 740, 747

implementing, 740

BufferedReader
class

lines
method, 72

readLine
method, 71

Buffered
Xxx

Stream
classes, 67

Buffers, 139–141

capacity of, 139

flushing, 57, 69

in-memory, 62

limits of, 139

marks in, 139

positions in, 132, 139

traversing all bytes in, 132

vs. random access, 131

BufferUnderflowException
, 137

@BugReport
annotation, 486

build
method

of
HttpClient.Builder
, 279–280, 285

of
HttpRequest.Builder
, 286

Bundle classes, 424–426

Butt cap, 693

ButtonFrame
class, 451

addActionListener
method, 469–470

buttons1/ButtonFrame.java
, 455

buttons2/action.properties
, 465

buttons2/ButtonFrame.java
, 464

buttons3/ButtonFrame.java

, 473

Byte order mark, 76, 420

byte
type

streams of, 43–49

type code for, 96, 806

vs. C types, 793

BYTE_ARRAY
class (
DocFlavor
), 770

ByteArrayClass
class, 459

ByteArrayClassLoader
class, 460

ByteArrayOutputStream
class, 110

ByteBuffer
class, 132, 139–141

allocate
method, 138, 140

asCharBuffer
method, 138

get
,
get

Xxx methods, 133, 137–138

order

method, 133, 138

put

,

put

Xxx methods, 133, 137–138

wrap

method, 138, 140

bytecodeAnnotations/EntryLogger.java

, 495

bytecodeAnnotations/EntryLoggingAgent.java

, 500

Bytecodes

engineering, 493–501

at load time, 499–500

with hex editor, 548

verifying, 545–549

writing to memory, 459–460

ByteLookupTable

class, 742

constructor, 748

ByteOrder

class

BIG_ENDIAN

,
LITTLE_ENDIAN
constants, 138

Byte-oriented input/output streams, 56

Bytes, reading/writing, 56–59

C
(
char
), type code, 96, 806

C programming language

array types in, 816–819

calling:

from Java programs, 786–792

Java methods from, 809–815

database access in, 292

embedding JVM into, 825–830

FILE*
type in, 59

pointers in, 786

strings in, 795

types, vs. Java types, 793

\c
, in regular expressions, 145

C++ programming language

accessing JNI functions in, 796

array types in, 816

embedding JVM into, 825–830

exceptions in, 820

for native methods, 786, 789

pointers in, 786, 811

Cached row sets, 339–344

CachedRowSet

interface, 339–342

acceptChanges

method, 340, 342

execute

method, 340, 342

getPageSize

method, 340, 342

getTableName

method, 341–342

nextPage

method, 340, 342

populate

method, 339, 342

previousPage

method, 342

setPageSize
method, 340, 342

setTableName
method, 341–342

CachedRowSetImpl
class, 510

Caesar cipher, 539–544

Calendar
class, 361

formatting objects of, 404

weekends in, 368

call
escape (SQL), 329

call
method (
CompilationTask
), 458, 466

Callable
interface, 458

Callback
interface, 554

CallbackHandler
interface

handle
method, 561

CallNonvirtual

Xxx

Method

functions (C), **811**, **815**

CallStatic

Xxx

Method

functions (C), **810**, **815**

Call

Xxx

Method

functions (C), **809**, **814**–**815**

cancelCellEditing

method (

CellEditor

), **622**–**623**, **630**

cancelRowUpdates

method (

ResultSet

), **335**, **338**

canInsertImage

method (

ImageWriter

), **725**, **732**

capacity

method (

Buffer

), **141**

Carriage return character, displaying, **170**

Casts, type use annotations in, **480**

catalog
element (XML), 177

CatalogFeatures
class

defaults
method, 178, 184

CatalogManager
class

catalogResolver
method, 178, 184

Catalogs, 352

CDATA
declaration (DTD), 180–181

CDATA sections (XML), 165

Cell editors (Swing), 619–623

Cell renderers (Swing)

for tables, 600, 617–619

for trees, 651–654

CellEditor
interface

add/removeCellEditorListener
methods, 630

cancelCellEditing
method, 622–623, 630

getCellEditorValue

method, 620, 622–623, 630

isCellEditable

method, 630

shouldSelectCell

method, 622–623, 630

stopCellEditing

method, 622–623, 630

Cells (Swing)

editing, 619–630

selecting, 604

Certificates, 550, 569–571

for software developers, 577

Java Plug-in and, 577

managing, 575–576

publishing fingerprints of, 570

signing, 574–576

CertificateSigner

class, 575

CGI (Common Gateway Interface), 269

Chain of trust, 574

Channels, 253

for files, 132

Channels

class

`newInputStream`

method, 259

`newOutputStream`

method, 253, 259

`char`

type

streams of, 43–49

type code for, 96, 806

vs. C types, 793

`CHAR_ARRAY`

class (`DocFlavor`), 770

Character classes, 144

`CHARACTER`

data type (SQL), 301, 357

Character encodings, 68, 75–78

character order in, 407

explicitly specified, 77

of source files, 420–421

partial, 77

platform, 77–78, 418

Character references (XML), 164

CharacterData

interface

getData

method, 169, 175

Characters

differences between, 408

escaping, 73

normalizing, 409

outlines of, 710

printing, 69

writing in binary format, 78

characters

method (

ContentHandler

), 203, 208

CharBuffer

class, 62, 139

get

method, 138

put

method, 139

CharSequence

interface, 62

charAt

method, 63

chars
method, 44

codePoints
method, 44, 48

length
method, 63

splitting, 6

subSequence
method, 63

toString
method, 63

Charset
class

availableCharsets
method, 77

defaultCharset
method, 77, 419

forName
method, 77

Checkboxes (Swing), 617

checked
attribute (HTML, XML), 162

Checker framework, 480

checkError
method (
PrintWriter

), 69–70

Child elements (XML), 163

namespace of, 200

Child nodes (Swing), 630

adding, 633

connecting lines for, 636–637

children

method (

TreeNode

), 649

choice

element (XML Schema), 187

choice

keyword (message formatting), 416

Church, Alonzo, 366

Cipher

class, 579–580

doFinal

method, 580, 582, 585–586

getInstance

method, 579, 584

get

Xxx

Size

methods, 584

init
method, 584

update
method, 579, 582, 585–586

XXX
_MODE
modes, 579

CipherInputStream
class

read
method, 586

CipherOutputStream
class, 585

constructor, 586

flush
method, 586

write
method, 586

Ciphers

Caesar, 539–544

keys for:

generating, 580–585

public, 566–573, 587–590

performance of, 587

streams for, 585–586

symmetric, 579–580, 587

Class

class

forName

method, 460

getClassLoader

method, 535, 544

getFields

method, 665

getResourceAsStream

method, 517

implementing

AnnotatedElement

, 470

.class

file extension, 534

Class files, 534

corrupted, 546–548

encrypted, 539–545

format of, 493

loading, 534–535

modifying, 493–499

portability of, 420

transformers for, 500

verifying, 545–549

Class loaders, 461, 534–549

as namespaces, 538–539

bootstrap, 535–536

context, 537

extension, 535

hierarchy of, 536–538

separate for each web page, 539

specifying, 537

system, 535

writing, 539–545

Class path, adding JAR files to, 537

Class references, in native code, 803

Classes

adding validation to, 101

annotating, 468, 479, 483

compiling on the fly, 459

encapsulation of, 504

externalizable, 96

inheritance trees of, 650

loading, 460

nonserializable, 101

platform, 535

resolving, 534

separate for each web page, 539

serializable, 89, 109

deserializing, 113–114

static inner, 92

versioning, 107–110

Classifier functions, 35

ClassLoader

class, 535

defineClass

method, 539, 544–545

extending, 460, 539

findClass

method, 539, 544

getParent

method, 544

getSystemClassLoader

method, 544

loadClass

method, 537, 539

Classloader inversion, 537

classLoader/Caesar.java

, 543

classLoader/ClassLoaderTest.java
, 541

CLASSPATH
environment variable, 535

CLEAR
composition rule, 714

clear
method

of
AttributesImpl
, 233

of
Buffer
, 140

clearParameters
method (
PreparedStatement
), 325

client/HttpClientTest.java
, 282

Client/server applications, 295

Clients

connecting to servers, 238–240

multiple, serving, 247–251

CLinker
interface, 847

clip
method (
Graphics2D
), 672, 710–712, 752

Clipping shapes, 672, 710–712

printing, 752

setting region for, 672

CLOB
data type (SQL), 301, 357

Clob
interface, 326

getCharacterStream
method, 326–327

getSubString
method, 326–327

length
method, 327

setCharacterStream
method, 327

CLOBs (character large objects), 326

creating empty, 328

placing in database, 326

clone
method (
Object
), 89, 110

Cloning, 110-113

close

method

of

AutoCloseable

, 62

of

Closeable

, 61-63

of

Connection

, 309, 312, 360

of

FileLock

, 143

of

Flushable

, 61

of

InputStream

, 57-58

of

OutputStream

, 59

of

ResultSet

, 311-312

of

ServerSocket

, 247

of
Statement
, 310, 312

of
XMLStreamWriter
, 222

Closeable
interface, 61

close
method, 61–63

flush
method, 61

closeEntry
method (
Zip
Xxx
Stream
), 85–87

closeOnCompletion
method (
Statement
), 310, 312

closePath
method (
Path2D
), 680, 691

Closure types, 678

cmd
shell, 419

Code generation, annotated, 467–475, 484

Code points, 11

Code units, 44

in regular expressions, 145

writing, 82

Codebreakers, The (Kahn), 540

codePoints
method (
CharSequence
), 44, 48

Collation, 407–413

collation/CollationTest2.java
, 410

CollationKey
class

compareTo
method, 413

Collator
class, 408

compare
method, 412

equals
method, 412

get/setDecomposition
methods, 413

get/setStrength
methods, 412

getAvailableLocales
method, 412

getCollationKey
method, 410, 413

getInstance
method, 412

collect
method (
Stream
), 26–29, 43

collecting/CollectingIntoMaps.java
, 32

collecting/CollectingResults.java
, 27

collecting/DownstreamCollectors.java
, 38

collectingAndThen
method (
Collectors
), 37, 40

Collection
interface

parallelStream

method, 2–4, 49–53

stream

method, 2–4

Collections

iterating over elements of, 2–4

vs. streams, 3

Collections

class

sort

method, 408

Collector

interface, 26

Collectors, 26–41

composing, 38

downstream, 36–41, 50

Collectors

class

averaging

Xxx methods, 36

collectingAndThen

method, 37, 40

counting

method, 36, 40

filtering

method, 38, 41

flatMapping
method, 37, 41

groupingBy
method, 35–40

groupingByConcurrent
method, 35–36, 50

joining
method, 27, 30

mapping
method, 37, 41

maxBy
,
minBy
methods, 37, 40

partitioningBy
method, 35–36, 38

reducing
method, 38

summarizing
Xxx methods, 27, 30, 37

summing
Xxx methods, 36, 40

teeing
method, 38

toCollection
method, 27, 30

toConcurrentMap
method, 32, 34

toList
method, 26, 30

toMap
method, 31–34

toSet
method, 26, 30, 36

toUnmodifiableList
method, 30

toUnmodifiableMap
method, 34

toUnmodifiableSet
method, 30

Color choosers, 621

Color
class, 701

constructor, 740

getRGB
method, 740

translating values into pixel data, 736

Color space conversions, 742

ColorConvertOp
class, 740, 742

ColorModel

class, 736

getDataElements

method, 739

getRGB

method, 735, 739

Colors

components of, 712

composing, 713–716

interpolating, 701–702

negating, 741

solid, 672

Columns (databases)

accessing by number, in result set, 309

names of, 295

number of, 344

Columns (Swing)

accessing, 601–602

adding, 608

detached, 593

hiding, 608

names of, 597–598

rendering, 600

resizing, 593–594, 602–603

selecting, 604

com.sun.security.auth.module

package, 550–551

Combo box editors, 620

Comments (XML), 165

commit

method

of

Connection

, 354–356

of

LoginModule

, 562

commonPool

method (

ForkJoinPool

), 51

Commons CSV library, 519–520

Comparable

interface, 15

compareTo

method, 606

Comparator

interface, 15, 408

Comparators, 606

compare
method (
Collator
), 412

compareTo
method

of
CollationKey
, 413

of
Comparable
, 606

of
Instant
, 363

of
String
, 407

Compilable
interface, 450–451

compile
method, 451

CompilationTask
interface, 457

call
method, 458, 466

compile
method

of
Compilable
, 451

of
Pattern
, 149, 155–156

CompiledScript
interface

eval
method, 451

Compiler

annotations for, 483

invoking, 457

just-in-time, 825

compiler/CompilerTest.java
, 462

Complex types, 185

complexType
element (XML Schema), 186

Composite
interface, 715

composite/CompositeComponent.java
, 718

composite/CompositeTestFrame.java
, 717

composite/Rule.java
, 720

Composition rules, 672–673, 712–721

Computer Graphics: Principles and Practice (Hughes et al.), 680, 734

concat
method (
Stream
), 14

Confidential information, 578

Configuration files, 114, 141

connect
method

of
Socket
, 241

of
URLConnection
, 262, 264, 268

Connection
interface

close
method, 309, 312, 360

commit
method, 354–356

createBlob
,
createClob

methods, 326, 328

createStatement
method, 308–309, 331–332, 334, 336, 354

getAutoCommit
method, 355–356

getMetaData
method, 343, 352

getWarnings
method, 314

prepareStatement
method, 319–320, 325, 331, 336

releaseSavepoint
method, 354, 356

rollback
method, 354–356

setAutoCommit
method, 353, 355–356

setSavepoint
method, 356

Connections (databases)

closing, 312

using row sets after, 339

debugging, 288

pooling, 359

starting new threads, 248

console
method (
System
), 419

Constructive area geometry, 691

Constructor
class, 470

Constructors

annotating, 479

bypassing, 113–114

invoking from native code, 811

no-argument, 101, 113

type use annotations in, 480

Content types, 262

ContentHandler
class, 203–204

characters
method, 203, 208

startDocument
,
endDocument
methods, 203, 207

startElement
,
endElement
methods, 203–208

Context class loader, 537

Control points

dragging, 682

of curves, 679–680

of shapes, 681

convert

Xxx

IndexToModel

methods (

JTable

), 604, 614

Convolution operation, 742

ConvolveOp

class, 740, 742–743

constructor, 748

CookieHandler

class

setDefault

method, 274

Cookies, 274

Coordinate system

custom, 673

translating, 752

Coordinate transformations, 703–709

Copies
class, 776–779

getValue
method, 779

CopiesSupported
class, 776

copy
method (
Files
), 120–122, 130

CORBA (Common Object Request Broker Architecture), 504, 535

Core Swing (Topley), 592, 630, 643

count
function (XPath), 195

count
method (
Stream
), 3–4, 16

counting
method (
Collectors
), 36, 40

Country codes, 35, 390

CRC32 checksum, 88, 131, 133

CRC32
class, 133

CREATE TABLE

statement (SQL), 300

executing, 308, 310, 326

in batch updates, 355

createBindings method (*ScriptEngine*), 447

createBlob, createClob methods (*Connection*), 326, 328

createCachedRowSet method (*RowSetFactory*), 339–340, 342

createDirectory, createDirectories methods (Files), 119–120

createElement, createElementNS methods (Document), 213, 215

createFile

method (
Files
), 119-120

createFilteredRowSet
method (
RowSetFactory
), 342

createImage
Xxx
Stream
methods (
ImageIO
), 724, 730

createJdbcRowSet
,
createJoinRowSet
methods (
RowSetFactory
), 342

createLSOutput
method (
DOMImplementationLS
), 215

createLSSerializer
method (
DOMImplementationLS
), 214

createPrintJob
method (
PrintService
), 771-772

createStatement
method (
Connection
), 308–309, 331–332, 334, 336, 354

createTemp
Xxx methods (
Files
), 120

createTextNode
method (
Document
), 213, 215

createWebRowSet
method (
RowSetFactory
), 342

createXMLStreamReader
method (
XMLInputFactory
), 211

createXMLStreamWriter
method (
XMLOutputFactory
), 217, 221

creationTime
method (
BasicFileAttributes
), 124

Credit card numbers, 578

crypt
program, 582

Cryptography and Network Security (Stallings), 564

CSV files, 519–520

Cubic curves, 679–680

CubicCurve2D
class, 674, 680

CubicCurve2D.Double
class, 675, 677, 690

CubicCurve2D.Float
class, 675, 677

Currencies, 402–403

available, 403

formatting, 401

identifiers for, 402

Currency
class, 402–403

getAvailableCurrencies
method, 403

getCurrencyCode
method, 403

getDefaultFractionDigits
method, 403

getInstance
method, 402–403

getNumeric
Xxx methods, 403

getSymbol
method, 403

toString
method, 403

curveTo
method (
Path2D.Float
), 680, 691

Cyclic references, 113

Cygwin, 790

compiling invocation API, 830

OpenSSL in, 576

D
(
double
), type code, 96, 806

d
literal (SQL), 328

\d
,
\D
, in regular expressions, 146

Dashed lines, 694–695

Data

encrypting/decrypting, 585

fingerprints of, 563–566

signed, 566–569

Data sources (for JNDI service), 359

Data types

codes for, 96, 806

in Java vs. C, 793

mangling names of, 806

print services for, 769–770

database.properties

file, 315, 358

DatabaseMetaData

interface, 343–353

getJDBC

Xxx

Version

methods, 352

getMaxConnection

method, 352

getMaxStatements

method, 311, 352

getSQLStateType

method, 312

getTables
method, 343, 352

supportsBatchUpdates
method, 355, 357

supportsResultSet
Xxx methods, 332, 338

Databases, 291–360

accessing, in C language, 292

autocommit mode of, 353–355

batch updates for, 354–357

caching prepared statements, 320

changing data with SQL, 300

connections to, 302, 304–307, 316

closing, 312, 316

in web and enterprise applications, 358–360

pooling, 359

drivers for, 293–294

duplicating data in, 297

error handling in, 355

escape syntax in, 328–329

integrity of, 353

JAR files for, 302

keys in, 330–331

LOBs in, 326–328

metadata for, 343–353

modifying, 339

native storage for XML in, 358

numbering columns in, 309

outer joins in, 328

populating, 315–318

registering classes for, 304

saving objects to, 487

scalar functions in, 328

schemas for, 352

scrollable/updatable result sets in, 332

setting up parameters in, 340

starting, 303

stored procedures in, 329

structure of, 295, 343

synchronization of, 341

tools for, 345

truncated data from, 313

URLs of, 302

DataFlavor

class, 505

DataInput

interface

readBoolean

method, 79–80

readChar

method, 79–81

readDouble

method, 79–80, 90, 102

readFloat

method, 79–80

readFully

method, 80

readInt

method, 79–81, 90

readLong

method, 79–80

readShort

method, 79–80

readUTF

method, 79–80

skipBytes

method, 80

DataInputStream

class, 60, 65, 79

DataIO

class

xxx

FixedString

methods, **82**

DataOutput

interface, **78**

writeBoolean

method, **78**, **80**

writeByte

method, **78**, **80**

writeChar

method, **78**, **80**–**81**

writeChars

method, **78**–**80**

writeDouble

method, **78**, **80**, **90**, **102**

writeFloat

method, **78**, **80**

writeInt

method, **78**, **80**–**81**, **90**

writeLong

method, **78**, **80**

writeShort

method, **78**, **80**

writeUTF

method, **78**–**80**

DataOutputStream

class, 60, 79

DataSource

interface, 359

DataTruncation

class, 313

get

Xxx methods, 314

Date and Time API, 361–385

legacy code and, 384–385

Date

class (

java.sql

), 384

valueOf

method, 385

Date

class (

java.util

), 96, 103, 361, 384

formatting objects of, 404

months and years in, 367

toInstant

method, 384–385

DATE

data type (SQL), 301, 328, 357

dateFilter

method (
RowFilter
), 607, 616

DateFormat
class, 381, 385, 405

dateFormat/DateTimeFormatTest2.java
, 406

DateFormatter
class (
java.text
), 404

Dates

computing, 367, 372–373

filtering, 607

formatting, 379–384, 388–389, 403–407, 413–415

literals for, 328

local, 366–371

nonexistent, 404

parsing, 381

datesUntil
method (
LocalDate
), 368, 371

DateTimeFormatter
class, 379–384, 403–407

format

method, 379, 383, 407

legacy classes and, 384–385

ofLocalized

Xxx methods, 380, 383, 403, 407

ofPattern

method, 381, 384

parse

method, 381

toFormat

method, 381, 385

withLocale

method, 380, 384, 404, 407

DateTimeParseException

, 407

DateTimeSyntax

class, 779

Daylight savings time, 375–379

DayOfWeek

enumeration, 368

getDisplayName

method, 381, 405

dayOfWeekInMonth

method (

TemporalAdjusters

), 373

Days of week, 405

DBeaver program, 345

DDL
statement (SQL), 310, 326

Debugging
in JNI, 826

JDBC-related problems, 306

locales, 394

mail connections, 288

streams, 15

with
telnet
, 235–238

DECIMAL
data type (SQL), 301, 357

Decimal separators, 388, 395, 402

DecimalFormat
class, 399–402

DecimalFormatSymbols
class, 401

Declaration annotations, 479–481

decode
method (
URLDecoder
), 278

Decomposition, 409

default
statement, 475

DefaultCellEditor
class, 645

constructor, 629

variations of, 619

defaultCharset
method (
Charset
), 77, 419

DefaultHandler
class, 204

DefaultMutableTreeNode
class, 632, 649–651, 653

add
method, 633, 641

constructor, 641

pathFromAncestorEnumeration
method, 650

setAllowsChildren
method, 639, 641

xxx
FirstEnumeration
methods, 649, 654

xxx
OrderEnumeration
methods, 650, 654

defaultPage
method (
PrinterJob
), 758

DefaultRowSorter
class

setComparator
method, 606, 615

setRowFilter
method, 606–608, 615

setSortable
method, 605, 615

defaults
method (
CatalogFeatures
), 178, 184

DefaultTableCellRenderer
class, 618

DefaultTableModel
class

isCellEditable
method, 619

DefaultTreeCellRenderer
class, 651–654

getTreeCellRendererComponent
method, 652–653

set

Xxx

Icon

methods, 652, 654

DefaultTreeModel

class, 632, 642, 664

automatic notifications by, 643

getPathToRoot

method, 644

insertNodeInto

method, 643, 649

isLeaf

method, 639

nodeChanged

method, 643, 649

nodesChanged

method, 649

reload

method, 643, 649

removeNodeFromParent

method, 643, 649

setAsksAllowsChildren

method, 639, 641

defaultWriteObject

method (

ObjectOutputStream

), 102

defineClass

method (
`ClassLoader`
), 539, 544–545

`delete`
method (
`Files`
), 121–122

`DELETE`
method (
`HttpRequest.Builder`
), 286

`DELETE`
statement (SQL), 300

executing, 308, 310, 326

in batch updates, 355

vs. methods of
ResultSet
, 335

`DeleteGlobalRef`
function (C), 803

`deleteIfExists`
method (
`Files`
), 121–122

`deleteRow`
method (
ResultSet
), 335, 337

Delimiters, in text files, 72

@Deprecated

annotation, 483

Depth-first enumerations, 649–650

depthFirstEnumeration

method (

DefaultMutableTreeNode

), 649, 654

Derby databases. *See* **Apache**, **Derby**

derbyclient.jar

file, 302

DES (Data Encryption Standard), 579

Deserialization, 113–114

DestroyJavaVM

function (C), 826, 830

Device coordinates, 704

Diagnostic

interface, 458

get

Xxx methods, 466

DiagnosticCollector

class, 458

constructor, 466

getDiagnostics

method, 466

DiagnosticListener
interface, 458

DialogCallbackHandler
class, 554

Dictionary ordering, 408

digest
method (
MessageDigest
), 565–566

DigiCert, 570, 574

Digital fingerprints, 95–100, 563–566
computing, 108
different for a class and its objects, 98

Digital signatures, 562–577
verifying, 569–571

Direct buffers, 818

Directories
creating, 119–120
current, 129
hierarchical structure of, 630
printing all subdirectories of, 128
traversing, 124–129
user's working, 64

DirectoryStream
interface, 126

discarding
method (
BodyHandlers
), 281

distinct
method (
Stream
), 15–16, 50

dividedBy
method (
Duration
), 366

Doc
interface, 771

DocAttribute
interface, 776

implementing, 778

printing attributes of, 780–783

DocAttributeSet
interface, 777–778

DocFlavor
class, 769–770, 772

DocPrintJob
interface

getAttributes

method, 784

print
method, 772

DOCTYPE
declaration (DTD), 177

including in output, 214

Document
interface, 166

create
Xxx methods, 213, 215

getDocumentElement
method, 166, 174

Document flavors, for print services, 769–770

DocumentBuilder
class

newDocument
method, 213, 215, 228

parse
method, 173

setEntityResolver
method, 178, 183

setErrorHandler
method, 183

DocumentBuilderFactory
class

isIgnoringElementContentWhitespace
method, 185

isNamespaceAware
method, 202

isValidating
method, 185

newDocumentBuilder
method, 166, 173, 213

newInstance
method, 166, 173, 201

newNSInstance
method, 201–202, 205

setIgnoringElementContentWhitespace
method, 182, 185

setNamespaceAware
method, 188, 201–202, 205, 213

setValidating
method, 182, 185

@Documented
annotation, 483, 485–486

doFinal
method (
Cipher
), 580, 582, 585–586

DOM (Document Object Model) parser, 165–166, 203

namespace-awareness of, 201, 205

trees in:

accessing with XPath, 194–199

analyzing, 168–170

building, 203, 212–223, 228

writing, 214–216

dom/JSONConverter.java
, 170

DOMImplementationLS
interface

createLSOutput
method, 215

createLSSerializer
method, 214

DOMResult
class, 228, 233

DOMSource
class, 216, 227

DOUBLE
data type (SQL), 301, 357

double
type

printing, 69

streams of, 43–49

type code for, 96, 806

vs. C types, 793

writing in binary format, 78

`DoubleBuffer`

class, 139

`doubles`

method

of

`Random`

, 45

of

`RandomGenerator`

, 48

of

`SplittableRandom`

, 52

`DoubleStream`

interface, 43–49

`average`

method, 44, 47

`boxed`

method, 44, 47

`mapToDouble`

method, 44

`max`

,

`min`

methods, 44, 47

of
method, 47

sum
,
summaryStatistics
methods, 44, 47

toArray
method, 44, 47

DoubleSummaryStatistics
class, 27, 30–31, 44, 49

doubleValue
method (
Number
), 396

Downstream collectors, 36–41, 50

draw
method (
Graphics2D
), 673–675, 692–693

Drawings

creating, 671–721

printing, 749–759

draw
Xxx methods (
Graphics
), 674

DriverManager
class, 304

getConnection
method, 305, 307, 316, 360

setLogWriter
method, 306

DROP TABLE
statement (SQL), 305

executing, 308, 310

in batch updates, 355

dropWhile
method (
Stream
), 14

DSA (Digital Signature Algorithm), 567–568

DST
,
DST_
Xxx composition rules, 714

DTDHandler
class, 204

DTDs (Document Type Definitions), 176–185

element content in, 178–179

entities in, 181

external, 177

in XML documents, 162, 176–185

locating, 177–178

unambiguous, 180

URLs for, 177

Duration

class

between

method, 363, 365

dividedBy

method, 366

getSeconds

method, 363

immutability of, 363

isNegative

,

isZero

methods, 366

multipliedBy

method, 366

negated

method, 366

of

Xxx methods, 365

to

Xxx methods, 363, 365–366

Dynamic links, 826

Dynamic web pages, 461–467

\e
,
\E
, in regular expressions, 145

Echo servers, 246–247

Eclipse

IDE, 513

Yasson framework, 518

Edge detection, 743

element
element (XML Schema), 186

ELEMENT
element content (DTD), 178–179

Element
interface, 166, 489

getAttribute
method, 170, 174

getSimpleName
method, 489

getTagName
method, 167, 174, 202

setAttribute
,
setAttributeNS
methods, 213–215

Elements (XML)

child, 163

accessing in XPath, 195

namespace of, 200

constructing, 213

counting, in XPath, 195

empty, 162

legal attributes of, 180

mixed content in, 163, 179

names of, 167, 202

root, 163, 185

trimming whitespace in, 169

vs. attributes, 163–164, 181, 223

Ellipse2D

class, 674–675

Ellipse2D.Double

,

Ellipse2D.Float

classes, 675, 677

Ellipses, 675

E-mails

sending, 287–290

terminating lines in, 287

`employee/Employee.c`, 805

`employee/Employee.java`, 804

`employee/EmployeeTest.java`, 804

`EMPTY`
element content (DTD), 178

`empty`
method

of
`Optional`, 21–22

of
`Stream`, 5, 9

Empty tags (XML), 162

Encapsulation, 504

compile-time, 522

`encode`
method (
`URLEncoder`), 278

Encodings. *See* **Character encodings**

Encryption, 578–590

decryption keys for, 540

exporting strong methods of, 540

final block padding in, 580

of class files, 539–545

`end` method

of `Matcher`, 157

of *`MatchResult`*, 158

End cap styles, 693–695

End points, 679

End tags (XML), 162

`endDocument` method (`ContentHandler`), 203, 207

`endElement` method (`ContentHandler`), 203–208

End-of-line character. *See* **Line feed**

Enterprise applications, 358–360

Enterprise JavaBeans (EJBs), 295

Entity references (XML), 164, 181

Entity resolvers, 166, 177

ENTITY

,

ENTITIES

attribute types (DTDs), 180–181

EntityResolver

interface, 184, 204

resolveEntity

method, 177, 183

entries

method (

ZipFile

), 88

Entrust, 574

Entry

class, 607

get

Xxx methods, 616–617

EntryLogger

class, 500

EntryLoggingAgent.mf

file, 499

enum

keyword, 104

enumeration

element (XML Schema), 186

Enumeration
interface, 88

hasMoreElements
method, 832–835

nextElement
method, 649, 832–835

Enumerations

customizing serialization of, 104

ignoring
serialVersionUID
fields, 110

of nodes, in a tree, 649–651

typesafe, 104–107

using attributes for, 181

EnumSyntax
class, 779

EOFException
, 820

Epoch, 103, 362

equals
method

of
Annotation
, 476

of
Collator

, 412

of
Instant
, 363

error
method (
ErrorHandler
), 183–184

Error handlers

in native code, 819–825

installing, 183

ErrorHandler
class, 204

error
,
fatalError
methods, 183–184

warning
method, 183–184

Errors

OutOfMemoryError
, 821

UnsatisfiedLinkError
, 787

Escape hatch mechanism, 641

escape

keyword (SQL), 329

Escapes

in regular expressions, 73

in SQL, 328–329

Essential XML (Box et al.), 159, 224

Euro symbol, 402, 419

`eval` method

of `CompiledScript`, 451

of `ScriptEngine`, 445–447

`evaluate`, `evaluateExpression` methods (*XPath*), 195–196, 199

Event handlers, annotating, 469–475

Event listeners, 468

`EventHandler` class, 471

`EventListenerList` class, 664

Evins, Jim, 600

evn
pointer (C), 796

Exceptions

ArrayIndexOutOfBoundsException
, 820

ArrayStoreException
, 820

BufferUnderflowException
, 137

DateTimeParseException
, 407

EOFException
, 820

FileNotFoundException
, 274

from native code, 819–825

IllegalArgumentException
, 211, 821

IllegalStateException
, 31, 724

in C++, 820

in SQL, 312–314

IndexOutOfBoundsException
, 724, 731

InvalidObjectException
, 110

InvalidPathException
, 115

IOException
, 62, 239

MissingResourceException
, 422

NoSuchAlgorithmException
, 566, 584

NoSuchElementException
, 835

NotSerializableException
, 102

NullPointerException
, 821

OverlappingFileLockException
, 142

ParseException
, 396, 398

ReadOnlyBufferException
, 132

SocketTimeoutException
, 241, 268

SQLException
, 312–314, 332, 354, 356

SQLWarning
, 332

SyncProviderException
, 341–342

type use annotations in, 480

UnknownHostException
, 239

Exception
Xxx functions (C), 820–821, 825

Exclusive lock, 142

exclusiveOr
method (
Area
), 692

exec
method (
Runtime
), 114

exec/ExecSQL.java
, 316

ExecutableElement
interface, 489

execute
method

of
CachedRowSet
, 340, 342

of
RowSet
, 341

of
Statement
, 310, 316, 329, 331

executeBatch
method (
Statement
), 355–356

executeLargeBatch
method (
Statement
), 356

executeLargeUpdate
method (
Statement
), 310

executeQuery
method

of
PreparedStatement
, 320, 326

of
Statement
, 308, 310, 332, 334

executeUpdate
method

of

PreparedStatement
, 320, 326

of
Statement
, 308, 310, 331, 354

executor
method (
HttpClient.Builder
), 285

ExecutorService
interface, 458

exists
method (
Files
), 123–124

EXIT
statement (SQL), 303

exports
keyword, 510, 512–513, 525

Extension class loader, 535

extern "C"
, in native methods (C++), 789

External entities, 181

Externalizable
interface

methods of, 103–104

F
(
float
), type code, 96, 806

\f
, in regular expressions, 145

Factoring algorithms, 568

fatalError
method (
ErrorHandler
), 183–184

Field
class

getName
,
getType
methods, 665

implementing
AnnotatedElement
, 470

Fields

accessing from native code, 801–806

annotating, 468, 483

transient, 101–102

File
class

separator

constant, 64

toPath

method, 117–118

File pointers, 81

File systems, POSIX-compliant, 123

file:

(URI scheme), 260

file.encoding

property, 77

FileChannel

class

lock

method, 141–143

map

method, 132, 137

open

method, 132, 137

tryLock

method, 141–143

FileHandler

class, 420

FileInputStream

class, 64–67

constructor, 66

getChannel

method, 136

read

method, 56

fileKey

method (

BasicFileAttributes

), 124

FileLock

class

close

method, 143

isShared

method, 142

FileNotFoundException

, 274

FileOutputStream

class, 64–67

constructor, 67

getChannel

method, 136

Files

channels for, 132

closing, 124, 126

configuration, 141

copying, 120–122

creating, 119–120

deleting, 121–122

encrypted data in, 585

filtering, 126–127, 723

generated automatically, 467, 488

hierarchical structure of, 630

I/O modes of, 85

locking, 141–143

memory-mapped, 51, 131–141

MIME type of, 118

missing, 458

moving, 120–122

random-access, 81–85, 131

reading/writing, 65, 118–119

by one byte, 56–59

total number of bytes in, 81

traversing, 126–130

with multiple images, 724–732

Files

class, 115, 118–129

copy

method, 120–122, 130

create

Xxx methods, 119–120

delete

,

deleteIfExists

methods, 121–122

exists

method, 123–124

find

method, 125

getOwner

method, 123

is

Xxx methods, 123–124

lines

method, 6, 10, 51, 118

list

method, 124–125

mismatch

method, 118–119

move

method, 120–122

newBuffered

Xxx methods, 118–119

newDirectoryStream

method, 126, 129

new
Xxx
Stream
methods, 118–119

probeContentType
method, 118–119

readAll
Xxx methods, 118–119

readAttributes
method, 123–124

readString
method, 118–119

size
method, 123–124

walk
method, 125–126

walkFileTree
method, 127–129

write
,
writeString
methods, 118–119

FileSystem
class

getPath
method, 130–131

FileSystems

class

newFileSystem

method, 130–131

FileTime

class

toInstant

method, 385

FileTypeDetector

class, 118

FileVisitor

interface, 128–129

methods of, 127

fill

method (

Graphics2D

), 673–674, 692

Filling shapes, 673

fill

Xxx methods (

Graphics

), 674

filter

method

of

BufferedImageOp

, 740, 747

of

Optional
, 19–20

of
Stream
, 3–11, 16

FilteredRowSet
interface, 339

filtering
method (
Collectors
), 38, 41

Filters

for images, 740–749

for numbers, 606–607

for table rows, 606–608

glob patterns for, 126–127

implementing, 607

Filter
Xxx
Stream classes
, 65

Final block padding, 580

find
method

of
Files

, 125

of

Matcher

, 157

findAll

method (

Scanner

), 158

findAny

method (

Stream

), 17

FindClass

function (C), 802, 805, 810

findClass

method (

ClassLoader

), 539, 544

findColumn

method (

ResultSet

), 311

findFirst

method (

Stream

), 16–17

Fingerprints. *See* **Digital fingerprints**

first

method (

ResultSet
), 333, 337

firstDayOf*Xxx* methods (TemporalAdjuster
), 373

firstValue
method (HttpHeaders
), 281, 286

#FIXED
attribute (DTD), 181

flatMap
method

of
Optional
, 22–26

of
Stream
, 12

flatMapping
method (Collectors
), 37, 41

flip
method (Buffer
), 140

FLOAT

data type (SQL), 301, 357

`float`
type

printing, 69

streams of, 43–49

type code for, 96, 806

vs. C types, 793

writing in binary format, 78

`FloatBuffer`
class, 139

Floating-point numbers, 388, 395–403

`flush`
method

of
`CipherOutputStream`
, 586

of
`Closeable`
, 61

of
`Flushable`
, 61, 63

of
`OutputStream`
, 57, 59

`Flushable`

interface, 61–62

close

method, 61

flush

method, 61, 63

fn

keyword (SQL), 328

Folders, icons for, 638–639, 651

followRedirects

method (

HttpClient.Builder

), 279, 285

Font render context, 710

forEach

method (

Stream

), 26, 29

forEachOrdered

method (

Stream

), 26

Foreign functions, 846–847

Forest (Swing), 630, 638

ForkJoinPool

class

commonPool

method, 51

forLanguageTag
method (
Locale
), 391, 394

Format
class, 384, 415

format
method

of
DateTimeFormatter
, 379, 383, 407

of
Format
, 415

of
LocalDate
, 404

of
LocalDateTime
, 404

of
LocalTime
, 404

of
MessageFormat
, 413–415

of
NumberFormat
, 396, 398

of
`String`
, 393

of
`ZonedDateTime`
, 404

Formatting

dates, 388–389, 403–407, 413–415

messages, 413–418

numbers, 388–389, 395–403, 413–415

`formatting/Formatting.java`
, 382

Forms, processing, 269–278

`forName`
method

of
`Charset`
, 77

of
`Class`
, 460

`ForwardingJavaFileManager`
class

constructor, 467

`getFileForOutput`
method, 467

fprintf
function (C), 809

Frame
class, 461

from
method

of
Instant
, 384–385

of
ZonedDateTime
, 384–385

FROM
statement (SQL), 298

FTP (File Transfer Protocol), 264

ftp:
(URI scheme), 260, 264

Function
interface

identity
method, 31

@FunctionalInterface
annotation, 483

\G
, in regular expressions, 148

Gadget chains, 114

Garbage collection

arrays and, 818

native methods and, 797

GB encoding, 421

GeneralPath

class, 674–675, 680

constructor, 690

generate

method (

Stream

), 5, 9, 44

@Generated

annotation, 483–484

generateKey

method (

KeyGenerator

), 580, 585

Generators, converting to streams, 50

Generic types, type use annotations in, 480

get

method

of

AttributeSet

, 779, 783

of

Bindings
, 447

of
ByteBuffer
, 133, 137

of
CharBuffer
, 138

of
Optional
, 20-23

of
Paths
, 115, 117

of
ScriptEngine
, 447

of
ScriptEngineManager
, 447

of
Supplier
, 11

GET
method (
HttpRequest.Builder
), 279, 286

GET
request (HTML), 270, 272

building, 279

getAddress
method (
InetAddress
), 242–243

getAdvance
method (
TextLayout
), 712

getAllByName
method (
InetAddress
), 242–243

getAllowsChildren
method (
TreeNode
), 640

getAnnotation
method (
AnnotatedElement
), 470, 474, 488–489

getAnnotations
method (
AnnotatedElement
), 474

getAnnotationsByType
method (
AnnotatedElement
), 474, 488–489

GetArrayLength
function (C), 816, 819

getAscent
method (
TextLayout
), 712

getAs
Xxx methods (
Optional
Xxx), 44, 48

getAttribute
method (
Element
), 170, 174

getAttributes
method

of
DocPrintJob
, 784

of
Node
, 170, 174

of
PrintService
, 784

getAttribute
Xxx methods (
XMLStreamReader
), 209, 212

`getAuthority`
method (
`URI`
), **261**

`getAutoCommit`
method (
Connection
), **355**-**356**

`getAutoCreateRowSorter`
method (
`JTable`
), **596**

`getAvailableCurrencies`
method (
`Currency`
), **403**

`getAvailableLocales`
method

of
`Collator`
, **412**

of
`Locale`
, **31**

of
`NumberFormat`
, **391**, **396**, **398**

`getAvailableZoneIds`
method (
`ZoneId`

), 375

getAverage

method (*Xxx*

SummaryStatistics

), 27, 30, 49

getBinaryStream

method (

Blob

), 326–327

getBlob

method (

ResultSet

), 326–327

getBlockSize

method (

Cipher

), 584

GetBooleanArrayElements

function (C), 816–819

GetBooleanArrayRegion

function (C), 818–819

GetBooleanField

function (C), 806

getBundle

method (

ResourceBundle

), 422–425

getByName

method (

InetAddress
), 242–243

GetByteArrayElements
function (C), 816–819, 834

GetByteArrayRegion
function (C), 818–819

GetByteField
function (C), 806

getBytes
method (
Blob
), 326–327

getCandidateLocales
method (
ResourceBundle.Control
), 423

getCategory
method (
Attribute
), 778, 783

getCellEditorValue
method (
CellEditor
), 620, 622–623, 630

getCellRenderer
method (
JTable
), 619

getCellSelectionEnabled

method (
JTable
), 614

getChannel
method

of
File
Xxx
Stream
, 136

of
RandomAccessFile
, 136

getChar
method (
ByteBuffer
), 133, 138

getCharacterStream
method (
Clob
), 326–327

GetCharArrayElements
function (C), 816–819

GetCharArrayRegion
function (C), 818–819

getCharContent
method (
SimpleJavaFileObject
), 467

GetCharField
function (C), 806

getChild
method (
TreeModel
), 663–665, 670

getChildAt
method (
TreeNode
), 648

getChildCount
method

of
TreeModel
, 663–665, 670

of
TreeNode
, 649

getChildNodes
method (
Node
), 167, 174

getClassLoader
method (
Class
), 535, 544

getClip
method (
Graphics
), 711, 752

getClob

method (

ResultSet

), **326**–**327**

getCollationKey

method (

Collator

), **410**, **413**

getColorModel

method (

BufferedImage

), **735**, **738**

getColumn

method (

TableColumnModel

), **601**, **614**

getColumnClass

method (

TableModel

), **600**, **613**

getColumnCount

method

of

ResultSetMetaData

, **344**

of

TableModel

, **596**–**597**, **600**

getColumnModel

method (

JTable
), 601, 613

getColumnName
method (
AbstractTableModel
), 597–598, 600

getColumnNumber
method

of
Diagnostic
, 466

of
SAXParseException
, 184

getColumnSelectionAllowed
method (
JTable
), 614

getColumnType
method (
TableModel
), 620

getColumn
Xxx methods (
ResultSetMetaData
), 344, 353

getCommand
method (
RowSet
), 341

getCompactNumberInstance
method (
NumberFormat
), 398

getConcurrency
method (
ResultSet
), 332, 334, 336

getConnection
method (
DriverManager
), 305, 307, 316, 360

getConnectTimeout
method (
URLConnection
), 268

getContent
method (
URLConnection
), 269

getContentEncoding
,
getContentType
methods (
URLConnection
), 262, 265, 269, 274

getContentLength
method (
URLConnection
), 262, 265, 268

getContext
method (
ScriptEngine
), 448

getContextClassLoader
method (
Thread
), 537, 545

getCount
method (*Xxx*
SummaryStatistics
), 30, 49

getCountry
method (
Locale
), 35, 394

getCrc
method (
ZipEntry
), 88

getCurrencyCode
method (
Currency
), 403

getCurrencyInstance
method (
NumberFormat
), 395, 398, 402

getData
method (

CharacterData

), 169, 175

getDataElements

method

of

ColorModel

, 739

of

Raster

, 735, 738

getDataSize

method (

DataTruncation

), 314

getDate

method

of

ResultSet

, 309, 311

of

URLConnection

, 262, 265, 269

getDayOf

Xxx methods

of

LocalDate

, 368, 370

of

ZonedDateTime
, 378

getDays
method (
Period
), 371

getDeclaredAnnotations
method (
AnnotatedElement
), 475

getDecomposition
method (
Collator
), 413

getDefault
method (
Locale
), 392–394

getDefaultEditor
method (
JTable
), 628

getDefaultFractionDigits
method (
Currency
), 403

getDefaultName
method (
NameCallback
), 561

getDefaultRenderer
method (
JTable
), 619, 628

getDescent
method (
TextLayout
), 712

getDiagnostics
method (
DiagnosticCollector
), 466

GetDirectBuffer
Xxx functions (C), 818

getDisplayCountry
,
getDisplayLanguage
methods (
Locale
), 32, 394

getDisplayName
method

of
DayOfWeek
,
Month
, 381, 405

of
Locale
, 392–394, 396

getDocumentElement
method (
Document
), 166, 174

getDoInput
,
getDoOutput
methods (
URLConnection
), 267

getDouble
method

of
ByteBuffer
, 133, 138

of
ResultSet
, 309, 311

GetDoubleArrayElements
function (C), 816–819

GetDoubleArrayRegion
function (C), 818–819

GetDoubleField
function (C), 802, 806

getEnclosedElements
method (
TypeElement
), 489

getEngine

Xxx methods (
ScriptEngineManager
), 444–445

getEntry
method (
ZipFile
), 88

getErrorCode
method (
SQLException
), 312, 314

getErrorStream
method (
HttpURLConnection
), 274, 278

getErrorWriter
method (
ScriptContext
), 448

getExpiration
method (
URLConnection
), 262, 265, 269

getExtensions
method (
ScriptEngineFactory
), 445

GetFieldID
function (C), 802, 806

getFields
method (
Class
), 665

getFileForOutput
method (
ForwardingJavaFileManager
), 467

getFileName
method (
StackTraceElement
), 116–117

getFilePointer
method (
RandomAccessFile
), 81, 85

getFileSuffixes
method (
ImageReaderWriterSpi
), 731

getFillsViewportHeight
method (
JTable
), 596

getFirstChild
method (
Node
), 169, 174

getFloat
method (

ByteBuffer
), 133, 138

GetFloatArrayElements
function (C), 816–819

GetFloatArrayRegion
function (C), 818–819

GetFloatField
function (C), 806

getFontRenderContext
method (
Graphics2D
), 710, 712

getFormatNames
method (
ImageReaderWriterSpi
), 731

getFragment
method (
URI
), 261

getHeader
Xxx methods (
URLConnection
), 262–265, 268

getHeight
method

of
ImageReader
, 725, 731

of
`PageFormat`
, 752, 759

`getHost`
method (
`URI`
), 261

`getHost`
Xxx methods (
`InetAddress`
), 243

`getHour`
method

of
`LocalTime`
, 374

of
`ZonedDateTime`
, 379

`getIdentifier`
method (
`Entry`
), 616

`getIfModifiedSince`
method (
`URLConnection`
), 268

`getImageable`
Xxx methods (
`PageFormat`

), 752, 759

getImage

Xxx

By

Xxx methods (

ImageIO

), 723, 730

getIndex

method (

DataTruncation

), 314

getIndexOfChild

method (

TreeModel

), 663, 670

getInputStream

method

of

Socket

, 239–240, 244

of

URLConnection

, 262, 269, 272, 274

of

ZipFile

, 88

getInstance

method

of

AlphaComposite
, 715, 721

of
Cipher
, 579, 584

of
Collator
, 412

of
Currency
, 402–403

of
KeyGenerator
, 585

of
Locale
, 408

of
MessageDigest
, 564–566

getInt
method

of
ByteBuffer
, 133, 138

of
ResultSet
, 309, 311

GetIntArrayElements

function (C), 816–819

GetIntArrayRegion

function (C), 818–819

getInterface

method (

Invocable

), 450

GetIntField

function (C), 802, 806, 834

getISOCountries

method (

Locale

), 392, 394

getISOLanguages

method (

Locale

), 392

getJavaFileObjectsFrom

Xxx methods (

StandardJavaFileManager

), 466

getJDBC

Xxx

Version

methods (

DatabaseMetaData

), 352

getKeys

method (

ResourceBundle

), 425–426

getKind

method (

Diagnostic

), 466

getLanguage

method (

Locale

), 394

getLargeUpdateCount

method (

Statement

), 310

getLastChild

method (

Node

), 169–170, 174

getLastModified

method (

URLConnection

), 262, 265, 269

getLastPathComponent

method (

TreePath

), 642, 648

getLastSelectedPathComponent

method (

JTree

), 642, 648

getLeading
method (
TextLayout
), 712

getLength
method

of
Attributes
, 208

of
NamedNodeMap
, 175

of
NodeList
, 167, 175

getLineNumber
method

of
Diagnostic
, 466

of
SAXParseException
, 184

getLocale
method (
MessageFormat
), 415

getLocalHost
method (

InetAddress
), 242-243

getLocalName
method

of
Attributes
, 208

of
Node
, 202

of
XMLStreamReader
, 212

getLong
method (
ByteBuffer
), 133, 138

GetLongArrayElements
function (C), 816-819

GetLongArrayRegion
function (C), 818-819

GetLongField
function (C), 806

getMax
method (*Xxx*
SummaryStatistics
), 27, 31, 49

getMaxConnections

method (
DatabaseMetaData
), 352

getMaxStatements
method (
DatabaseMetaData
), 311, 352

getMessage
method (
Diagnostic
), 466

getMetaData
method

of
Connection
, 343, 352

of
ResultSet
, 344, 353

getMethodCallSyntax
method (
ScriptEngineFactory
), 449

GetMethodID
function (C), 811, 814

getMimeTypes
method (
ScriptEngineFactory
), 445

getMIMETypes
method (
ImageReaderWriterSpi
), 731

getMin
method (*Xxx*
SummaryStatistics
), 31, 49

getMinute
method

of
LocalTime
, 374

of
ZonedDateTime
, 379

getModel
method (
Entry
), 617

getMonth
,
getMonthValue
methods

of
LocalDate
, 370

of
ZonedDateTime
, 378

`getMonths`
method (
`Period`
), 371

`getMoreResults`
method (
`Statement`
), 329-330

`getName`
method

of
`Attribute`
, 783

of
`Field`
, 665

of
`NameCallback`
, 561

of
`Principal`
, 553

of
`PrintService`
, 771

of
`XMLStreamReader`
, 212

of

ZipEntry
, 88

of
ZipFile
, 88

getNames
method (
ScriptEngineFactory
), 445

getNamespaceURI
method (
Node
), 202

getNano
method

of
LocalTime
, 374

of
ZonedDateTime
, 379

getNextEntry
method (
ZipInputStream
), 85–87

getNextException
method (
SQLException
), 312, 314

getNextSibling
method (
Node
), 169-170, 174

getNextWarning
method (
SQLWarning
), 314

getNode
Xxx methods (
Node
), 170, 174, 202

getNumberInstance
method (
NumberFormat
), 395, 398

getNumeric
Xxx methods (
Currency
), 403

getNum
Xxx methods (
ImageReader
), 724, 731

getObject
method

of
ResourceBundle
, 424-425

of

ResultSet
, 309, 311

GetObjectArrayElement
function (C), 816, 819

GetObjectClass
function (C), 802–803

GetObjectField
function (C), 802, 806

getOffset
method (
ZonedDateTime
), 379

getOrientation
method (
PageFormat
), 759

getOriginatingProvider
method

of
ImageReader
, 723, 731

of
ImageWriter
, 732

getOutputSize
method (
Cipher
), 584

getOutputStream
method

of
Socket
, 240, 244

of
URLConnection
, 262, 269, 272

getOwner
method (
Files
), 123

getPageCount
method (
Banner
), 760

getPageSize
method (
CachedRowSet
), 342

getParameter
method (
DataTruncation
), 314

getParent
method

of
ClassLoader
, 544

of
Path
, 116–117

of
TreeNode
, 648, 650

getParentNode
method (
Node
), 174

getPassword
method

of
PasswordCallback
, 561

of
RowSet
, 341

getPath
method

of
FileSystem
, 130–131

of
TreeSelectionEvent
, 662

of
URI
, 261

getPaths
method (
TreeSelectionEvent
), 656, 662

getPathToRoot
method (
DefaultTreeModel
), 644

getPercentInstance
method (
NumberFormat
), 395, 398

getPixel
,
getPixels
methods (
Raster
), 734, 739

getPointCount
method (
ShapeMaker
), 681

getPort
method (
URI
), 261

getPreviousSibling
method (
Node
), 174

getPrincipals
method (
Subject
), 553

getPrinterJob
method (
PrinterJob
), 749, 758

getPrintService
method (
StreamPrintServiceFactory
), 773

getPrompt
method

of
NameCallback
, 561

of
PasswordCallback
, 561

getQName
method (
Attribute
), 208

getQualifiedName
method (
TypeElement
), 489

getQuery
method (

URI
), 261

getRaster
method (
BufferedImage
), 733, 738

getReader
method (
ScriptContext
), 448

getReader
Xxx methods (
ImageIO
), 723, 730

getReadTimeout
method (
URLConnection
), 268

getRequestProperties
method (
URLConnection
), 268

getResourceAsStream
method (
Class
,
Module
), 517

getResponseCode
method (

HttpURLConnection
), 275

getResultSet
method (
Statement
), 310

getRGB
method

of
Color
, 740

of
ColorModel
, 735, 739

getRoot
method

of
Path
, 116–117

of
TreeModel
, 663–665, 670

getRotateInstance
method (
AffineTransform
), 706, 708

getRow
method (
ResultSet

), 333, 337

getRowCount
method (
TableModel
), 596–597, 600

getRowSelectionAllowed
method (
JTable
), 614

getRow
Xxx methods (
JTable
), 613

getSavepoint
Xxx methods (
Savepoint
), 356

getScaleInstance
method (
AffineTransform
), 706, 708

getSecond
method

of
LocalTime
, 374

of
ZonedDateTime
, 379

getSeconds

method (

Duration

), 363

getSelectedColumns

method (

JTable

), 604, 608

getSelectedRows

method (

JTable

), 604

getSelectionModel

method (

JTable

), 613

getSelectionPath

method (

JTree

), 642, 648, 661

getSelectionPaths

method (

JTree

), 656, 661

getShearInstance

method (

AffineTransform

), 706, 708

getShort

method (

ByteBuffer
), 133, 138

GetShortArrayElements
function (C), 816–819

GetShortArrayRegion
function (C), 818–819

GetShortField
function (C), 806

getSimpleName
method (
Element
), 489

getSize
method (
ZipEntry
), 88

getSource
method (
Diagnostic
), 466

getSQLState
method (
SQLException
), 312, 314

getSQLStateType
method (
SQLException
), 312

getStandardFileManager

method (
JavaCompiler
), **465**

GetStaticFieldID
,
GetStatic
Xxx
Field
functions (C), **805**–**806**

GetStaticMethodID
function (C), **810**, **815**

getStrength
method (
Collator
), **412**

getString
method

of
ResourceBundle
, **423**, **425**

of
ResultSet
, **309**, **311**

getStringArray
method (
ResourceBundle
), **426**

GetStringChars
,
GetStringLength

functions (C), 798

GetStringRegion

function (C), 797

GetStringUTFChars

function (C), 796, 798–799, 834

GetStringUTFLength

,

GetStringUTFRegion

functions (C), 797

getStringValue

method (

Entry

), 617

getSubject

method (

LoginContext

), 552

getSubString

method (

Clob

), 326–327

getSum

method (*Xxx*

SummaryStatistics

), 30, 49

GetSuperclass

function (C), 846

getSymbol

method (

Currency
), 403

getSystemClassLoader
method (
ClassLoader
), 544

getSystemJavaCompiler
method (
ToolProvider
), 457

getTableCellEditorComponent
method (
TableCellEditor
), 621–623, 629

getTableCellRendererComponent
method (
TableCellRenderer
), 617, 629

getTableHeader
method (
JTable
), 594

getTableName
method (
CachedRowSet
), 342

getTables
method (
DatabaseMetaData
), 343, 352

getTagName
method (
Element
), 167, 174, 202

getTask
method (
JavaCompiler
), 457–458, 465

Getters/setters, generated automatically, 492

getText
method (
XMLStreamReader
), 212

getTimeZone
method (
TimeZone
), 385

getTransferSize
method (
DataTruncation
), 314

getTranslateInstance
method (
AffineTransform
), 706, 709, 711

getTreeCellRendererComponent
method

of
DefaultTreeCellRenderer
, 652–653

of
`TreeCellRenderer`
, 652–654

`getType`
method

of
`Field`
, 665

of
`ResultSet`
, 332, 336

`getUpdateCount`
method (
`Statement`
), 310, 330

`getURI`
method (
`Attribute`
), 208

`getURL`
method (
`RowSet`
), 341

`getURLs`
method (
`URLClassLoader`
), 537

`getUserInfo`
method (
`URI`

), 261

getUsername

method (

RowSet

), 341

getValue

method

of

Attributes

, 208

of

Copies

, 779

of

Entry

, 617

of

Win32RegKey

, 832–833

getValueAt

method (

TableModel

), 596–597, 600, 619

getValueCount

method (

Entry

), 617

getVendorName

,

`getVersion`
methods (
`IIOServiceProvider`
), 723, 731

`getWarnings`
method (
`Connection`
,
`ResultSet`
,
`Statement`
), 314

`getWidth`
method

of
`ImageReader`
, 725, 731

of
`PageFormat`
, 752, 759

`getWriter`
method (
`ScriptContext`
), 448

`getWriter`
Xxx methods (
`ImageIO`
), 723, 730

`getYear`
method

of
LocalDate
, 370

of
ZonedDateTime
, 378

getYears
method (
Period
), 371

GIF format, 722

animated, 724

image manipulations on, 744

printing, 769

GlassFish server, 359

Glob patterns, 126–127

GlobalSign, 574

GMail, 287–288

Gnu C compiler, 789–790

Gödel's theorem, 546

Google Maps, 271

GradientPaint
class, 701–702

constructor, 702–703

cyclic

parameter, 702

Graphic Java™ (Geary), 592, 630

Graphics

class, 671–672

draw

Xxx,

fill

Xxx methods, 674

get/setClip

methods, 710–711, 752

Graphics2D

class, 672

clip

method, 672, 710–712, 752

draw

method, 673–675, 692–693

fill

method, 673–674, 692

getFontRenderContext

method, 710, 712

rotate

method, 705, 709

scale

method, 704–705, 709

setComposite

method, 673, 715, 721

setPaint
method, 672, 701–703

setRenderingHint
,
setRenderingHints
methods, 672

setStroke
method, 672, 693, 701

setTransform
method, 707, 709

shear
method, 705, 709

transform
method, 673, 707, 709

translate
method, 705, 709, 761

Greenwich Royal Observatory, 362, 375

Gregorian calendar reform, 371

GregorianCalendar
class

toZonedDateTime
method, 384–385

Groovy programming language, 444, 451–452

group
method

of

Matcher
, 157

of
MatchResult
, 158

groupCount
method (
Matcher
), 157

Grouping, 35–36

classifier functions of, 35

reducing to numbers, 36

groupingBy
method (
Collectors
), 35–40

groupingByConcurrent
method (
Collectors
), 35–36, 50

>
, entity reference, 164

GUI (Graphical User Interface), scripting events for, 451–456

\h
,
\H
, in regular expressions, 146

Half-closing connections, 251–252

Handbook of Applied Cryptography, The (Menezes et al.), 567

handle
method (
CallbackHandler
), 561

handleGetObject
method (
ResourceBundle
), 425–426

Handles (Swing), 635, 652

hash/Digest.java
, 565

hashCode
method (
Annotation
), 476

HashSet
class

readObject
,
writeObject
methods, 102

Hash
Xxx
AttributeSet
classes, 750, 777

Haskell programming language, 444

hasMoreElements
method (
Enumeration
), 832-835

hasNext
method (
XMLStreamReader
), 211

hasRemaining
method (
Buffer
), 137

Header information, from server, 262

header
method (
HttpRequest.Builder
), 286

Headers (Swing tables)

rendering, 619

scrolling, 593

headers
method (
HttpResponse
), 281, 286

helloNative/HelloNative.c
, 789

helloNative/HelloNative.h
, 788

helloNative/HelloNative.java
, 787

helloNative/HelloNativeTest.java
, 790

Hex editors

creating class files in, 546

modifying bytecodes with, 548

Hidden commands, in XML comments, 165

Hosts, 242–243

HTML (HyperText Markup Language)

attributes in, 162, 164

end and empty tags in, 162

forms in, 269

generating from XML files, 223–226

mixing with JSP, 461

printing, 769

vs. XML, 161–162

HTTP (Hypertext Transfer Protocol), 295

redirects between HTTPS and, 275

request headers in, 263–264

http:
(URI scheme), 260

HttpClient

class, 279–286

enabling logging for, 282

newBuilder

method, 279, 281, 285

newHttpClient

method, 279, 285

send

method, 285

sendAsync

method, 281, 285

HttpClient.Builder

class

build

method, 279–280, 285

executor

method, 285

followRedirects

method, 279, 285

HttpHeaders

class

firstValue

method, 281, 286

map

method, 281, 286

HttpRequest

class

newBuilder

method, 279, 281, 286

HttpRequest.Builder

class

build

method, 286

DELETE

method, 286

GET

method, 279, 286

header

method, 286

POST

method, 280, 286

PUT

method, 286

uri

method, 279–281, 286

HttpResponse

class

methods of, 280, 286

HttpResponse.BodyHandlers

class

discarding

method, 281

ofString
method, 280–281

HTTPS (Hyper Text Transfer Protocol Secure), 275

https:
(URI scheme), 260

HttpURLConnection
class, 274

getErrorStream
method, 274, 278

getResponseCode
method, 275

setInstanceFollowRedirects
method, 275

I

I
(
int
), type code, 96, 806

I/O streams. *See* **Input streams**, **Output**

streams

IANA (Internet Assigned Numbers Authority), 375

IBM, 159

DB2 database, 301

DOM parser, 166

IBM437 encoding, 419

ICC profiles, 734

Icons

in column headers, 619

in table cells, 617

in trees, 638–639, 651

ID

,

IDREF

,

IDREFS

attribute types (DTDs), 180–181

Identity (do-nothing) transformation, 216

identity

method (

Function

), 31

Identity values, 42

IDs, uniqueness of, 181, 189

IETF BCP 47, 390, 393

ifPresent

method

of

Optional

, 18–19

of

Optional

Xxx, 48

ifPresentOrElse
method (
Optional
), 19

of
Optional
, 19

IIOImage
class, 725, 732

IIOServiceProvider
class

get
Xxx methods, 723, 731

IllegalAccessException
, 665

IllegalArgumentException
, 211, 821

IllegalStateException
, 31, 724

ImageInputStream
class, 724

“Seek forward only” mode, 724

ImageIO
class

createImage
Xxx
Stream

methods, 724, 730

determining image type, 722–723

getImage

Xxx

By

Xxx methods, 723, 730

getReader

Xxx,

getWriter

Xxx methods, 723, 730

read

,

write

methods, 722, 729

imageIO/ImageIOFrame.java

, 726

ImageOutputStream

interface, 725

imageProcessing/ImageProcessingFrame.java

, 744

ImageReader

class, 722–723

getHeight

method, 725, 731

getNum

Xxx methods, 724, 731

getOriginatingProvider

method, 723, 731

getWidth

method, 725, 731

read

,

readThumbnail

methods, 731

setInput

method, 730

ImageReaderWriterSpi

class

get

Xxx methods, 731

Images

blurring, 742

color values of, 735

edge detection of, 743

filtering, 740–749

getting size of, before reading, 725

incremental rendering of, 732

manipulating, 732–749

metadata in, 725

multiple, in a file, 724–732

printing, 749–759, 769, 773

raster, 721–749

constructing from pixels, 733–740

readers/writers for, 722–732

rotating, 741

superimposing, 712–713

thumbnails for, 725

vector, 671–721

ImageWriter

class, 722, 725

canInsertImage

method, 725, 732

getOriginatingProvider

method, 732

setOutput

method, 732

write

,

writeInsert

methods, 725, 732

implements

specification, 480

#IMPLIED

attribute (DTD), 181

import

statement, 538

INCLUDE
environment variable, 830

include
method (
RowFilter
), 607, 616

Incremental rendering, 732

Indexed color model, 742

IndexOutOfBoundsException
, 724, 731

InetAddress
class

get
Xxx methods, 242–243

inetAddress/InetAddressTest.java
, 242

InetSocketAddress
class

isUnresolved
method, 259

Inheritance trees, 312

@Inherited
annotation, 483, 487

init
method

of

Cipher
, 584

of
KeyGenerator
, 585

Initialization blocks, for shared libraries, 792

initialize
method (
LoginModule
), 562

INPUT_STREAM
class (
DocFlavor
), 770

Input streams, 56–78

as input source, 166

buffered, 65–67

byte processing in, 65

byte-oriented, 56

chaining, 65

closing, 57

encoding for, 68

filters for, 64–67

hierarchy of, 59–63

keeping open, 251

objects in, 89–114

redirecting, 447–448

Unicode, 56

InputSource

class, 184

InputStream

class, 56–59, 61

available

method, 57–58

close

method, 57–58

mark

method, 58

markSupported

method, 59

nullInputStream

method, 59

read

method, 56–58

readAllBytes

,

readNBytes

methods, 56, 58

reset

method, 59

skip

,
skipNBytes
methods, 58

transferTo
method, 58

InputStreamReader
class, 68

INSERT
statement (SQL), 300

autogenerated keys and, 331

executing, 308, 310, 326

in batch updates, 355

vs. methods of
ResultSet
, 335

insertNodeInto
method (
DefaultTreeModel
), 643, 649

insertRow
method (
ResultSet
), 335, 337

Instance fields

accessing from native code, 801–805

annotating, 479

instanceof
keyword, 480

Instant
class, 362

compareTo
method, 363

equals
method, 363

from
method, 384–385

immutability of, 363

legacy classes and, 384–385

minus
,
minus
Xxx methods, 365–366

now
method, 363, 365

plus
,
plus
Xxx methods, 365–366

Instrumentation API, 499

int
type

printing, 69

storing, 79

streams of, 43–49

type code for, 96, 806

vs. C types, 793

writing in binary format, 78

IntBuffer

class, 139

INTEGER

data type (SQL), 301, 357

IntegerSyntax

class, 779

IntelliJ IDE, 102

@interface

declaration, 469, 475

Interfaces

accessing script classes with, 450

annotating, 479, 483

implementing in script engines, 449

Internationalization, 387–442

Internet Engineering Task Force, 390

Interpolation, 741

for gradients, 701–702

strategies of, 741

when transforming images, 741

Interruptible sockets, 252–259

interruptible/InterruptibleSocketTest.java
, 254

intersect
method (
Area
), 692

ints
method

of
Random
, 45

of
RandomGenerator
, 48

of
SplittableRandom
, 52

IntStream
interface, 43–49

average
method, 44, 46

boxed
method, 44, 46

mapToInt
method, 44

max
,
min
methods, 44, 46

of
method, 44, 46

range
,
rangeClosed
methods, 44, 46

sum
,
summaryStatistics
methods, 44, 46

toArray
method, 44, 46

IntSummaryStatistics
class, 27, 30–31, 44, 49

intValue
method (
Number
), 396

Invalid pointers (C, C++), 786

InvalidObjectException
, 110

InvalidPathException
, 115

Invocable

interface, 448

getInterface
method, 450

invoke
Xxx methods, 448, 450

Invocation API, 825–830

invocation/InvocationTest.c
, 826

IOException
, 62, 239

IP addresses, 237, 242–243

IPP (Internet Printing Protocol) 1.1, 783

IPv6 addresses, 242

isAfter
method

of
LocalDate
, 371

of
LocalTime
, 374

of
ZonedDateTime
, 379

isAfterLast
method (

ResultSet
), 333, 337

isAnnotationPresent
method (
AnnotatedElement
), 474

IsAssignableFrom
function (C), 834, 846

isBefore
method

of
LocalDate
, 371

of
LocalTime
, 374

of
ZonedDateTime
, 379

isBeforeFirst
method (
ResultSet
), 333, 337

isCellEditable
method

of
AbstractCellEditor
, 622

of
`AbstractTableModel`
, **619**

of
CellEditor
, **630**

of
`DefaultTableModel`
, **619**

of
TableModel
, **600**, **619**

`isCharacters`
method (
XMLStreamReader
), **212**

`isClosed`
method

of
ResultSet
, **311**

of
`Socket`
, **241**

of
Statement
, **310**

`isConnected`
method (

Socket
), 241

isDirectory
method

of
BasicFileAttributes
, 124

of
ZipEntry
, 88

isEchoOn
method (
PasswordCallback
), 561

isEndElement
method (
XMLStreamReader
), 212

isExecutable
method (
Files
), 123–124

isFirst
method (
ResultSet
), 333, 337

isGroupingUsed
method (
NumberFormat
), 399

isHidden
method (
Files
), 123–124

isIgnoringElementContentWhitespace
method (
DocumentBuilderFactory
), 185

isInputShutdown
method (
Socket
), 252

isLast
method (
ResultSet
), 333, 337

isLeaf
method

of
DefaultTreeModel
, 639

of
TreeModel
, 640, 663, 671

of
TreeNode
, 639–640

isLeapYear
method (
LocalDate

), 371

isNamespaceAware
method

of
DocumentBuilderFactory
, 202

of
SAXParserFactory
, 207

isNegative
method (
Duration
), 366

ISO 216 standard, 425

ISO 639-1 standard, 390, 394

ISO 3166-1 standard, 390, 394

ISO 4217 standard, 401, 403

ISO 8601 standard, 328, 484

ISO 8859-1 standard, 68, 77

isOutputShutdown
method (
Socket
), 252

isParseIntegerOnly
method (
NumberFormat
), 399

isPresent
method (
Optional
), 20–23

isReadable
method (
Files
), 123–124

isRegularFile
method

of
BasicFileAttributes
, 124

of
Files
, 123–124

isShared
method (
FileLock
), 142

isStartElement
method (
XMLStreamReader
), 212

isSymbolicLink
method

of
BasicFileAttributes
, 124

of
Files
, 123–124

isUnresolved
method (
InetSocketAddress
), 259

isValidating
method

of
DocumentBuilderFactory
, 185

of
SAXParserFactory
, 207

isWhiteSpace
method (
XMLStreamReader
), 212

isWritable
method (
Files
), 123–124

isZero
method (
Duration
), 366

item
method

of
NamedNodeMap
, 175

of
NodeList
, 167, 175, 183

Iterable
interface, 126, 457

spliterator
method, 10

iterate
method (
Stream
), 5, 9, 15, 44

Iterator
interface, 308

iterator
method

of
BaseStream
, 29

of
SQLException
, 312, 314

of
Stream
, 26

Iterators, 26

converting to streams, 6, 50

splittable, 9–10

J

(

long

), type code, 96, 806

JAAS (Java Authentication and Authorization Service), 550–553

configuration files in, 550, 552

login modules in, 553–562

jaas/jaas.config

, 560

jaas/JAASTest.java

, 560

jaas/SimpleCallbackHandler.java

, 559

jaas/SimpleLoginModule.java

, 557

jaas/SimplePrincipal.java

, 555

JAR files

adding to class path, 537

analyzing dependencies of, 528–529

automatic registration in, 304

file resources in, 517

for plugins, 536

manifest of, 86, 519

META-INF/services
directory, 526

modular, 514–515, 520

resources in, 421

signing, 571

jar
program, 514

jar:
(URI scheme), 260

jarray
type (C), 833

jarsigner
program, 571

Jar
Xxx
Stream
classes, 86

Java 2D API, 671–721

affine transformations in, 706

colors in, 734

constructive area geometry operations in, 691

features supported in, 672

filters in, 740–749

paint in, 701–703

printing in, 760

rendering pipeline in, 672–674

sample values in, 733

shape classes in, 674–675, 679

strokes in, 693

transparency in, 712–715

Java Bug Database, 742

Java EE (Java Platform, Enterprise Edition), 295

Java Platform Module System, 504–531

migration to, 519–523

Java Plug-in, loading signed code, 577

`java`
program

`--add-exports`
option, 521–523

`--add-modules`
option, 279

`--add-opens`
option, 521–523

`--illegal-access`

option, 521–523

-javaagent

option, 499

jdbc.drivers

property in, 304

--module

,

--module-path

options, 507

-noverify

option, 548

specifying locales in, 392

Java programming language

internationalization support in, 387

platform-independent, 79

vs. SQL, 321

Java Virtual Machine Specification, The, 493, 547

java.awt

package, 505

java.awt.AlphaComposite

API, 721

java.awt.BasicStroke

API, 701

java.awt.Color

API, 740

java.awt.font.TextLayout
API, 712

java.awt.geom
package, 102

java.awt.geom.AffineTransform
API, 707–709

java.awt.geom.Arc2D.Double
API, 690

java.awt.geom.Area
API, 692

java.awt.geom.CubicCurve2D.Double
API, 690

java.awt.geom.GeneralPath
API, 690

java.awt.geom.Path2D
API, 691

java.awt.geom.Path2D.Float
API, 691

java.awt.geom.QuadCurve2D.Double
API, 690

java.awt.geom.RoundRectangle2D.Double
API, 690

java.awt.GradientPaint
API, 703

java.awt.Graphics
API, 711

java.awt.Graphics2D

API, 674, 701, 703, 709, 712, 721

java.awt.image.AffineTransformOp

API, 747

java.awt.image.BufferedImage

API, 738

java.awt.image.BufferedImageOp

API, 747

java.awt.image.ByteLookupTable

API, 748

java.awt.image.ColorModel

API, 739

java.awt.image.ConvolveOp

API, 748

java.awt.image.Kernel

API, 749

java.awt.image.LookupOp

API, 748

java.awt.image.Raster

API, 738–739

java.awt.image.RescaleOp

API, 747

java.awt.image.ShortLookupTable

API, 748

java.awt.image.WritableRaster

API, 739

java.awt.print.PageFormat

API, 759

java.awt.print.Printable

API, 758

java.awt.print.PrinterJob

API, 758

java.awt.TexturePaint

API, 703

java.base

module, 535

java.datatransfer

module, 535

java.desktop

module, 523–524, 535

java.instrument

module, 535

java.io

package, 78

java.io.Buffered

Xxx

Stream

APIs, 67

java.io.Closeable

API, 63

java.io.DataInput

API, 80

java.io.DataOutput

API, **80**

java.io.File

API, **118**

java.io.FileInputStream

API, **66**, **136**

java.io.FileOutputStream

API, **67**, **136**

java.io.Flushable

API, **63**

java.io.InputStream

API, **58**–**59**

java.io.ObjectInputStream

API, **94**

java.io.ObjectOutputStream

API, **94**

java.io.OutputStream

API, **59**

java.io.PrintWriter

API, **70**

java.io.PushbackInputStream

API, **67**

java.io.RandomAccessFile

API, **85**, **136**

java.lang

,

java.lang.annotation
packages, 482

java.lang.annotation.Annotation
API, 476

java.lang.Appendable
API, 63

java.lang.CharSequence
API, 48, 63

java.lang.Class
API, 544

java.lang.ClassLoader
API, 544–545

java.lang.Iterable
API, 10

java.lang.Readable
API, 63

java.lang.reflect.AnnotatedElement
API, 474–475

java.lang.System
API, 792

java.lang.Thread
API, 545

java.logging
module, 524, 535

java.management
module, 535

java.management.rmi
module, 535

java.naming
module, 535

java.net
package

socket connections in, 240

supporting IPv6 addresses in, 242

URLs vs. URIs in, 260

java.net.http
package, 279

java.net.http.HttpClient
API, 285

java.net.http.HttpClient.Builder
API, 285

java.net.http.HttpHeaders
API, 286

java.net.http.HttpRequest
API, 286

java.net.http.HttpRequest.Builder
API, 286

java.net.http.HttpResponse
API, 286

java.net.HttpURLConnection
API, 278

java.net.InetAddress
API, 243

java.net.InetSocketAddress
API, 259

java.net.ServerSocket
API, 247

java.net.Socket
API, 240–241, 252

java.net.URL
API, 267

java.net.URLClassLoader
API, 545

java.net.URLConnection
API, 267–269

java.net.URLDecoder
API, 278

java.net.URLEncoder
API, 278

java.nio
package, 249, 252

direct buffers in, 818

memory mapping in, 132

java.nio.Buffer
API, 137, 140–141

java.nio.ByteBuffer
API, 137–138

java.nio.channels.Channels
API, 259

java.nio.channels.FileChannel
API, 137, 143

java.nio.channels.FileLock
API, 143

java.nio.channels.SocketChannel
API, 259

java.nio.CharBuffer
API, 138–139

java.nio.file.attribute.BasicFileAttributes
API, 124

java.nio.file.Files
API, 10, 119–120, 122, 124, 129

java.nio.file.FileSystem
API, 131

java.nio.file.FileSystems
API, 131

java.nio.file.Path
API, 117

java.nio.file.Paths
API, 117

java.nio.file.SimpleFileVisitor
API, 129–130

java.prefs
module, 535

java.rmi
module, 535

java.se
module, 524

java.security
package, 563

java.security.MessageDigest
API, 566

java.security.Principal
API, 553

java.security.sasl
API, 535

java.sql
package, 384

java.sql.Blob
API, 327

java.sql.Clob
API, 327

java.sql.Connection
API, 309, 314, 325, 328, 336, 352, 356

java.sql.DatabaseMetaData
API, 338, 352, 357

java.sql.DataTruncation
API, 314

java.sql.DriverManager
API, 307

java.sql.PreparedStatement

API, 325–326

java.sql.ResultSet

API, 310–311, 314, 327, 336–338, 353

java.sql.ResultSetMetaData

API, 353

java.sql.Savepoint

API, 356

java.sql.SQLException

API, 314

java.sql.SQLWarning

API, 314

java.sql.Statement

API, 310, 314, 330–331, 356

java.text.CollationKey

API, 413

java.text.Collator

API, 412–413

java.text.Format

API, 415

java.text.MessageFormat

API, 415

java.text.Normalizer

API, 413

java.text.NumberFormat

API, 398–399

java.time
package, 403–404

java.time.Duration
API, 365–366

java.time.format.DateTimeFormatter
API, 383–384, 407

java.time.Instant
API, 365

java.time.LocalDate
API, 370–371, 373, 384, 407

java.time.LocalDateTime
API, 407

java.time.LocalTime
API, 374, 407

java.time.Period
API, 371

java.time.temporal.TemporalAdjusters
API, 373

java.time.ZonedDateTime
API, 378–379, 384, 407

java.util.Arrays
API, 9

java.util.Collection
API, 4, 53

java.util.Currency
API, 403

java.util.DoubleSummaryStatistics

API, 30–31, 49

java.util.function.Supplier

API, 11

java.util.IntSummaryStatistics

API, 30–31, 49

java.util.Locale

API, 393–394

java.util.LongSummaryStatistics

API, 30–31, 49

java.util.Optional

API, 18–23, 26

java.util.Optional

Xxx APIs, 48

java.util.random.RandomGenerator

API, 48

java.util.regex.Matcher

API, 157–158

java.util.regex.MatchResult

API, 158

java.util.regex.Pattern

API, 10, 156

java.util.ResourceBundle

API, 425–426

java.util.Scanner

API, 10, 158

java.util.Spliterators

API, 9

java.util.Stream

API, 43

java.util.stream.BaseStream

API, 29, 53

java.util.stream.Collectors

API, 30, 34, 36, 40–41

java.util.stream.DoubleStream

API, 47

java.util.stream.IntStream

API, 46

java.util.stream.LongStream

API, 47

java.util.stream.Stream

API, 4, 13–14, 16–17, 29

java.util.stream.StreamSupport

API, 10

java.util.zip.ZipEntry

API, 87–88

java.util.zip.ZipFile

API, 88

java.util.zip.ZipInputStream

API, 87

java.util.zip.ZipOutputStream

API, 87

java.xml
module, 535

javac
program

byte order mark in, 420

-encoding
option, 421

passing parameters to, 457

-XprintRounds
option, 492

JavaCompiler
interface

getStandardFileManager
method, 465

getTask
method, 457–458, 465

Javadoc, 485

JavaFileObject
interface, 457

JavaMail, 287

javap
program, 808

JavaScript programming language, 444, 451–452

javax.annotation
package, 482

javax.crypto.Cipher

API, 584–585

javax.crypto.Cipher

Xxx

Stream

APIs, 586

javax.crypto.KeyGenerator

API, 585

javax.crypto.spec.SecretKeySpec

API, 585

javax.imageio

package, 722

javax.imageio.IIOImage

API, 732

javax.imageio.ImageIO

API, 729–730

javax.imageio.ImageReader

API, 730–731

javax.imageio.ImageWriter

API, 732

javax.imageio.spi.IIOServiceProvider

API, 731

javax.imageio.spi.ImageReaderWriterSpi

API, 731

javax.print.attribute.Attribute

API, 783

javax.print.attribute.AttributeSet

API, 783–784

javax.print.DocPrintJob

API, 772, 784

javax.print.PrintService

API, 772, 784

javax.print.PrintServiceLookup

API, 771

javax.print.SimpleDoc

API, 772

javax.print.StreamPrintServiceFactory

API, 773

javax.script.Bindings

API, 447

javax.script.Compilable

API, 451

javax.script.CompiledScript

API, 451

javax.script.Invocable

API, 450

javax.script.ScriptContext

API, 448

javax.script.ScriptEngine

API, 447–448

javax.script.ScriptEngineFactory

API, 445

javax.script.ScriptEngineManager

API, 445, 447

javax.security.auth.callback.CallbackHandler

API, 561

javax.security.auth.callback.

Xxx

Callback

APIs, 561

javax.security.auth.login.LoginContext

API, 552

javax.security.auth.spi.LoginModule

API, 562

javax.security.auth.Subject

API, 553

javax.sql

package, 359

javax.sql.rowset

package, 339

javax.sql.RowSet

API, 341

javax.sql.rowset.CachedRowSet

API, 342

javax.sql.rowset.RowSetFactory

API, 342

javax.sql.rowset.RowSetProvider

API, 342

javax.swing.CellEditor

API, 630

javax.swing.DefaultCellEditor

API, 629

javax.swing.DefaultRowSorter

API, 615

javax.swing.event.TreeModelEvent

API, 671

javax.swing.event.TreeModelListener

API, 671

javax.swing.event.TreeSelectionEvent

API, 662

javax.swing.event.TreeSelectionListener

API, 662

javax.swing.JComponent

API, 641

javax.swing.JTable

API, 596, 613–614, 628

javax.swing.JTree

API, 640, 648, 661

javax.swing.ListSelectionModel

API, 615

javax.swing.RowFilter

API, 616

javax.swing.RowFilter.Entry

API, 616–617

javax.swing.table.TableCellEditor

API, 629

javax.swing.table.TableCellRenderer

API, 629

javax.swing.table.TableColumn

API, 615, 629

javax.swing.table.TableColumnModel

API, 614

javax.swing.table.TableModel

API, 600, 613

javax.swing.table.TableRowSorter

API, 615

javax.swing.table.TableStringConverter

API, 616

javax.swing.tree.DefaultMutableTreeNode

API, 641, 654

javax.swing.tree.DefaultTreeCellRenderer

API, 654

javax.swing.tree.DefaultTreeModel

API, 641, 649

javax.swing.tree.MutableTreeNode

API, 640

javax.swing.tree.TreeCellRenderer

API, 654

javax.swing.tree.TreeModel

API, 640, 670–671

javax.swing.tree.TreeNode

API, 640, 648-649

javax.swing.tree.TreePath

API, 648

javax.tools.Diagnostic

API, 466

javax.tools.DiagnosticCollector

API, 466

javax.tools.ForwardingJavaFileManager

API, 467

javax.tools.JavaCompiler

API, 465

javax.tools.JavaCompiler.CompilationTask

API, 466

javax.tools.SimpleJavaFileObject

API, 467

javax.tools.StandardJavaFileManager

API, 466

javax.tools.Tool

API, 465

javax.xml.catalog.CatalogFeatures

API, 184

javax.xml.catalog.CatalogManager

API, 184

javax.xml.catalog.files

system property, 178

javax.xml.parsers.DocumentBuilder

API, 173, 183, 215

javax.xml.parsers.DocumentBuilderFactory

API, 173, 185, 202

javax.xml.parsers.SAXParser

API, 207

javax.xml.parsers.SAXParserFactory

API, 207

javax.xml.stream.XMLInputFactory

API, 211

javax.xml.stream.XMLOutputFactory

API, 221

javax.xml.stream.XMLStreamReader

API, 211–212

javax.xml.stream.XMLStreamWriter

API, 221–222

javax.xml.transform.dom.DOMResult

API, 233

javax.xml.transform.dom.DOMSource

API, 216

javax.xml.transform.sax.SAXSource

API, 233

javax.xml.transform.stream.StreamResult

API, 216

javax.xml.transform.stream.StreamSource

API, 233

javax.xml.transform.Transformer

API, 216

javax.xml.transform.TransformerFactory

API, 216, 232

javax.xml.xpath.XPath

API, 199

javax.xml.xpath.XPathEvaluationResult

API, 199

javax.xml.xpath.XPathFactory

API, 199

JAXB (Java Architecture for XML Binding), 516

JAXP (Java API for XML Processing) library, 166, 537

jboolean

type (C), 793

jbooleanArray

type (C), 816

JButton

class, 452

jbyte

type (C), 793

jbyteArray

type (C), 816

jchar

type (C), 793, 795

jcharArray

type (C), 816

JCheckBox
class, 619

jclass
type (C), 811

JComboBox
class, 619

JCommander
framework, 469

JComponent
class

paint
method, 617, 672

paintComponent
method, 672

putClientProperty
method, 636, 641

JDBC API, 291–360

configuration of, 301–307

debugging, 306

design of, 292–295

specification for, 293

tracing, 306

uses of, 294–295

versions of, 291

JDBC API Tutorial and Reference (Fisher et al.), 336, 358

JDBC drivers

escape syntax in, 328–329

JAR files for, 302

registering classes for, 304

scrollable/updatable result sets in, 332

types of, 293–294

JDBC/ODBC bridge, 293

JdbcRowSet

interface, 339

jdeprscan

program, 484

jdeps

program, 528–529

JDK (Java Development Kit)

DOM parser, 166

keytool

program, 569

obsolete features in, 504

serialver

program, 107

src.jar

file, 826

SunJCE ciphers, 579

jdk.incubator.http
package, 279

jdouble
type (C), 793

jdoubleArray
type (C), 816

JEP 290, JEP 415, 114

jfloat
type (C), 793

jfloatArray
type (C), 816

jimage
command, 530

jint
type (C), 793

jintArray
type (C), 816

JLabel
class, 651–652

jlink
program, 530

jlong
type (C), 793

jlongArray
type (C), 816

JMOD files, 530, 535

jmod
program, 530

JNDI service, 359, 537

JndiLoginModule
class, 551

JNI (Java Native Interface), 786–846

accessing:

array elements in, 816–819

functions in C++, 796

calling convention in, 796

debugging mode of, 826

error handling in, 819–825

invoking Java methods in, 809–815

online documentation for, 797

JNI_CreateJavaVM
function (C), 825–826, 830

JNI_OnLoad
,
JNI_OnUnload
methods (C), 792

jni.h
file, 793

JNICALL
,
JNIEXPORT

macros, 788

JobAttributes

class (obsolete), 783

jobject

type (C), 811, 816, 833

jobjectArray

type (C), 816

Join styles, 694

joining

method (

Collectors

), 27, 30

JoinRowSet

interface, 339

JPanel

class, 452, 753

JPEG format, 722

image manipulations on, 744

printing, 769

reading, 723

js.properties

file, 451

JScrollPane

class, 593

JSF (JavaServer Faces), 269

JShell, loading modules into, 515

jshort

type (C), 793

jshortArray

type (C), 816

JSON-B (JSON Binding), 516, 518

JSP (JavaServer Pages), 461–467

jstring

type (C), 796, 811, 833

JTable

class, 591–630

addColumn

method, 608, 614

constructor, 596

convert

Xxx

IndexToModel

methods, 604, 614

default rendering actions, 600

getAutoCreateRowSorter

method, 596

getCellRenderer

method, 619

getCellSelectionEnabled

method, 614

getColumnModel
method, 601, 613

getColumnSelectionAllowed
method, 614

getDefaultEditor
method, 628

getDefaultRenderer
method, 619, 628

getFillsViewportHeight
method, 596

getRowHeight
,
getRowMargin
methods, 613

getRowSelectionAllowed
method, 614

getSelectedColumns
method, 604, 608

getSelectedRows
method, 604

getSelectionModel
method, 613

getTableHeader
method, 594

installing cell editors automatically, 619

moveColumn
method, 608, 614

print
method, 594, 596

removeColumn
method, 608, 614

resize modes of, 603

setAutoCreateRowSorter
method, 594, 596, 605

setAutoResizeMode
method, 603, 613

setCellSelectionEnabled
method, 604, 614

setColumnSelectionAllowed
method, 604, 614

setDefaultRenderer
method, 618

setFillsViewportHeight
method, 596

setRowHeight
,
setRowMargin
methods, 603, 613

setRowSelectionAllowed
method, 604, 614

setRowSorter
method, 605, 614

JTextField
class, 619

JTree
class, 630–671

addTreeSelectionListener
method, 655

constructor, 632, 640

getLastSelectedPathComponent
method, 642, 648

getSelectionPath
method, 642, 648, 661

getSelectionPaths
method, 656, 661

identifying nodes, 641

makeVisible
method, 644, 648

scrollPathToVisible
method, 644, 648

setEditable
method, 645

setRootVisible
method, 638, 640

setShowsRootHandles
method, 637, 640

JUnit tool, 468

Just-in-time compiler, 825

JVM (Java virtual machine)

class files in, 534

class loaders in, 535

creating, 825

embedding into native code, 825–830

specification for, 493, 547

terminating, 826

jvm

pointer (C), 825–826

\k

, in regular expressions, 147

Kerberos protocol, 550

Kernel

class, 743, 749

Kernel, of a convolution, 743

Key/value pairs. *See* **Property files**

Keyboard, reading from, 56, 68

KeyGenerator

class, 580

generateKey

method, 580, 585

getInstance

method, 585

init

method, 585

KeyPairGenerator
class, 587

KeyStoreLoginModule
class, 551

Keystores, 569–571

keytool
program, 569–571

Krb5LoginModule
class, 551

L
(object), type code, 96, 806

Lambda expressions, 11

Landscape orientation, 707

Language codes, 35, 390

Language Model API, 489

Language tags, 393

last
method (
ResultSet
), 333, 337

lastDayOf
Xxx,
lastInMonth
methods (

TemporalAdjuster
), 373

last
Xxx
Time
methods (
BasicFileAttributes
), 124

Layout algorithm, 760

layoutPages
method (
Banner
), 760

Lazy operations, 3, 7, 15, 154

LCD displays, 734

LD_LIBRARY_PATH
environment variable, 792, 830

Leap seconds, 362

Leap years, 367, 371

Learn SQL The Hard Way (Shaw), 295

Learning SQL (Beaulieu), 295

Leaves (Swing), 630, 638, 663

icons for, 638–639, 651

Legacy APIs, 117, 384–385

Legacy data, converting into XML, 228

length
method

of
Blob
, 327

of
CharSequence
, 63

of
Clob
, 327

of
RandomAccessFile
, 81, 85

LIB
environment variable, 830

lib/ext
directory, 535

LIKE
statement (SQL), 299, 329

limit
method (
Stream
), 13, 50, 137

Line feed, 69, 418

in e-mails, 287

in regular expressions, 148

Line2D
class, 674–675

Line2D.Double
,
Line2D.Float
classes, 675, 677

lines
method

of
BufferedReader
, 72

of
Files
, 6, 10, 51, 118

lineTo
method (
Path2D.Float
), 680, 691

Linux operating system

compiling invocation API, 829

library path in, 792

OpenSSL in, 576

using GNU C compiler, 789

list
method (
Files
), 124–125

ListResourceBundle
class, 424

Lists, converting to streams, 50

ListSelectionModel
interface

setSelectionMode
method, 604, 615

LITTLE_ENDIAN
constant (
ByteOrder
), 138

Little-endian order, 76, 79, 133, 420

Load time, 499

loadClass
method

of
ClassLoader
, 537, 539

of
URLClassLoader
, 536

loadLibrary
method (
System
), 790, 792

LOBs (large objects), 326–328

creating empty, 328

placing in database, 326

reading, 326

Local hosts, 242

Local names, 202

Local variables, annotating, 479

LocalDate
class

datesUntil
method, 368, 371

format
method, 404

getDayOf
Xxx methods, 368, 370

getMonth
,
getMonthValue
methods, 370

getYear
method, 370

isAfter
,
isBefore
,
isLeapYear
methods, 371

legacy classes and, 385

minus
,
minus
Xxx methods, 368, 370

now
method, 367, 370

of
method, 367, 370, 372

parse
method, 384, 404, 407

plus
,
plus
Xxx methods, 367–368, 370

toLocalDate
method, 385

until
method, 367, 370

weekends in, 368

with
method, 372–373

with
Xxx methods, 370

localdates/LocalDates.java
, 369

LocalDateTime
class, 374

atZone
method, 375

format
method, 404

legacy classes and, 385

parse
method, 404, 407

toLocalDateTime
method, 385

Locale
class, 389–394

constructor, 393

debugging, 394

forLanguageTag
method, 391, 394

getAvailableLocales
method, 31

getCountry
method, 35, 394

getDefault
method, 392–394

getDisplayCountry
,
getDisplayLanguage
methods, 32, 394

getDisplayName

method, 392–394, 396

getInstance

method, 408

getISOCountries

method, 392, 394

getISOLanguages

method, 392

getLanguage

method, 394

predefined objects, 391

setDefault

method, 392, 394

toLanguageTag

method, 391, 394

toString

method, 394

Locales, 388–394

current, 415

date and time formatting in, 403–407

default, 380, 392

dictionary ordering in, 408

display names of, 32, 392–394

formatting styles for, 381

grouping, 35–36

mapping names of, 31–32

numbers in, 388–389, 395–403

predefined, 391

resources bundles and, 422–423

variants in, 389, 423

LocalTime

class, 373–374

format

method, 404

get

Xxx methods, 374

isAfter

,

isBefore

methods, 374

legacy classes and, 385

minus

,

minus

Xxx methods, 373–374

now

method, 373–374

of

method, 373–374

parse

method, 404, 407

plus
,
plus
Xxx methods, 373–374

toLocalTime
method, 385

to
Xxx
OfDay
methods, 374

with
Xxx methods, 374

lock
method (
FileChannel
), 141–143

Locks, 141–143

for the tail portion of a file, 142

shared, 142

unlocking, 142

Log files, 420

Log messages, adding to classes, 493–499

@LogEntry
annotation, 493

Logging, code generation for, 467

logging.properties

file, 282

LoginContext
class, 550

constructor, 552

getSubject
method, 552

login
,
logout
methods, 550, 552

LoginException
, 552

LoginModule
interface

documentation for, 555

methods of, 562

Logins

committed, 555

modules for, 550–551

custom, 553–562

separating from action code, 555

Long
class

MAX_VALUE
constant, 142

LONG NVARCHAR
data type (SQL), 357

long
type

printing, 69

streams of, 43–49

type code for, 96, 806

vs. C types, 793

writing in binary format, 78

LONG VARCHAR
data type (SQL), 357

LongBuffer
class, 139

longs
method

of
Random
, 45

of
RandomGenerator
, 48

of
SplittableRandom
, 52

LongStream
interface, 43–49

average
method, 44, 47

boxed
method, 44, 47

mapToLong
method, 44

max
,
min
methods, 44, 47

of
method, 47

range
,
rangeClosed
methods, 44, 47

sum
,
summaryStatistics
methods, 44, 47

toArray
method, 44, 47

LongSummaryStatistics
class, 27, 30–31, 44, 49

Look-and-feel

displaying trees in, 636

handles for subtrees in, 652

selecting multiple nodes in, 656

lookingAt
method (
Matcher
), 157

lookup
method (
MethodHandles
), 518

LookupOp
class, 740–741

constructor, 748

lookupPrintServices
method (
PrintServiceLookup
), 770–771

lookupStreamPrintServiceFactories
method (
StreamPrintServiceFactory
), 773

LookupTable
class, 742

LSB (least significant byte), 79

LSOutput
interface, 215

LSSerializer
interface, 214

writeToString
method, 215

<
, entity reference, 164

Mac OS X

character encodings in, 418

OpenSSL in, 576

resources in, 421

Mac Roman encoding, 418

mail/MailTest.java
, 289

main
method, 534

makeShape
method (
ShapeMaker
), 681

makeVisible
method (
JTree
), 644, 648

Mandelbrot set, 735–736

Mangling names, 789, 806

Manifest files, 86

map
method

of
FileChannel
, 132, 137

of
HttpHeaders
, 281, 286

of
Optional
, 19-20

of
Stream
, 11

mapping
method (
Collectors
), 37, 41

Maps

concurrent, 32

of stream elements, 31-34, 50

mapToInt
method (
Stream
), 42

mapTo
Xxx methods (*Xxx*
Stream
), 44

mark
method

of
Buffer
, 140–141

of
InputStream
, 58

Marker annotations, 477

markSupported
method (
InputStream
), 59

Mastering Regular Expressions (Friedl), 149

match
attribute (XSLT), 225

match/HrefMatch.java
, 150

Matcher
class, 149

end
method, 157

find
method, 157

group
,
groupCount
methods, 157

lookingAt
method, 157

matches
method, 157

quoteReplacement
method, 157

replaceAll
method, 154, 157–158

replaceFirst
method, 155, 157

results
method, 158

start
method, 157

matcher
method (
Pattern
), 149, 156

matches
method

of
Matcher
, 157

of
Pattern
, 149

MatchResult

interface, 150

methods of, 158

Matrices, transformations of, 706

`max`
method

of primitive streams, 44, 46–47

of
`Stream`
, 16–17

`MAX_VALUE`
constant (
`Long`
), 142

`maxBy`
method (
`Collectors`
), 37, 40

`maxoccurs`
attribute (XML Schema), 187

MD5 algorithm, 564

Memory addresses, vs. serial numbers, 91

Memory mapping of files, 131–141

`memoryMap/MemoryMapTest.java`
, 134

Message digests, 563–566

`MessageDigest`

class

digest

method, 565–566

extending, 564

getInstance

method, 564–566

reset

method, 566

update

method, 564, 566

MessageFormat

class, 413–418, 427

applyPattern

method, 415

constructor, 415

format

method, 413–415

get/setLocale

methods, 415

ignoring the first limit, 417

Meta-annotations, 469, 484–488

Metadata (databases), 343–353

Metal look-and-feel

selecting multiple nodes in, 656

trees in, 635–636

Method

class, 470

Method references, type use annotations in, 480

Method verification errors, 548

MethodHandle

class, 847

MethodHandles

class

lookup

method, 518

Methods

adding logging messages to, 493–499

annotating, 468, 479, 483

calling from native code, 809–815

getters/setters, generated automatically, 492

instance, 809–810

mangling names of, 789, 806

native, 785–847

of annotation interfaces, 476

overriding, 484

protected, 537

signatures of:

generating, 808

mangling, 806–808

static, 810–811

Microsoft

Active Server Pages (ASP), 269

compiler, 789–790

invocation API in, 829

Notepad, 76

ODBC API, 292

SQL Server, 301

Windows. *See* **Windows operating system**

MIME (Multipurpose Internet Mail Extensions), 722

for print services, 770

getting, of a file, 118

`MimeMessage`
class

methods of, 288

`min`
method

of primitive streams, 44, 46–47

of
Stream
, 16–17

minBy
method (
Collectors
), 37, 40

minoccurs
attribute (XML Schema), 187

minus
,
minus
Xxx methods

of
Duration
, 366

of
Instant
, 365

of
LocalDate
, 368, 370

of
LocalTime
, 373–374

of
Period
, 371

of
ZonedDateTime
, 378

mismatch

method (
Files
), 118–119

MissingResourceException
, 422

Miter join, miter limit, 694

Mixed content (XML), 163, 179

Modernist painting example, 222–223

Modified UTF-8, 79–80, 420

native code and, 795–798

Module
class

getResourceAsStream
method, 517

module
keyword, 507

module-info.class
file, 514, 519

module-info.java
file, 507, 519

Modules, 504–531

accessing, 515–518, 522

automatic, 518–521

declaration of, 507–508

explicit, 521

exporting packages, 510–514

loading into JShell, 515

migration to, 519–523

naming, 505–506, 519

not passing access rights, 509

open, 517

opening packages in, 517

packages with the same names in, 514

platform classes in, 535

qualified exports of, 525

requiring, 508–510

service implementations and, 526

tools for, 528–531

unnamed, 521

versioning, 505, 508

Month

enumeration, 367

getDisplayName

method, 381, 405

MonthDay

class, 368

move
method (
Files
), 120–122

moveColumn
method (
JTable
), 608, 614

moveTo
method (
Path2D.Float
), 680–681, 691

moveTo
Xxx
Row
methods (
ResultSet
), 335, 337

MSB (most significant byte), 79

Multiple-page printing, 758–761

multipliedBy
method (
Duration
), 366

MutableTreeNode
interface

implementing, 632

setUserObject
method, 632, 640

MySQL database, 301

\n

as line feed, 69, 170, 287, 418

in regular expressions, 145–147, 156

NameCallback

class, 554

constructor and methods of, 561

NamedNodeMap

interface

getLength

method, 175

item

method, 175

names

method (

Win32RegKey

), 832

Namespaces, 199–202

activating processing of, 188

aliases (prefixes) for, 185, 201

of attributes, 201

of child elements, 200

using class loaders as, 538–539

National character strings, 358

National Institute of Standards and Technology, 236, 564

native

keyword, 787

Native methods, 785–847

array elements in, 816–819

calling from Java programs, 786–792

class references in, 803

compiling, 789

enumerating keys with, 834

error handling in, 819–825

exceptions in, 820

garbage collection and, 797

instance fields in, 801–805

invoking Java constructors in, 811

linking to Java, 792

naming, 787–788

numeric parameters in, 793–795

overloading, 788

reasons to use, 786

registry access functions in, 833–846

static, 787

static fields in, 805–806

strings in, 795

native.encoding
property, 77

native2ascii
program, 423

NCHAR
,
NCLOB
data types (SQL), 357–358

negated
method (
Duration
), 366

Nervous text applet, 562

net.properties
file, 282

Networking, 235–290

connecting to a server, 235–243

debugging, 235–238

getting web data, 259–278

HTTP client for, 279–286

implementing servers, 244–259

sending e-mails, 287–290

newBuffered

Xxx methods (
Files
), 118-119

newBuilder
method

of
HttpClient
, 279, 285

of
HttpRequest
, 281, 286

NewDirectByteBuffer
function (C), 818

newDirectoryStream
method (
Files
), 126, 129

newDocument
method (
DocumentBuilder
), 213, 215, 228

newDocumentBuilder
method (
DocumentBuilderFactory
), 166, 173, 213

newFactory
method (
RowSetProvider
), 339, 342

newFileSystem
method (
FileSystems
), 130–131

NewGlobalRef
function (C), 803

newHttpClient
method (
HttpClient
), 279, 285

newInputStream
method

of
Channels
, 259

of
Files
, 118–119

newInstance
method

of
DocumentBuilderFactory
, 166, 173, 201

of
SAXParserFactory
, 204, 207

of
TransformerFactory
, 214, 216

of
`XMLInputFactory`
, 211

of
`XMLOutputFactory`
, 217, 221

of
`XPathFactory`
, 195, 199

`newNSInstance`
method (
`DocumentBuilderFactory`
), 201–202, 205

`NewObject`
function (C), 811, 815, 820

`newOutputStream`
method

of
`Channels`
, 253, 259

of
`Files`
, 118–119

`newSAXParser`
method (
`SAXParserFactory`
), 204, 207

`NewString`
function (C), 798

NewStringUTF
function (C), 796–797, 799, 833

newTransformer
method (
TransformerFactory
), 214, 216, 232

newXpath
method (
XPathFactory
), 199

New
Xxx
Array
functions (C), 818, 833

next
method

of
ResultSet
, 308, 310, 331

of
TemporalAdjusters
, 373

of
XMLStreamReader
, 211–212

nextElement
method (
Enumeration
), 649, 832–835

nextOrSame
method (
TemporalAdjusters
), 372–373

nextPage
method (
CachedRowSet
), 340, 342

NMTOKEN
,
NMTOKENS
attribute types (DTDs), 180–181

No-argument constructors, 101, 113

Node
interface

appendChild
method, 213, 215

getAttributes
method, 170, 174

getChildNodes
method, 167, 174

getFirstChild
method, 169, 174

getLastChild
method, 169–170, 174

getLocalName
method, 202

getNamespaceURI
method, 202

getNextSibling
method, 169–170, 174

getNode
Xxx methods, 170, 174, 202

getParentNode
method, 174

getPreviousSibling
method, 174

subinterfaces of, 167

nodeChanged
method (
DefaultTreeModel
), 643, 649

NodeList
interface, 167

getLength
method, 167, 175

item
method, 167, 175, 183

Nodes (Swing), 630

adding, 643

child, 630, 633

collapsed, 645

connecting lines for, 636–637

currently selected, 642

editing, 645, 664

enumerating, 649–651

expanding, 643, 645

handles for, 635, 637, 652

highlighting, 652

identifying, by tree paths, 641

making visible, 644

parent, 630, 633

removing, 643

rendering, 639, 651–654

root, 630–638

row positions of, 643

searching, 651, 656

selecting, 655

user objects for, 632, 643, 651, 656

`nodesChanged` method (`DefaultTreeModel`), 649

Nondeterministic parsing, 180

`noneMatch`

method (
Stream
), 17

Noninterference, of stream operations, 7

@NonNull
annotation, 480–481

Normalization, 409

normalize
method

of
Normalizer
, 413

of
Path
, 116–117

Normalized color values, 733

Normalizer
class, 410

normalize
method, 413

NoSuchAlgorithmException
, 566, 584

NoSuchElementException
, 20–21, 835

notFilter
method (
RowFilter

), 607, 616

NotSerializableException
, 102

now
method

of
Instant
, 363, 365

of
LocalDate
, 367, 370

of
LocalTime
, 373–374

of
ZonedDateTime
, 378

NTLoginModule
class, 551

nullInputStream
method (
InputStream
), 59

nullOutputStream
method (
OutputStream
), 59

NullPointerException

, 821

vs.
Optional
, 16

Number
class

doubleValue
method, 396

intValue
method, 396

numberFilter
method (
RowFilter
), 606, 616

NumberFormat
class, 395–403

format
method, 396, 398

get/set
Xxx
Digits
methods, 399

getAvailableLocales
method, 391, 396, 398

getCompactNumberInstance
method, 398

getCurrencyInstance

method, 395, 398, 402

getNumberInstance

method, 395, 398

getPercentInstance

method, 395, 398

is/setGroupingUsed

methods, 399

is/setParseIntegerOnly

methods, 399

parse

method, 395–396, 399

setCurrency

method, 402

numberFormat/NumberFormatTest2.java

, 397

Numbers

filtering, 606–607

floating-point, 388, 395–403

formatting, 388–389, 395–403, 413–415

supported locales for, 396

with C, 793

from grouped elements, 36

in regular expressions, 146

printing, 69

random, 5, 13, 45, 581

reading:

from files, 65

from ZIP archives, 66

using locales, 395

storing in memory, 79

writing in binary format, 78

NUMERIC

data type (SQL), 301, 357

NVARCHAR

data type (SQL), 357

Object

class

clone

method, 89, 110

Object inspection tree, 662–671

Object serialization, 89–114

cloning with, 110–113

file format for, 94–101

modifying default, 101–104

of singletons, 104–107

serial numbers for, 90–91

ObjectInputStream

class, 89

constructor, 94

readObject

method, 89, 94, 102

ObjectInputValidation

interface, 113–114

ObjectOutputStream

class, 89–90

constructor, 94

defaultWriteObject

method, 102

writeObject

method, 89, 94, 102

Object-relational mappers, 516

Objects

cloning, 110–113

converting to streams, 6, 24

fingerprints of, 95

printing, 69

reading from an input stream, 89

saving:

in database, 487

in output streams, 89–90

in text format, 72–75

serializable, 89–94

transmitting over network, 91

type code for, 96, 806

versioning, 107–110

ODBC API, 292, 294

`of` method

of *DoubleStream*, 47

of *IntStream*, 44, 46

of `LocalDate`, 367, 370, 372

of `LocalTime`, 373–374

of *LongStream*, 47

of `Optional`, 21–22

of

Path
, 115

of
Period
, 371

of
Stream
, 5, 9

of
ZonedDateTime
, 375, 378

of
ZoneId
, 375

ofDateAdjuster
method (
TemporalAdjusters
), 372

ofDays
method

of
Duration
, 365

of
Period
, 367, 371, 376

ofFile
,
ofFileDownload

methods (
BodyHandlers
), 281

OffsetDateTime
class, 376

ofHours
method (
Duration
), 365

ofInstant
method (
ZonedDateTime
), 378

ofLocalized
Xxx methods (
DateTimeFormatter
), 380, 383, 403, 407

ofMillis
,
ofMinutes
methods (
Duration
), 365

ofMonths
method (
Period
), 368, 371

ofNanos
method (
Duration

), 365

ofNullable
method

of
Optional
, 21–22

of
Stream
, 6, 9, 24

ofPattern
method (
DateTimeFormatter
), 381, 384

ofSeconds
method (
Duration
), 365

ofString
method (
BodyHandlers
,
BodyPublishers
), 280–281

ofWeeks
,
ofYears
methods (
Period
), 371

oj

literal (SQL), 328

open

keyword, 517

open

method

of

FileChannel

, 132, 137

of

SocketChannel

, 252, 259

openConnection

method (

URL

), 262, 267

openOutputStream

method (

SimpleJavaFileObject

), 467

opens

keyword, 517, 525

OpenSSL toolkit, 576

openStream

method (

URL

), 64, 259, 267

Operating system

character encodings in, 77, 418

default locales in, 392

paths in, 64, 115

resources in, 421

Operations

associative, 42

lazy, 3, 7, 15, 154

stateless, 49

Optional

class, 16–23

creating values of, 21

empty

method, 21–22

filter

method, 19–20

flatMap

method, 22–26

for empty streams, 41–42

get

method, 20–23

ifPresent

method, 18–19

ifPresentOrElse

method, 19

isPresent

method, 20–23

map
method, 19–20

of
,
ofNullable
methods, 21–22

or
method, 20

orElse
method, 16, 18

orElseGet
method, 18

orElseThrow
method, 18, 21

stream
method, 23–26

optional
keyword, 551

optional/OptionalTest.java
, 24

OptionalInt
,
OptionalDouble
,
OptionalLong
classes, 44, 48

Oracle

JDBC, 292, 301

JVM implementation, 77, 818

ORDER BY
statement (SQL), 309

order
method (
ByteBuffer
), 133, 138

orElse
,
orElseGet
methods (
Optional
Xxx), 48

orFilter
method (
RowFilter
), 607, 616

org.omg.corba
package, 504

org.w3c.dom
package, 166

org.w3c.dom.CharacterData
API, 175

org.w3c.dom.Document
API, 174, 215

org.w3c.dom.Element

API, 174, 215

org.w3c.dom.NamedNodeMap

API, 175

org.w3c.dom.Node

API, 174, 202, 215

org.w3c.dom.NodeList

API, 175

org.xml.sax.Attributes

API, 208

org.xml.sax.ContentHandler

API, 207–208

org.xml.sax.EntityResolver

API, 183

org.xml.sax.ErrorHandler

API, 184

org.xml.sax.helpers.AttributesImpl

API, 233

org.xml.sax.InputSource

API, 184

org.xml.sax.SAXParseException

API, 184

org.xml.sax.XMLReader

API, 233

Orientation, 104–105

Outer joins, 328

OutOfMemoryError
, 821

output
element (XSLT), 225

Output streams, 56–78

buffered, 65–67

byte processing in, 65

byte-oriented, 56

closing, 57, 251

filters for, 64–67

hierarchy of, 59–63

objects in, 89–114

redirecting, 447–448

Unicode and, 56

OutputStream
class, 56, 61–62, 217

close
method, 59

flush
method, 57, 59

nullOutputStream
method, 59

write
method, 57, 59

OutputStreamWriter
class, 68

OverlappingFileLockException
, 142

Overloading, 788

@Override
annotation, 483–484

\p
,
\P
, in regular expressions, 146

Package
class, 470

package-info.java
file, 479

Packages, 504

annotating, 479, 483

avoiding name clashes with, 538–539

exporting, 510–514

hidden, 514

opening, 517

split, 514

Packets, 240

Padding schemes, 580

Page setup dialog box, 753–754

Pageable

interface

implementing, 759

objects, printing, 769

PageAttributes

class (obsolete), 783

pageDialog

method (

PrinterJob

), 753, 755, 758

PageFormat

class

getHeight

method, 752, 759

getImageable

Xxx methods, 752, 759

getOrientation

method, 759

getWidth

method, 752, 759

Pages

measurements of, 752–753

multiple, printing, 759–769

orientation of, 707, 753, 759

Paint

interface, 701–703

paint

method (

JComponent

), 617, 672

paintComponent

method

of

JComponent

, 672

of

StrokePanel

, 696

panama/PanamaDemo.java

, 847

Paper

margins of, 752

sizes of, 425, 752

parallel

method (

BaseStream

), 53

parallel/ParallelStreams.java

, 52

parallelStream

method (
Collection
), 2–4, 49–53

Parameter variables, annotating, 479

Parent nodes (Swing), 630, 633

parse
method

of
DateTimeFormatter
, 381

of
DocumentBuilder
, 173

of
LocalDate
, 384, 404, 407

of
LocalDateTime
,
LocalTime
, 407

of
NumberFormat
, 395–396, 399

of
SAXParser
, 204, 207

of
XMLReader

, 233

of
ZonedDateTime
, 384, 404, 407

Parsed character data, 179

ParseException
, 396, 398

Parsers, 165–175

checking uniqueness of IDs in, 181, 189

pull, 208

validating in, 176

Parsing (XML), 165–175

nondeterministic, 180

with XML Schema, 188

partitioningBy
method (
Collectors
), 35–36, 38

PasswordCallback
class, 554

constructor and methods of, 561

Password-protected resources, 264

Path
interface, 115–118

get
Xxx methods, 116–117

normalize
method, 116–117

of
method, 115

relativize
method, 116–117

resolve
,
resolveSibling
methods, 116–117

toAbsolutePath
,
toFile
methods, 116–117

Path2D
class

append
method, 681, 691, 711

closePath
method, 680, 691

Path2D.Double
class, 675, 677

Path2D.Float
class, 675, 677

curveTo

,
lineTo
,
moveTo
,
quadTo
methods, 680–681, 691

pathFromAncestorEnumeration
method (
DefaultMutableTreeNode
), 650

Paths (file system), 115–118

absolute vs. relative, 64, 115–116

checking properties of, 123–124

filtering, 125

relativizing, 116

resolving, 66, 116

root component of, 115

separators in, 64, 115

Paths (graphics), 680–681

Paths
class, 130

get
method, 115, 117

Pattern
class, 149

asMatchPredicate
,
asPredicate
methods, 149

compile
method, 149, 155–156

flags, 155–158

matcher
method, 149, 156

matches
method, 149

split
method, 154, 156

splitAsStream
method, 6, 10, 154, 156

Patterns, 143–158

#PCDATA
element content (DTD), 178–179

PDF format, 769

peek
method (
Stream
), 15–16

PEM (Privacy Enhanced Mail), 576

Pentium processor, little-endian order in, 79

Percentages, formatting, 395–396

Performance

of encryption algorithms, 587

of file operations, 131-139

Period

class

get

Xxx methods, 371

minus

,

minus

Xxx methods, 371

of

method, 371

of

Xxx methods, 367-368, 371, 376

plus

,

plus

Xxx methods, 371

using for daylight savings time, 376

with

Xxx methods, 371

Perl programming language, 149

@Persistent

annotation, 487

Personal data, 578

Picocli framework, 469

Pixels

affine transformations on, 740

average value of, 743

composing, 712–721

interpolating, 701–702, 741

sample values of, 733

setting individual, 733–740

Placeholders, in messages, 413–418

Plugins, loading, 536

`plus`

,

`plus`

Xxx methods

of

`Duration`

, 366

of

`Instant`

, 365

of

`LocalDate`

, 367–368, 370

of

`LocalTime`

, 373–374

of
Period
, 371

of
ZonedDateTime
, 378

PNG format, 722

printing, 769

Point2D
class, 677

Point2D.Double
class, 102, 675, 677

Point2D.Float
class, 675, 677

Points, in typography, 752

Policy files, 577

Polygons, 675, 681

Pools, for parallel streams, 51

populate
method (
CachedRowSet
), 339, 342

Porter–Duff rules, 713–716

Portrait orientation, 753

Ports, 237

blocking, 236

in URIs, 261

position

function (XPath), 227

position

method (

Buffer

), 141

POSIX-compliant file systems, 123

PosixFileAttributes

interface, 123

POST

method (

HttpRequest.Builder

), 280, 286

POST

request (HTML), 270, 272–274

building, 280

post/PostTest.java

, 275

@PostConstruct

annotation, 483

PostgreSQL database, 301

connecting to, 305

drivers for, 302

Postorder traversal, 650

postOrderEnumeration
method (
DefaultMutableTreeNode
), 650, 654

PostScript format

printing, 769, 772

writing to, 772

postVisitDirectory
method

of
FileVisitor
, 127

of
SimpleFileVisitor
, 130

Predefined character classes, 144, 146, 148

@PreDestroy
annotation, 483

Predicate functions, 35

premain
method (Instrumentation API), 499

preOrderEnumeration
method (
DefaultMutableTreeNode
), 650, 654

Prepared statements, 319–326

caching, 320

executing, 320

PreparedStatement

interface

clearParameters

method, 325

execute

Xxx methods, 320, 326

set

Xxx methods, 320, 325

prepareStatement

method (

Connection

), 319–320, 325, 331, 336

previous

method (

ResultSet

), 332, 336

previous

,

previousOrSame

methods (

TemporalAdjusters

), 373

previousPage

method (

CachedRowSet

), 342

preVisitDirectory

method

of
FileVisitor
, 127

of
SimpleFileVisitor
, 130

Primitive types

arrays of, 818

I/O in binary format in, 60

streams of, 42–49

Principal
interface

getName
method, 553

Principals (logins), 551

Print dialog box, 750

displaying page ranges in, 751, 759

native, 751, 755

print
method

of
DocPrintJob
, 772

of
JTable
, 594, 596

of
Printable
, 749, 758–759

of
PrintWriter
, 69–70, 809–810

Print services, 769–772

document flavors for, 769–770

for images, 771

stream, 772–775

print
,
println
functions (JavaScript), 448

print/PrintComponent.java
, 756

print/PrintTestFrame.java
, 755

Printable
interface

implementing, 749, 753

objects, printing, 769

print
method, 749, 758–759

Printer graphics context, 760

PrinterException

, 750

PrinterJob

class

defaultPage

method, 758

getPrinterJob

method, 749, 758

pageDialog

method, 753, 755, 758

print

method, 750–751, 758

printDialog

method, 750–751, 758

setPageable

method, 759

setPrintable

method, 758

printf

function (C), 793

printf

method (

PrintWriter

), 69–70, 393

printf1/Printf1.c

, 794

printf1/Printf1.java

, 794

printf1/Printf1Test.java
, 795

printf2/Printf2.c
, 800

printf2/Printf2.java
, 799

printf2/Printf2Test.java
, 799

printf3/Printf3.c
, 812

printf3/Printf3.java
, 812

printf3/Printf3Test.java
, 812

printf4/Printf4.c
, 821

printf4/Printf4.java
, 823

printf4/Printf4Test.java
, 824

Printing

clipped areas, 752

counting pages during, 751

images, 749–759

layout of, 760

multipage documents, 758–761

number of copies for, 776

page orientation of, 707, 753

paper sizes in, 752

quality of, 779

selecting settings for, 750

starting, 749

text, 749–759

using:

banding for, 751

transformations for, 761

Printing attributes, 776–784

adding, 779

categories of, 778–779

checking values of, 779

hierarchy of, 777

retrieving, 779

PrintJob

class (obsolete), 749

PrintJobAttribute

interface, 776

printing attributes of, 780–783

PrintJobAttributeSet
interface, 777

println
method

of
PrintWriter
, 69–70, 72

of
System.out
, 418–419

PrintQuality
class, 779

PrintRequestAttribute
interface, 776

printing attributes of, 780–783

PrintRequestAttributeSet
interface, 750, 777

PrintService
interface

createPrintJob
method, 771–772

getAttributes
method, 784

getName
method, 771

printService/PrintServiceTest.java
, 774

PrintServiceAttribute
interface, 776

printing attributes of, 780–783

PrintServiceAttributeSet
interface, 777

PrintServiceLookup
class

lookupPrintServices
method, 770–771

PrintStream
class, 69

PrintWriter
class, 68–70

checkError
method, 69–70

constructor, 70

print
method, 69–70, 809–810

printf
method, 69–70, 393

println
method, 69–70, 72

Private keys, 566, 587

probeContentType
method (
Files

), 118–119

processAnnotations

method (

ActionListenerInstaller

), 470

Processing instructions (XML), 165

Processing tools, 467

Processor

interface, 488

Programmer's Day, 367

Programs. *See* **Applications**

Project Panama, 846–848

Properties

class, 160

Property files, 160

character encoding of, 423

event handlers in, 451

for resources bundles, 422–423

for string resources, 421

for strings, 423

no passwords in, 288

@Property

annotation, 492

provides

keyword, 528

Proxy objects, 470

PUBLIC
identifier (DTD), 214

Public key ciphers, 566–573, 587–590

performance of, 587

Public Key Cryptography Standard (PKCS) #5, 580

Pull parsers, 208

PushbackInputStream
class, 65

constructor, 67

unread
method, 67

put
method

of
Bindings
, 447

of
ByteBuffer
, 137–138

of
CharBuffer
, 139

of
ScriptEngine

, 447

of
ScriptEngineManager
, 447

PUT
method (
HttpRequest.Builder
), 286

putClientProperty
method (
JComboBox
), 636, 641

putNextEntry
method (
ZipOutputStream
), 86–87

put
Xxx methods (
ByteBuffer
), 133, 138

\Q
, in regular expressions, 145

QBE (query by example) tools, 297–298

QuadCurve2D
class, 674, 680

QuadCurve2D.Double
class, 675, 677, 690

QuadCurve2D.Float
class, 675, 677

Quadratic curves, 679–680

quadTo
method (
Path2D.Float
), 680, 691

Qualified exports, 525

Qualified names (XML), 202

Queries (databases), 298–300

by example, 297–298

executing, 308, 319–331

multiple, 311

populating row sets with results of, 340

preparing, 319–326

returning multiple results, 329–330

query/QueryTest.java
, 321

"
, entity reference, 164

quoteReplacement
method (
Matcher
), 157

R programming language, 444, 451

\r

line feed character, 69, 170, 418

in e-mails, 287

\r

,

\R

, in regular expressions, 145, 148

Race conditions, 49

Random

class, 581

methods of, 45

Random numbers, streams of, 5, 13, 45, 48, 52

Random-access files, 81–85

randomAccess/RandomAccessTest.java

, 83

RandomAccessFile

class, 81–85, 131

constructor, 85

getChannel

method, 136

getFilePointer

method, 81, 85

length

method, 81, 85

seek
method, 81, 85

RandomGenerator
class

methods of, 48

Randomness, 581

range
,
rangeClosed
methods (*Xxx*
Stream
), 44, 46–47

Ranges, converting to streams, 50

Raster
class

getDataElements
method, 735, 738

getPixel
,
getPixels
methods, 734, 739

Raster images, 721–749

constructing from pixels, 733–740

filtering, 740–749

readers/writers for, 722–732

rasterImage/RasterImageFrame.java

, 736

read

method

of

CipherInputStream

, 586

of

FileInputStream

, 56

of

ImageIO

, 722, 729

of

ImageReader

, 731

of

InputStream

, 56-58

of

Readable

, 62-63

of

Reader

, 60

read/config.dtd

, 193

read/config.xml

, 192

read/config.xsd
, 193

read/XMLReadTest.java
, 189

Readable
interface, 61

read
method, 62–63

ReadableByteChannel
interface, 253

readAllBytes
method (
InputStream
), 56, 58

readAll
Xxx methods (
Files
), 118–119

readAttributes
method (
Files
), 123–124

readBoolean
method (
DataInput
), 79–80

readChar
method (
DataInput

), 79–81

readDouble
method (
DataInput
), 79–80, 90, 102

Reader
class, 56, 61

read
method, 60

READER
class (
DocFlavor
), 770

readExternal
method (
Externalizable
), 103–104

readFixedString
method (
DataIO
), 82

readFloat
method (
DataInput
), 79–80

readFully
method (
DataInput
), 80

readInt
method (
DataInput
), 79–81, 90

readLine
method (
Console
), 71

readLong
method (
DataInput
), 79–80

readNBytes
method (
InputStream
), 56, 58

readObject
method

of
HashSet
, 102

of
ObjectInputStream
, 89, 94, 102

ReadOnlyBufferException
, 132

readResolve
method (
Serializable
), 105–107

readShort
method (
DataInput
), 79–80

readString
method (
Files
), 118–119

readThumbnail
method (
ImageReader
), 731

readUTF
method (
DataInput
), 79–80

REAL
data type (SQL), 301, 357

Receiver parameters, 482

Records, 72–75

customizing serialization of, 104

deserializing, 113

fixed-size, 82–83

ignoring
serialVersionUID
fields, 110

Rectangle2D
class, 674–675

Rectangle2D.Double
,
Rectangle2D.Float
classes, 675

RectangularShape
class, 675

Redirects, of URLs, 274–275

reduce
method (
Stream
), 41–43

reducing
method (
Collectors
), 38

Reductions, 16, 41–43

ref
attribute (XML Schema), 186

Reflection
accessing:
private members, 515–518, 522
protected methods, 537
constructing class trees, 656
enumerating fields from a variable, 665

regex/RegexTest.java
, 153

regexFilter
method (
RowFilter
), 607, 616

Registry editor, 831, 836

Registry keys, 832–834

Regular expressions, 143–158

escapes in, 73

filtering, 607

finding matches of, 149

flags for, 155–158

groups in, 151–154

in DTDs, 179–180

splitting sequences with, 6

relative
method (
ResultSet
), 333, 337

Relativization, in URLs, 261

relativize
method (
Path
), 116–117

releaseSavepoint
method (
Connection

), 354, 356

ReleaseStringChars

function (C), 798

ReleaseStringUTFChars

function (C), 797–799

Release

Xxx

ArrayElements

functions (C), 816–817, 819

reload

method (

DefaultTreeModel

), 643, 649

remaining

method (

Buffer

), 140–141

remove

method (

AttributeSet

), 784

removeCellEditorListener

method (

CellEditor

), 630

removeColumn

method (

JTable

), 608, 614

removeNodeFromParent
method (
DefaultTreeModel
), 643, 649

removeTreeModelListener
method (
TreeModel
), 663, 671

RenderableImage
interface, 769

Rendering (Swing)

cells, 617–619

columns, 600

headers, 619

nodes, 651–654

Rendering pipeline (AWT), 672–674

Renjin project, 444, 452

@Repeatable
annotation, 483

replaceAll
method

of
Matcher
, 154, 157–158

of
String

, 155

replaceFirst
method (
Matcher
), 157

of
Matcher
, 155

required
keyword, 551

#REQUIRED
attribute (DTD), 181

requires
keyword, 508, 510, 512–513, 519, 523–525

requisite
keyword, 551

RescaleOp
class, 740, 747

Rescaling operation, 741

reset
method

of
Buffer
, 140–141

of
InputStream
, 59

of
MessageDigest
, 566

resolve
method (
Path
), 116–117

resolveEntity
method (
EntityResolver
), 177, 183

resolveSibling
method (
Path
), 116–117

Resolving

classes, 534

relative URLs, 261

Resource bundles, 421–426

loading, 423–424

locating, 422–423

lookup tables for, 424

naming, 424

searching for, 424

Resource editors, 421

@Resource

annotation, 359, 483

ResourceBundle

class

extending, 424–425

getBundle

method, 422–425

getKeys

method, 425–426

getObject

method, 424–425

getString

method, 423, 425

getStringArray

method, 426

handleGetObject

method, 425–426

ResourceBundle.Control

class

getCandidateLocales

method, 423

Resources

hierarchy of, 422

in JAR files, 517

@Resources

annotation, 483

ResourceScope
interface, 847

Response headers, 264–265

Response pages, 269

Result
interface, 227–228, 358

Result sets (databases)

accessing columns in, 309

analyzing, 308

closing, 312

for multiple queries, 311

iterating over rows in, 331

metadata for, 344

numbering rows in, 333

order of rows in, 309

retrieving multiple, 329–330

scrollable, 331–333

updatable, 331, 334–338

results
method (
Matcher
), 158

ResultSet
interface, 338

absolute
method, 333, 337

afterLast
,
beforeFirst
methods, 333, 337

cancelRowUpdates
method, 335, 338

close
method, 311–312

concurrency values, 333–334, 336, 338

deleteRow
method, 335, 337

findColumn
method, 311

first
method, 333, 337

getBlob
,
getClob
methods, 326–327

getConcurrency
method, 332, 334, 336

getDate
,
getDouble
,
getInt

methods, 309, 311

getMetaData

method, 344, 353

getObject

method, 309, 311

getRow

method, 333, 337

getString

method, 309, 311

getType

method, 332, 336

getWarnings

method, 314

insertRow

method, 335, 337

isAfterLast

,

isBeforeFirst

methods, 333, 337

isClosed

method, 311

isFirst

,

isLast

methods, 333, 337

iteration protocol, 308

last

method, 333, 337

moveTo

Xxx

Row

methods, 335, 337

next

method, 308, 310, 331

previous

method, 332, 336

relative

method, 333, 337

type values, 333–334, 336, 338

update

Xxx methods, 311, 334–335, 337–338

ResultSetMetaData

interface, 344

getColumn

Xxx methods, 344, 353

Retention policies, 485

@Retention

annotation, 469, 483, 485

retire/Retire.java

, 428

retire/RetireResources_de.java

, 440

retire/RetireResources_zh.java

, 440

retire/RetireResources.java

, 439

retire/RetireStrings_de.properties

, 441

retire/RetireStrings_zh.properties

, 441

retire/RetireStrings.properties

, 441

Retirement calculator example, 426–442

RETURN_GENERATED_KEYS

field (

Statement

), 331

Return values, missing, 16

rewind

method (

Buffer

), 140–141

RFC 821 standard, 287

RFC 822 standard, 380

RFC 1123 standard, 380

RFC 2396 standard, 261

RFC 2616 standard, 263

RFC 2911 standard, 783

RGB color model, 712, 734

Rhino engine, 444, 452

Rivest, Ronald, 564, 568, 587

Role-based authentication, 553

`rollback` method (*Connection*), 354–356

Root component (file system), 115

Root element (XML), 163

referencing schemas in, 185

Root node (Swing), 630–638

handles for, 637–638

separating children of, 637

`rotate` method (Graphics2D), 705, 709

Rotation, 704–705

interpolating pixels and, 741

with center point, 705

Round cap, 693

Round join, 694

Rounded rectangles, 677

RoundEnvironment
interface, 489

RoundRectangle2D
class, 674–675, 677

RoundRectangle2D.Double
class, 675, 677, 690

RoundRectangle2D.Float
class, 675, 677

Row sets (databases), 338–342

cached, 339–344

constructing, 339

modifying, 339

page size of, 340

RowFilter
class, 606–608

andFilter
method, 607, 616

dateFilter
method, 607, 616

include
method, 607, 616

notFilter
method, 607, 616

numberFilter
method, 606, 616

orFilter
method, 607, 616

regexFilter
method, 607, 616

RowFilter.Entry
class, 607

ROWID
data type (SQL), 357–358

RowId
interface, 358

Rows (databases), 295
deleting/inserting, 335
iterating through, 334
order of, in result set, 309
retrieving, 358
selecting, 298
updating, 334–338

Rows (Swing)
filtering, 606–608
height of, 603
hiding, 608
margins of, 603
position, in a node, 643

resizing, 603

selecting, 593–594, 604

sorting, 594, 605–606

RowSet

interface, 338–341

execute

method, 341

get

Xxx methods, 341

set

Xxx methods, 340–341

RowSetFactory

interface

createCachedRowSet

method, 339–340, 342

create

Xxx

RowSet

methods, 342

RowSetProvider

class

newFactory

method, 339, 342

RSA algorithm, 568, 587

RSA Security, Inc., 580

rsa/RSATest.java
, 588

rt.jar
file, 530, 535

Ruby programming language, 444

run
method (
Tool
), 457, 465

Runnable
interface, 248

Runtime
class

exec
method, 114

Runtime image file, 530

runtimeAnnotations/ActionListenerFor.java
, 474

runtimeAnnotations/ActionListenerInstaller.java
, 471

S
(
short
), type code, 96, 806

\s
,

\S
, in regular expressions, 146

@SafeVarargs
annotation, 483

Sample values of pixels, 733

Sandbox, 577

Save points (databases), 354

Savepoint
interface

getSavepoint
Xxx methods, 356

SAX (Simple API for XML) parser, 165, 203–208

activating namespace processing in, 205

sax/SAXTest.java
, 206

SAXParseException
class

get
Xxx
Number
methods, 184

SAXParser
class

parse
method, 204, 207

SAXParserFactory
class

is/setNamespaceAware
methods, 207

is/setValidating
methods, 207

newInstance
,
newSAXParser
methods, 204, 207

setFeature
method, 205

SAXResult
class, 228

SAXSource
class, 227–228

constructor, 233

Scalar functions, 328

scale
method (
Graphics2D
), 704–705, 709

Scaling, 704–705

Scanner
class, 70–72

constructor, 116, 253

findAll
method, 158

tokens
method, 6, 10

useLocale
method, 393, 396

Scheduling applications

computing dates for, 372–373

time zones and, 367, 375

schema
element (XML Schema), 187

Schemas, 352

Scheme programming language, 444

script/ScriptTest.java
, 453

ScriptContext
interface, 447

get
Xxx
/set
Xxx methods, 447–448

ScriptEngine
interface

createBindings
method, 447

eval
method, 445–447

get
method, 447

getContext
method, 448

put
method, 447

ScriptEngineFactory
interface

getExtensions
method, 445

getMethodCallSyntax
method, 449

getMimeTypes
method, 445

getNames
method, 445

ScriptEngineManager
class, 444

get
method, 447

getEngine
Xxx methods, 444–445

put
method, 447

Scripting engines, 444–445

adding variable bindings to, 446

calling functions in, 448–450

implementing Java interfaces, 449

invoking, 445

Scripting languages, 444–456

Scripts, 444

accessing classes in, 450

compiling, 450–451

executing, 446, 450

invoking, 445

redirecting I/O of, 447–448

using Java method call syntax in, 449

Scroll panes (Swing)

with tables, 593

with trees, 644–645

`scrollPathToVisible` method (`JTree`), 644, 648

SecretKey interface, 581

`SecretKeySpec`

class, 585

Secure random generator, 581

`SecureRandom`
class

`setSeed`
method, 581

Security, 533–590

bypassing constructors, 113–114

bytecode verification, 545–549

class loaders, 534–549

code signing, 534

different levels of, 562

digital signatures, 562–577

encryption, 578–590

user authentication, 549–562

Security manager, 534

“Seek forward only” mode (
`ImageInputStream`
), 724

`seek`
method (
`RandomAccessFile`
), 81, 85

`select`
attribute (XSLT), 226

SELECT
statement (SQL), 298–299

executing, 308

for LOBs, 326

multiple, in a query, 329

not supported in batch updates, 355

Selection models, 604

send
method (
HttpClient
), 285

sendAsync
method (
HttpClient
), 281, 285

separator
constant (
File
), 64

Separators (file system), 64, 115

sequence
element (XML Schema), 187

Sequences, producing, 5

Serial numbers, 90–91

serial/ObjectStreamTest.java
, 93

@Serial
annotation, 102–103

serialClone/SerialCloneTest.java
, 110

SerialCloneable
class, 110

Serializable
interface, 89, 96, 487

readResolve
method, 105–107

writeReplace
method, 106–107

@Serializable
annotation, 487

Serialization, 89–114

cloning with, 110–113

file format for, 94–101

filters for, 114

modifying default, 101–104

of singletons, 104–107

serial numbers for, 90–91

serialver
program, 107

serialVersionUID
constant, 107–110

server/EchoServer.java
, 245

Servers

accessing, 259–278

connecting clients to, 238–240

echo, 246–247

implementing, 244–259

invoking programs, 269

Server-side programs, 269–278

redirecting URLs in, 274–275

ServerSocket
class, 244–259

accept
method, 244, 247–248

close
method, 247

constructor, 247

Service loading, 526–528

Service provider interfaces, 723

SERVICE_FORMATTED
class (
DocFlavor
), 770

ServiceLoader

class, 526

Servlets, 269, 461–467

Session
class

setDebug
method, 288

set/Item.java
, 497

set/SetTest.java
, 498

setAllowsChildren
method (
DefaultMutableTreeNode
), 639, 641

setAllowUserInteraction
method (
URLConnection
), 262

setAsksAllowsChildren
method (
DefaultTreeModel
), 639, 641

setAttribute
,
setAttributeNS
methods (
Element
), 213–215

setAutoCommit
method (
Connection
), **353**, **355**–**356**

setAutoCreateRowSorter
method (
JTable
), **594**, **596**, **605**

setAutoResizeMode
method (
JTable
), **603**, **613**

setBinaryStream
method (
Blob
), **327**

SetBooleanArrayRegion
function (C), **818**

SetBooleanField
function (C), **806**

SetByteArrayRegion
function (C), **818**–**819**, **833**

SetByteField
function (C), **806**

setCellEditor
method (
TableColumn
), **620**, **629**

setCellRenderer

method (
TableColumn
), 629

setCellSelectionEnabled
method (
JTable
), 604, 614

setCharacterStream
method (
Clob
), 327

SetCharArrayRegion
function (C), 818–819

SetCharField
function (C), 806

setClip
method (
Graphics
), 710–711, 752

setClosedIcon
method (
DefaultTreeCellRenderer
), 652, 654

setColumnSelectionAllowed
method (
JTable
), 604, 614

setCommand
method (

RowSet
), 340-341

setComparator
method (
DefaultRowSorter
), 606, 615

setComposite
method (
Graphics2D
), 673, 715, 721

setConnectTimeout
method (
URLConnection
), 262, 268

setContentHandler
method (
XMLReader
), 233

setContextClassLoader
method (
Thread
), 537, 545

setCrc
method (
ZipEntry
), 88

setCurrency
method (
NumberFormat
), 402

`setDataElements`
method (
`WritableRaster`
), 735, 739

`setDate`
method (
`PreparedStatement`
), 320, 325

`setDebug`
method (
`Session`
), 288

`setDecomposition`
method (
`Collator`
), 413

`setDefault`
method

of
`CookieHandler`
, 274

of
`Locale`
, 392, 394

`setDefaultNamespace`
method (
`XMLStreamWriter`
), 221

`setDefaultRenderer`
method (

JTable
), 618

setDoInput
method (
URLConnection
), 262–263, 267

setDoOutput
method (
URLConnection
), 262–263, 267, 272, 274

setDouble
method (
PreparedStatement
), 320, 325

SetDoubleArrayRegion
function (C), 818–819

SetDoubleField
function (C), 802, 806

setEditable
methodmethod (
JTree
), 645

setEntityResolver
method (
DocumentBuilder
), 178, 183

setErrorHandler
method (
DocumentBuilder
), 183

setErrorWriter
method (
ScriptContext
), 448

setFeature
method (
SAXParserFactory
), 205

setFillsViewportHeight
method (
JTable
), 596

SetFloatArrayRegion
function (C), 818–819

SetFloatField
function (C), 806

setFrom
method (
MimeMessage
), 288

setGroupingUsed
method (
NumberFormat
), 399

setHeader
Xxx methods (
TableColumn
), 619, 629

setIfModifiedSince

method (

`URLConnection`

), 262–263, 268

`setIgnoringElementContentWhitespace`

method (

`DocumentBuilderFactory`

), 182, 185

`setInput`

method (

`ImageReader`

), 730

`setInstanceFollowRedirects`

method (

`HttpURLConnection`

), 275

`setInt`

method (

PreparedStatement

), 320, 325

`SetIntArrayRegion`

function (C), 818–819

`SetIntField`

function (C), 802, 806, 834

`setLeafIcon`

method (

`DefaultTreeCellRenderer`

), 652, 654

`setLevel`

method (

`ZipOutputStream`

), 87

setLocale
method (
MessageFormat
), 415

setLogWriter
method (
DriverManager
), 306

SetLongArrayRegion
function (C), 818–819

SetLongField
function (C), 806

setMaximum
Xxx
Digits
methods (
NumberFormat
), 399

setMaxWidth
method (
TableColumn
), 602, 615

setMethod
method

of
ZipEntry
, 88

of

ZipOutputStream
, 87

setMinimum
Xxx
Digits
methods (
NumberFormat
), 399

setMinWidth
method (
TableColumn
), 602, 615

setName
method (
NameCallback
), 561

setNamespaceAware
method

of
DocumentBuilderFactory
, 188, 201–202, 205, 213

of
SAXParserFactory
, 207

SetObjectArrayElement
function (C), 816, 819–820

SetObjectField
function (C), 802, 806

setOpenIcon

method (
`DefaultTreeCellRenderer`
), **652**, **654**

`setOutput`
method (
`ImageWriter`
), **732**

`setOutputProperty`
method (
`Transformer`
), **214**, **216**

`setPageable`
method (
`PrinterJob`
), **759**

`setPageSize`
method (
CachedRowSet
), **340**, **342**

`setPaint`
method (
`Graphics2D`
), **672**, **701**–**703**

`setParseIntegerOnly`
method (
`NumberFormat`
), **399**

`setPassword`
method

of

PasswordCallback
, 561

of
RowSet
, 340–341

setPixel
,
setPixels
methods (
WritableRaster
), 733, 739

setPreferredWidth
method (
TableColumn
), 602, 615

setPrefix
method (
XMLStreamWriter
), 221

setPrintable
method (
PrinterJob
), 758

setProperty
method (
XMLInputFactory
), 209, 211

setReader
method (
ScriptContext

), 447–448

setReadTimeout
method (
URLConnection
), 262, 268

setRenderingHint
,
setRenderingHints
methods
(
Graphics2D
), 672

setRequestProperty
method (
URLConnection
), 262–263, 268

setResizable
method (
TableColumn
), 602, 615

setRootVisible
method (
JTree
), 638, 640

setRowFilter
method (
DefaultRowSorter
), 606–608, 615

setRowHeight
,

setRowMargin
methods (
JTable
), 603, 613

setRowSelectionAllowed
method (
JTable
), 604, 614

setRowSorter
method (
JTable
), 605, 614

setSavepoint
method (
Connection
), 356

setSeed
method (
SecureRandom
), 581

setSelectionMode
method (
ListSelectionModel
), 604, 615

SetShortArrayRegion
function (C), 818–819

SetShortField
function (C), 806

setShowsRootHandles

method (
JTree
), 637, 640

setSize
method (
ZipEntry
), 88

setSortable
method (
DefaultRowSorter
), 605, 615

setSoTimeout
method (
Socket
), 240–241

SetStatic
Xxx
Field
functions (C), 805–806

setStrength
method (
Collator
), 412

setString
method

of
PreparedStatement
, 320, 325

of
RowSet

, 340

setStringConverter
method (
TableRowSorter
), 615

setStroke
method (
Graphics2D
), 672, 693, 701

setSubject
method (
MimeMessage
), 288

setTableName
method (
CachedRowSet
), 341-342

setText
method (
MimeMessage
), 288

setTo
Xxx methods (
AffineTransform
), 707, 709

setTransform
method (
Graphics2D
), 707, 709

setURL
method (
RowSet
), **340**-**341**

setUseCaches
method (
URLConnection
), **262**

setUsername
method (
RowSet
), **340**-**341**

setUserObject
method (
MutableTreeNode
), **632**, **640**

setValidating
method

of
DocumentBuilderFactory
, **182**, **185**

of
SAXParserFactory
, **207**

setValue
method (
Win32RegKey
), **832**-**834**

setValueAt
method (

TableModel
), 600, 623

setWidth
method (
TableColumn
), 602, 615

setWriter
method (
ScriptContext
), 447–448

SGML (Standard Generalized Markup Language), 161

SHA-1 algorithm, 95, 563

Shamir, Adi, 568, 587

Shape
interface, 675, 692

implementing, 692

shape/ShapeTest.java
, 682

ShapeMaker
class

getPointCount
method, 681

makeShape
method, 681

ShapePanel
class, 682

Shapes

clipping, 672, 710–712

combining, 673, 691–692

control points of, 681–682

drawing, 672–675

filling, 672–673, 701–703

rendering, 674

transforming, 672

Shared libraries, 792, 830

Shear, 704–705

`shear` method (`Graphics2D`), 705, 709

Shift-JIS encoding, 77

`short` type

printing, 69

streams of, 43–49

type code for, 96, 806

vs. C types, 793

writing in binary format, 78

`ShortBuffer`

class, 139

ShortLookupTable

class, 742, 748

shouldSelectCell

method (

CellEditor

), 622–623, 630

shutdown

Xxx methods (

Socket

), 252

Side files, 488

Signatures. *See* **Digital signatures**

Simple types, 185

SimpleDateFormat

class, 414

SimpleDoc

class, 771–772

SimpleFileVisitor

class, 128

visitFile

method, 128–129

visitFileFailed

method, 128, 130

xxx

VisitDirectory

methods, 130

SimpleJavaFileObject
class, 459

getCharContent
method, 467

openOutputStream
method, 467

SimpleScriptContext
class, 447

simpleType
element (XML Schema), 186

Single value annotations, 477

Singletons, serializing, 104–107

size
method

of
BasicFileAttributes
, 124

of
Files
, 123–124

skip
method

of
InputStream
, 58

of
Stream

, 13

skipBytes
method (
DataInput
), 80

skipNBytes
method (
InputStream
), 58

SMALLINT
data type (SQL), 301, 357

SMTP (Simple Mail Transport Protocol), 287–290

SOAP (Simple Object Access Protocol), 505

Socket
class

connect
method, 241

constructor, 240–241

getInputStream
method, 239–240, 244

getOutputStream
method, 240, 244

isClosed
,
isConnected
methods, 241

is

Xxx

Shutdown

methods, 252

setSoTimeout

method, 240–241

shutdown

Xxx methods, 252

socket/SocketTest.java

, 239

SocketChannel

class, 252

open

method, 252, 259

Sockets

half-closing, 251–252

interrupting, 252–259

opening, 239

server, 244–247

timeouts of, 240–241

SocketTimeoutException

, 241, 268

Software developer certificates, 577

sort

method (

Collections

), 408

sorted
method (
Stream
), 15–16

Source files

character encoding of, 420–421

reading from memory, 458

Source
interface, 227, 358

Source-level annotations, 488–493

Space. *See* **Whitespace**

SPARC processor, big-endian order in, 79

split
method

of
Pattern
, 154, 156

of
String
, 72, 154

Split packages, 514

splitAsStream
method (
Pattern
), 6, 10, 154, 156

spliterator

method (
Iterable
), 10

Spliterators
class

spliteratorUnknownSize
method, 6, 9

SplittableRandom
class, 45

methods of, 52

sprint
,
sprintf
functions (C), 798

SQL (Structured Query Language), 291, 295–301

changing data inside databases, 300

commands in, 303

data types in, 301, 357–358

equality testing in, 299

escapes in, 328–329

exceptions in, 312–314

executing statements in, 308–311

keywords in, 298

reading instructions from a file, 315

strings in, 299

vs. Java, 321

warnings in, 313

wildcards in, 299

SQLException

class, 312–314, 332

get

Xxx methods, 312, 314

iterator

method, 312, 314

rolling back and, 354

save points and, 356

SQLWarning

class, 313, 332

getNextWarning

method, 314

SQLXML

data type (SQL), 357–358

Square cap, 693

Square root, computing, 22

SQuirreL program, 345

SRC

,

SRC_

Xxx composition rules, 714–716

src.jar

file, 826

sRGB standard, 734

Standard extensions, 535

Standard input, 56

`StandardCharsets`
class, 77–78

`StandardJavaFileManager`
interface, 457–459

`getJavaFileObjectsFrom`
Xxx methods, 466

`start`
method
of
`Matcher`
, 157

of
`MatchResult`
, 158

`startDocument`
method (
`ContentHandler`
), 203, 207

`startElement`
method (
`ContentHandler`
), 203–208

Stateless operations, 49

Statement
interface, 308–311

addBatch
method, 355–356

close
,
closeOnCompletion
methods, 310, 312

execute
method, 310, 316, 329, 331

executeBatch
method, 355–356

executeLargeBatch
method, 356

executeLargeUpdate
method, 310

executeQuery
method, 308, 310, 332, 334

executeUpdate
method, 308, 310, 331, 354

getLargeUpdateCount
method, 310

getMoreResults
method, 329–330

getResultSet
method, 310

getUpdateCount
method, 310, 330

getWarnings
method, 314

isClosed
method, 310

RETURN_GENERATED_KEYS
field, 331

using for multiple queries, 311

Statements (databases)

closing, 312

complex, 321

concurrently open, 311

executing, 308–311

grouping into transactions, 353–358

in batch updates, 355

multiple, 311

prepared, 319–326

truncations in, 313

static
access modifier, 524

Static fields, in native code, 805–806

Static initialization blocks, 790

Static inner classes, 92

Static methods, calling from native code, 810–811

`statusCode` method (`HttpResponse`), 281, 286

StAX parser, 208–212, 217–222

namespace processing in, 209

no indented output in, 217–218

`stax/StAXTest.java`, 210

`StAXSource` class, 227

`stopCellEditing` method (*`CellEditor`*), 622–623, 630

Stored procedures, 328–329

`Stream` interface

`allMatch`, `anyMatch` methods, 17

`collect` method, 26–29, 43

concat
method, 14

count
method, 3–4, 16

distinct
method, 15–16, 50

dropWhile
method, 14

empty
method, 5, 9

filter
method, 3–11, 16

findAny
method, 17

findFirst
method, 16–17

flatMap
method, 12

forEach
method, 26, 29

forEachOrdered
method, 26

generate
method, 5, 9, 44

iterate
method, 5, 9, 15, 44

iterator
method, 26

limit
method, 13, 50

map
method, 11

mapToInt
method, 42

max
,
min
methods, 16–17

noneMatch
method, 17

of
method, 5, 9

ofNullable
method, 6, 9, 24

peek
method, 15–16

reduce
method, 41–43

skip
method, 13

sorted
method, 15–16

takeWhile
method, 14

toArray
method, 26, 29

toList
method, 6, 26, 29

unordered
method, 50

stream
method

of
Arrays
, 5, 9, 44

of
Collection
, 2–4

of
Optional
, 23–26

of
StreamSupport
, 6, 10

Streaming parsers, 165, 203–212

StreamPrintService
class, 773

StreamPrintServiceFactory
class, 772

getPrintService
method, 773

lookupStreamPrintServiceFactories
method, 773

StreamResult
class, 216, 228

Streams, 1–53

collecting results from, 26–31

computing values from, 41–43

converting to/from arrays, 5, 26, 50

creating, 5–11

debugging, 15

empty, 5, 16, 41–42

encrypted, 585–586

filtering, 23

finite, 5

flattening, 12, 23

for print services, 772–775

infinite, 3, 5, 13, 15

intermediate operations for, 3

noninterference of, 7

of primitive types, 42–49

of random numbers, 45

parallel, 2, 17, 26, 32, 35, 38, 42, 49–53

processed lazily, 3, 7, 15

reductions of, 16

removing duplicates from, 15

returned by
`Files.lines`
, 51

sorted, 15, 50

splitting/combining, 13–14

summarizing, 27

terminal operations for, 3, 16

transformations of, 11–13, 44

vs. collections, 3

`streams/CountLongWords.java`
, 3

`streams/CreatingStreams.java`
, 7

`streams/PrimitiveTypeStreams.java`
, 45

`StreamSource`
class, 227

constructor, 233

`transform`
method, 228

StreamSupport
class

stream
method, 6, 10

String
class, 62

compareTo
method, 407

format
method, 393

replaceAll
method, 155

split
method, 72, 154

toLowerCase
method, 11, 393

toUpperCase
method, 393

trim
method, 169, 396

STRING
class (
DocFlavor
), 770

String parameters, 795–801

StringBuffer
class, 62, 139

StringBuilder
class, 62, 82

Strings
converting to code points, 11
encoding, 387, 420
fixed-size, I/O of, 82–83
in native code, 795–801
in SQL, 299
internationalizing, 421–423
ordering, 407
patterns for, 143–158
printing, 69
sorting, 408
splitting, 6
transforming to lower/uppercase, 11, 393
writing in binary format, 78

StringSource
class, 458

Stroke
interface, 693

stroke/StrokeTest.java
, 696

StrokePanel

class, 696

Strokes, 672, 693–701

dashed, 694–695

setting, 672

styling, 693–695

Stylesheets (XSLT), 223–234

Subject
class

getPrincipals
method, 553

Subjects (logins), 551

subSequence
method (
CharSequence
), 63

subtract
method (
Area
), 692

Subtraction operator, not associative, 42

Subtrees (Swing), 635, 652

adding nodes to, 643

collapsed and expanded, 635–636

Suetonius, Gaius Tranquillus, 540

sufficient
keyword, 551

sum
,
summaryStatistics
methods (primitive streams), 44, 46–47

summarizing
Xxx methods (
Collectors
), 27, 30, 37

summing
Xxx methods (
Collectors
), 36, 40

Sun, 291

SunJCE ciphers, 579

Superclasses

adding, 110

not serializable, 101

type use annotations in, 480

Supplier
interface

get
method, 11

@SupportedAnnotationTypes
annotation, 488

SupportedValuesAttribute
interface, 776

supportsBatchUpdates
method (
DatabaseMetaData
), 355, 357

supportsResultSet
Xxx methods (
DatabaseMetaData
), 332, 338

@SuppressWarnings
annotation, 109, 483–484

SVG (Scalable Vector Graphics), 222–223

Swing, 591–671

generating dynamic code for, 461

tables in, 591–630

trees in, 630–671

Symmetric ciphers, 579–580

performance of, 587

SyncProviderException
interface, 341–342

System
class

console
method, 419

loadLibrary
method, 790, 792

System class loader, 535

SYSTEM
identifier (DTD), 177, 214

System.err
object, 69, 457

System.in
object, 56, 69

character encoding and, 419

System.out
object, 69, 457

character encoding and, 419

println
method, 418–419

t
literal (SQL), 328

\t
, in regular expressions, 145

Table cell renderers, 600

Table models (Swing), 592, 596–600

updating after cell editing, 623

table/TableTest.java
, 594

TableCellEditor
interface

getTableCellEditorComponent
method, 621–622–623, 629

implementing, 621, 623

tableCellRender/ColorTableCellEditor.java
, 627

tableCellRender/ColorTableCellRenderer.java
, 626

tableCellRender/PlanetTableModel.java
, 625

tableCellRender/TableCellRenderFrame.java
, 624

TableCellRenderer
interface

getTableCellRendererComponent
method, 617, 629

implementing, 617

TableColumn
class, 601–603, 608

constructor, 615

setCellEditor
method, 620, 629

setCellRenderer
method, 629

setHeader
Xxx methods, 619, 629

setResizable
,
set
Xxx
Width
methods, 602, 615

setWidth
method, 602, 615

TableColumnModel
interface, 601–602

getColumn
method, 601, 614

TableModel
interface, 605

getColumnClass
method, 600, 613

getColumnName
method, 600

getColumnType
method, 620

getValueAt
method, 596–597, 600, 619

get
Xxx
Count
methods, 596–597, 600

implementing, 596

isCellEditable

method, 600, 619

setValueAt

method, 600, 623

tableModel/InvestmentTable.java

, 598

tableRowColumn/PlanetTableFrame.java

, 609

TableRowSorter

class, 605–606

setStringConverter

method, 615

Tables (databases), 295

changing data in, 300

creating, 300

duplicating data in, 297

inspecting, 297–298

metadata for, 343

multiple, selecting data from, 299

removing, 305

Tables (Swing), 591–630

asymmetric, 600

cells in:

editing, 619–620

rendering, 617–619

selecting, 604

columns in:

accessing, 601–602

adding/hiding, 608

naming, 597–598

rearranging, 593

rendering, 600

resizing, 593–594, 602–603

selecting, 604

combo boxes in, 620

constructing, 593, 597

custom editors in, 621–623

headers in, 593

rendering, 619

index values in, 604

printing, 594

relationship between classes of, 602

rows in:

filtering, 606–608

hiding, 608

margins of, 603

resizing, 603

selecting, 593–594, 604

sorting, 594, 605–606

scrolling, 593

text fields in, 619

`TableStringConverter` class

`toString` method, 606, 616

`takeWhile` method (*Stream*), 14

`@Target` annotation, 469, 483–485

TCP (Transmission Control Protocol), 240

`teeing` method (`Collectors`), 38

telnet, 235–238

activating/connecting, 236

windows communicating in, 248–249

`template`

element (XSLT), 225

Temporal

interface, 365

TemporalAdjuster

interface, 372

TemporalAdjusters

class, 372–373

dayOfWeekInMonth

method, 373

firstDayOf

Xxx,

lastDayOf

Xxx methods, 373

lastInMonth

method, 373

next

method, 373

nextOrSame

method, 372–373

ofDateAdjuster

method, 372

previous

,

previousOrSame

methods, 373

TemporalAmount

interface, 365–366, 370–371

test/TestDB.java
, 306

@Test
annotation, 468

@TestCase
,
@TestCases
annotations, 487

Text, 68

encoding of, 75–78

generating from XML files, 226–228

output, 68–70

printing, 749–759, 769

reading, 70–72

saving objects in, 72–75

transmitting through sockets, 244–259

vs. binary data, 68

Text fields (Swing), 619

Text files, encoding of, 418, 420

Text nodes (XML)

constructing, 213

retrieving from XML, 169

TextCallbackHandler
class, 554

textFile/TextFileTest.java
, 73

TextLayout
class, 711

constructor, 712

get
Xxx methods, 712

TextStyle
enumeration, 405

TextSyntax
class, 779

TexturePaint
class, 702–703

this
keyword, 802

annotating, 481–482

Thread
class

get/setContextClassLoader
methods, 537, 545

threaded/ThreadedEchoServer.java
, 249

ThreadedEchoHandler
class, 247–251

Threads

blocking, 57, 252–259

executing scripts in, 446

Internet connections with, 247–251

race conditions in, 49

referencing class loaders in, 537

Throw

,

ThrowNew

functions (C), 819–820, 824

Throwable

class, 820

Thumbnails, 725

Time

current, 362

formatting, 379–384, 403–407

instances of, 373

literals for, 328

local, 373–374

measuring, 363

parsing, 381

zoned, 375–379, 403

Time

class, 384

valueOf
method, 385

TIME
data type (SQL), 301, 328, 357

Time of day service, 236

timeline/TimeLine.java
, 364

Timeouts, 240–241

Timestamp
class, 384

toInstant
method, 385

valueOf
method, 385

TIMESTAMP
data type (SQL), 301, 328, 357

Timestamps, 379

using instants as, 363

TimeZone
class

getTimeZone
method, 385

toZoneId
method, 385

toAbsolutePath

method (
Path
), 116–117

toArray
method

of
AttributeSet
, 784

of primitive streams, 44, 46–47

of
Stream
, 26

of streams, 29

toCollection
method (
Collectors
), 27, 30

toConcurrentMap
method (
Collectors
), 32, 34

toDays
method (
Duration
), 363, 365–366

toDaysPart
method (
Duration
), 366

toFile
method (
Path
), 117

toFormat
method (
DateTimeFormatter
), 381, 385

toHours
method (
Duration
), 363, 365–366

toInstant
method

of
Date
, 384–385

of
FileTime
, 385

of
Timestamp
, 385

of
ZonedDateTime
, 375, 379

tokens
method (
Scanner
), 6, 10

toLanguageTag
method (
Locale
), 391, 394

toList
method
of
Collectors
, 26, 30
of
Stream
, 6, 26, 29

toLocal
Xxx methods
of
Local
Xxx, 385
of
ZonedDateTime
, 379

toLowerCase
method (
String
), 11, 393

toMap
method (
Collectors
), 31–34

toMillis

,
`toMinutes`
,
`toNanos`
methods (
`Duration`
), 363, 365–366

`toNanoOfDay`
method (
`LocalTime`
), 374

`Tool`
interface

`run`
method, 457, 465

`ToolProvider`
class

`getSystemJavaCompiler`
method, 457

`toPath`
method (
`File`
), 117–118

`toSecondOfDay`
method (
`LocalTime`
), 374

`toSeconds`
method (
`Duration`

), 363, 365–366

toSet
method (
Collectors
), 26, 30, 36

toString
method

implementing with annotations, 490–493

of
Annotation
, 476

of
CharSequence
, 63

of
Currency
, 403

of
Locale
, 394

of
TableStringConverter
, 606, 616

of
Variable
, 665

toUnmodifiableList
method (
Collectors

), 30

toUnmodifiableMap
method (
Collectors
), 34

toUnmodifiableSet
method (
Collectors
), 30

toUpperCase
method (
String
), 393

toZonedDateTime
method (
GregorianCalendar
), 384–385

toZoneId
method (
TimeZone
), 385

Transactions, 353–358

committing, 353

error handling in, 355

rolling back, 353

transferTo
method (
InputStream

), 58

transform

method

of

Graphics2D

, 673, 707, 709

of

StreamSource

, 228

of

Transformer

, 214, 216, 227

transform/makehtml.xsl

, 229

transform/makeprop.xsl

, 229

transform/TransformTest.java

, 230

Transformations, 672, 703–709

affine, 706, 740

composing, 705–706

fundamental types of, 704–705

matrices for, 706

order of, 705

setting, 673

using for printing, 761

Transformer

class

setOutputProperty

method, 214, 216

transform

method, 214, 216, 227

TransformerFactory

class

newInstance

method, 214, 216

newTransformer

method, 214, 216, 232

transient

keyword, 101–102

transitive

keyword, 523–524

translate

method (

Graphics2D

), 705, 709, 761

Translation, 704–705

Transparency, 712–721

Traversal order, 649–650

Tree events, 654–662

Tree models

constructing, 632, 663

custom, 662–671

default, 632

Tree parsers, 165

Tree paths, 641–645

constructing, 644, 650

Tree selection listeners, 655

tree/SimpleTreeFrame.java
, 634

TreeCellRenderer
interface, 651–654

getTreeCellRendererComponent
method, 652–654

implementing, 652

treeEdit/TreeEditFrame.java
, 645

TreeMap
class, 32

TreeModel
interface, 632, 642

add/removeTreeModelListener
methods, 663, 671

getChild

,

getChildCount

methods, 663–665, 670

getIndexOfChild

method, 663, 670

getRoot

method, 663–665, 670

implementing, 632

isLeaf

method, 640, 663, 671

valueForPathChanged

method, 664, 671

treeModel/ObjectInspectorFrame.java

, 666

treeModel/ObjectTreeModel.java

, 667

treeModel/Variable.java

, 669

TreeModelEvent

class, 671

TreeModelListener

interface, 663

treeNodes

Xxx methods, 663, 671

treeStructureChanged

method, 663, 671

TreeNode
interface, 632, 642

children
method, 649

getAllowsChildren
method, 640

getChildAt
method, 648

getChildCount
method, 649

getParent
method, 648, 650

isLeaf
method, 639–640

TreePath
class, 642

getLastPathComponent
method, 642, 648

treeRender/ClassNameTreeCellRenderer.java
, 661

treeRender/ClassTreeFrame.java
, 657

Trees (Swing), 630–671

adding listeners to, 655

background color for, 652

connecting lines in, 636–637

displaying, 632–649

editing, 641–645, 664

handles in, 635, 637, 652

hierarchy of classes for, 633

indexes in, 643

infinite, 666

leaves in, 630, 638–639, 651, 663

nodes in, 630, 639, 651, 663

paired with other components, 654

rendering, 651–654

scrolling to newly added nodes, 644–645

structure of, 630

subtrees in, 635–636

traversals for, 649–651

updating vs. reloading, 643

user objects for, 632, 643

view of, 643

with horizontal lines, 637

`TreeSelectionEvent`
class

`getPath`

method, 662

getPaths

method, 656, 662

TreeSelectionListener

interface

implementing, 654–662

valueChanged

method, 655, 657, 662

TreeSelectionModel

interface, 655

trim

method (

String

), 169, 396

Troubleshooting. *See* **Debugging**

True Odds: How Risks Affect Your Everyday Life (Walsh), 563

tryLock

method (

FileChannel

), 141–143

try

-with-resources statement, 62

closing files with, 124, 126

for database connections, 312

with locks, 142

ts
literal (SQL), 328

Type bounds, type use annotations in, 480

Type codes, 96, 806

Type definitions, 185

anonymous, 187

nesting, 186

type
method (
XPathEvaluationResult
), 199

Type parameters, annotating, 479

Type use annotations, 480

TYPE_BICUBIC
,
TYPE_BILINEAR
fields (
AffineTransformOp
), 741, 747

TYPE_BYTE_GRAY
field (
BufferedImage
), 736, 738

TYPE_BYTE_INDEXED
field (
BufferedImage
), 738

TYPE_INT_ARGB
field (
BufferedImage
), 733–734, 738

TYPE_NEAREST_NEIGHBOR
field (
AffineTransformOp
), 741, 747

TypeElement
interface, 489

Types. *See* **Data types**

Typesafe enumerations, 104–107

U.S. government on exporting encryption methods, 540

\u
, in regular expressions, 145

UDP (User Datagram Protocol), 240

UIManager
class, 618

Unicode standard, 44, 75

character order in, 407

converting to binary data, 68

in property files, 423

input/output streams and, 56

native code and, 795

normalization forms in, 409

using for all strings, 387

Units of measurement, 164

UNIX operating system

authentication in, 550

line feed in, 69, 418

paths in, 115

specifying locales in, 392

`UnixLoginModule`
class, 551

`UnixNumericGroupPrincipal`
class, 551

`UnixPrincipal`
class, 551

`UnknownHostException`
, 239

`unordered`
method (
BaseStream
), 50, 53

Unparsed external entities, 181

`unread`
method (
`PushbackInputStream`
), 67

`UnsatisfiedLinkError`, 787

`until` method (`LocalDate`), 367, 370

`update` method of `Cipher`, 579, 582, 585–586

of `MessageDigest`, 564, 566

`UPDATE` statement (SQL), 300, 320, 334

executing, 308, 310, 326

in batch updates, 355

truncations in, 313

vs. methods of *`ResultSet`*, 335

`update` *Xxx* methods (*`ResultSet`*), 311, 334–335, 337–338

`URI` class, 280

get
Xxx methods, 261

no resource accessing with, 260

uri
method (
HttpRequest.Builder
), 279–281, 286

URIs (Uniform Resource Identifiers), 200, 260

absolute vs. relative, 260–261

base, 261

hierarchical, 260

namespace, 199–202

opaque vs. nonopaque, 260

schemes for, 260

with HTTP, 280

URISyntax
class, 779

URL
class (
DocFlavor
), 770

URL
class (
java.lang.Object
), 259–261, 280

accepted schemes for, 260

openConnection
method, 262, 267

openStream
method, 64, 259, 267

URLClassLoader
class

addURLs
method, 537

constructor, 545

getURLs
method, 537

loadClass
method, 536

URLConnection
class, 259, 262–269, 279

connect
method, 262, 264, 268

getConnectTimeout
method, 268

getContent
method, 269

getContentEncoding
,
getContentType
methods, 262, 265, 269, 274

getContentLength
method, 262, 265, 268

getDate
method, 262, 265, 269

getDoInput
,
getDoOutput
methods, 267

getExpiration
method, 262, 265, 269

getHeader
Xxx methods, 262–265, 268

getIfModifiedSince
method, 268

getInputStream
method, 262, 269, 272, 274

getLastModified
method, 262, 265, 269

getOutputStream
method, 262, 269, 272

getReadTimeout
method, 268

getRequestProperty
method, 268

setAllowUserInteraction
method, 262

setConnectTimeout
method, 262, 268

setDoInput
method, 262–263, 267

setDoOutput
method, 262–263, 267, 272, 274

setIfModifiedSince
method, 262–263, 268

setReadTimeout
method, 262, 268

setRequestProperty
method, 262–263, 268

setUseCaches
method, 262

urlConnection/URLConnectionTest.java
, 265

URLDecoder
class

decode
method, 278

URLEncoder
class

encode
method, 278

URLs (Uniform Resource Locators), 260

attaching parameters to, 270

connections via, 259

encoding, 271

for databases, 302

for namespace identifiers, 200

redirecting, 274–275

relative vs. absolute, 177

URNs (Uniform Resource Names), 260

US Letter paper, 752

`useLocale` method (`Scanner`), 393, 396

User coordinates, 704

User objects, 632

`User-Agent` request parameter, 275

Users

authentication of, 549–562

preferences of, 141

`uses` keyword, 527–528

UTC (Coordinated Universal Time), 375

UTF-8 encoding, 76–79

byte order in, 76, 420

for text files, 418

modified, 79–80, 420, 795–798

UTF-16 encoding, 44, 68, 76, 79

byte order in, 76

in regular expressions, 145

native code and, 795

`V`
(
`void`
), type code, 806

`\v`
,
`\V`
, in regular expressions, 146

`validateObject`
method (
`ObjectInputValidation`
), 113–114

Validation, 175–194

activating, 182

adding to classes, 101

`value`
method (
`XPathEvaluationResult`
), 196, 199

valueChanged
method (
TreeSelectionListener
), 655, 657, 662

valueForPathChanged
method (
TreeModel
), 664, 671

value-of
element (XSLT), 226

valueOf
method (date/time legacy classes), 385

VARCHAR
data type (SQL), 301, 357

VarHandle
class, 518

Variable
class, 664

toString
method, 665

Variable handles, 518

VariableElement
interface, 489

Variables

annotating, 468, 480

binding, 446

fields of, 665

initializing, 546

scope of, 447

Vendor name, of a reader, 723

verifier/VerifierTest.java
, 549

Verifiers, 545–549

Version number, of a reader, 723

Versioning, 107–110

view/ViewDB.java
, 345

visitFile
,
visitFileFailed
methods

of
FileVisitor
, 127

of
SimpleFileVisitor
, 128–130

'

\w
,
\W
, in regular expressions, 146

W3C (World Wide Web Consortium), 166, 204

walk
method (
Files
), 125–126

walkFileTree
method (
Files
), 127–129

warning
method (
ErrorHandler
), 183–184

Warnings

SQLWarning
, 313–314

suppressing, 484

WBMP format, 722

WeakReference
object, 666

Web applications, 358–360

Web crawlers, 204

with SAX parser, 205

with StAX parser, 209

Web pages

dynamic, 461–467

separating class loaders for, 539

WebRowSet

interface, 339

Weekends, 368

Weeks, 405

WHERE

statement (SQL), 299

Whitespace

ignoring, while parsing, 168–169

in e-mail URIs, 271

in regular expressions, 146

Wildcards, type use annotations in, 480

Wilde, Oscar, 388

win32reg/Win32RegKey.c

, 838

win32reg/Win32RegKey.java

, 836

win32reg/Win32RegKeyTest.java

, 845

Win32RegKey

class, 832, 835

getValue

method, 832–833

names

method, 832

setValue

method, 832–834

Win32RegKeyNameEnumeration

class, 834–835

Windows operating system

activating telnet in, 236

authentication in, 550

character encodings in, 418

classpath in, 302

compiling invocation API, 829

dynamic linking in, 826

glob syntax in, 127

line feed in, 69, 418

look-and-feel of, 636

paths in, 64, 115

registry, accessing from native code, 830–846

resources in, 421

using Microsoft compiler, 789–790

Windows-1252 encoding, 418–419

with

method (

Temporal

), 372–373

withLocale method (DateTimeFormatter), 380, 384, 404, 407

with *Xxx* methods

of LocalDate, 370

of LocalTime, 374

of Period, 371

of ZonedDateTime, 378

Words, in regular expressions, 146

Working directory, 64

wrap method (ByteBuffer), 138, 140

WritableByteChannel interface, 253

WritableRaster

class, 733

setDataElements

method, 735, 739

setPixel

,

setPixels

methods, 733, 739

write

method

of

CipherOutputStream

, 586

of

Files

, 118–119

of

ImageIO

, 722, 729

of

ImageWriter

, 725, 732

of

OutputStream

, 57, 59

of

Writer

, 60

write/XMLWriteTest.java

, 218

writeAttribute

method (

XMLStreamWriter

), 217, 222

writeBoolean

method (

DataOutput

), 78, 80

writeByte

method (

DataOutput

), 78, 80

writeCData

method (

XMLStreamWriter

), 222

writeChar

method (

DataOutput

), 78, 80–81

writeCharacters

method (

XMLStreamWriter

), 217, 222

writeChars

method (

DataOutput

), 78–80

writeComment

method (

XMLStreamWriter

), 222

writeDouble

method (

DataOutput

), 78, 80, 90, 102

writeDTD

method (

XMLStreamWriter

), 222

writeEmptyElement

method (

XMLStreamWriter

), 217, 221

writeEnd

Xxx methods (

XMLStreamWriter

), 217, 221

writeExternal

method (

Externalizable

), 103–104

writeFixedString

method (

DataIO

), 82

writeFloat

method (

DataOutput

), 78, 80

writeInsert
method (
ImageWriter
), 725, 732

writeInt
method (
DataOutput
), 78, 80–81, 90

writeLong
method (
DataOutput
), 78, 80

writeObject
method

of
HashSet
, 102

of
ObjectOutputStream
, 89, 94, 102

Writer
class, 56, 61–62

write
method, 60

writeReplace
method (
Serializable
), 106–107

writeShort

method (
DataOutput
), 78, 80

writeStart
Xxx methods (
XMLStreamWriter
), 217, 221

writeString
method (
Files
), 118–119

writeUTF
method (
DataOutput
), 78–80

X.509 format, 570

\x
, in regular expressions, 145

XHTML (Extensible Hypertext Markup Language), 162, 204

XML (Extensible Markup Language), 159–234

annotated version of the standard, 161

attributes in, 162

case sensitivity of, 162

end and empty tags in, 162

in databases, 358

namespaces in, 199–202

vs. HTML, 161–162

XML catalogs, 177

XML documents

DTDs in, 162, 176–185

format of, 161

generating, 212–223

from non-XML legacy data, 228

HTML files from, 223–226

plain text from, 226–228

with StAX, 217–222

locating information in, 194–199

malformed, 217–218

parsing, 165–175

structure of, 162–166, 176

validating, 175–194

with/without namespaces, 213–214

XML Schema, 176, 185–188

attributes in, 187

documentation for, 200

parsing with, 188

referencing in XML documents, 185

repeated elements in, 187

type definitions in, 185–187

XML/JSON binding, 517

XMLInputFactory

class

createXMLStreamReader

method, 211

newInstance

method, 211

setProperty

method, 209, 211

xmlns

attribute (XSLT), 201

XMLOutputFactory

class

createXMLStreamWriter

method, 217, 221

newInstance

method, 217, 221

XMLReader

interface

implementing, 227

parse

method, 233

setContentHandler

method, 233

XMLStreamReader

interface

getAttribute

Xxx methods, 209, 212

getName

,

getLocalName

,

getText

methods, 212

hasNext

method, 211

is

Xxx methods, 212

next

method, 212

XMLStreamWriter

interface, 217

close

method, 222

not autocloseable, 217

setDefaultNamespace

,

setPrefix

methods, 221

writeAttribute

method, 217, 222

writeCData

method, 222

writeCharacters

method, 217, 222

writeComment

method, 222

writeDTD

method, 222

writeEmptyElement

method, 217, 221

writeEnd

Xxx methods, 217, 221

writeStart

Xxx methods, 217, 221

XOR

composition rule, 714

XPath (XML Path Language), 194–199

count

function, 195

XPath

interface

evaluate

method, 195–196, 199

evaluateExpression

method, 195–196, 199

xpath/XPathTest.java
, 197

XPathEvaluationResult
interface

type
method, 199

value
method, 196, 199

XPathFactory
class

newInstance
method, 195, 199

newXpath
method, 199

XPathNodes
class, 196

xs:
,
xsd:
prefixes (XSL Schema), 186

xsd:attribute
element (XML Schema), 187

xsd:choice
element (XML Schema), 187

xsd:complexType
element (XML Schema), 186

xsd:element

element (XML Schema), 186

xsd:enumeration

element (XML Schema), 186

xsd:schema

element (XML Schema), 187

xsd:sequence

element (XML Schema), 187

xsd:simpleType

element (XML Schema), 186

xsl:apply-templates

element (XSLT), 225

xsl:output

element (XSLT), 225

xsl:template

element (XSLT), 225

xsl:value-of

element (XSLT), 226

XSLT (Extensible Stylesheet Language Transformations), 214, 223–234

copying attribute values in, 226

templates in, 225

XSLT processors, 223

Yasson

framework, 518

`Year`
,
`YearMonth`
classes, 368

`Z`
(
`boolean`
), type code, 96, 806

`\z`
,
`\Z`
, in regular expressions, 148

ZIP archives, 85–88

for JMOD files, 530

reading, 66, 85–86

writing, 86

Zip code lookup, 272

ZIP file systems, 130–131

`ZipEntry`
class

constructor, 87

`get`
Xxx,
`set`
Xxx methods, 88

isDirectory
method, 88

ZipFile
class

constructor, 88

entries
method, 88

get
Xxx methods, 88

ZipInputStream
class, 60, 85

closeEntry
method, 85–87

constructor, 87

getNextEntry
method, 85–87

read
method, 85

ZipOutputStream
class, 60, 86

closeEntry
method, 86–87

constructor, 87

putNextEntry
method, 86–87

setLevel
,
setMethod
methods, 87

ZonedDateTime
class, 375–379

format
method, 404

from
method, 384–385

get
Xxx methods, 378–379

isAfter
,
isBefore
methods, 379

legacy classes and, 384–385

minus
,
minus
Xxx methods, 378

now
method, 378

of
,
ofInstant
methods, 375, 378

parse

method, 384, 404, 407

plus

,

plus

Xxx methods, 378

toInstant

method, 375, 379

toLocal

Xxx methods, 379

with

Xxx methods, 378

zonedtimes/ZonedTimes.java

, 377

ZoneId

class, 385

getAvailableZoneIds

method, 375

of

method, 375

Previous chapter
Chapter 12. Native Methods

Next chapter
Core Java, Vol. II-Advanced Features, 12th Edition