Chapter 11 ▪ Annotations

Annotations are tags that you insert into your source code so that some tool can process them. The tools can operate on the source level, or they can process class files into which the compiler has placed annotations.

Annotations do not change the way your programs are compiled. The Java compiler generates the same virtual machine instructions with or without the annotations.

To benefit from annotations, you need to select a processing tool and use annotations that your processing tool understands, before you can apply that tool to your code.

There is a wide range of uses for annotations. For example, JUnit (available at **https://junit.org**) uses annotations to mark methods that execute tests and to specify how the tests should be run. Jakarta Persistence (**https://jakarta.ee/specifications/persistence/**) uses annotations to define mappings between classes and database tables, so that objects can be persisted automatically without the developer having to write SQL queries.

In this chapter, you will learn the details of the annotation syntax, how to define your own annotations, and how to write annotation processors.



Note: For a compelling use of annotations, check out `JCommander` (**https://jcommander.org**) and picocli (**https://picocli.info**). These libraries use annotations for the processing of command-line arguments.

11.1. Using Annotations

Here is an example of a simple annotation:

```
class CacheTest
{
  . . .
  @Test void checkRandomInsertions()
}
```

The annotation `@Test` annotates the `checkRandomInsertions` method. In Java, an annotation is used like a modifier (such as `public` or `static`). The name of each annotation is preceded by an `@` symbol.

By itself, the `@Test` annotation does not do anything. It needs a tool to be useful. When running JUnit, it finds the methods that are annotated with `@Test` and calls them.

11.1.1. Annotation Elements

Annotations can have key/value pairs called *elements*, such as

```
@RepeatedTest(value=10, failureThreshold=3)
```

The names and types of the permissible elements are defined by each annotation (see **Section 11.2**). The elements can be processed by the tools that read the annotations.

An annotation element is one of the following:

- A primitive type value

- A `String`
- A `Class` object
- An instance of an `enum`
- An annotation
- An array of the preceding (but not an array of arrays)

To illustrate these possibilities, here is a `@BugReport` annotation, not from an actual library:

```
@BugReport(showStopper=true,
  assignedTo="Harry",
  testCase=CacheTest.class,
  status=BugReport.Status.CONFIRMED,
  ref=@Reference(id=11235811),
  reportedBy={"Harry", "Fred"})
```



Note: Since annotations are processed by the compiler, all element values must be compile-time constants.



Caution: An annotation element can never have the value `null`.

If an element value is an array with a single element, you can omit the braces:

```
@BugReport(reportedBy="Harry") // Same as reportedBy={"Harry"}
```

Elements can have default values. For example, the `failureThreshold` element of the JUnit `@RepeatedTest` annotation has default `Integer.MAX_VALUE`. Therefore, the annotation `@RepeatedTest(value=10)` is equivalent to `@RepeatedTest(value=10, failureThreshold=Integer.MAX_VALUE)`. When running this test, it is repeated ten times, no matter how often it failed.

If the element name is `value`, and that is the only element you specify, you can omit `value=`. For example, `@RepeatedTest(10)` is the same as `@RepeatedTest(value=10)`.

11.1.2. Multiple and Repeated Annotations

An item can have multiple annotations:

```
@Test
@Tag("localized")
void testHello()
```

If the author of an annotation declared it to be repeatable, you can repeat the same annotation multiple times:

```
@Tag("localized")
@Tag("showstopper")
void testHello()
```

11.1.3. Annotating Declarations

So far, you have seen annotations applied to method declarations. There are many other places where annotations can occur. They fall into two categories: *declarations* and *type uses*. Declaration annotations can appear at the declarations of

- Classes (including `enum`) and interfaces (including annotation interfaces)
- Methods
- Constructors
- Fields (including `enum` constants and record components)

- Local variables (including those declared in `for` and try-with-resources statements)
- Parameter variables and `catch` clause parameters
- Type parameters
- Packages and modules

For classes, interfaces, and modules, put the annotations before the `class`, `interface`, or `module` keyword and any modifiers:

```
@Entity public class User { . . . }
```

For variables, put them before the type:

```
@SuppressWarnings("unchecked") List<User> users = . . .;
public User getUser(@Param("id") String userId)
```

This also holds for record components:

```
public record Rectangle(@ToString(includeName=false) Point topLeft,
  int width, int height) {}
```

A type parameter in a generic class or method can be annotated like this:

```
public class Cache<@NonNull V> { . . . }
```

A package is annotated in a file `package-info.java` that contains only the package statement preceded by annotations.

```
/**
   Package-level documentation
*/
@Generated("com.horstmann.generator")
package com.horstmann.corejava.generated;
import javax.annotation.processing.Generated;
```

Note that the `import` statement for the annotation comes *after* the `package` declaration.



Note: Annotations for local variables and packages are discarded when a class is compiled. Therefore, they can only be processed at the source level.

11.1.4. Annotating Type Uses

A declaration annotation provides some information about the item being declared. For example, in the declaration

```
public User getUser(@NonNull String userId)
```

it is asserted that the `userId` parameter is not `null`.



Note: The `@NonNull` and `@Localized` annotations are a part of the Checker Framework (**https://types.cs.washington.edu/checker-framework**). With that framework, you can include assertions in your program, such that a parameter is non-`null` or that a `String` has been localized—that is, adapted to the user's local language and usage. A static analysis tool then checks whether the assertions are valid in a given body of source code.

Now, suppose we have a parameter of type `List<String>`, and we want to express that all of the strings are non-`null`. That is where type use annotations come in. Place the annotation before the type argument: `List<@NonNull String>`

Type use annotations can appear in the following places:

- With generic type arguments: `List<@NonNull String>`, `Comparator.<@NonNull String> reverseOrder()`.
- In any position of an array: `@NonNull String[][] words` (`words[i][j]` is not `null`), `String @NonNull [][] words` (`words` is not `null`), `String[] @NonNull [] words` (`words[i]` is not `null`).
- With superclasses and implemented interfaces: `class Warning extends @Localized Message`.
- With constructor invocations: `new @Localized String(. . .)`.
- With nested types: `Map.@Localized Entry`.
- With casts and `instanceof` checks: `(@Localized String) text`, `if (text instanceof @Localized String)`. (The annotations are only for use by external tools. They have no effect on the behavior of a cast or an `instanceof` check.)
- With exception specifications: `public String read() throws @Localized IOException`.
- With wildcard types and type bounds: `List<@Localized ? extends Message>`, `List<? extends @Localized Message>`.
- With method and constructor references: `@Localized Message::getText`.

There are a few type positions that cannot be annotated:

```
@NonNull String.class // Error--cannot annotate class literal
import java.lang.@NonNull String; // Error--cannot annotate import
```

You can place annotations before or after other modifiers such as `private` and `static`. It is customary (but not required) to put type use annotations after other modifiers, and declaration annotations before other modifiers. For example,

```
private @NonNull String text; // Annotates the type use
@Id private String userId; // Annotates the variable
```



Note: As you will see in Section 11.2, an annotation author needs to specify where a particular annotation can appear. If an annotation is permissible both for a variable and a type use, and it is used in a variable declaration, then both the variable and the type use are annotated. For example, consider

```
public User getUser(@NonNull String userId)
```

if `@NonNull` can apply both to parameters and to type uses, the `userId` parameter is annotated, and the parameter type is `@NonNull String`.

11.1.5. Making Receivers Explicit

Suppose you want to annotate parameters that are not being mutated by a method.

```
public class Point
{
  public boolean equals(@Nullable Object other) { . . . }
}
```

Then a tool that processes this annotation would, upon seeing a call

```
p.equals(q)
```

reason that `q` has not been changed.

But what about `p`?

When the method is called, the receiver variable `this` is bound to `p`, but `this` is never declared, so you cannot annotate it.

Actually, you can declare it, with a rarely used syntax variant, just so that you can add an annotation:

```
public class Point
{
  public boolean equals(@NonNull Point this, @Nullable Object other) { . . . }
}
```

The first parameter is called the *receiver parameter*. It must be named `this`. Its type is the class that is being constructed.



Note: You can provide a receiver parameter only for methods, not for constructors. Conceptually, the `this` reference in a constructor is not an object of the given type until the constructor has completed. Instead, an annotation placed on the constructor describes a property of the constructed object.

A different hidden parameter is passed to the constructor of an inner class, namely the reference to the enclosing class object. You can make this parameter explicit as well:

```
static class Sequence
{
  private int from;
  private int to;
```

```
  class Iterator implements java.util.Iterator<Integer>
  {
    private int current;

    public Iterator(@NonNull Sequence Sequence.this)
    {
      this.current = Sequence.this.from;
    }
    . . .
  }
  . . .
}
```

The parameter must be named just like when you refer to it, `EnclosingClass.this`, and its type is the enclosing class.

11.2. Defining Annotations

Each annotation must be declared by an *annotation interface*, with the `@interface` syntax. The methods of the interface correspond to the elements of the annotation. For example, the JUnit Test annotation is defined by the following interface:

```
@Target(ElementType.METHOD)
@Retention(RetentionPolicy.RUNTIME)
public @interface RepeatedTest
{
  int failureThreshold();
  . . .
}
```

The `@interface` declaration creates an actual Java interface. Tools that process annotations receive objects that implement the annotation interface. When the JUnit test runner tool gets an object that implements `RepeatedTest`, it simply invokes the `failureThreshold` method to retrieve the failure threshold of a particular `RepeatedTest` annotation.

The element declarations in the annotation interface are actually method declarations. The methods of an annotation interface can have no parameters and no `throws` clauses, and they cannot be generic.

The `@Target` and `@Retention` annotations are *meta-annotations*. They annotate the `@RepeatedTest` annotation, indicating the places where the annotation can occur and where it can be accessed.

The value of the `@Target` meta-annotation is an array of `ElementType` objects, specifying the items to which the annotation can apply. You can specify any number of element types, enclosed in braces. For example,

```
@Target({ElementType.FIELD, ElementType.RECORD_COMPONENT, ElementType.TYPE})
public @interface ToString
```

Table 11.1 shows all possible targets. The compiler checks that you use an annotation only where permitted. For example, if you apply `@ToString` to a method, a compile-time error results.



Note: An annotation without an `@Target` restriction can be used with any declarations but not with type parameters and type uses. (These were the only possible targets in the first Java release that supported annotations.)

Table 11.1: Element Types for the `@Target` Annotation

Element Type	Annotation Applies To
ANNOTATION_TYPE	Annotation type declarations

`MODULE`	Modules
PACKAGE	Packages
`TYPE`	Classes (including `enum`) and interfaces (including annotation types)
METHOD	Methods
`CONSTRUCTOR`	Constructors
FIELD	Fields (including `enum` constants)
`PARAMETER`	Method or constructor parameters
RECORD_COMPONENT	Record components
`LOCAL_VARIABLE`	Local variables
TYPE_PARAMETER	Type parameters
`TYPE_USE`	Uses of a type

When you annotate a record component, the annotation is applied to the fields and methods to which the component gives rise, provided the annotation is permitted on fields or methods. For example, in the annotation

```
public record Rectangle(@ToString(includeName=false) Point topLeft,
  int width, int height) {}
```

the `topLeft` field receives the annotation if its target types include `ElementType.FIELD`.

The `@Retention` meta-annotation specifies where the annotation can be accessed. There are three choices.

1. `RetentionPolicy.SOURCE`: The annotation is available to source processors, but it is not included in class files.
2. `RetentionPolicy.CLASS`: The annotation is included in class files, but the virtual machine does not load them. This is the default.
3. `RetentionPolicy.RUNTIME`: The annotation is available at runtime and can be accessed through the reflection API.

You will see examples of all three scenarios later in this chapter.

There are several other meta-annotations—see **Section 11.3** for a complete list.

To specify a default value for an element, add a `default` clause after the method defining the element. For example,

```
public @interface RepeatedTest
{
  int failureThreshold() default Integer.MAX_VALUE;
  . . .
}
```

This example shows how to denote a default of an empty array and a default for an annotation:

```
public @interface BugReport
{
  String[] reportedBy() default {};
    // Defaults to empty array
  Reference ref() default @Reference(id=0);
    // Default for an annotation
  . . .
}
```



Caution: Defaults are not stored with the annotation; instead, they are dynamically computed. If you change a default and recompile the annotation class, all annotated elements will use the new default, even in class files that have been compiled before the default changed.

All annotation interfaces implicitly extend the `java.lang.annotation.Annotation` interface. That interface is a regular interface, *not* an annotation interface. See the API notes at the end of this section for the methods provided by this interface.

You cannot extend annotation interfaces, and you never supply classes that implement annotation interfaces. Instead, source processing tools and the virtual machine generate proxy classes and objects when needed.

java.lang.annotation.Annotation **5.0**

- `Class<? extends Annotation> annotationType()`
  returns the `Class` object that represents the annotation interface of this annotation object. Note that calling `getClass` on an annotation object would return the actual class, not the interface.
- `boolean equals(Object other)`
  returns `true` if `other` is an object that implements the same annotation interface as this annotation object and if all elements of this object and `other` are equal.

- `int hashCode()`
  returns a hash code, compatible with the `equals` method, derived from the name of the annotation interface and the element values.
- `String toString()`
  returns a string representation that contains the annotation interface name and the names and values of the elements.

11.3. Annotations in the Java API

The Java API defines a number of annotation interfaces in the `java.lang`, `java.lang.annotation`, and `javax.annotation` packages. Four of them are meta-annotations that describe the behavior of annotation interfaces. The others are regular annotations that you can use to annotate items in your source code. **Table 11.2** shows these annotations. I will discuss them in detail in the following two sections.

Table 11.2: Annotations in the Java API

Annotation Interface	Applicable To	Purpose
Override	Methods	Checks that this method overrides a superclass method.
`Serial`	Methods	Checks that this method is a correct serialization method.
Deprecated	All declarations	Marks item as deprecated.
`SuppressWarnings`	All declarations except packages	Suppresses warning messages of a given type.
SafeVarargs	Methods and constructors	Asserts that the varargs parameter is safe to use.

`FunctionalInterface`	Interfaces	Marks an interface as functional (with a single abstract method).
Generated	All declarations	Marks an item as source code that has been generated by a tool.
`Target`	Annotations	Specifies the locations to which this annotation can be applied.
Retention	Annotations	Specifies where this annotation can be used.
`Documented`	Annotations	Specifies that this annotation should be included in the documentation of annotated items.
Inherited	Annotations	Specifies that this annotation is inherited by subclasses.
`Repeatable`	Annotations	Specifies that this annotation can be applied multiple times to the same item.

11.3.1. Annotations for Compilation

The `@Deprecated` annotation can be attached to any items whose use is no longer encouraged. The compiler will warn when you use a deprecated item. This annotation has the same role as the `@deprecated` JavaDoc tag. However, the annotation persists until runtime.



Note: The `jdeprscan` utility which is part of the JDK can scan a set of JAR files for deprecated elements.

The `@Override` annotation makes the compiler check that the annotated method really overrides a method from the superclass. For example, if you declare

```
public class Point
{
  @Override public boolean equals(Point other) { . . . }
  . . .
}
```

then the compiler will report an error—this `equals` method does not override the `equals` method of the `Object` class because that method has a parameter of type `Object`, not `Point`.

The `@Serial` annotation checks that methods used for serialization, which are not declared in interfaces, have the correct parameter types.

The `@SuppressWarnings` annotation tells the compiler to suppress warning messages of a particular category, for example

```
@SuppressWarnings("unchecked") T[] result
   = (T[]) Array.newInstance(cl, n);
```

The `@SafeVarargs` annotation asserts that a method does not corrupt its varargs parameter (see **Chapter 8**).

The `@Generated` annotation is intended for use by code generator tools. Any generated source code can be annotated to differentiate it from programmer-provided code. For example, a code editor can hide the generated code, or a code generator can remove older versions of generated code. Each annotation must contain a unique identifier for the code generator. A date string (in ISO 8601/RFC 3339 format) and a comment string are optional. For example,

```
@Generated(value="com.horstmann.generator",
   date="2015-01-04T12:08:56.235-0700");
```

You have seen the `FunctionalInterface` annotation in **Chapter 6**. It is used to annotate conversion targets for lambda expressions, such as

```
@FunctionalInterface
public interface IntFunction<R>
{
  R apply(int value);
}
```

If you later add another abstract method, the compiler will generate an error.

Of course, you should only add this annotation to interfaces that describe functions. There are other interfaces with a single abstract method (such as `AutoCloseable`) that are not conceptually functions.

11.3.2. Meta-Annotations

You have already seen the `@Target` and `@Retention` meta-annotations in **Section 11.2**.

The `@Documented` meta-annotation gives a hint to documentation tools such as JavaDoc. Documented annotations should be treated just like other modifiers (such as `private` or `static`) for documentation purposes. In contrast, other annotations should not be included in the documentation.

For example, the `@SuppressWarnings` annotation is not documented. If a method or field has that annotation, it is an implementation detail that is of no interest to the JavaDoc reader. On the other hand, the `@FunctionalInterface` annotation is documented since it is useful for the programmer to know that the interface is intended to describe a function. **Figure 11.1** shows the documentation.

Module java.base
Package java.util.function

Interface Predicate<T>

Type Parameters:

T - the type of the input to the predicate

Functional Interface:

This is a functional interface and can therefore be used as the assignment target for a lambda expression or method reference.

```
@FunctionalInterface
public interface Predicate<T>
```

Represents a predicate (boolean-valued function) of one argument.

This is a functional interface whose functional method is `test(Object)`.

Since:

1.8

Method Summary

All Methods | Static Methods | Instance Methods | Abstract Methods | Default Methods

Modifier and Type	Method	Description
`default Predicate<T>`	`and(Predicate<? super T> other)`	Returns a composed predicate that represents a short-circuiting logical AND of this predicate and another.

`static <T> Predicate<T> isEqual(Object targetRef)`	Returns a predicate that tests if two arguments are equal according to `Objects.equals(Object, Object)`.
`default Predicate<T> negate()`	Returns a predicate that represents the logical negation of this predicate.

Figure 11.1: A documented annotation

The `@Inherited` meta-annotation applies only to annotations for classes. When a class has an inherited annotation, then all of its subclasses automatically have the same annotation. This makes it easy to create annotations that work similar to marker interfaces (such as the `Serializable` interface).

Suppose you define an inherited annotation `@Persistent` to indicate that objects of a class can be saved in a database. Then the subclasses of persistent classes are automatically annotated as persistent.

```
@Inherited @interface Persistent { }

@Persistent class Employee { . . . }
class Manager extends Employee { . . . } // Also @Persistent
```

The `@Repeatable` meta-annotation makes it possible to apply the same annotation multiple times. For example, the JUnit `@Tag` annotation is repeatable. It can be used like this:

```
@Tag("localized")
@Tag("showstopper")
void testHello() { . . . }
```

For historical reasons, the implementor of a repeatable annotation needs to provide a *container annotation* that holds the repeated annotations in an array.

Here is how to define the `@Tag` annotation and its container:

```
@Repeatable(Tag.class)
@interface Tag
{
  String value();
}

@interface Tags
{
  Tag[] value();
}
```

Whenever the user supplies two or more `@Tag` annotations, they are automatically wrapped into a `@Tags` annotation. This complicates processing of the annotation, as you will see in the next section.

11.4. Processing Annotations at Runtime

So far, you have seen how to add annotations to source files and how to define annotation types. Now the time has come to see what good can come out of that.

In this section, I show you a simple example of processing an annotation at runtime using the reflection API that you have already seen in **Chapter 5**. Suppose we want to reduce the tedium of implementing `toString` methods. Of course, one can write a generic `toString` method using reflection that simply includes all field names and values. But suppose we want to customize that process.

We may not want to include all fields, or we may want to skip class and variable names. For example, for the `Point` class we may prefer `[5,10]` instead of `Point[x=5,y=10]`. Of course, any number of other enhancements would be plausible, but let's keep it simple. The point is to demonstrate what an annotation processor can do.

Annotate all classes that you want to benefit from this service with the `@ToString` annotation. In addition, all fields that should be included need to be annotated as well. The annotation is defined like this:

```
@Target({ElementType.FIELD, ElementType.RECORD_COMPONENT, ElementType.TYPE})
@Retention(RetentionPolicy.RUNTIME)
public @interface ToString
{
  boolean includeName() default true;
}
```

Here are annotated `Point` and `Rectangle` classes:

```
@ToString(includeName=false)
public class Point
{
  @ToString(includeName=false) private int x;
  @ToString(includeName=false) private int y;
  . . .
}

@ToString
public record Rectangle(
  @ToString(includeName=false) Point topLeft,
```

```
  @ToString int width,
  @ToString int height)
{}
```

The intent is for a rectangle to be represented as string as `Rectangle[[5, 10],width=20,height=30]`.

At runtime, we cannot modify the implementation of the `toString` method for a given class. Instead, let us provide a method that can format any object, discovering and using the `ToString` annotations if they are present.

The key are the methods

```
T getAnnotation(Class<T>)
T getDeclaredAnnotation(Class<T>)
T[] getAnnotationsByType(Class<T>)
T[] getDeclaredAnnotationsByType(Class<T>)
Annotation[] getAnnotations()
Annotation[] getDeclaredAnnotations()
boolean isAnnotationPresent(Class<? extends Annotation> annotationClass)
```

of the `AnnotatedElement` interface. The reflection classes `Class`, `Field`, `Parameter`, `Method`, `Constructor`, and `Package` implement that interface.

As with other reflection methods, the methods with `Declared` in their name yield annotations in the class itself, whereas the others include inherited ones. In the context of annotations, this means that the annotation is `@Inherited` and applied to a superclass.

If an annotation is not repeatable, call `getAnnotation` to locate it. For example:

```
Class<?> cl = obj.getClass();
ToString ts = cl.getAnnotation(ToString.class);
if (ts != null && ts.includeName()) . . .
```

Note that you pass the class object for the annotation (here, `ToString.class`) and you get back an object of some proxy class that implements the `ToString` interface. You can then invoke the interface methods to get the values of the annotation elements. If the annotation is not present, the `getAnnotation` method returns `null`.

It gets a bit messy if an annotation is repeatable. If you call `getAnnotation` to look up a repeatable annotation, and the annotation was actually repeated, then you also get `null`. That is because the repeated annotations were wrapped inside the container annotation.

In this case, you should call `getAnnotationsByType`. That call "looks through" the container and gives you an array of the repeated annotations. If there was just one annotation, you get it in an array of length 1. With this method, you don't have to worry about the container annotation.

The `getAnnotations` method gets all annotations (of any type) with which an item is annotated, with repeated annotations wrapped into containers.

Listing 11.2 shows the implementation of the annotation-aware `toString` method.

When a class is annotated with `ToString`, the method iterates over its fields and prints the ones that are also annotated. If the `includeName` element is `true`, then the class or field name is included in the string.

Note that the method calls itself recursively. Whenever an object belongs to a class that isn't annotated, its regular `toString` method is used and the recursion stops.

Figure 11.2 shows how annotations are handled in this example.




Figure 11.2: Processing annotations at runtime

This is a simple but typical use of the runtime annotation API. Look up classes, fields, and so on, using reflection; call `getAnnotation` or `getAnnotationsByType` on the potentially annotated elements to retrieve the annotations; then, invoke the methods of the annotation interfaces to obtain the element values.

Listing 11.1 runtimeAnnotations/RuntimeAnnotationDemo.java

```
1 package runtimeAnnotations;
2
3 public class RuntimeAnnotationDemo
```

```
{
  public static void main(String[] args)
  {
    var rect = new Rectangle(new Point(5, 10), 20, 30);
    System.out.println(ToStrings.toString(rect));
  }
}
```

Listing 11.2 runtimeAnnotations/ToStrings.java

```
package runtimeAnnotations;

import java.lang.reflect.*;

public class ToStrings
{
  public static String toString(Object obj)
  {
    if (obj == null) return "null";
    Class<?> cl = obj.getClass();
    ToString ts = cl.getAnnotation(ToString.class);
    if (ts == null) return obj.toString();
    var result = new StringBuilder();
    if (ts.includeName()) result.append(cl.getName());
    result.append("[");
    boolean first = true;
    for (Field f : cl.getDeclaredFields())
    {
      ts = f.getAnnotation(ToString.class);
      if (ts != null) {
```

```
21            if (first) first = false; else result.append(",");
22            f.setAccessible(true);
23            if (ts.includeName())
24            {
25              result.append(f.getName());
26              result.append("=");
27            }
28            try
29            {
30              result.append(ToStrings.toString(f.get(obj)));
31            }
32            catch (ReflectiveOperationException ex)
33            {
34              ex.printStackTrace();
35            }
36          }
37        }
38        result.append("]");
39        return result.toString();
40      }
41    }
```

java.lang.reflect.AnnotatedElement **5.0**

- `boolean isAnnotationPresent(Class<? extends Annotation> annotationType)`
  returns `true` if this item has an annotation of the given type.
- `<T extends Annotation> T getAnnotation(Class<T> annotationType)`
  gets the annotation of the given type, or `null` if this item has no such annotation.

- `<T extends Annotation> T[] getAnnotationsByType(Class<T> annotationType)` 8
  gets all annotations of a repeatable annotation type (see **Section 11.3.2**). If none are present, an array of length 0 is returned.
- `Annotation[] getAnnotations()`
  gets all annotations present for this item, including inherited annotations. If none are present, an array of length 0 is returned.
- `Annotation[] getDeclaredAnnotations()`
  gets all annotations declared for this item, excluding inherited annotations. If none are present, an array of length 0 is returned.

11.5. Source-Level Annotation Processing

In the preceding section, you saw how to analyze annotations in a running program. Another use for annotation is the automatic processing of source files to produce more source code, configuration files, scripts, or whatever else one might want to generate.

To show you the mechanics, I will repeat the example of generating `toString` methods. However, this time, let's generate them in Java source. Then the methods will get compiled with the rest of the program, and they will run at full speed instead of using reflection.

11.5.1. Annotation Processors

Annotation processing is integrated into the Java compiler. During compilation, you can *invoke annotation processors* by running

javac -processor $\text{ProcessorClassName}_1$,$\text{ProcessorClassName}_2$,. . . sourceFiles

The compiler locates the annotations of the source files. Each annotation processor is executed in turn and given the annotations in which it expressed an interest. If an annotation processor creates a new source file, the process is repeated. Once a processing round yields no further source files, all source files are compiled.



Note: An annotation processor can only generate new source files. It cannot modify an existing source file.

An annotation processor implements the `Processor` interface, generally by extending the `AbstractProcessor` class. You need to specify which annotations your processor supports. In our case:

```
@SupportedAnnotationTypes("annotations.ToString")
@SupportedSourceVersion(SourceVersion.RELEASE_8)
public class ToStringAnnotationProcessor extends AbstractProcessor
{
  public boolean process(Set<? extends TypeElement> annotations,
      RoundEnvironment currentRound)
  {
    ...
  }
}
```

A processor can claim specific annotation types, wildcards such as `"com.horstmann.*"` (all annotations in the `com.horstmann` package or any subpackage), or even `"*"` (all annotations).

The `process` method is called once for each round, with the set of all annotations that were found in any files during this round, and a `RoundEnvironment` reference that contains information about the current processing round.

11.5.2. The Language Model API

Use the *language model* API for analyzing source-level annotations. Unlike the reflection API, which presents the virtual machine representation of classes and methods, the language model API lets you analyze a Java program according to the rules of the Java language.

The compiler produces a tree whose nodes are instances of classes that implement the `javax.lang.model.element.Element` interface and its subinterfaces, `TypeElement`, `VariableElement`, `ExecutableElement`, and so on. These are the compile-time analogs to the `Class`, `Field`/`Parameter`, `Method`/`Constructor` reflection classes.

I do not want to cover the API in detail, but here are the highlights that you need to know for processing annotations.

- The `RoundEnvironment` gives you a set of all elements annotated with a particular annotation, by calling the one of the methods

  ```
  Set<? extends Element> getElementsAnnotatedWith(Class<? extends Annotation> a)
  Set<? extends Element> getElementsAnnotatedWithAny(
     Set<Class<? extends Annotation>> annotations)
  ```

  The second method is useful for repeated annotations.
- The source-level equivalent of the `AnnotatedElement` interface is `AnnotatedConstruct`. Use the methods

  ```
  A getAnnotation(Class<A> annotationType)
  A[] getAnnotationsByType(Class<A> annotationType)
  ```

  to get the annotation or repeated annotations for a given annotation class.
- A `TypeElement` represents a class or interface. The `getEnclosedElements` method yields a list of its fields and methods.

- Calling `getSimpleName` on an `Element` or `getQualifiedName` on a `TypeElement` yields a `Name` object that can be converted to a string with `toString`.

11.5.3. Using Annotations to Generate Source Code

Let us return to our task of automatically generating `toString` methods. We can't put these methods into the original classes—annotation processors can only produce new classes, not modify existing ones.

Therefore, we'll add all methods into a utility class `ToStrings`:

```
public class ToStrings
{
  public static String toString(Point obj)
  {
    Generated code
  }
  public static String toString(Rectangle obj)
  {
    Generated code
  }
  . . .
  public static String toString(Object obj)
  {
    return Objects.toString(obj);
  }
}
```

Since we don't want to use reflection, we annotate accessor methods, not fields:

```
@ToString
public class Rectangle
{
  . . .
  @ToString(includeName=false) public Point getTopLeft() { return topLeft; }
  @ToString public int getWidth() { return width; }
  @ToString public int getHeight() { return height; }
}
```

The annotation processor should then generate the following source code:

```
public static String toString(Rectangle obj)
{
  var result = new StringBuilder();
  result.append("Rectangle");
  result.append("[");
  result.append(toString(obj.getTopLeft()));
  result.append(",");
  result.append("width=");
  result.append(toString(obj.getWidth()));
  result.append(",");
  result.append("height=");
  result.append(toString(obj.getHeight()));
  result.append("]");
  return result.toString();
}
```

The “boilerplate” code is in gray. Here is an outline of the method that produces the `toString` method for a class with given `TypeElement`:

```
private void writeToStringMethod(PrintWriter out, TypeElement te)
{
  String className = te.getQualifiedName().toString();
  Print method header and declaration of string builder
  ToString ann = te.getAnnotation(ToString.class);
  if (ann.includeName()) Print code to add class name
  for (Element c : te.getEnclosedElements())
  {
    ann = c.getAnnotation(ToString.class);
    if (ann != null)
    {
      if (ann.includeName()) Print code to add field name
      Print code to append toString(obj.methodName())
    }
  }
  Print code to return string
}
```

And here is an outline of the `process` method of the annotation processor. It creates a source file for the helper class and writes the class header and one method for each annotated class.

```
public boolean process(Set<? extends TypeElement> annotations,
      RoundEnvironment currentRound)
{
  if (annotations.size() == 0) return true;
  try
```

```
    {
      JavaFileObject sourceFile = processingEnv.getFiler().createSourceFile(
        "annotations.ToStrings");
      try (var out = new PrintWriter(sourceFile.openWriter()))
      {
        Print code for package and class
        for (Element e : currentRound.getElementsAnnotatedWith(ToString.class))
          if (e instanceof TypeElement te)
            writeToStringMethod(out, te);
        Print code for toString(Object)
      }
    }
    catch (IOException ex)
    {
      processingEnv.getMessager().printMessage(Kind.ERROR, ex.getMessage());
    }
    return true;
  }
```

Note that the `process` method is called in subsequent rounds with an empty list of annotations. It then returns immediately so it doesn't create the source file twice.



Tip: To see the rounds, run the `javac` command with the `-XprintRounds` flag:

```
Round 1:
  input files: {rect.Point, rect.Rectangle, rect.SourceLevelAnnotationDemo}
  annotations: [sourceAnnotations.ToString]
  last round: false
Round 2:
```

```
  input files: {sourceAnnotations.ToStrings}
  annotations: []
  last round: false
Round 3:
  input files: {}
  annotations: []
  last round: true
```

To run the example program, first build the annotation processor, then use it to compile the demo:

```
javac sourceAnnotations/ToStringAnnotationProcessor.java
javac -XprintRounds -processor sourceAnnotations.ToStringAnnotationProcessor rect/*.java
java rect.SourceLevelAnnotationDemo
```

This example demonstrates how tools can harvest source file annotations to produce other files. The generated files don't have to be source files. Annotation processors may choose to generate XML descriptors, property files, shell scripts, HTML documentation, and so on.



Note: Some people have suggested using annotations to remove an even bigger drudgery. Wouldn't it be nice if trivial getters and setters were generated automatically? For example, the annotation

```
@Property private String title;
```

could produce the methods

```
public String getTitle() { return title; }
public void setTitle(String title) { this = title; }
```

However, those methods need to be added to the *same class*. This requires editing a source file, not just generating another file, and is beyond the capabilities of annotation processors. It would be possible to build another tool for this purpose, but such a tool would go beyond the mission of annotations. An annotation is intended as a description *about* a code item, not a directive for adding or changing code.

A popular tool called Project Lombok has found a way around this limitation. By modifying internal compiler data structures during annotation processing, it can produce getter and setter methods. At least for now, it works, but it is not standard Java.

Listing 11.3 rect/SourceLevelAnnotationDemo.java

```
1  package rect;
2
3  import sourceAnnotations.ToStrings;
4
5  public class SourceLevelAnnotationDemo
6  {
7     public static void main(String[] args)
8     {
9        var rect = new Rectangle(new Point(5, 10), 20, 30);
10       System.out.println(ToStrings.toString(rect));
11    }
12 }
```

Listing 11.4 sourceAnnotations/ToStringAnnotationProcessor.java

```
1  package sourceAnnotations;
2
3  import java.beans.*;
4  import java.io.*;
5  import java.util.*;
6
7  import javax.annotation.processing.*;
8  import javax.lang.model.*;
9  import javax.lang.model.element.*;
10 import javax.tools.*;
11 import javax.tools.Diagnostic.Kind;
12
13 @SupportedAnnotationTypes("sourceAnnotations.ToString")
14 @SupportedSourceVersion(SourceVersion.RELEASE_21)
15 public class ToStringAnnotationProcessor extends AbstractProcessor
16 {
17   public boolean process(Set<? extends TypeElement> annotations,
18         RoundEnvironment currentRound)
19   {
20     if (annotations.size() == 0) return true;
21     try
22     {
23       JavaFileObject sourceFile
24         = processingEnv.getFiler().createSourceFile("sourceAnnotations.ToStrings");
25       try (var out = new PrintWriter(sourceFile.openWriter()))
26       {
27         out.println("// Automatically generated by"
28           + " sourceAnnotations.ToStringAnnotationProcessor");
```

```
29          out.println("package sourceAnnotations;");
30          out.println("public class ToStrings {");
31
32          for (Element e : currentRound.getElementsAnnotatedWith(ToString.class))
33            if (e instanceof TypeElement te)
34              writeToStringMethod(out, te);
35           out.println("    public static String toString(Object obj) {");
36           out.println("        return java.util.Objects.toString(obj);");
37           out.println("    }");
38           out.println("}");
39        }
40     }
41     catch (IOException e)
42     {
43        processingEnv.getMessager().printMessage(Kind.ERROR, e.getMessage());
44     }
45     return true;
46  }
47
48  private void writeToStringMethod(PrintWriter out, TypeElement te)
49  {
50     String className = te.getQualifiedName().toString();
51     out.println("    public static String toString(" + className + " obj) {");
52     ToString ann = te.getAnnotation(ToString.class);
53     out.println("        var result = new StringBuilder();");
54     if (ann.includeName())
55        out.println("        result.append(\"" + className + "\");");
56     out.println("        result.append(\"[\");");
57     boolean first = true;
58     for (Element c : te.getEnclosedElements())
59     {
```

```
60        String methodName = c.getSimpleName().toString();
61        ann = c.getAnnotation(ToString.class);
62        if (ann != null)
63        {
64          if (first) first = false; else out.println("       result.append(\",\");");
65          if (ann.includeName())
66          {
67            String fieldName = Introspector.decapitalize(
68              methodName.replaceAll("^(get|is)", ""));
69              // Turn getWidth into width, isDone into done, getURL into URL
70            out.println("       result.append(\"" + fieldName + "=" + "\");");
71          }
72          out.println("       result.append(toString(obj." + methodName + "()));");
73        }
74      }
75      out.println("       result.append(\"]\");");
76      out.println("       return result.toString();");
77      out.println("    }");
78    }
79  }
```

11.6. Bytecode Engineering

You have seen how annotations can be processed at runtime or at the source code level. There is a third possibility: processing at the bytecode level. Unless annotations are removed at the source level, they are present in the class files. The class file format is documented (see **https://docs.oracle.com/javase/specs/jvms/se21/html**). The format is rather complex, and it would be challenging to process class files without special libraries. One such library is the ASM library, available at **https://asm.ow2.org**. Download `asm-9.6.jar` and `asm-commons-9.6.jar` and place them in a directory of your choice, called asm in the instructions.

11.6.1. Modifying Class Files

In this section, we use ASM to add logging messages to annotated methods. If a method is annotated with

```
@LogEntry(logger=loggerName)
```

then we add the bytecodes for the following statement at the beginning of the method:

```
System.getLogger(loggerName).log(System.Logger.Level.TRACE,
  "Entering {0}.{1}", className, methodName);
```

For example, if you annotate the `hashCode` method of the `Item` class as

```
@LogEntry(logger="com.horstmann") public int hashCode()
```

then a message similar to the following is printed whenever the method is called:

```
Dec 03, 2023 5:58:44 PM set.Item hashCode
INFO: Entering set.Item.hashCode
```

To achieve this, we do the following:

1. Load the bytecodes in the class file.
2. Locate all methods.

3. For each method, check whether it has a `LogEntry` annotation.
4. If it does, add the bytecodes for the following instructions at the beginning of the method:

```
ldc loggerName
invokestatic System.getLogger(String)
getstatic System.Logger.Level.INFO
ldc "Entering {0}.{1}"
iconst_2
anewarray
dup
iconst_0
ldc className
aastore
dup
iconst_1
ldc methodName
aastore
invokeinterface System.Logger.log(System.Logger.Level, String, Object[])
```

Inserting these bytecodes sounds tricky, but the ASM library makes it fairly straightforward. I won't describe the process of analyzing and inserting bytecodes in detail. The important point is that the program in **Listing 11.5** edits a class file and inserts a logging call at the beginning of the methods annotated with the `LogEntry` annotation.

For example, here is how you add the logging instructions to `Item.java` in **Listing 11.6**, where `asm` is the directory into which you installed the ASM library:

```
javac set/Item.java
javac -classpath .:asm/\* bytecodeAnnotations/EntryLogger.java
java -classpath .:asm/\* bytecodeAnnotations.EntryLogger set/Item.class
```

As always, with Windows, you use `\` instead of `/` as file separator and `;` instead of `:` as path separator, and you do not escape the `*`.

Try running

```
javap -c set.Item
```

before and after modifying the `Item` class file. You can see the inserted instructions at the beginning of the `hashCode`, `equals`, and `compareTo` methods.

```
public int hashCode();
  Code:
     0: ldc #42 // String com.horstmann
     2: invokestatic #48
        // Method java/lang/System.getLogger:(Ljava/lang/String;)Ljava/lang/System$Logger;
     5: getstatic #54
        // Field java/lang/System$Logger$Level.INFO:Ljava/lang/System$Logger$Level;
     8: ldc #56 // String Entering {0}.{1}
    10: iconst_2
    11: anewarray #4 // class java/lang/Object
    14: dup
    15: iconst_0
    16: ldc #58 // String set.Item
```

```
18: aastore
19: dup
20: iconst_1
21: ldc  #77 // String hashCode
23: aastore
24: invokeinterface #65,  4  // InterfaceMethod java/lang/System$Logger.log:
   // (Ljava/lang/System$Logger$Level;Ljava/lang/String;[Ljava/lang/Object;)V
. . .
```

The index values into the constant pool may be different when you try this.

The `SetTest` program in **Listing 11.7** inserts `Item` objects into a hash set. When you run it with the modified class file, you will see the logging messages.

```
Dec 03, 2023 5:58:44 PM set.Item hashCode
INFO: Entering set.Item.hashCode
Dec 03, 2023 5:58:44 PM set.Item hashCode
INFO: Entering set.Item.hashCode
Dec 03, 2023 5:58:44 PM set.Item hashCode
INFO: Entering set.Item.hashCode
Dec 03, 2023 5:58:44 PM set.Item equals
INFO: Entering set.Item.equals
[[description=Microwave, partNumber=4104], [description=Toaster, partNumber=1279]]
```

Note the call to `equals` when we insert the same item twice.

This example shows the power of bytecode engineering. Annotations are used to add directives to a program, and a bytecode editing tool picks up the directives and modifies the virtual machine instructions.

Listing 11.5 bytecodeAnnotations/EntryLogger.java

```
1  package bytecodeAnnotations;
2
3  import java.io.*;
4  import java.nio.file.*;
5
6  import org.objectweb.asm.*;
7  import org.objectweb.asm.commons.*;
8
9  /**
10  * Adds "entering" logs to all methods of a class that have the LogEntry annotation.
11  * @version 1.22 2023-12-01
12  * @author Cay Horstmann
13  */
14 public class EntryLogger extends ClassVisitor
15 {
16   private String className;
17
18   /**
19    * Constructs an EntryLogger that inserts logging into annotated methods of a given class.
20    */
21   public EntryLogger(ClassWriter writer, String className)
22   {
23     super(Opcodes.ASM8, writer);
24     this.className = className;
25   }
26
27   public MethodVisitor visitMethod(int access, String methodName, String desc,
28         String signature, String[] exceptions)
```

```
29  {
30    MethodVisitor mv = cv.visitMethod(access, methodName, desc, signature, exceptions);
31    return new AdviceAdapter(Opcodes.ASM8, mv, access, methodName, desc)
32    {
33      private String loggerName;
34
35      public AnnotationVisitor visitAnnotation(String desc, boolean visible)
36      {
37        return new AnnotationVisitor(Opcodes.ASM8)
38          {
39            public void visit(String name, Object value)
40            {
41              if (desc.equals("LbytecodeAnnotations/LogEntry;")
42                  && name.equals("logger"))
43                loggerName = value.toString();
44            }
45          };
46      }
47
48      public void onMethodEnter()
49      {
50        if (loggerName != null)
51        {
52          /*
53          visitLdcInsn(loggerName);
54          visitMethodInsn(INVOKESTATIC, "java/util/logging/Logger", "getLogger",
55            "(Ljava/lang/String;)Ljava/util/logging/Logger;", false);
56          visitLdcInsn(className);
57          visitLdcInsn(methodName);
58          visitMethodInsn(INVOKEVIRTUAL, "java/util/logging/Logger", "entering",
59            "(Ljava/lang/String;Ljava/lang/String;)V", false);
```

```
            */
            visitLdcInsn(loggerName);
            visitMethodInsn(INVOKESTATIC, "java/lang/System", "getLogger",
              "(Ljava/lang/String;)Ljava/lang/System$Logger;", false);
            visitFieldInsn(Opcodes.GETSTATIC, "java/lang/System$Logger$Level", "INFO",
              "Ljava/lang/System$Logger$Level;");
            visitLdcInsn("Entering {0}.{1}");

            // Create an array of Objects with a length of 2
            mv.visitInsn(Opcodes.ICONST_2);  // array length
            mv.visitTypeInsn(Opcodes.ANEWARRAY, "java/lang/Object");  // array type

            // Add two objects to the array
            mv.visitInsn(Opcodes.DUP);  // duplicate array reference
            mv.visitInsn(Opcodes.ICONST_0);  // index 0
            visitLdcInsn(className);
            mv.visitInsn(Opcodes.AASTORE);  // store in array

            mv.visitInsn(Opcodes.DUP);  // duplicate array reference
            mv.visitInsn(Opcodes.ICONST_1);  // index 1
            visitLdcInsn(methodName);
            mv.visitInsn(Opcodes.AASTORE);  // store in array

            visitMethodInsn(INVOKEINTERFACE, "java/lang/System$Logger", "log",
              "(Ljava/lang/System$Logger$Level;Ljava/lang/String;[Ljava/lang/Object;)V",
              true);
            loggerName = null;
          }
        }
      };
    }
```

```
91
92    /**
93     * Adds entry logging code to the given class.
94     * @param args the name of the class file to patch
95     */
96    public static void main(String[] args) throws IOException
97    {
98       if (args.length == 0)
99       {
100         System.out.println("USAGE: java bytecodeAnnotations.EntryLogger classfile");
101         System.exit(1);
102      }
103      Path path = Path.of(args[0]);
104      var reader = new ClassReader(Files.newInputStream(path));
105      var writer = new ClassWriter(
106         ClassWriter.COMPUTE_MAXS | ClassWriter.COMPUTE_FRAMES);
107      var entryLogger = new EntryLogger(writer,
108         path.toString().replace(".class", "").replaceAll("[/\\\\]", "."));
109      reader.accept(entryLogger, ClassReader.EXPAND_FRAMES);
110      Files.write(Path.of(args[0]), writer.toByteArray());
111   }
112}
```

Listing 11.6 set/Item.java

```
1  package set;
2
3  import java.util.*;
4  import bytecodeAnnotations.*;
5
```

```
/**
 * An item with a description and a part number.
 * @version 1.01 2012-01-26
 * @author Cay Horstmann
 */
public class Item
{
   private String description;
   private int partNumber;

   /**
    * Constructs an item.
    * @param aDescription the item's description
    * @param aPartNumber the item's part number
    */
   public Item(String aDescription, int aPartNumber)
   {
      description = aDescription;
      partNumber = aPartNumber;
   }

   /**
    * Gets the description of this item.
    * @return the description
    */
   public String getDescription()
   {
      return description;
   }

   public String toString()
```

```
37    {
38       return "[description=" + description + ", partNumber=" + partNumber + "]";
39    }
40
41    @LogEntry(logger = "com.horstmann")
42    public boolean equals(Object otherObject)
43    {
44       if (this == otherObject) return true;
45       if (otherObject == null) return false;
46       if (getClass() != otherObject.getClass()) return false;
47       var other = (Item) otherObject;
48       return Objects.equals(description, other.description) && partNumber == other.partNumber;
49    }
50
51    @LogEntry(logger = "com.horstmann")
52    public int hashCode()
53    {
54       return Objects.hash(description, partNumber);
55    }
56 }
```

Listing 11.7 set/SetTest.java

```
1  package set;
2
3  import java.util.*;
4  import java.util.logging.*;
5
6  /**
7   * @version 1.03 2018-05-01
```

```
 * @author Cay Horstmann
 */
public class SetTest
{
  public static void main(String[] args)
  {
    Logger.getLogger("com.horstmann").setLevel(Level.FINEST);
    var handler = new ConsoleHandler();
    handler.setLevel(Level.FINEST);
    Logger.getLogger("com.horstmann").addHandler(handler);

    var parts = new HashSet<Item>();
    parts.add(new Item("Toaster", 1279));
    parts.add(new Item("Microwave", 4104));
    parts.add(new Item("Toaster", 1279));
    System.out.println(parts);
  }
}
```

11.6.2. Modifying Bytecodes at Load Time

In the last section, you saw a tool that edits class files. However, it can be cumbersome to add yet another tool into the build process. An attractive alternative is to defer the bytecode engineering until *load time*, when the class loader loads the class.

The *instrumentation API* has a hook for installing a bytecode transformer. The transformer must be installed before the `main` method of the program is called. You can meet this requirement by defining an *agent*, a library that is loaded to monitor a program in some way. The agent code can carry out initializations in a `premain` method.

Here are the steps required to build an agent:

1. Implement a class with a method

```
public static void premain(String arg, Instrumentation instr)
```

   This method is called when the agent is loaded. The agent can get a single command-line argument, which is passed in the `arg` parameter. The `instr` parameter can be used to install various hooks.
2. Make a manifest file `EntryLoggingAgent.mf` that sets the `Premain-Class` attribute, for example:

```
Premain-Class: bytecodeAnnotations.EntryLoggingAgent
```

3. Package the agent code and the manifest into a JAR file:

```
javac -classpath .:asm/\* bytecodeAnnotations/EntryLoggingAgent.java
jar cvfm EntryLoggingAgent.jar bytecodeAnnotations/EntryLoggingAgent.mf \
  bytecodeAnnotations/Entry*.class
```

To launch a Java program together with the agent, use the following command-line options:

```
java -javaagent:AgentJARFile=agentArgument . . .
```

For example, to run the `SetTest` program with the entry logging agent, call

```
javac set/*.java
java -javaagent:EntryLoggingAgent.jar=set.Item -classpath .:asm/\* set.SetTest
```

The `Item` argument is the name of the class that the agent should modify.

Listing 11.8 shows the agent code. The agent installs a class file transformer. The transformer first checks whether the class name matches the agent argument. If so, it uses the `EntryLogger` class from the preceding section to modify the bytecodes. However, the modified bytecodes are not saved to a file. Instead, the transformer returns them for loading into the virtual machine (see **Figure 11.3**). In other words, this technique carries out "just in time" modification of the bytecodes.




Figure 11.3: Modifying classes at load time

Listing 11.8 bytecodeAnnotations/EntryLoggingAgent.java

```
1  package bytecodeAnnotations;
2
3  import java.lang.instrument.*;
4  import java.security.*;
5  import org.objectweb.asm.*;
6
7  /**
8   * @version 1.11 2018-05-01
9   * @author Cay Horstmann
10  */
11 public class EntryLoggingAgent
12 {
13   public static void premain(final String arg, Instrumentation instr)
14   {
15     instr.addTransformer(new ClassFileTransformer() {
16       public byte[] transform(ClassLoader loader, String className, Class<?> cl,
17         ProtectionDomain pd, byte[] data) throws IllegalClassFormatException
18       {
19         if (!className.replace("/", ".").equals(arg)) return null;
20         var reader = new ClassReader(data);
21         var writer = new ClassWriter(
22           ClassWriter.COMPUTE_MAXS | ClassWriter.COMPUTE_FRAMES);
23         var el = new EntryLogger(writer, className);
24         reader.accept(el, ClassReader.EXPAND_FRAMES);
25         return writer.toByteArray();
26       }});
27   }
28 }
```

In this chapter, you have learned how to

- Add annotations to Java programs
- Design your own annotation interfaces
- Implement tools that make use of the annotations

You have seen three technologies for processing code: scripting, compiling Java programs, and processing annotations. The first two were quite straightforward. On the other hand, building annotation tools is undeniably complex and not something that most developers will need to tackle. This chapter gave you the background for understanding the inner workings of the annotation tools you will encounter, and perhaps piqued your interest in developing your own tools.

The following chapter discusses the Java Platform Module System, a key feature for insuring the integrity of the Java platform.

Previous chapter
< 10. Concurrency

Next chapter
12. The Java Platform Module System >