Appendix

This appendix lists all keywords and keyword-like words of the Java language. A "restricted keyword" is a keyword only in a module declaration, and otherwise an identifier. A "restricted identifier" is an identifier unless it is used in certain positions. For example, `var` is always an identifier unless it is used where a type is expected. The symbols `null`, `false`, and `true` are not keywords but literals.

Table : Java Keywords

Keyword	Meaning	Type	See Chapter
`abstract`	An abstract class or method	Keyword	5
assert	Used to locate internal program error	Keyword	7
`boolean`	The Boolean type	Keyword	3
break	Breaks out of a switch or loop	Keyword	3
`byte`	The 8-bit integer type	Keyword	3
case	A case of a switch	Keyword	3
`catch`	The clause of a `try` block catching an exception	Keyword	7
char	The type for UTF-16 code units	Keyword	3
`class`	Defines a class type	Keyword	4
const	Not used	Keyword	
`continue`	Continues at the end of a loop	Keyword	3

Keyword	Meaning	Type	See Chapter
default	The default clause of a `switch`, or a default method in an interface	Keyword	3, 6
`do`	The top of a `do`/`while` loop	Keyword	3
double	The double-precision floating-number type	Keyword	3
`else`	The `else` clause of an `if` statement	Keyword	3
enum	An enumerated type	Keyword	3
`exports`	Exports a package of a module	Restricted keyword	12
extends	Defines the parent class of a class, or an upper bound of a wildcard	Keyword	4
`false`	One of the two Boolean values	Literal	3
final	A constant, or a class or method that cannot be overridden	Keyword	5
`finally`	The part of a `try` block that is always executed	Keyword	7
float	The single-precision floating-point type	Keyword	3
`for`	A loop type	Keyword	3
goto	Not used	Keyword	
`if`	A conditional statement	Keyword	3

Keyword	Meaning	Type	See Chapter
implements	Defines the interface(s) that a class implements	Keyword	6
`import`	Imports a package	Keyword	4
instanceof	Tests if an object is an instance of a class	Keyword	5
`int`	The 32-bit integer type	Keyword	3
interface	An abstract type with methods that a class can implement	Keyword	6
`long`	The 64-bit long integer type	Keyword	3
native	A method implemented by the host system	Keyword	13 (Vol. II)
`new`	Allocates a new object or array	Keyword	3
non-sealed	A subtype of a sealed type of which arbitrary subtypes may be formed	Keyword	5
`null`	A null reference	Literal	3
module	Declares a module	Restricted keyword	12
`open`	Modifies a `module` declaration	Restricted keyword	12
opens	Opens a package of a module	Restricted keyword	12

Keyword	Meaning	Type	See Chapter
package	A package of classes	Keyword	4
permits	Introduces a list of permitted sub-types of a sealed type	Restricted identifier	3
private	A feature that is accessible only by methods of this class	Keyword	4
protected	A feature that is accessible only by methods of this class, its children, and other classes in the same package	Keyword	5
provides	Indicates that a module uses a service	Restricted keyword	12
public	A feature that is accessible by meth-ods of all classes	Keyword	4
record	Declares a class with a given set of final instance variables	Restricted identifier	4
return	Returns from a method	Keyword	3
sealed	A type with a controlled set of direct subtypes	Restricted identifier	5
short	The 16-bit integer type	Keyword	3
static	A feature that is unique to a class or interface, not to instances of a class	Keyword	3, 6
strictfp	Use strict rules for floating-point computations (obsolete)	Keyword	2

Keyword	Meaning	Type	See Chapter
`super`	The superclass object or constructor, or a lower bound in a wildcard	Keyword	5
switch	A selection statement or expression	Keyword	3
`synchro-nized`	A method or code block that is atomic to a thread	Keyword	12
this	The implicit argument of a method, or a constructor of this class	Keyword	4
`throw`	Throws an exception	Keyword	7
throws	The exceptions that a method can throw	Keyword	7
`to`	A part of an `exports` or `opens` declaration	Restricted keyword	12
transient	Marks data that should not be persistent	Keyword	2 (Vol. II)
`transitive`	Modifies a `requires` declaration	Restricted keyword	12
true	One of the two Boolean values	Literal	3
`try`	A block of code that traps exceptions	Keyword	7
uses	Indicates that a module uses a service	Restricted keyword	12
`var`	Declares a variable whose type is inferred	Restricted identifier	3

Keyword	Meaning	Type	See Chapter
void	Denotes a method that returns no value	Keyword	3
`volatile`	Ensures that a field is coherently accessed by multiple threads	Keyword	12
when	Introduces a guard of a pattern	Restricted keyword	5
`while`	A loop	Keyword	3
with	Defines the service class in a `provides` statement	Restricted keyword	12
`yield`	Yields the value of a `switch` expression	Restricted identifier	3
_ (underscore)	An unnamed variable or pattern (preview)	Keyword	5

Previous chapter
‹ 12. The Java Platform Module System

Next chapter
Index ›