Index

A

- A records (DNS), What Is Service Discovery?, Services Without Selectors
- abstracting your infrastructure, Abstracting Your Infrastructure
- access control (see RBAC (role-based access control))
- admission controllers, Points of Extensibility, Admission Flow
  - built into Kubernetes API server, Points of Extensibility
  - validating admission controller, Points of Extensibility-Points of Extensibility
- admission flow, Admission Flow
- AdmissionReview type, Points of Extensibility
- aggregation rule, Aggregating ClusterRoles
- annotations, Labels and Annotations, Annotations-Summary
  - change-cause, Updating a Container Image, Rollout History
  - domain names in, Labels
  - on Ingress object, Advanced Ingress Topics and Gotchas
  - kubectl annotate command, Labeling and Annotating Objects
  - using object annotations to create internal load balancer, Load Balancer Integration
- anycast networking, Starting at the Top with a Load-Balancing Approach
- API group, Accessing the Kubernetes API
- APIs
  - benefits of move to application-oriented container APIs, Abstracting Your Infrastructure
  - decoupling of operations teams via, Separation of Concerns for Consistency and Scaling
  - for each component in decoupled architectures, Decoupling
  - extensions to Kubernetes API, Points of Extensibility
  - Kubernetes API server request flow, Points of Extensibility, Admission Flow
- application container images, Creating and Running Containers
  - building with Docker, Building Application Images with Docker-Image Security
    - image security, Image Security
    - optimizing image sizes, Optimizing Image Sizes

    - using Dockerfiles, Dockerfiles
- application containers, Container Images
- applications
    - building for multiple clusters, Building Applications for Multiple Clusters-Better Flexibility: Microservice Routing
        - better flexibility with microservice routing, Better Flexibility: Microservice Routing
        - replicated silos, simplest cross-regional model, Replicated Silos: The Simplest Cross-Regional Model
        - sharding, Sharding: Regional Data
    - organizing Kubernetes applications, Organizing Your Application-Summary
        - deploying your application around the world, Deploying Your Application Around the World-Dashboards and Monitoring for Worldwide Deployments
        - feature gates, Feature Gates
        - filesystems as source of truth, Filesystems as the Source of Truth
        - guiding principles, Principles to Guide Us
        - managing application in source control, Managing Your Application in Source Control-Versioning with directories
        - parameterizing application with templates, Parameterizing Your Application with Templates
        - role of code review, The Role of Code Review
        - structuring for development, testing, and deployment, Structuring Your Application for Development, Testing, and Deployment
    - running in the same or different Pods, Pods in Kubernetes
- Audit mode (Pod Security Standard), What Is Pod Security?
- auditing, Audit
- authentication, Role-Based Access Control for Kubernetes
    - authenticating to Kubernetes API, Authenticating to the Kubernetes API
    - for cloud providers, Authenticating to the Kubernetes API
    - with container registries, Storing Images in a Remote Registry
    - generic interface for providers, Identity in Kubernetes
    - groups supplied by authentication providers in Kubernetes, Using Groups for Bindings
    - providers supported by Kubernetes, Identity in Kubernetes
    - using mTLS, Encryption and Authentication with Mutal TLS
- authorization, Role-Based Access Control for Kubernetes
    - testing auth can-i command, Testing Authorization with can-i
- automatic scaling of resources, Easy Scaling for Applications and Clusters
- automation, Before You Even Begin

- autoscaling
  - metrics-server required for, Autoscaling a ReplicaSet
  - ReplicaSets, Autoscaling a ReplicaSet
- availability, Introduction
  - benefits of containers and Kubernetes for, Velocity
- Azure Active Directory, Identity in Kubernetes
- Azure Kubernetes Service
  - creating internal load balancer in a cluster, Load Balancer Integration
  - installing Kubernetes with, Installing Kubernetes with Azure Kubernetes Service
- Azure storage class automatically provisioning disk objects, Dynamic Volume Provisioning

B

- base64 encoding of data values in Secrets, Naming Constraints, Re-create and update
- bash-completion package, Command Autocompletion
- branches, versioning with, Versioning with branches and tags
- build image, Multistage Image Builds
- build infrastructure, Before You Even Begin

C

- can-i command, testing authorization, Testing Authorization with can-i
- canary label, Label Selectors
- certificate signing request (CSR), Points of Extensibility
- certificates
  - client certificates in mTLS, Encryption and Authentication with Mutal TLS
  - generating certificate to serve webhook, Points of Extensibility-Points of Extensibility
  - TLS
    - creating secret to store, Serving TLS
    - key and certificate for kuard application, Creating Secrets
- cgroups, Pods in Kubernetes
- change-cause annotation, Updating a Container Image, Rollout History
- clients, The Kubernetes API: A Client's Perspective-But What About kubectl x?
  - installing client libraries to program Kubernetes API, Installing the Client Libraries
  - kubectl, The Kubernetes Client, But What About kubectl x?

    - (see also kubectl tool)
  - obtaining authentication information, Authenticating to the Kubernetes API
  - OpenAPI and generated client libraries, OpenAPI and Generated Client Libraries
- cloud
  - authentication for cloud providers, Authenticating to the Kubernetes API
  - authentication providers, Identity in Kubernetes
  - cloud native ecosystem, navigating with Kubernetes, Cloud Native Ecosystem
  - cloud-based RBAC, Before You Even Begin
  - container registries, Storing Images in a Remote Registry
  - creating a Kubernetes cluster, Deploying a Kubernetes Cluster
  - creating cloud-based load balancer, Load Balancer Integration
  - DNS name for cloud databases and services, Services Without Selectors
  - Ingress implementations by cloud providers, Alternate Ingress Implementations
  - installing Kubernetes on public cloud provider, Installing Kubernetes on a Public Cloud Provider-Installing Kubernetes Locally Using minikube
  - integration into identity and access management systems by providers, Using Groups for Bindings
  - persistent volume drivers for providers, Running a MySQL Singleton
  - provider-specific annotations, Labels
  - service meshes from providers, Do You Really Need a Service Mesh?
  - storage for replicated data store, Building Applications for Multiple Clusters
  - using DaemonSets to install software on nodes in a cloud-based cluster, DaemonSets
- Cloud Native Computing Foundation (CNCF), Cloud Native Ecosystem
- cloud native development
  - cloud native HTTP-routing API, Service Meshes
  - service meshes, Service Meshes
  - storage solutions, Integrating Storage Solutions and Kubernetes
- cluster IPs, The Service Object
  - creating headless service using, Manually Replicated MongoDB with StatefulSets
  - environment variables, Cluster IP Environment Variables
  - kube-proxy and, kube-proxy and Cluster IPs
- cluster-admin permissions, Installing Contour
- cluster-level resources, Accessing the Kubernetes API
- ClusterRoleBindings, Roles and Role Bindings in Kubernetes, Using built-in roles, Accessing the Kubernetes API
- ClusterRoles, Roles and Role Bindings in Kubernetes
  - aggregating, Aggregating ClusterRoles
  - auto-reconciliation of built-in roles, Auto-reconciliation of built-in roles

    - binding a group to, Using Groups for Bindings
- clusterRoleSelector field, Aggregating ClusterRoles
- clusters
    - autoscaling, Autoscaling a ReplicaSet
    - building your own Kubernetes cluster, Building Your Own Kubernetes Cluster-Summary
        - first boot, First Boot
        - flashing images, Flashing Images
        - installing container runtime, Installing a Container Runtime
        - installing Kubernetes, Installing Kubernetes
        - parts list, Parts List
        - setting up cluster networking, Setting Up Cluster Networking
        - setting up networking, Setting Up Networking
        - setting up the cluster, Setting Up the Cluster
    - built-in cluster roles, Using built-in roles
    - components, Cluster Components-Kubernetes UI
        - Kubernetes DNS server, Kubernetes DNS
        - Kubernetes proxy, Kubernetes Proxy
        - Kubernetes UI, Kubernetes UI
    - deploying, Deploying a Kubernetes Cluster-Summary
        - installing Kubernetes locally using minikube, Installing Kubernetes Locally Using minikube
        - installing Kubernetes on public cloud provider, Installing Kubernetes on a Public Cloud Provider-Installing Kubernetes Locally Using minikube
        - running Kubernetes in Docker, Running Kubernetes in Docker
    - deploying application into multiple clusters (see deployments)
    - easy scaling for, Easy Scaling for Applications and Clusters
    - exploring with kubectl, The Kubernetes Client-Listing Kubernetes Nodes
        - checking cluster status, Checking Cluster Status
        - listing Kubernetes nodes, Listing Kubernetes Nodes
    - isolating users within single cluster, Multicluster Application Deployments
    - kubectl cluster management commands, Cluster Management
    - listing all Pods running in, Listing Pods
    - MongoDB cluster creation, automating, Automating MongoDB Cluster Creation-Automating MongoDB Cluster Creation
    - policy and governance for, Policy and Governance for Kubernetes Clusters-Summary
    - replicating your application across multiple clusters, Replicated Silos: The Simplest Cross-Regional Model
    - storage classes, Dynamic Volume Provisioning

    - viewing, alternatives to kubectl, Alternative Ways of Viewing Your Cluster
- CNAME records (DNS), Services Without Selectors
- CNI (Container Network Interface), Points of Extensibility
- code review, The Role of Code Review
- command-line arguments, using ConfigMap, Using a ConfigMap, Using a ConfigMap
- communication/synchronization, using volumes, Different Ways of Using Volumes with Pods
- compiler (or abstraction) pattern, Compilers
- completions parameter (jobs), Job Patterns, Creating the consumer job
- ConfigMaps, ConfigMaps and Secrets-Secrets
    - ConfigMap for MongoDB, Automating MongoDB Cluster Creation
    - creating, Creating ConfigMaps
    - managing, Managing ConfigMaps and Secrets-Summary
        - creating ConfigMaps, Creating
        - editing current version, Edit current version
        - listing all ConfigMaps in namespace, Listing
        - live updates, Live updates
        - recreating and updating, Re-create and update
        - updating from a file, Updating
    - naming constraints, Naming Constraints
    - using, Using a ConfigMap-Secrets
- configurations
    - advanced probe configuration, Advanced Probe Configuration
    - application, code review for, The Role of Code Review
    - container configuration file, Container Images
    - declarative versus imperative, Declarative Configuration
    - declarative YAML configurations, Accessing Kubernetes from Common Programming Languages
    - fail open configuration, Installing Gatekeeper
    - misconfiguring Ingress, The Future of Ingress
    - parameterizing with templates and Helm, Parameterizing with Helm and Templates
    - using can-i command to validate settings, Testing Authorization with can-i
- consistency, Building Applications for Multiple Clusters
- constraint templates, Configuring Policies
    - understanding, Understanding Constraint Templates
    - unique ingress host, Data Replication
- constraints
    - auditing list of non-compliant resources for, Audit
    - creating, Creating Constraints

  - enforcementAction of dryrun, Audit
  - updating, Audit
- consumer job, creating, Creating the consumer job
- container images, Container Images-Container Images
  - creating without bundling sensitive data, Secrets
  - deleting, Cleanup
  - Docker format, Container Images
  - immutable, The Value of Immutability
  - multistage builds, Multistage Image Builds
  - security, Image Security
  - storing in remote registry, Storing Images in a Remote Registry
- Container Runtime Interface (see CRI)
- Container Storage Interface (CSI), Points of Extensibility
- containerd, Installing a Container Runtime
- containers
  - and container APIs, benefits, Introduction
  - decoupling application container image from machines, Scaling Development Teams with Microservices
  - grouping into a Pod, Pods
  - initialization containers, Automating MongoDB Cluster Creation
  - installing container runtime, Installing a Container Runtime
  - ReplicaSets adopting existing containers, Adopting Existing Containers
  - resource requests per container, Resource Requests: Minimum Required Resources
  - running commands in using kubectl exec, Running Commands in Your Container with exec
  - running in a Pod, information about, Pod Details
  - running with Docker, Running Containers with Docker
  - runtime selection, RuntimeClass
  - SecurityContext, Understanding SecurityContext
  - system and application, Container Images
  - updating a container image, Updating a Container Image
- contexts, managing with kubectl, Contexts
- Contour Ingress controller, installing, Installing Contour-Configuring a Local hosts File
  - configuring DNS, Configuring DNS
  - configuring local hosts file, Configuring a Local hosts File
- control-plane nodes, Listing Kubernetes Nodes
- controller-manager, Checking Cluster Status
- controllers

  - Deployment, Deployments
  - Ingress, running multiple, Running Multiple Ingress Controllers
- costs
  - forecasting future compute costs, Easy Scaling for Applications and Clusters
  - reduction through Kubernetes' efficiency, Efficiency
- CPUs
  - autoscaling based on CPU usage, Autoscaling a ReplicaSet
  - limiting utilization by applications, Limiting CPU resources
  - limits on usage of, Capping Resource Usage with Limits
  - requested by each Pod from the node, Listing Kubernetes Nodes
  - requests for, Resource Requests: Minimum Required Resources
- CrashLoopBackOff, One Shot
- creating resources, Creating and Patching Objects
- credentials, ConfigMaps and Secrets
  - (see also ConfigMaps; secrets)
  - storing for private container registries using Secrets, Private Container Registries
- CRI (Container Runtime Interface), The Container Runtime Interface-Cleanup, Points of Extensibility, RuntimeClass
  - exploring kuard example application, Exploring the kuard Application
  - limiting CPU usage, Limiting CPU resources
  - limiting memory resource usage, Limiting memory resources
  - limiting resource usage, Limiting Resource Usage
  - running containers with Docker, Running Containers with Docker
- CronJobs, CronJobs
- CRUD (Create/Read/Update/Delete) API, Points of Extensibility
- CSI (Container Storage Interface), Points of Extensibility
- custom resource definitions (CRDs), Points of Extensibility
  - service mesh implementations using, Introspecting a Service Mesh Implementation
  - use by Gatekeeper, Policy and Governance with Gatekeeper
- custom resources, Points of Extensibility-Operators
  - patterns for, Patterns for Custom Resources-Operators
    - compilers, Compilers
    - just data, Just Data
    - operators, Operators
  - validation and defaulting, Points of Extensibility
- CustomResourceDefinition, Accessing the Kubernetes API
  - defining, Points of Extensibility
  - interaction between controller and API server, Points of Extensibility

D

- DaemonSets, Kubernetes Proxy, DaemonSets-Summary
  - creating, Creating DaemonSets-Creating DaemonSets
  - deleting, Deleting a DaemonSet
  - demonstrating value of decoupled architecture in Kubernetes, DaemonSet Scheduler
  - limiting to particular nodes, Limiting DaemonSets to Specific Nodes
    - adding labels to nodes, Adding Labels to Nodes
    - node selectors, Node Selectors
  - scheduler, DaemonSet Scheduler
  - updating, Updating a DaemonSet
- dash-suffix, removing a label with, Modifying Labels
- dashboards for worldwide application deployment, Dashboards and Monitoring for Worldwide Deployments
- data consistency, Building Applications for Multiple Clusters
- data elements of a Secret, Creating Secrets
- data replication, Data Replication
- data values, specifying for ConfigMaps or Secrets, Naming Constraints
- databases
  - importing external database service into Kubernetes, Services Without Selectors
  - MySQL ReplicaSet, Running a MySQL Singleton
  - running MySQL singleton, Running a MySQL Singleton
- debugging
  - introspection capabilities in service meshes, Introspection
  - kubectl commands for, Debugging Commands
  - of Pods that are misbehaving, Quarantining Containers
  - of running containers using logs, Getting More Information with Logs
- declarative configuration, The Pod Manifest
  - versus imperative configuration, Declarative Configuration
- declarative configuration objects, Declarative Configuration
- decoupled architectures, Scaling Your Service and Your Teams
  - DaemonSets and ReplicaSets in Kubernetes, DaemonSet Scheduler
  - decoupling of components in, Decoupling
  - decoupling of Pods and ReplicaSets, Relating Pods and ReplicaSets
  - microservice, abstractions and APIs provided by Kubernetes for, Scaling Development Teams with Microservices
  - no direct link between HPA and ReplicaSet, Autoscaling a ReplicaSet
  - separation of concerns, Separation of Concerns for Consistency and Scaling
- defaulting, Points of Extensibility, Points of Extensibility

- deployment image, Multistage Image Builds
- Deployment object, Deployments
  - (see also deployments)
  - deleting, Your First Deployment
- deployments, Deployments-Summary
  - creating, Your First Deployment, Creating Deployments
  - creating deployments and services, The Service Object
  - creating for alpaca and bandicoot, using interesting labels, Applying Labels
  - deleting, Deleting a Deployment
  - deploying your application around the world, Deploying Your Application Around the World-Dashboards and Monitoring for Worldwide Deployments
    - dashboards and monitoring, Dashboards and Monitoring for Worldwide Deployments
    - implementing worldwide deployment, Implementing Worldwide Deployment
  - exploring workings of, Your First Deployment
  - managing, Managing Deployments
  - monitoring, Monitoring a Deployment
  - multicluster application deployments, Multicluster Application Deployments-Summary
    - building applications for multiple clusters, Building Applications for Multiple Clusters-Better Flexibility: Microservice Routing
    - foundations for, Before You Even Begin
    - load balancing approach, Starting at the Top with a Load-Balancing Approach
  - patching a Deployment, Creating and Patching Objects
  - ReplicaSets powering Deployment objects, Designing with ReplicaSets
  - strategies for, Deployment Strategies-Deleting a Deployment
    - Recreate, Recreate Strategy
    - RollingUpdate, RollingUpdate Strategy-Configuring a rolling update
    - slowing rollouts to ensure service health, Slowing Rollouts to Ensure Service Health
  - updating, Updating Deployments-Deployment Strategies
    - scaling a deployment, Scaling a Deployment
    - updating a container image, Updating a Container Image
- desired state versus observed or current state, Reconciliation Loops
- development tag, introducing, Introducing a development tag
- development teams, scaling with microservices, Scaling Development Teams with Microservices
- development, velocity in, Velocity

- directories, versioning with, Versioning with directories
- distributed systems, reliable and scalable, Introduction
- DNS
  - address for cluster IP, Service DNS
  - configuring entries to external address for load balancer, Configuring DNS
  - headless service to manage DNS entries for StatefulSet, Manually Replicated MongoDB with StatefulSets
  - Kubernetes DNS server, Kubernetes DNS
  - Kubernetes DNS service, CNAME record for external service, Services Without Selectors
  - Kubernetes service discovery via, Connecting to Resources Outside of a Cluster
  - load balancers based on, Load Balancer Integration
  - lookup in multicluster load balancing strategy, Starting at the Top with a Load-Balancing Approach
  - names for external services, Services Without Selectors
  - service discovery on the internet, What Is Service Discovery?
  - subdomains, in label prefix, Labels
- Docker, Creating and Running Containers
  - building application container images with, Building Application Images with Docker-Image Security
  - Container Runtime Interface implementation, containerd-cri, The Container Runtime Interface
  - installing Docker package repository, Installing a Container Runtime
  - multistage image builds, Multistage Image Builds
  - packaging an executable and pushing it to remote registry, Creating and Running Containers
  - running containers with, Running Containers with Docker
  - running Kubernetes in, Running Kubernetes in Docker
  - storing images in remote registry, Storing Images in a Remote Registry
- Docker Desktop, Installing Kubernetes Locally Using minikube
- Docker Hub, Storing Images in a Remote Registry
- docker login command, Storing Images in a Remote Registry
- docker push command, Storing Images in a Remote Registry
- docker rmi command, Cleanup
- docker run -d --name --publish command, Creating a Pod Manifest
- docker run command, Running Containers with Docker, Limiting memory resources, Limiting CPU resources
- docker system prune command, Cleanup
- Dockerfiles
  - automating container image creation with, Dockerfiles

    - kuard application example, Multistage Image Builds
    - multistage build for kuard example application, Multistage Image Builds
- .dockerignore file, Dockerfiles
- domain names, What Is Service Discovery?
    - (see also DNS)
    - in labels and annotations, Labels
- dynamic volume provisioning, Dynamic Volume Provisioning

E

- Eclipse, Alternative Ways of Viewing Your Cluster
- edit role, Aggregating ClusterRoles
- editors, plugins for Kubernetes, Alternative Ways of Viewing Your Cluster
- efficiency provided by Kubernetes, Efficiency
- elasticsearch tool, Getting More Information with Logs
- emptyDir volume, Different Ways of Using Volumes with Pods
- encryption with mTLS, Encryption and Authentication with Mutal TLS
- endpoints, Starting at the Top with a Load-Balancing Approach
    - Endpoints objects for Service objects, Endpoints
    - for external services, Services Without Selectors
    - manually adding to a service, Connecting to Resources Outside of a Cluster
- Enforce mode (Pod Security Standard), What Is Pod Security?
- environment variables, setting with ConfigMap, Using a ConfigMap
- Envoy-based Ingress controllers, Alternate Ingress Implementations
- equals operator (=) in older label selectors, Label Selectors in API Objects
- etcd, The Pod Manifest
    - Kubernetes Secrets stored in, Secrets
- etcd server, Checking Cluster Status
- events
    - related to a Pod, information about, Pod Details
    - viewing with kubectl get events command, Debugging Commands
    - watch or event-based semantics, Watching Kubernetes APIs for Changes
- eventual consistency, Building Applications for Multiple Clusters
- exec probes, Other Types of Health Checks
- extending Kubernetes, Extending Kubernetes-Summary
    - getting started, using Kubebuilder project library, Getting Started
    - meaning of, What It Means to Extend Kubernetes
    - patterns for custom resources, Patterns for Custom Resources-Operators
    - points of extensibility, Points of Extensibility-Points of Extensibility
- ExternalDNS, Configuring DNS

F

- fail open configuration, Installing Gatekeeper
- failed deployment, Monitoring a Deployment
- feature gates, Feature Gates
- filesystems
  - filesystem layout, Filesystem Layout
  - filesystem layout for parameterization, Filesystem Layout for Parameterization
  - filesystems as source of truth, Filesystems as the Source of Truth
  - using ConfigMap as filesystem, Using a ConfigMap
- fluentd tool, Getting More Information with Logs
  - creating logging agent on every node in target cluster, Creating DaemonSets
- forecasting future compute costs, Easy Scaling for Applications and Clusters

G

- Gatekeeper, Policy and Governance with Gatekeeper-Policy Library
  - auditing, Audit
  - configuring policies, Configuring Policies-Configuring Policies
  - creating constraints, Creating Constraints
  - data replication, Data Replication
  - installing, Installing Gatekeeper
  - metrics, Metrics
  - mutation features, Mutation
  - Open Policy Agent, What Is Open Policy Agent?
  - policy library, Policy Library
  - understanding constraint templates, Understanding Constraint Templates
- Gateway API, The Future of Ingress
- gcloud tool, installing, Installing Kubernetes with Google Kubernetes Engine
- GeoDNS, Starting at the Top with a Load-Balancing Approach
- GitHub Actions, Implementing Worldwide Deployment
- Go language, Accessing Kubernetes from Common Programming Languages
  - program running backend API server for kuard example application, Multistage Image Builds
- goals for your application in development and testing, Goals
- Google Cloud Platform (GCP), Installing Kubernetes with Google Kubernetes Engine
- Google Kubernetes Engine (GKE), installing Kubernetes with, Installing Kubernetes with Google Kubernetes Engine
- governance, Policy and Governance for Kubernetes Clusters

    - (see also policy and governance)
- GPUs, Resource Requests: Minimum Required Resources
- grace period (Pod termination), Deleting a Pod
- groups
    - API group for custom resource, Points of Extensibility
    - API group for resources, Accessing the Kubernetes API
    - using for role bindings, Using Groups for Bindings
- GUIs (graphical user interfaces), Kubernetes UI
    - open source GUIs for Kubernetes, Alternative Ways of Viewing Your Cluster

H

- Headlamp project, Alternative Ways of Viewing Your Cluster
- health checks, Scaling Development Teams with Microservices
    - liveness probes, Liveness Probe, One Final Thing: Readiness Probes
    - no health checking for external services, Limitations of External Services: Health Checking
    - probe configuration, advanced, Advanced Probe Configuration
    - readiness probes, Readiness Probe
    - startup probes, Startup Probe
    - tcpSocket and exec probes, Other Types of Health Checks
    - verifying health of Kubernetes cluster, Checking Cluster Status
- Helm tool, Accessing Kubernetes from Common Programming Languages
    - installing Gatekeeper with, Installing Gatekeeper
    - parameterizing configurations with, Parameterizing with Helm and Templates
- host filesystem, mounting, Different Ways of Using Volumes with Pods
- hostnames
    - stable hostnames for StatefulSet replicas, Properties of StatefulSets
    - using with Ingress to direct traffic, Using Hostnames
- hostPath volumes, Different Ways of Using Volumes with Pods
- hosts file (local), configuring for Contour, Configuring a Local hosts File
- HPA (Horizontal Pod Autoscaling), Autoscaling a ReplicaSet
    - no direct link between HPA and ReplicaSet, Autoscaling a ReplicaSet
- HTTP layer, load balancing on, Starting at the Top with a Load-Balancing Approach
- HTTP load balancing (see load balancing)
- HTTP methods, Verbs for Kubernetes roles
- httpGet probe, Liveness Probe
- hypervisors
    - isolating Pods for multitenant security, Role-Based Access Control for Kubernetes

- prerequisite for using minikube, Installing Kubernetes Locally Using minikube

I

- identity in Kubernetes, Identity in Kubernetes
  - single identity system for all clusters, Before You Even Begin
- image pull Secrets, Private Container Registries
- immutability
  - immutable images and infrastructure, Creating and Running Containers
  - value of, The Value of Immutability
- immutable infrastructure, DaemonSets
- imperative versus declarative configuration, Declarative Configuration, The Pod Manifest
- Informer pattern, Points of Extensibility
- infrastructure
  - abstracting, Abstracting Your Infrastructure
  - immutable, DaemonSets
- Ingress, HTTP Load Balancing with Ingress-Summary
  - advanced topics and gotchas, Advanced Ingress Topics and Gotchas-Serving TLS
    - interactions with namespaces, Ingress and Namespaces
    - multiple Ingress objects, Multiple Ingress Objects
    - path rewriting, Path Rewriting
    - running multiple Ingress controllers, Running Multiple Ingress Controllers
    - serving TLS, Serving TLS
  - alternate implementations, Alternate Ingress Implementations
  - future of, The Future of Ingress
  - installing Contour controller, Installing Contour-Configuring a Local hosts File
  - resource specification versus controller implementation, Ingress Spec Versus Ingress Controllers
  - typical software Ingress controller configuration, HTTP Load Balancing with Ingress
  - using, Using Ingress-Advanced Ingress Topics and Gotchas
    - cleaning up, Cleanup
    - hostnames, routing traffic via, Using Hostnames
    - paths of HTTP requests, Using Paths
    - simplest usage, Simplest Usage
- Ingress objects, Scaling Development Teams with Microservices
- IngressClass, Running Multiple Ingress Controllers
- initialization containers, Automating MongoDB Cluster Creation

- IntelliJ, Alternative Ways of Viewing Your Cluster
- interactive commands (kubectl), One Shot
- introspection
  - capabilities provided by service meshes, Introspection
  - introspecting a service mesh implementation, Introspecting a Service Mesh Implementation
- IP addresses
  - in anycast networking, Starting at the Top with a Load-Balancing Approach
  - assigned to Pods, getting with kubectl, Manual Service Discovery
  - IP address for external database service, Services Without Selectors
  - virtual, cluster IP, The Service Object
- iptables rules, kube-proxy and Cluster IPs

J

- Java
  - client library, Installing the Client Libraries
  - creating in-cluster client, Authenticating to the Kubernetes API
  - creating Kubernetes API client, Authenticating to the Kubernetes API
  - exec the ls /foo command in a Pod, Interacting with Pods
  - listing and creating Pods in, Putting It All Together: Listing and Creating Pods in Python, Java, and .NET
  - patching a Deployment, Creating and Patching Objects
  - reading and streaming logs for a Pod, Interacting with Pods
  - setting up port forwarding, Interacting with Pods
  - watching Pods for changes, Watching Kubernetes APIs for Changes
- JavaScript client library, Installing the Client Libraries
- jobs, Jobs-Summary
  - CronJobs, CronJobs
  - Job object, The Job Object
  - patterns, Job Patterns-CronJobs
    - one shot, One Shot
    - parallelism, Parallelism
    - work queues, Work Queues-CronJobs
- JSON, Viewing Kubernetes API Objects
  - Kubernetes objects represented as, Creating, Updating, and Destroying Kubernetes Objects
  - Pod manifests in, Creating a Pod Manifest
- JSONPath object, Points of Extensibility
- JSONPath query language, Viewing Kubernetes API Objects

- just data pattern, Just Data
- just in time (JIT) access, Using Groups for Bindings

K

- KaaS (Kubernetes-as-a-Service), Separation of Concerns for Consistency and Scaling, Cloud Native Ecosystem
- keys
  - private, Secrets
  - TLS, naming, Naming Constraints
- kind (Kubernetes IN Docker), Running Kubernetes in Docker
- kube-api server, --service-cluster-ip-range flag, kube-proxy and Cluster IPs
- kube-proxy, Kubernetes Proxy
  - cluster IPs and, kube-proxy and Cluster IPs
  - running on external resource, Connecting External Resources to Services Inside a Cluster
- kube-system namespace, Cluster Components
  - listing Pods in, Autoscaling a ReplicaSet
- kubeadm tool, Deploying a Kubernetes Cluster
- Kubebuilder project, library for Kubernetes API extensions, Getting Started
- kubeconfig file for authentication information, Authenticating to the Kubernetes API
- kubectl tool, The Kubernetes Client
  - authentication information, obtaining, Authenticating to the Kubernetes API
  - checking cluster status, Checking Cluster Status
  - commands, Common kubectl Commands-Summary
    - apply --dry-run, Creating, Updating, and Destroying Kubernetes Objects
    - apply -f, Creating, Updating, and Destroying Kubernetes Objects, Running Pods, Installing Contour, Simplest Usage, Creating a ReplicaSet, Declaratively Scaling with kubectl apply, Creating DaemonSets, One Shot, Starting a work queue, Update from file
    - attach, Debugging Commands
    - auth can-i, Testing Authorization with can-i
    - autocompletion of, Command Autocompletion
    - autoscale rs, Autoscaling a ReplicaSet
    - cluster management, Cluster Management
    - contexts, Contexts
    - cp (copy), Debugging Commands
    - create, Your First Deployment
    - create -f, Points of Extensibility

- create configmap, Creating ConfigMaps, Creating
- create secret, Re-create and update
- create secret docker-registry, Private Container Registries
- creating, updating, and destroying Kubernetes objects, Creating, Updating, and Destroying Kubernetes Objects
- debugging, Debugging Commands
- delete, Creating, Updating, and Destroying Kubernetes Objects, Deleting a Pod, Cleanup, Cleanup, Deleting ReplicaSets, Your First Deployment, Deleting a Deployment, Deleting a DaemonSet, Cleanup
- delete deployments --all, Cleanup
- delete job parallel, Parallelism
- delete jobs oneshot, One Shot
- delete pods, Creating a Pod, Deleting a Pod, One Shot
- describe, Listing Kubernetes Nodes, Viewing Kubernetes API Objects, Pod Details, Simplest Usage, Inspecting a ReplicaSet, Managing Deployments
- describe configmap, Listing
- describe daemonset, Creating DaemonSets
- describe jobs oneshot, One Shot
- describe pods, Liveness Probe
- describe secrets, Creating Secrets
- edit, Creating, Updating, and Destroying Kubernetes Objects, Looking Beyond the Cluster, Edit current version
- exec, Debugging Commands, Running Commands in Your Container with exec, Interacting with Pods
- explain, Viewing Kubernetes API Objects
- expose, The Service Object, Looking Beyond the Cluster
- get clusterroles, Using built-in roles
- get commands --watch flag, Viewing Kubernetes API Objects
- get configmaps, Listing
- get daemonSets, Kubernetes Proxy
- get deployments, Kubernetes DNS, Modifying Labels, Label Selectors, Your First Deployment, Creating Deployments, Scaling a Deployment
- get endpoints --watch, Endpoints
- get events, Debugging Commands
- get ingress, Simplest Usage
- get jobs -a, One Shot
- get loadtests, Points of Extensibility
- get nodes --selector, Adding Labels to Nodes
- get pods, Creating a Pod, Listing Pods, Deleting a Pod, Label Selectors, Label Selectors, Manual Service Discovery, Finding a Set of Pods for a

ReplicaSet, Declaratively Scaling with kubectl apply, Deleting ReplicaSets, Creating DaemonSets, Parallelism
    - get secrets, Listing
    - get services, Kubernetes DNS
    - kubectl port-forward rs, Starting a work queue
    - label, Modifying Labels, Adding Labels to Nodes
    - labeling and annotating objects, Labeling and Annotating Objects
    - logs, Debugging Commands, Getting More Information with Logs, One Shot
    - namespaces, Namespaces
    - -o wide flag, Listing Pods
    - port-forward, Debugging Commands, Readiness Checks, Live updates
    - reconcile, Managing RBAC in Source Control
    - replace, Creating Deployments, Update from file
    - rolling-update, Deployments
    - rollout, Managing Deployments
    - rollout history, Rollout History
    - rollout pause, Updating a Container Image
    - rollout resume, Updating a Container Image
    - rollout status, Updating a Container Image, Updating a DaemonSet
    - rollout undo, Rollout History, Rollout History
    - run, Creating a Pod, Label Selectors, One Shot
    - scale, Imperative Scaling with kubectl scale
    - top, Debugging Commands
    - --v=10 for comprehensive logging, Listing Pods, But What About kubectl x?
    - viewing Kubernetes API objects, Viewing Kubernetes API Objects
    - --watch flag, Readiness Checks
  - Kubernetes API and, But What About kubectl x?
  - listing nodes in a cluster, Listing Kubernetes Nodes
  - local configuration file pointing to a cluster, Installing Kubernetes Locally Using minikube
- kubelet, One Shot
  - Secrets volumes managed by, Consuming Secrets
- Kubernetes objects, Viewing Kubernetes API Objects
  - creating, updating, and destroying with kubectl, Creating, Updating, and Destroying Kubernetes Objects
  - label selectors in, Label Selectors in API Objects
  - labeling and annotating with kubectl, Labeling and Annotating Objects
  - new API objects, Points of Extensibility
  - viewing with kubectl, Viewing Kubernetes API Objects
- Kubernetes, introduction to, Introduction

- Kubernetes-as-a-Service (KaaS), Separation of Concerns for Consistency and Scaling, Cloud Native Ecosystem

L

- labels, Labels and Annotations-Labels in the Kubernetes Architecture, Summary
  - adding to nodes, Adding Labels to Nodes
    - filtering nodes with label selector, Adding Labels to Nodes
  - applying, Applying Labels
  - changing on sick Pods, Quarantining Containers
  - filtering labels in ReplicaSet specifications, Labels
  - Job objects and, One Shot
  - key/value pairs, rules for, Labels
  - in the Kubernetes architecture, Labels in the Kubernetes Architecture
  - label selectors, Label Selectors-Labels in the Kubernetes Architecture
    - in API objects, Label Selectors in API Objects
    - creating selectorless service, Connecting to Resources Outside of a Cluster
    - for Deployment object, Your First Deployment
    - external services without selectors, Services Without Selectors
    - finding Pods that match, Finding a Set of Pods for a ReplicaSet
    - label operators, Label Selectors
    - negative and positive versions of, Label Selectors
    - selector field for PersistentVolumeClaim, Running a MySQL Singleton
    - Service object creating named selector, The Service Object
    - specifying ClusterRoles to be aggregated, Aggregating ClusterRoles
  - modifying, Modifying Labels
  - reasons for using, Labels
  - using to apply Pod Security Standards, Applying Pod Security Standards
- layering (container), Container Images
  - changes to layers, Optimizing Image Sizes
- "Let's Encrypt", running free Certificate Authority, Serving TLS
- libraries, external and shared, Creating and Running Containers
- limits, Resource Management
  - capping resource usage with, Capping Resource Usage with Limits
  - for resources for each Pod running on a machine, Listing Kubernetes Nodes
- liveness probes, Liveness Probe, One Final Thing: Readiness Probes
- load balancers
  - creation on different types of infrastructure, Abstracting Your Infrastructure
  - decoupling components via, Decoupling

  - no single HTTP load balancer for universal use, Ingress Spec Versus Ingress Controllers
  - for services, Load Balancer Integration-Load Balancer Integration
- load balancing
  - anycast technique, Starting at the Top with a Load-Balancing Approach
  - approach to multicluster application deployment, Starting at the Top with a Load-Balancing Approach
  - HTTP load balancing with Ingress, HTTP Load Balancing with Ingress-Summary
  - Kubernetes service performing for DNS server, Kubernetes DNS
  - on TCP or HTTP level, Starting at the Top with a Load-Balancing Approach
- LoadBalancer type, Load Balancer Integration, HTTP Load Balancing with Ingress
- LoadTest custom resource, Points of Extensibility
- logs
  - getting more information about your application with, Getting More Information with Logs
  - log aggregation services, Getting More Information with Logs
  - reading and streaming logs for a Pod, Interacting with Pods
  - viewing for one-shot job, One Shot
  - viewing with kubectl, Debugging Commands

M

- machine resources
  - decoupling application container image from machine, Scaling Development Teams with Microservices
  - predicting use for scaling purposes, Easy Scaling for Applications and Clusters
  - separation of developers from specific machines, Abstracting Your Infrastructure
- malloc utility, Capping Resource Usage with Limits
- managed Kubernetes-as-a-Service (KaaS), Separation of Concerns for Consistency and Scaling
- manifests (Pod), The Pod Manifest
  - complete manifest for kuard Pod, Putting It All Together
  - declaring a Secrets volume, Consuming Secrets
  - Secrets declared in, Secrets
  - writing, Creating a Pod Manifest
- maxUnavailable parameter, Configuring a rolling update, Updating a DaemonSet
- memory
  - limiting use of memory resources, Limiting memory resources
  - limits on usage of, Capping Resource Usage with Limits
  - requested by each Pod from the node, Listing Kubernetes Nodes

  - requests for, Resource Requests: Minimum Required Resources, Resource Requests: Minimum Required Resources
- metadata
  - CustomResourceDefinition, Points of Extensibility
  - in Pod manifests, Creating a Pod Manifest
- metrics from Gatekeeper, Metrics
- metrics-server, required for autoscaling, Autoscaling a ReplicaSet
- microservices, Decoupling
  - microservice routing, Better Flexibility: Microservice Routing
  - scaling development teams with, Scaling Development Teams with Microservices
- milli-units and mega-units, Resource Management
- minikube, Deploying a Kubernetes Cluster
  - hypervisor as prerequisite for, Installing Kubernetes Locally Using minikube
  - installing Kubernetes locally with, Installing Kubernetes Locally Using minikube
  - minikube tunnel command, Installing Contour
- minReadySeconds parameter, Slowing Rollouts to Ensure Service Health, Updating a DaemonSet
- MongoDB, Properties of StatefulSets-Summary
  - automating MongoDB cluster creation, Automating MongoDB Cluster Creation-Automating MongoDB Cluster Creation
  - manually replicated with StatefulSets, Manually Replicated MongoDB with StatefulSets-Manually Replicated MongoDB with StatefulSets
  - setting up a ReplicaSet in, Integrating Storage Solutions and Kubernetes
- monitoring worldwide application deployments, Dashboards and Monitoring for Worldwide Deployments
- mounting host filesystem, using volumes, Different Ways of Using Volumes with Pods
- mTLS (Mutual Transport Layer Security), Encryption and Authentication with Mutal TLS
- multistage image builds, Multistage Image Builds
- mutability, The Value of Immutability
- MutatingWebhookConfiguration, Points of Extensibility
- mutation, Mutation
- MySQL database, running singleton for, Running a MySQL Singleton-Running a MySQL Singleton
  - exposing MySQL as Kubernetes service, Running a MySQL Singleton
  - ReplicaSet for MySQL, Running a MySQL Singleton

N

- namespaced resources, Accessing the Kubernetes API
- namespaces, Scaling Development Teams with Microservices, Efficiency
  - default, changing with kubectl, Namespaces
  - Ingress interactions with, Ingress and Namespaces
  - listing in Python, Accessing the Kubernetes API
  - projectcontour, Installing Contour
  - roles and, Roles and Role Bindings in Kubernetes
- native interprocess communication channels, Pods in Kubernetes
- .NET
  - client library, Installing the Client Libraries
  - creating in-cluster client, Authenticating to the Kubernetes API
  - creating Kubernetes API client, Authenticating to the Kubernetes API
  - exec the ls /foo command in a Pod, Interacting with Pods
  - listing and creating Pods in, Putting It All Together: Listing and Creating Pods in Python, Java, and .NET
  - patching a Deployment, Creating and Patching Objects
  - reading and streaming logs for a Pod, Interacting with Pods
  - setting up port forwarding, Interacting with Pods
  - watching Pods for changes, Watching Kubernetes APIs for Changes
- Network Policy, Network Policy-Network Policy
- networking
  - cloud native capabilities with service meshes, Service Meshes
  - Services and Ingress, Service Meshes
  - setting up for Kubernetes cluster, Setting Up Networking, Setting Up Cluster Networking
- networks
  - layers in OSI model, HTTP Load Balancing with Ingress
- NewReplicaSet, Managing Deployments
- NFS (Network File System)
  - persistent volume, Running a MySQL Singleton
- NGINX
  - Ingress controller, Path Rewriting, Alternate Ingress Implementations
  - limiting to nodes with label set to ssd=true, Node Selectors
- nginx-fast-storage DaemonSet, submitting to Kubernetes API, Node Selectors
- Node.js, building image for an application, Dockerfiles
- NodePorts, Looking Beyond the Cluster, Connecting External Resources to Services Inside a Cluster
  - installing Contour to use services of type NodePort, Installing Contour

    - services of type NodePort, HTTP Load Balancing with Ingress
- nodes
    - DaemonSet creating fluentd agent on each node in cluster, Creating DaemonSets-Creating DaemonSets
    - limiting DaemonSets to particular nodes, Limiting DaemonSets to Specific Nodes
        - adding labels to nodes, Adding Labels to Nodes
        - node selectors, Node Selectors
    - listing in Kubernetes cluster, Listing Kubernetes Nodes
    - scheduler placing Pods onto, The Pod Manifest
    - scheduling Pods to, resource requests, Resource Requests: Minimum Required Resources
- NotIn expression, using to represent != operator, Label Selectors in API Objects
- npm/Node/Express apps, Dockerfiles

O

- OCI (Open Container Initiative), Container Images
- OldReplicaSets, Managing Deployments
- one-shot jobs, One Shot
- Open Container Initiative (OCI), Container Images
- Open Policy Agent, What Is Open Policy Agent?, Data Replication
- OpenAPI and generated client libraries, OpenAPI and Generated Client Libraries
- operations teams, Separation of Concerns for Consistency and Scaling
- operator paradigm for Kubernetes, Self-Healing Systems
- operators, Extending Kubernetes
    - extensions using, Operators
- organizing your application (see applications)
- OSI (Open Systems Interconnection) model, HTTP Load Balancing with Ingress
- overlay filesystem, Container Images
- ownerReferences section (ReplicaSet controller), Finding a ReplicaSet from a Pod

P

- parallel job work queue, Work Queues
- parallelism parameter (jobs), Job Patterns, Parallelism
- parameterizing your application with templates, Parameterizing Your Application with Templates
    - filesystem layout for parameterization, Filesystem Layout for Parameterization
    - parameterizing with Helm and templates, Parameterizing with Helm and Templates

- parameters, Parameterizing Your Application with Templates
- patching resources, Creating and Patching Objects
- paths
  - of HTTP requests, using with Ingress, Using Paths
  - path rewriting by Ingress controllers, Path Rewriting
- Pending state (Pods), Creating a Pod, Listing Pods
- persistent volume claim template, Persistent Volumes and StatefulSets
- persistent volumes
  - creating for MySQL database, Running a MySQL Singleton
  - and StatefulSets, Persistent Volumes and StatefulSets
- PersistentVolume object, Running a MySQL Singleton
- PersistentVolumeClaim object, Running a MySQL Singleton
  - reclamation policy, Dynamic Volume Provisioning
  - using default storage class, Dynamic Volume Provisioning
- persisting data with volumes, Persisting Data with Volumes-Putting It All Together
- Pod Security, Pod Security-Applying Pod Security Standards
  - about, What Is Pod Security?
  - applying Pod Security Standards, Applying Pod Security Standards-Applying Pod Security Standards
  - standards, What Is Pod Security?
- pod-template-hash label, Label Selectors
- Pods, Scaling Development Teams with Microservices, Pods-Summary
  - accessing, Accessing Your Pod-Copying Files to and from Containers
    - copying files to and from containers, Copying Files to and from Containers
    - getting more info with logs, Getting More Information with Logs
    - running commands in container with exec, Running Commands in Your Container with exec
  - CrashLoopBackOff, One Shot
  - creating a manifest, Creating a Pod Manifest
  - creating to test policy, Configuring Policies
  - creating via kubectl run command, Creating a Pod
  - currently running on a node, information about, Listing Kubernetes Nodes
  - deleting, Creating a Pod
  - designing, questions to ask, Thinking with Pods
  - discovering for particular ReplicaSet using labels, Labels
  - example Pod with two containers and shared filesystem, Pods
  - exposure of secrets to, Secrets
  - finding a ReplicaSet from a Pod, Finding a ReplicaSet from a Pod
  - finding Pods managed by a ReplicaSet, Finding a Set of Pods for a ReplicaSet
  - health checks, Health Checks-Other Types of Health Checks

    - liveness probes, Liveness Probe
    - probe configuration, advanced, Advanced Probe Configuration
    - readiness probes, Readiness Probe
    - startup probes, Startup Probe
    - tcpSocket and exec probes, Other Types of Health Checks
  - identity providers for, Identity in Kubernetes
  - in Kubernetes, Pods in Kubernetes
  - interacting with, Interacting with Pods
  - managed by a ReplicaSet, deleting, Deleting ReplicaSets
  - managed replica Pods for StatefulSets, deletion of, Properties of StatefulSets
  - manifests, The Pod Manifest
  - node selectors limiting nodes Pod can run on, Node Selectors
  - persisting data with volumes, Persisting Data with Volumes-Putting It All Together
  - putting it all together in kuard manifest, Putting It All Together
  - relating ReplicaSets to, Relating Pods and ReplicaSets
  - resource management for, Resource Management-Capping Resource Usage with Limits
    - capping resource usage with limits, Capping Resource Usage with Limits
    - resource requests, minimum required resources, Resource Requests: Minimum Required Resources
  - returning all currently running in a cluster with kubectl get pods, Label Selectors
  - running, Running Pods
    - deleting a Pod, Deleting a Pod
    - getting Pod details, Pod Details
    - listing Pods, Listing Pods
  - Security Context config applied to running Pod, Understanding SecurityContext
  - SecurityContext, Understanding SecurityContext
  - in service meshes, sidecar container added to, Introspecting a Service Mesh Implementation
  - templates in ReplicaSet specification, Pod Templates
  - using ReplicaSet to construct singleton Pod, Running a MySQL Singleton
- PodSecurityContext, Understanding SecurityContext
- PodSecurityPolicy, Policy Library
- policy and governance, Policy and Governance for Kubernetes Clusters-Summary
  - admission flow, Admission Flow
  - defining policy for your clusters, Before You Even Begin
  - importance of, Why Policy and Governance Matter
  - using Gatekeeper, Policy and Governance with Gatekeeper-Policy Library
    - auditing, Audit

    - configuring policies, Configuring Policies-Configuring Policies
    - creating constraints, Creating Constraints
    - data replication, Data Replication
    - installing Gatekeeper, Installing Gatekeeper
    - metrics, Metrics
    - mutation, Mutation
    - Open Policy Agent, What Is Open Policy Agent?
    - policy library, Policy Library
    - understanding constraint templates, Understanding Constraint Templates
- polling, Watching Kubernetes APIs for Changes
- port forwarding, Running Containers with Docker, Readiness Checks
    - kubectl port-forward command, Debugging Commands
    - setting up in Java, Python, and .NET, Interacting with Pods
    - testing authorization with can-i command, Testing Authorization with can-i
- portability, benefits of move to application-oriented container APIs, Abstracting Your Infrastructure
- private container registries, Storing Images in a Remote Registry
- process health checks, Health Checks
    - (see also health checks)
- programming languages, accessing Kubernetes from, Accessing Kubernetes from Common Programming Languages-Summary
    - Kubernetes API, client's perspective, The Kubernetes API: A Client's Perspective-But What About kubectl x?
    - programming the Kubernetes API, Programming the Kubernetes API
        - accessing the Kubernetes API, Accessing the Kubernetes API
        - authenticating to the Kubernetes API, Authenticating to the Kubernetes API
        - creating and patching objects, Creating and Patching Objects
        - installing client libraries, Installing the Client Libraries
        - interacting with Pods, Interacting with Pods
        - listing and creating Pods, Putting It All Together: Listing and Creating Pods in Python, Java, and .NET
        - watching Kubernetes APIs for changes, Watching Kubernetes APIs for Changes
- progressDeadlineSeconds parameter, Slowing Rollouts to Ensure Service Health
- progression of a release, Progression of a Release
- projectcontour namespace, Installing Contour
- provisioning, Easy Scaling for Applications and Clusters
    - automatic provisioning of persistent volume, Dynamic Volume Provisioning, Dynamic Volume Provisioning
- proxy (Kubernetes), Kubernetes Proxy

    - (see also kube-proxy)
- public container registries, Storing Images in a Remote Registry
- Python
    - client library, Installing the Client Libraries
    - creating in-cluster client, Authenticating to the Kubernetes API
    - creating Kubernetes API client, Authenticating to the Kubernetes API
    - exec the ls /foo command in a Pod, Interacting with Pods
    - listing and creating Pods in, Putting It All Together: Listing and Creating Pods in Python, Java, and .NET
    - listing Pods in default namespace, Accessing the Kubernetes API
    - patching a Deployment, Creating and Patching Objects
    - reading and streaming logs for a Pod, Interacting with Pods
    - setting up port forwarding, Interacting with Pods
    - watching Pods for changes, Watching Kubernetes APIs for Changes

R

- Rancher dashboard, Alternative Ways of Viewing Your Cluster
- Raspberry Pi, Introduction
    - building Kubernetes cluster on, Building Your Own Kubernetes Cluster-Summary
- RBAC (role-based access control), Role-Based Access Control for Kubernetes-Summary
    - advanced topics, Advanced Topics-Summary
        - aggregating ClusterRoles, Aggregating ClusterRoles
        - using groups for bindings, Using Groups for Bindings
    - application to service accounts, Service Account Management
    - consistent access control to clusters, Before You Even Begin
    - identity in Kubernetes, Identity in Kubernetes
    - management techniques, Techniques for Managing RBAC
        - managing RBAC in source control, Managing RBAC in Source Control
        - testing authorization with can-i, Testing Authorization with can-i
    - roles and role bindings in Kubernetes, Roles and Role Bindings in Kubernetes
        - auto-reconciliation of built-in roles, Auto-reconciliation of built-in roles
        - built-in roles, using, Using built-in roles
        - verbs for Kubernetes roles, Verbs for Kubernetes roles
    - understanding roles and role bindings, Understanding Roles and Role Bindings
- rbac.authorization.kubernetes.io/autoupdate annotation, Auto-reconciliation of built-in roles
- React.js, Multistage Image Builds

- readiness probes, Readiness Probe, Slowing Rollouts to Ensure Service Health
  - adding to Mongo-serving containers, One Final Thing: Readiness Probes
  - for services, Readiness Checks
- reconciliation loops, ReplicaSets, DaemonSet Scheduler
- Recreate strategy, Creating Deployments, Recreate Strategy
- redundancy, Multicluster Application Deployments
- regional data sharding, Sharding: Regional Data
- regions
  - regional clusters, Multicluster Application Deployments
  - replicating your application across multiple regions, Replicated Silos: The Simplest Cross-Regional Model
- registries
  - container, Creating and Running Containers
    - storing container images in remote registry, Storing Images in a Remote Registry
  - private, storing credentials in Secrets, Private Container Registries
- Rego query language, What Is Open Policy Agent?
- release, stages of, Progression of a Release
- reliability, Introduction
- replacing resources, Creating and Patching Objects
- replicas
  - increasing number of in deployment.yaml file, Scaling a Deployment
  - StatefulSet, Properties of StatefulSets
- ReplicaSets, Label Selectors, ReplicaSets-Summary
  - adjusting number in a Deployment, Rollout History
  - benefits of, ReplicaSets
  - creating, Creating a ReplicaSet
  - creating to manage singleton work queue daemon, Starting a work queue
  - deleting, Deleting ReplicaSets
  - Deployments managing, Your First Deployment
  - designing with, Designing with ReplicaSets
  - inspecting, Inspecting a ReplicaSet
  - OldReplicaSets and NewReplicaSet fields in Deployment, Managing Deployments
  - reconciliation loops, Reconciliation Loops
  - relating Pods and, Relating Pods and ReplicaSets
  - relationship with Deployment in action, Your First Deployment
  - scaling, Finding a Set of Pods for a ReplicaSet-Autoscaling a ReplicaSet
  - setting up in MongoDB, Integrating Storage Solutions and Kubernetes
  - specification, ReplicaSet Spec

    - using label selector to find Pods they're managing, Labels in the Kubernetes Architecture
    - using to construct singleton Pod, Running a MySQL Singleton
- replicated silos, Replicated Silos: The Simplest Cross-Regional Model
- requests for resources, Listing Kubernetes Nodes, Resource Management
- resiliency, Multicluster Application Deployments
- resource management, Resource Management-Capping Resource Usage with Limits
    - capping resource usage with limits, Capping Resource Usage with Limits
    - limiting resource usage, Limiting Resource Usage
    - resource requests, minimum required resources, Resource Requests: Minimum Required Resources
- resource mutation, Policy and Governance with Gatekeeper, Mutation
- resources
    - creating, patching, and replacing, Creating and Patching Objects
    - external, connecting to services inside a cluster, Connecting External Resources to Services Inside a Cluster
    - Ingress, specifying, Running Multiple Ingress Controllers
    - namespaced and cluster-level, Accessing the Kubernetes API
    - outside of the cluster, connecting to, Connecting to Resources Outside of a Cluster
    - showing usage with kubectl top command, Debugging Commands
- restartPolicy (Pods), Liveness Probe
- restartPolicy: Never, One Shot
- RESTful API, OpenAPI and Generated Client Libraries
- revisionHistoryLimit property (Deployment), Rollout History
- revisions, mapping stages to, Mapping stages to revisions
- role bindings, Understanding Roles and Role Bindings
- Role object, Roles and Role Bindings in Kubernetes
    - binding a group to, Using Groups for Bindings
    - namespaces and, Roles and Role Bindings in Kubernetes
- role-based access control (see RBAC)
- RoleBinding object, Roles and Role Bindings in Kubernetes
    - creating, Roles and Role Bindings in Kubernetes
- roles, Understanding Roles and Role Bindings
- rolling updates, Deployments
- RollingUpdate strategy, Creating Deployments, RollingUpdate Strategy-Configuring a rolling update
    - configuring, Configuring a rolling update
        - maxSurge parameter, Configuring a rolling update

    - maxUnavailable parameter, Configuring a rolling update
  - configuring for DaemonSet updates, Updating a DaemonSet
- rollouts, Scaling Development Teams with Microservices, Deployments
  - (see also deployments)
  - change-cause annotation and, Updating a Container Image
  - history of, Rollout History
  - kubectl rollout and rollout history commands, Managing Deployments
  - monitoring status of, Updating a Container Image, Updating a DaemonSet
  - pausing, Updating a Container Image
  - resuming, Updating a Container Image
  - strategies for, Creating Deployments
  - undoing, Rollout History
- root privileges, Role-Based Access Control for Kubernetes
- routing
  - cloud native HTTP-routing API, Service Meshes
  - traffic shaping, Traffic Shaping
- Running state (Pods), Creating a Pod
- runtime scanning, Image Security
- RuntimeClass, RuntimeClass-RuntimeClass

S

- scalability, Introduction
  - scaling your service and your teams, Scaling Your Service and Your Teams-Abstracting Your Infrastructure
    - decoupling of each component, Decoupling
    - easy scaling for applications and clusters, Easy Scaling for Applications and Clusters
    - scaling development teams with microservices, Scaling Development Teams with Microservices
    - separation concerns for consistency and scaling, Separation of Concerns for Consistency and Scaling
- scaling
  - of deployments, Scaling a Deployment
  - of ReplicaSets, Scaling ReplicaSets-Autoscaling a ReplicaSet
    - autoscaling, Autoscaling a ReplicaSet
    - declaratively scaling with kubectl apply, Declaratively Scaling with kubectl apply
    - imperatively scaling with kubectl scale, Imperative Scaling with kubectl scale
  - scaling both Deployment and ReplicaSet, Your First Deployment

- scheduler, Checking Cluster Status
  - DaemonSet, DaemonSet Scheduler
  - placing Pods onto nodes, The Pod Manifest
- scope field (CustomResourceDefinition), Points of Extensibility
- secrets, ConfigMaps and Secrets, Secrets-Private Container Registries
  - consuming, Consuming Secrets
  - creating, Creating Secrets
  - managing, Managing ConfigMaps and Secrets-Summary
    - listing all Secrets in namespace, Listing
    - live updates, Live updates
    - recreating and updating, Re-create and update
  - naming constraints, Naming Constraints
  - never mixing with images, Image Security
  - specifying with TLS certificate and keys, Serving TLS
  - storing access credentials for private container registries, Private Container Registries
- security
  - application container image, Image Security
  - attacker gaining root privileges, Role-Based Access Control for Kubernetes
  - securing applications in Kubernetes, Securing Applications in Kubernetes-Summary
    - container image security, Image Security
    - Network Policy, Network Policy-Network Policy
    - Pod Security, Pod Security-Applying Pod Security Standards
    - RBAC, Role-Based Access Control
    - RuntimeClass, RuntimeClass-RuntimeClass
    - security benchmark tools, Security Benchmark Tools
    - SecurityContext challenges, SecurityContext Challenges
    - SecurityContext, understanding, Understanding SecurityContext
    - service account management, Service Account Management
- SecurityContext, Understanding SecurityContext-SecurityContext Challenges
  - challenges, SecurityContext Challenges
  - core set of operating system controls covered by, Understanding SecurityContext
  - fields defined in Pod specification, Understanding SecurityContext
  - values applied at scale, Pod Security
    - (see also Pod Security)
- selector operators, Label Selectors
- selectors (label) (see labels)
- self-healing systems, Self-Healing Systems

- servers, decoupling via APIs, Decoupling
- service accounts, Identity in Kubernetes, Authenticating to the Kubernetes API
  - for each Pod, adding private registry Secrets to, Private Container Registries
  - management of, Service Account Management
  - storing identities in, Identity in Kubernetes
- service discovery, Service Discovery-Summary
  - about, What Is Service Discovery?
  - advanced details, Advanced Details
    - cluster IP environment variables, Cluster IP Environment Variables
    - endpoints, Endpoints
    - kube-proxy and cluster IPs, kube-proxy and Cluster IPs
    - manual service discovery, Manual Service Discovery
  - connecting with other environments, Connecting with Other Environments-Cleanup
  - load balancer integration, Load Balancer Integration-Load Balancer Integration
  - looking beyond the cluster, Looking Beyond the Cluster-Looking Beyond the Cluster
  - Service object, The Service Object
    - readiness checks, Readiness Checks
    - service DNS, Service DNS
- Service Mesh Interface (SMI), vendor-neutral, Introspecting a Service Mesh Implementation
- service meshes, Service Meshes-Service Mesh Landscape
  - deciding need for, Do You Really Need a Service Mesh?
  - encryption and authentication with mTLS, Encryption and Authentication with Mutal TLS
  - increasing security with, Service Mesh
  - introspecting an implementation, Introspecting a Service Mesh Implementation
  - introspection, Introspection
  - landscape, Service Mesh Landscape
  - traffic shaping, Traffic Shaping
- services, Scaling Development Teams with Microservices
  - backend, creating, Using Ingress
  - ensuring health by slowing rollouts, Slowing Rollouts to Ensure Service Health
  - headless service to manage DNS entries for StatefulSet, Manually Replicated MongoDB with StatefulSets
  - importing external storage services, Importing External Services-Limitations of External Services: Health Checking
  - running in hostile environment, not allowing anonymous authentication, Auto-reconciliation of built-in roles

  - of type LoadBalancer, HTTP Load Balancing with Ingress
    - (see also Ingress; LoadBalancer type)
  - of type NodePort, HTTP Load Balancing with Ingress
    - (see also NodePorts)
  - using kubectl port-forward command with, Debugging Commands
- sharding, Sharding: Regional Data
- shell, starting inside kuard container, Understanding SecurityContext
- sidecar containers, Pods
  - added to each Pod in service meshes, Introspecting a Service Mesh Implementation
- silos, replicated, Replicated Silos: The Simplest Cross-Regional Model
- singletons, Labels
  - running reliable singletons, Running Reliable Singletons-Dynamic Volume Provisioning
    - dynamic volume provisioning, Dynamic Volume Provisioning
    - running MySQL singleton, Running a MySQL Singleton-Running a MySQL Singleton
- source control
  - managing role-based access control in, Managing RBAC in Source Control
  - managing your application in, Managing Your Application in Source Control-Versioning with directories
    - filesystem layout, Filesystem Layout
    - periodic versions, Managing Periodic Versions
- spec section (Pod manifests), Creating a Pod Manifest
- specifications
  - Deployment, Creating Deployments
  - spec object for CustomResourceDefinition, Points of Extensibility
- SRV records (DNS), What Is Service Discovery?
- SSL-based admission controller, Points of Extensibility
- startup probes, Startup Probe
- state, Integrating Storage Solutions and Kubernetes
  - benefits of reconciliation loop approach to, Reconciliation Loops
  - desired state versus observed or current state, Reconciliation Loops
  - maintaining desired state in self-healing, Self-Healing Systems
  - managing cluster state via the filesystem, Filesystems as the Source of Truth
  - viewing cluster state as source of truth, Filesystems as the Source of Truth
- StatefulSets, Kubernetes-Native Storage with StatefulSets-Summary
  - automating MongoDB cluster creation, Automating MongoDB Cluster Creation-Automating MongoDB Cluster Creation

    - manually replicated MongoDB with StatefulSets, Manually Replicated MongoDB with StatefulSets-Manually Replicated MongoDB with StatefulSets
    - persistent volumes and, Persistent Volumes and StatefulSets
    - properties of, Properties of StatefulSets
- static scanning, Image Security
- storage
    - cloud-based storage for replicated data store, Building Applications for Multiple Clusters
    - consistency models, Building Applications for Multiple Clusters
    - persistent data, Different Ways of Using Volumes with Pods
    - storage field for CustomResourceDefinition, Points of Extensibility
- storage solutions, integrating with Kubernetes, Integrating Storage Solutions and Kubernetes-Summary
    - importing external services, Importing External Services-Limitations of External Services: Health Checking
        - limitation of external services, no health checking, Limitations of External Services: Health Checking
        - services without selectors, Services Without Selectors
    - Kubernetes-native storage with StatefulSets, Kubernetes-Native Storage with StatefulSets-Summary
        - automating MongoDB cluster creation, Automating MongoDB Cluster Creation-Automating MongoDB Cluster Creation
        - manually replicated MongoDB with StatefulSets, Manually Replicated MongoDB with StatefulSets-Manually Replicated MongoDB with StatefulSets
        - persistent volumes and StatefulSets, Persistent Volumes and StatefulSets
        - properties of StatefulSets, Properties of StatefulSets
    - running reliable singletons, Running Reliable Singletons-Running a MySQL Singleton
        - dynamic volume provisioning, Dynamic Volume Provisioning
        - MySQL singleton, Running a MySQL Singleton-Running a MySQL Singleton
- StorageClass objects, Dynamic Volume Provisioning
- strategies
    - deployment, Creating Deployments, Deployment Strategies-Deleting a Deployment
        - slowing rollouts to ensure service health, Slowing Rollouts to Ensure Service Health
    - RollingUpdate, configuring for DaemonSets, Updating a DaemonSet
- strong consistency, Building Applications for Multiple Clusters
- subresources, testing authorization for, Testing Authorization with can-i

- synchronization, using volumes, Different Ways of Using Volumes with Pods
- system containers, Container Images
- system:unauthenticated group, Identity in Kubernetes, Auto-reconciliation of built-in roles

T

- tags
  - deleting container images by tag name, Cleanup
  - introducing a development tag, Introducing a development tag
  - kuard application example with target Docker registry, Storing Images in a Remote Registry
  - source control, Versioning with branches and tags
- TCP, load balancing on, Starting at the Top with a Load-Balancing Approach
- tcpSocket health checks, Other Types of Health Checks
- templates, parameterizing your application with, Parameterizing Your Application with Templates-Deploying Your Application Around the World
- Terminating state (Pods), Deleting a Pod
- test environment, efficient creation with Kubernetes, Efficiency
- timeout for deployments, Slowing Rollouts to Ensure Service Health
- TLS (Transport Layer Security)
  - key and certificate for kuard application, Creating Secrets
  - Mutual TLS (mTLS), Encryption and Authentication with Mutal TLS
  - serving in Ingress system, Serving TLS
- tmpfs volumes, Secrets stored in, Consuming Secrets
- traffic shaping, Traffic Shaping

U

- UI (user interface) for Kubernetes, Kubernetes UI
- unit testing, Before You Even Begin
- Unix pipes, combining kubectl with, Viewing Kubernetes API Objects
- user accounts, Identity in Kubernetes
- utilization metric (resources), Resource Management

V

- validating admission controller, Points of Extensibility-Points of Extensibility
  - full definition, Points of Extensibility
  - implementing to provide defaulting, Points of Extensibility
- ValidatingWebhookConfiguration, Points of Extensibility, Installing Gatekeeper

- validation, Points of Extensibility
- valueFrom member, Using a ConfigMap
- velocity in software development, Velocity
- version skew in multicluster deployments, Before You Even Begin
- versioning
  - in Kubernetes, Checking Cluster Status
  - managing periodic versions, Managing Periodic Versions
    - versioning with branches and tags, Versioning with branches and tags
    - versioning with directories, Versioning with directories
  - mapping stages to revisions, Mapping stages to revisions
- virtual hosting, HTTP Load Balancing with Ingress
- Visual Studio Code, Alternative Ways of Viewing Your Cluster
- volumes
  - ConfigMap, Using a ConfigMap
  - creating persistent volume for MySQL database, Running a MySQL Singleton
  - dynamic volume provisioning, Dynamic Volume Provisioning
  - Kubernetes CSI, Secrets
  - persistent volume claim, Running a MySQL Singleton
  - persistent volumes and StatefulSets, Persistent Volumes and StatefulSets
  - persisting data with, Persisting Data with Volumes-Putting It All Together
  - Secrets, Consuming Secrets

W

- Warn mode (Pod Security Standard), What Is Pod Security?
- watch API on the API server, Points of Extensibility
- watch command, starting on service endpoints, Readiness Checks
- watching Kubernetes APIs for changes, Watching Kubernetes APIs for Changes
- webhooks, Admission Flow
  - access via HTTPS, Points of Extensibility
  - mutating and validating admission webhooks, Mutation
  - MutatingWebhookConfiguration, Points of Extensibility
  - ValidatingWebhookConfiguration, Points of Extensibility, Installing Gatekeeper
- WebSockets, Interacting with Pods
- work queues, Work Queues-CronJobs
  - cleaning up, Cleanup
  - creating a consumer job, Creating the consumer job
  - loading up the queue, Loading up the queue
  - starting, Starting a work queue
- worker nodes, Listing Kubernetes Nodes

Y

- YAML
  - for ConfigMap object, Creating ConfigMaps
  - declarative YAML configurations, Accessing Kubernetes from Common Programming Languages
  - deployment.yaml file, Creating Deployments, Scaling a Deployment, Updating a Container Image, Deleting a Deployment
  - Kubernetes objects represented as, Creating, Updating, and Destroying Kubernetes Objects
  - Pod manifests in, Creating a Pod Manifest
  - Secrets stored in YAML files, Naming Constraints

Z

- zsh shell, command autocompletion, Command Autocompletion