Digital Imaging Fundamentals

Subhadip Basu, Ph.D. Department of Computer Science and Engineering, Jadavpur University

Contents

This lecture will cover:

- The human visual system
- Light and the electromagnetic spectrum
- Image representation
- Image sensing and acquisition
- Sampling, quantisation and resolution

Human Visual System

The best vision model we have!

Knowledge of how images form in the eye can help us with processing digital images. We will take just a whirlwind tour of the human visual system

Structure Of The Human Eye

Anterior chamber

Lens

Blind spot

Retina

Ciliary muscle

Ciliary fibers

Visual axis

Vitreous humor

The lens focuses light from objects onto the

retina

The retina is covered with light receptors called cones (6-7 million) and rods (75-150 million)


Cones are concentrated around the fovea and are very sensitive to colour

Rods are more spread out and are sensitive to low levels of illumination



Image Formation In The Eye

Muscles within the eye can be used to change the shape of the lens allowing us focus on objects that are near or far away. An image is focused onto the retina causing rods and cones to become excited which ultimately send signals to the brain




Brightness Adaptation & Discrimination

The human visual system can perceive approximately 10¹⁰ different light intensity levels

However, at any one time we can only discriminate between a much smaller number – *brightness adaptation*


Similarly, the *perceived intensity* of a region is related to the light intensities of the regions surrounding it

Brightness Adaptation & Discrimination (cont...)






Brightness Adaptation & Discrimination (cont...)






Brightness Adaptation & Discrimination (cont...)







Optical Illusions

Our visual systems play lots of interesting tricks on us



Optical Illusions (cont...)






Optical Illusions (cont...)



Stare at the cross in the middle of the image and think circles


Mind Map Exercise: Mind Mapping For Note Taking




Light And The Electromagnetic Spectrum

Light is just a particular part of the electromagnetic spectrum that can be sensed by the human eye

The electromagnetic spectrum is split up according to the wavelengths of different forms of energy




Electromagnetic Spectrum



Reflected Light

The colours that we perceive are determined by the nature of the light reflected from an object

For example, if white light is shone onto a green object most wavelengths are absorbed, while green light is reflected from the object



Sampling, Quantisation And Resolution

In the following slides we will consider what is involved in capturing a digital image of a real-world scene

- Image sensing and representation
- Sampling and quantisation
- Resolution

Before we discuss image acquisition recall that a digital image is composed of M rows

and N columns of pixels each storing a value

Pixel values are most often grey levels in the range 0-255(black-white)

We will see later on that images can easily be represented as matrices







Image Acquisition

Images are typically generated by illuminating a scene and absorbing the energy reflected by the objects in that scene



- Typical notions of illumination and scene can be way off:
 - X-rays of a skeleton
 - Ultrasound of an unborn baby
 - Electro-microscopic images of molecules




Image Sensing

Incoming energy lands on a sensor material responsive to that type of energy and this generates a voltage

Collections of sensors are arranged to


capture images



Imaging Sensor



Line of Image Sensors



Array of Image Sensors

Image Sensing






Image Sampling And Quantisation

A digital sensor can only measure a limited number of **samples** at a **discrete** set of energy levels

Quantisation is the process of converting a continuous **analogue** signal into a digital representation of this signal






Image Sampling And Quantisation








Image Sampling And Quantisation






Sampling




Image Sampling And Quantisation (cont...)


Remember that a digital image is always only an **approximation** of a real world scene


















```
Origin
         · .5 .5 .5 · ·
           .5.5
 0
```



Spatial Resolution

The spatial resolution of an image is determined by how sampling was carried out Spatial resolution simply refers to the smallest discernable detail in an image

- Vision specialists will often talk about pixel size
- Graphic designers will talk about dots per inch (DPI)









































Spatial Resolution (cont...)






Intensity Level Resolution

Intensity level resolution refers to the number of intensity levels used to represent the image

- The more intensity levels used, the finer the level of detail discernable in an image
- Intensity level resolution is usually given in terms of the number of bits used to store each intensity level

Number of Bits	Number of Intensity Levels	Examples
1	2	0, 1
2	4	00, 01, 10, 11
4	16	0000, 0101, 1111
8	256	00110011, 01010101
16	65,536	1010101010101010





































Resolution: How Much Is Enough?

The big question with resolution is always how much is enough?

- This all depends on what is in the image and what you would like to do with it
- Key questions include
 - Does the image look aesthetically pleasing?
 - Can you see what you need to see within the image?

Resolution: How Much Is Enough? (cont...)





The picture on the right is fine for counting the number of cars, but not for reading the number plate









Low Detail

Medium Detail


High Detail













2.5.1 Neighbors of a Pixel

A pixel p at coordinates (x, y) has four *horizontal* and *vertical* neighbors whose coordinates are given by

$$(x + 1, y), (x - 1, y), (x, y + 1), (x, y - 1)$$

This set of pixels, called the 4-neighbors of p, is denoted by $N_4(p)$. Each pixel is a unit distance from (x, y), and some of the neighbors of p lie outside the digital image if (x, y) is on the border of the image.


The four *diagonal* neighbors of p have coordinates

$$(x + 1, y + 1), (x + 1, y - 1), (x - 1, y + 1), (x - 1, y - 1)$$

and are denoted by $N_D(p)$. These points, together with the 4-neighbors, are called the 8-neighbors of p, denoted by $N_8(p)$. As before, some of the points in $N_D(p)$ and $N_8(p)$ fall outside the image if (x, y) is on the border of the image.

Adjacency

- three types of adjacency:
- (a) 4-adjacency. Two pixels p and q with values from V are 4-adjacent if q is in the set $N_4(p)$.
- **(b)** 8-adjacency. Two pixels p and q with values from V are 8-adjacent if q is in the set $N_8(p)$.
- (c) m-adjacency (mixed adjacency). Two pixels p and q with values from V are m-adjacent if
 - (i) q is in $N_4(p)$, or
 - (ii) q is in $N_D(p)$ and the set $N_4(p) \cap N_4(q)$ has no pixels whose values are from V.



a b c

FIGURE 2.26 (a) Arrangement of pixels; (b) pixels that are 8-adjacent (shown dashed) to the center pixel; (c) *m*-adjacency.

Connectivity

- Two pixels p and q are said to be *connected* in S if there exists a path between them consisting entirely of pixels in S.
- For any pixel p in S, the *set* of pixels that are connected to it in S is called a *connected component* of S.
- If it only has one connected component, then set *S* is called a *connected set*.

- Regions

• Let *R* be a subset of pixels in an image. We call *R* a *region* of the image if *R* is a connected set.

Boundaries

• The *boundary* (also called *border* or *contour*) of a region *R* is the set of pixels in the region that have one or more neighbors that are not in *R*.

Distance Measures

For pixels p, q, and z, with coordinates (x, y), (s, t), and (v, w), respectively, D is a distance function or metric if

(a)
$$D(p,q) \ge 0$$
 $(D(p,q) = 0$ iff $p = q)$,

(b)
$$D(p,q) = D(q,p)$$
, and

(c)
$$D(p, z) \le D(p, q) + D(q, z)$$
.

The Euclidean distance between p and q is defined as

$$D_e(p,q) = \left[(x-s)^2 + (y-t)^2 \right]^{\frac{1}{2}}.$$
 (2.5-1)

For this distance measure, the pixels having a distance less than or equal to some value r from (x, y) are the points contained in a disk of radius r centered at (x, y). The D_4 distance (also called city-block distance) between p and q is defined as

$$D_4(p,q) = |x-s| + |y-t|. (2.5-2)$$

In this case, the pixels having a D_4 distance from (x, y) less than or equal to some value r form a diamond centered at (x, y). For example, the pixels with D_4 distance ≤ 2 from (x, y) (the center point) form the following contours of constant distance:

The pixels with $D_4 = 1$ are the 4-neighbors of (x, y).

The D_8 distance (also called chessboard distance) between p and q is defined as

$$D_8(p,q) = \max(|x-s|,|y-t|). \tag{2.5-3}$$

In this case, the pixels with D_8 distance from (x, y) less than or equal to some value r form a square centered at (x, y). For example, the pixels with D_8 distance ≤ 2 from (x, y) (the center point) form the following contours of constant distance:

```
2 2 2 2 2
2 1 1 1 2
2 1 0 1 2
2 1 1 1 2
2 2 2 2 2
```

The pixels with $D_8 = 1$ are the 8-neighbors of (x, y).

Summary

We have looked at:

- Human visual system
- Light and the electromagnetic spectrum
- Image representation
- Image sensing and acquisition
- Sampling, quantisation and resolution
- Basic relationship between pixels