

POE Dome



TECHNICAL SPECIFICATIONS

Model No:	AD-90NRP5DP
Product Name	POE Dome Plastic (Series)
Manufacturer	ADIANCE
Make	ARCIS AI
Model	POE DOME CAMERA (PLASTIC)
Image Sensor	5.0M 1/2.7" Black light illumination CMOS sensor, color 0.0001Lux@F1.2, black/white0.0001Lux@F1.2
Total Pixels	5MP
Day/Night	Auto IR-CUT
Lens	2.8mm
Lens Type	Fixed
Shutter	1/50(1/60) S To 1/10,000s
IR Distance	Up To 30M
Dynamic Range	HDR

Model No:	AD-90NRP5DP
Video Compression	H.265/AI H.265+(Compatible With H.265/H.264), Support Dual Stream, AVI;0.1M~8Mbps Variable; 1~30fps Variable
Image Output	Mainstream: 5MP2880*1616@25fps; 4MP2560*1440@25fps; 2MP1920*1080@25fps; Sub-Stream: 800*448@25fps
Min Resolution	Mainstream: 2880 X 1616
Frame Rate	Max 30fps
Audio Compression	G.711
Audio Input	Yes, Built in Mic
Audio Output	Yes, Built In Speaker
Protocols	HTTPS, RTSPS
ONVIF	Support
Ethernet	Yes, 10-100M Adaptive
Network Interface	1*RJ45 10/100M Adaptive Ethernet Port
POE	Support
SD Card	Support
Reliability	Comprehensive Lightning Protection, 72 Hours -10°C~65°C High-Temperature Stable And Reliable Testing
Power Supply	DC12V, 1A
Protection	IP67, 4000V Lightning protection



Scan to see how
our AI works



IS 13252(part 1)/
IEC 60950-1



R-72003735
www.bis.gov.in

