

IP Dome



Side



Front

TECHNICAL SPECIFICATIONS

Model No: AD-90NRE5DP

Product Name IP Dome Plastic (Series)

Manufacturer ADIANCE

Make ARCIS AI

Model IP DOME CAMERA (PLASTIC)

Image Sensor 5.0M 1/2.7" Black light illumination CMOS sensor, color 0.0001Lux@F1.2, black/white 0.0001Lux@F1.2

Total Pixels 5MP

Day/Night Auto IR-CUT

Lens 2.8mm

Lens Type Fixed

Shutter 1/50(1/60) S To 1/10,000s

IR Distance Up To 30M

Dynamic Range HDR

Model No:	AD-90NRE5DP
Video Compression	H.265AI/H.265+ (Compatible with H.265/H.264), Support Dual Stream, AVI; 0.1M~8Mbps Variable; 1~30f/S Variable
Image Output	Mainstream: 5MP 2880*1616@25fps 4MP 2560*1440@25fps 2MP 1920*1080@25fps; Sub-Stream: 800*448@25fps
Min Resolution	Mainstream: 2880 X 1616
Frame Rate	Max 30fps
Audio Compression	G.711
Audio Input	Yes, Built in Mic
Audio Output	Yes, Built In Speaker
Protocols	HTTPS, RTSPS
ONVIF	Support
Ethernet	Yes, 10-100M Adaptive
Network Interface	1*RJ45 10/100M Adaptive Ethernet Port
SD Card	Support
Reliability	Comprehensive Lightning Protection, 72 Hours -10°C~65°C High-Temperature Stable And Reliable Testing
Power Supply	DC12V, 1A
Protection	IP67, 4000V Lightning protection



Scan to see how
our AI works



IS 13252(part 1)/
IEC 60950-1



R-72003735
www.bis.gov.in

