

POE Bullet



Side



Front



Top

TECHNICAL SPECIFICATIONS

Model No: AD-90NRP5BM

| | |
|---------------|--|
| Product Name | POE Bullet Metal (Series) |
| Manufacturer | ADIANCE |
| Make | ARCIS AI |
| Model | POE BULLET CAMERA (METAL) |
| Image Sensor | 5.0M 1/2.7" Black light illumination CMOS sensor, color 0.0001Lux@F1.2, black/white 0.0001Lux@F1.2 |
| Total Pixels | 5MP |
| Day/Night | Auto IR-CUT |
| Lens | 2.8mm |
| Lens Type | Fixed |
| Shutter | 1/50(1/60) S To 1/10,000s |
| IR Distance | Up To 30M |
| Dynamic Range | HDR |

| | |
|-------------------|--|
| Model No: | AD-90NRP5BM |
| Video Compression | H.265AI/H.265+(CompatiblewithH.265/H.264), Support Dual Stream, AVI;0.1M~8Mbps Variable;1~30f/S Variable |
| Image Output | Mainstream: 5MP2880*1616@25fps 4MP2560*1440@25fps 2MP1920*1080@25fps; Sub-Stream:800*448@25fps |
| Min Resolution | Mainstream: 2880 X 1616 |
| Frame Rate | Max 30fps |
| Audio Compression | G.711 |
| Audio Input | Yes, Built in Mic |
| Audio Output | Yes, Built In Speaker |
| Protocols | HTTPS, RTSPS |
| ONVIF | Support |
| Ethernet | Yes, 10-100M Adaptive |
| Network Interface | 1*RJ45 10/100M Adaptive Ethernet Port |
| POE | Support |
| SD Card | Support |
| Reliability | Comprehensive Lightning Protection, 72 Hours -10°C~65°C High-Temperature Stable And Reliable Testing |
| Power Supply | DC12V, 1A |
| Protection | IP67, 4000V Lightning protection |



Scan to see how
our AI works



IS 13252(part 1)/
IEC 60950-1

