

Cocoa Pods

Questions for Cocoa pods

1. Explain the pod integration cycle.

Ans - Pod can attain the following states:

1. Pending - The pod is accepted by kubernetes API but hasn't been scheduled yet.
2. Creating - The image is pulled from a cloud based repository by the Virtual Machine Node, once its done the containers transitions to running state.
3. Running - The pod is scheduled on the node with atleast one of its container being run and other being created.
4. Succeeded - All the containers in the pod has been successfully executed without the program crashing.
5. Failed - All containers have been exited with atleast one container having a non-zero exit status.
6. Crash loop Back off - In this container fails to start and is scheduled again for execution.

2. How to update only a single pod.

Ans - A single pod can be updated using the command



pod update podName

```
[ttn@rahul-sharma1:CocoaPods] $ pod update Alamofire
Updating local specs repositories
Analyzing dependencies
Downloading dependencies
Generating Pods project
Integrating client project
Pod installation complete! There are 2 dependencies from the Podfile and 2 total
pods installed.

[!] Automatically assigning platform `iOS` with version `13.5` on target `CocoaP
ods` because no platform was specified. Please specify a platform for this targe
t in your Podfile. See `https://guides.cocoapods.org/syntax/podfile.html#platfor
```

3. Delete a pod from project.

Ans - To delete a pod from the project the following steps can be followed

1. Delete the entry of the pod from the pod file
2. Delete the ./Pods directory
3. Rerun Pod Install

4. update to a particular lib version.

Ans - In this case we can simply mention the version name with pod name



```
pod 'SVProgressHUD', '2.2.5'
```