


**Task 14.1 : Create a Network Topology where there are three systems and the architecture is as follows:**



First Check the IPs of the Three Systems

## System A

```
root@MiWiFi-R3L-srv:~  
File Edit View Search Terminal Help  
[root@MiWiFi-R3L-srv ~]# ifconfig  
enp0s3: flags=4163<UP,BROADCAST,RUNNING,MULTICAST> mtu 1500  
    inet 192.168.31.195 netmask 255.255.255.0 broadcast 192.168.31.255  
    inet6 fe80::dd42:7df:88f4:e828 prefixlen 64 scopeid 0x20<link>  
    ether 08:00:27:2c:04:a8 txqueuelen 1000 (Ethernet)  
    RX packets 2087 bytes 2941628 (2.8 MiB)  
    RX errors 0 dropped 0 overruns 0 frame 0  
    TX packets 522 bytes 46574 (45.4 KiB)  
    TX errors 0 dropped 0 overruns 0 carrier 0 collisions 0
```

## System B

```
[root@MiWiFi-R3L-srv ~]# ifconfig  
enp0s3: flags=4163<UP,BROADCAST,RUNNING,MULTICAST> mtu 1500  
    inet 192.168.31.181 netmask 255.255.255.0 broadcast 192.168.31.255  
    inet6 fe80::99d7:dedc:4930:9766 prefixlen 64 scopeid 0x20<link>  
    ether 08:00:27:11:a6:d4 txqueuelen 1000 (Ethernet)  
    RX packets 135 bytes 20753 (20.2 KiB)  
    RX errors 0 dropped 0 overruns 0 frame 0  
    TX packets 90 bytes 12429 (12.1 KiB)  
    TX errors 0 dropped 0 overruns 0 carrier 0 collisions 0
```

## System C

```
[root@MiWiFi-R3L-srv ~]# ifconfig
enp0s3: flags=4163<UP,BROADCAST,RUNNING,MULTICAST> mtu 1500
    inet 192.168.31.87 netmask 255.255.255.0 broadcast 192.168.31.255
    inet6 fe80::2c14:9b8d:9ab6:1894 prefixlen 64 scopeid 0x20<link>
    ether 08:00:27:a3:c1:86 txqueuelen 1000 (Ethernet)
    RX packets 165 bytes 26629 (26.0 KiB)
    RX errors 0 dropped 0 overruns 0 frame 0
    TX packets 73 bytes 8897 (8.6 KiB)
    TX errors 0 dropped 0 overruns 0 carrier 0 collisions 0
```

## Giving all the Systems a temporary Ip which will revert back on Reboot

### System A

```
[root@MiWiFi-R3L-srv ~]# ifconfig enp0s3 192.168.31.1
[root@MiWiFi-R3L-srv ~]# ifconfig
enp0s3: flags=4163<UP,BROADCAST,RUNNING,MULTICAST> mtu 1500
    inet 192.168.31.1 netmask 255.255.255.0 broadcast 192.168.31.255
    inet6 fe80::dd42:7df:88f4:e828 prefixlen 64 scopeid 0x20<link>
    ether 08:00:27:2c:04:a8 txqueuelen 1000 (Ethernet)
    RX packets 2101 bytes 2942618 (2.8 MiB)
    RX errors 0 dropped 0 overruns 0 frame 0
    TX packets 540 bytes 48878 (47.7 KiB)
    TX errors 0 dropped 0 overruns 0 carrier 0 collisions 0
```

### System B

```
[root@MiWiFi-R3L-srv ~]# ifconfig enp0s3 192.168.31.2
[root@MiWiFi-R3L-srv ~]# ifconfig
enp0s3: flags=4163<UP,BROADCAST,RUNNING,MULTICAST> mtu 1500
    inet 192.168.31.2 netmask 255.255.255.0 broadcast 192.168.31.255
    inet6 fe80::99d7:dedc:4930:9766 prefixlen 64 scopeid 0x20<link>
    ether 08:00:27:11:a6:d4 txqueuelen 1000 (Ethernet)
    RX packets 165 bytes 23867 (23.3 KiB)
    RX errors 0 dropped 0 overruns 0 frame 0
    TX packets 110 bytes 14943 (14.5 KiB)
    TX errors 0 dropped 0 overruns 0 carrier 0 collisions 0
```

## System C

```
[root@MiWiFi-R3L-srv ~]# ifconfig enp0s3 192.168.31.3
[root@MiWiFi-R3L-srv ~]# ifconfig
enp0s3: flags=4163<UP,BROADCAST,RUNNING,MULTICAST> mtu 1500
    inet 192.168.31.3 netmask 255.255.255.0 broadcast 192.168.31.255
    inet6 fe80::2c14:9b8d:9ab6:1894 prefixlen 64 scopeid 0x20<link>
    ether 08:00:27:a3:c1:86 txqueuelen 1000 (Ethernet)
    RX packets 203 bytes 31267 (30.5 KiB)
    RX errors 0 dropped 0 overruns 0 frame 0
    TX packets 91 bytes 11261 (10.9 KiB)
    TX errors 0 dropped 0 overruns 0 carrier 0 collisions 0
```

**Adjust the Routing Table of System A so that it can ping to both systems**

```
[root@MiWiFi-R3L-srv ~]# route -n
Kernel IP routing table
Destination Gateway Genmask Flags Metric Ref Use Iface
192.168.122.0 0.0.0.0 255.255.255.0 U 0 0 0 virbr0
[root@MiWiFi-R3L-srv ~]# route add -net 192.168.31.0/24 enp0s3
[root@MiWiFi-R3L-srv ~]# route -n
Kernel IP routing table
Destination Gateway Genmask Flags Metric Ref Use Iface
192.168.31.0 0.0.0.0 255.255.255.0 U 0 0 0 enp0s3
192.168.122.0 0.0.0.0 255.255.255.0 U 0 0 0 virbr0
```

**Adjust the Routing Table of System B so that it can ping to A but not to C**

```
[root@MiWiFi-R3L-srv ~]# route -n
Kernel IP routing table
Destination Gateway Genmask Flags Metric Ref Use Iface
192.168.122.0 0.0.0.0 255.255.255.0 U 0 0 0 virbr0
[root@MiWiFi-R3L-srv ~]# route add -net 192.168.31.0/31 enp0s3
[root@MiWiFi-R3L-srv ~]# route -n
Kernel IP routing table
Destination Gateway Genmask Flags Metric Ref Use Iface
192.168.31.0 0.0.0.0 255.255.255.254 U 0 0 0 enp0s3
192.168.122.0 0.0.0.0 255.255.255.0 U 0 0 0 virbr0
[root@MiWiFi-R3L-srv ~]#
```



## Adjust the Routing Table of System C so that it can ping to A but not to B

```
[root@MiWiFi-R3L-srv ~]# route -n
Kernel IP routing table
Destination      Gateway          Genmask          Flags Metric Ref    Use Iface
192.168.122.0    0.0.0.0         255.255.255.0    U        0      0        0 virbr0
[root@MiWiFi-R3L-srv ~]# route add -net 192.168.31.0/31 enp0s3
[root@MiWiFi-R3L-srv ~]# route -n
Kernel IP routing table
Destination      Gateway          Genmask          Flags Metric Ref    Use Iface
192.168.31.0     0.0.0.0         255.255.255.254  U        0      0        0 enp0s3
192.168.122.0    0.0.0.0         255.255.255.0    U        0      0        0 virbr0
[root@MiWiFi-R3L-srv ~]#
```

## Checking Connection in System A – It can ping to both Systems

```
[root@MiWiFi-R3L-srv ~]# ping 192.168.31.2
PING 192.168.31.2 (192.168.31.2) 56(84) bytes of data.
64 bytes from 192.168.31.2: icmp_seq=1 ttl=64 time=0.642 ms
64 bytes from 192.168.31.2: icmp_seq=2 ttl=64 time=0.278 ms
64 bytes from 192.168.31.2: icmp_seq=3 ttl=64 time=0.283 ms
^C
--- 192.168.31.2 ping statistics ---
3 packets transmitted, 3 received, 0% packet loss, time 30ms
rtt min/avg/max/mdev = 0.278/0.401/0.642/0.170 ms
[root@MiWiFi-R3L-srv ~]# ping 192.168.31.3
PING 192.168.31.3 (192.168.31.3) 56(84) bytes of data.
64 bytes from 192.168.31.3: icmp_seq=1 ttl=64 time=1.00 ms
64 bytes from 192.168.31.3: icmp_seq=2 ttl=64 time=0.357 ms
64 bytes from 192.168.31.3: icmp_seq=3 ttl=64 time=0.329 ms
^C
--- 192.168.31.3 ping statistics ---
3 packets transmitted, 3 received, 0% packet loss, time 27ms
rtt min/avg/max/mdev = 0.329/0.562/1.001/0.310 ms
[root@MiWiFi-R3L-srv ~]#
```

## Checking Connection in System B – It can ping to A but not to C

```
[root@MiWiFi-R3L-srv ~]# ping 192.168.31.3
connect: Network is unreachable
[root@MiWiFi-R3L-srv ~]# ping 192.168.31.1
PING 192.168.31.1 (192.168.31.1) 56(84) bytes of data.
64 bytes from 192.168.31.1: icmp_seq=1 ttl=64 time=17.3 ms
64 bytes from 192.168.31.1: icmp_seq=2 ttl=64 time=4.32 ms
64 bytes from 192.168.31.1: icmp_seq=3 ttl=64 time=5.21 ms
64 bytes from 192.168.31.1: icmp_seq=4 ttl=64 time=46.0 ms
^C
--- 192.168.31.1 ping statistics ---
4 packets transmitted, 4 received, 0% packet loss, time 16ms
rtt min/avg/max/mdev = 4.320/18.198/46.004/16.848 ms
[root@MiWiFi-R3L-srv ~]# ping 192.168.31.3
connect: Network is unreachable
```

## Checking Connection in System C – It can ping to A but not to B

```
[root@MiWiFi-R3L-srv ~]# ping 192.168.31.1
PING 192.168.31.1 (192.168.31.1) 56(84) bytes of data.
64 bytes from 192.168.31.1: icmp_seq=1 ttl=64 time=38.6 ms
64 bytes from 192.168.31.1: icmp_seq=2 ttl=64 time=0.900 ms
64 bytes from 192.168.31.1: icmp_seq=3 ttl=64 time=30.3 ms
64 bytes from 192.168.31.1: icmp_seq=4 ttl=64 time=8.83 ms
^C
--- 192.168.31.1 ping statistics ---
4 packets transmitted, 4 received, 0% packet loss, time 48ms
rtt min/avg/max/mdev = 0.900/19.658/38.573/15.335 ms
[root@MiWiFi-R3L-srv ~]# ping 192.168.31.2
connect: Network is unreachable
```

**Hence the Architecture is Created**