

RolPlay Database Documentation

1. Table Descriptions

r_app_features

- **Description:** Stores application navigation modules, page URLs, and shortcodes for menu building and permission control.

r_app_settings

- **Description:** Stores global system configuration options including default providers, site language, and access lock toggles.

r_avatar

- **Description:** Stores visual avatar model definitions, gender tags, and rendering scripts (e.g., HeyGen, SitePal).

r_avatar_provider

- **Description:** Catalog of supported 3D and video avatar service providers.

r_client

- **Description:** Stores enterprise tenant/organization accounts, authentication details, logos, and max simulation time limits.

r_client_activity

- **Description:** Stores administrative audit logs and operational page activity tracking for client accounts.

r_client_avatar

- **Description:** Maps avatar provider and model restrictions assigned to specific client organizations.

r_client_feature_access

- **Description:** Maps platform feature permissions directly to client organization accounts.

r_eval_session_segments

- **Description:** Tracks start/end execution timestamps for content segments evaluated during an evaluation session.

r_eval_sessions

- **Description:** Stores structured evaluation session metadata linking clients, simulators, and content segments.

r_llm

- **Description:** Catalog of supported Large Language Model codes, provider mappings, and failsafe backup options.

r_llm_provider

- **Description:** Catalog of supported AI model vendors (e.g., OpenAI, Anthropic).

r_recent_sims

- **Description:** Tracks quick-access history of recently launched simulations per client account.

r_segmented_content

- **Description:** Stores scenario content modules, instruction prompts, question banks, and templates for certification levels.

r_sim_attempts

- **Description:** Tracks user simulator attempt counters to enforce maximum attempt limits.

r_simulator

- **Description:** Stores core simulator scenario configurations, language options, interaction types, and assigned models.

r_simulator_addl_content

- **Description:** Stores reference files, external URLs, or supplemental text attached to a simulator.

r_simulator_ai_to_ai

- **Description:** Configures avatar providers and male/female TTS voice settings for autonomous AI-to-AI simulations.

r_simulator_ai_to_ai_prompt

- **Description:** Stores prompt directives guiding both primary and secondary AI participants in AI-to-AI runs.

r_simulator_avatar

- **Description:** Stores scenario-specific avatar model and provider restrictions.

r_simulator_client_access

- **Description:** Maps simulator scenario launch entitlements to specific client organizations.

r_simulator_closing_prompt

- **Description:** Stores post-session evaluation prompts, scoring rules, context strings, and HTML report templates.

r_simulator_direct_access

- **Description:** Stores direct launch shortcut configurations including pre-selected avatars, accents, and languages.

r_simulator_form_element

- **Description:** Stores dynamic user input field definitions (labels, placeholders, types) collected prior to scenario launch.

r_simulator_interaction_prompt

- **Description:** Stores live AI system prompts, character personas, DOs/DON'Ts lists, and variable placeholders.

r_simulator_replace_token

- **Description:** Stores reusable static or randomized key-value replacement tokens for prompt templates.

r_simulator_retro_prompt

- **Description:** Stores turn-by-turn evaluation prompts and HTML templates used to analyze individual user responses.

r_simulator_stage

- **Description:** Defines sequential stage and phase progressions within complex simulator scenarios.

r_simulator_termination_words

- **Description:** Stores exit trigger words/phrases that automatically end a simulation session upon detection.

r_sitepal_accents

- **Description:** Maps engine, language, and voice IDs specifically for SitePal speech output rendering.

r_stt_language

- **Description:** Catalog of supported Speech-to-Text languages and provider associations.

r_stt_provider

- **Description:** Catalog of supported Speech-to-Text service providers.

r_tts_language

- **Description:** Catalog of supported Text-to-Speech languages, gender tags, and provider associations.

r_tts_provider

- **Description:** Catalog of supported Text-to-Speech voice synthesis providers.

r_user

- **Description:** Stores user accounts, authentication hashes, contact info, designations, and organizational hierarchy links.

r_user_feature_access

- **Description:** Maps platform feature permissions directly to individual user accounts.

r_user_session

- **Description:** Master execution log storing session state, scores, pass/fail status, ratings, and closing analysis text.

r_user_session_details

- **Description:** Stores turn-by-turn conversation transcripts, audio/video file paths, and feedback per exchange.

r_user_simulator_access

- **Description:** Maps simulator scenario launch entitlements directly to individual user accounts.

2. Indexes and Foreign Keys

Table Name	Indexes	Foreign Keys
r_app_features	PRIMARY (ID), idx_page_url (page_url)	<i>None</i>
r_app_settings	PRIMARY (ID)	<i>None</i>
r_avatar	PRIMARY (ID), provider_id	provider_id → r_avatar_provider.ID
r_avatar_provider	PRIMARY (ID)	<i>None</i>
r_client	PRIMARY (ID), api_key_password (api_key, password)	<i>None</i>
r_client_activity	PRIMARY (id), fk_r_client_activity_client (client_id)	client_id → r_client.ID
r_client_avatar	PRIMARY (ID), client_id, avatar_provider_id	avatar_provider_id → r_avatar_provider.ID client_id → r_client.ID
r_client_feature_access	PRIMARY (ID), client_id, feature_id	client_id → r_client.ID feature_id → r_app_features.ID

Table Name	Indexes	Foreign Keys
r_eval_session_segments	PRIMARY (ID), idx_session_id, idx_segment_id	segment_id → r_segmented_content.ID session_id → r_eval_sessions.ID
r_eval_sessions	PRIMARY (ID), idx_client_id, idx_sim_id, idx_content_id	client_id → r_client.ID content_id → r_segmented_content.ID sim_id → r_simulator.ID
r_llm	PRIMARY (ID), provider_id, model_code	provider_id → r_llm_provider.ID
r_llm_provider	PRIMARY (ID)	<i>None</i>
r_recent_sims	PRIMARY (id), uq_client_sim (client_id, sim_id), idx_client_created	client_id → r_client.ID sim_id → r_simulator.ID

Table Name	Indexes	Foreign Keys
r_segmented_content	PRIMARY (ID), fk_segmented_content_simulator (sim_id)	sim_id → r_simulator.ID
r_sim_attempts	PRIMARY (ID), user_id, sim_id	user_id → r_user.ID sim_id → r_simulator.ID
r_simulator	PRIMARY (ID), created_by, llm_provider_id, llm_model_id, category	created_by → r_client.ID llm_provider_id → r_llm_provider.ID llm_model_id → r_llm.ID
r_simulator_addl_content	PRIMARY (ID), simulator_id	simulator_id → r_simulator.ID
r_simulator_ai_to_ai	PRIMARY (ID), simulator_id, user_avatar_provider_id, user_avatar_id, male_voice_tts_provider_id, female_voice_tts_provider_id, male_voice_tts_id, female_voice_tts_id	simulator_id → r_simulator.ID

Table Name	Indexes	Foreign Keys
		user_avatar_provider_id → r_avatar_provider.ID user_avatar_id → r_avatar.ID male_voice_tts_provider_id → r_tts_provider.ID female_voice_tts_provider_id → r_tts_provider.ID male_voice_tts_id → r_tts_language.ID female_voice_tts_id → r_tts_language.ID
r_simulator_ai_to_ai_prompt	PRIMARY (ID), simulator_id	simulator_id → r_simulator.ID

Table Name	Indexes	Foreign Keys
r_simulator_avatar	PRIMARY (ID), simulator_id, avatar_provider_id	simulator_id → r_simulator.ID avatar_provider_id → r_avatar_provider.ID
r_simulator_client_access	PRIMARY (ID), simulator_id, client_id	simulator_id → r_simulator.ID client_id → r_client.ID
r_simulator_closing_prompt	PRIMARY (ID), simulator_id	simulator_id → r_simulator.ID
r_simulator_direct_accesses	PRIMARY (ID), simulator_id, avatar_provider_id, avatar_id	simulator_id → r_simulator.ID avatar_provider_id → r_avatar_provider.ID avatar_id → r_avatar.ID
r_simulator_form_element	PRIMARY (ID), simulator_id_display_order (simulator_id, display_order)	simulator_id → r_simulator.ID

Table Name	Indexes	Foreign Keys
r_simulator_interaction_prompt	PRIMARY (ID), simulator_id	simulator_id → r_simulator.ID
r_simulator_replace_token	PRIMARY (ID), simulator_id	simulator_id → r_simulator.ID
r_simulator_retro_prompt	PRIMARY (ID), simulator_id	simulator_id → r_simulator.ID
r_simulator_stage	PRIMARY (ID), simulator_id_sequence (simulator_id, sequence)	simulator_id → r_simulator.ID
r_simulator_termination_words	PRIMARY (ID), simulator_id	simulator_id → r_simulator.ID
r_sitepal_accents	PRIMARY (ID)	<i>None</i>
r_stt_language	PRIMARY (ID), provider_id	provider_id → r_stt_provider.ID
r_stt_provider	PRIMARY (ID)	<i>None</i>
r_tts_language	PRIMARY (ID), provider_id	provider_id → r_tts_provider.ID
r_tts_provider	PRIMARY (ID)	<i>None</i>
r_user	PRIMARY (ID), email_password, client_id_sequence, parent_id_sequence	client_id → r_client.ID

Table Name	Indexes	Foreign Keys
r_user_feature_access	PRIMARY (ID), user_id, feature_id	user_id → r_user.ID feature_id → r_app_features.ID
r_user_session	PRIMARY (ID), user_id, simulator_id, sim_stage_id, avatar_provider_id, avatar_model_id, user_id_eval_session_id_segment_num, user_id_usecase_segment_id	user_id → r_user.ID simulator_id → r_simulator.ID sim_stage_id → r_simulator_stage.ID avatar_provider_id → r_avatar_provider.ID avatar_model_id → r_avatar.ID
r_user_session_details	PRIMARY (ID), session_id_sequence (session_id, sequence)	session_id → r_user_session.ID
r_user_simulator_access	PRIMARY (ID), user_id, simulator_id, client_id	user_id → r_user.ID

Table Name	Indexes	Foreign Keys
		simulator_id → r_simulator.ID client_id → r_client.ID

3. Deletion Rules

RESTRICT Rules (Deletions Blocked)

Rows cannot be deleted from the parent table if dependent rows exist in child tables:

- **r_user**: Blocked if referenced by r_user_session (user_id).
- **r_client**: Blocked if referenced by r_user (client_id) or r_simulator (created_by).
- **r_simulator**: Blocked if referenced by r_user_session (simulator_id).
- **r_simulator_stage**: Blocked if referenced by r_user_session (sim_stage_id).
- **r_avatar_provider**: Blocked if referenced by r_client_avatar, r_simulator_avatar, r_simulator_direct_access, r_simulator_ai_to_ai, or r_user_session.
- **r_avatar**: Blocked if referenced by r_simulator_direct_access, r_simulator_ai_to_ai, or r_user_session.
- **r_llm_provider**: Blocked if referenced by r_simulator (llm_provider_id).
- **r_llm**: Blocked if referenced by r_simulator (llm_model_id).
- **r_stt_provider**: Blocked if referenced by r_stt_language (provider_id).
- **r_tts_provider**: Blocked if referenced by r_tts_language (provider_id) or r_simulator_ai_to_ai.
- **r_tts_language**: Blocked if referenced by r_simulator_ai_to_ai.

- **r_segmented_content:** Blocked if referenced by r_eval_session_segments or r_eval_sessions.

CASCADE Rules (Automatic Child Deletion)

Deleting a row from the parent table automatically deletes matching rows in dependent tables:

- **r_client:** Automatically deletes from r_client_activity, r_client_avatar, r_client_feature_access, r_eval_sessions, r_recent_sims, r_simulator_client_access, and r_user_simulator_access.
- **r_user:** Automatically deletes from r_sim_attempts, r_user_feature_access, and r_user_simulator_access.
- **r_simulator:** Automatically deletes from r_eval_sessions, r_recent_sims, r_segmented_content, r_sim_attempts, r_simulator_addl_content, r_simulator_ai_to_ai, r_simulator_ai_to_ai_prompt, r_simulator_avatar, r_simulator_client_access, r_simulator_closing_prompt, r_simulator_direct_access, r_simulator_form_element, r_simulator_interaction_prompt, r_simulator_replace_token, r_simulator_retro_prompt, r_simulator_stage, r_simulator_termination_words, and r_user_simulator_access.
- **r_user_session:** Automatically deletes from r_user_session_details.
- **r_eval_sessions:** Automatically deletes from r_eval_session_segments.
- **r_avatar_provider:** Automatically deletes from r_avatar.
- **r_llm_provider:** Automatically deletes from r_llm.
- **r_app_features:** Automatically deletes from r_client_feature_access and r_user_feature_access.