



MANUAL TOOLS COMPANY

Manufacturer of Coke Oven Machinery

PRODUCT BROCHURE



CONVEYOR COMPONENTS

Idlers, Rollers & Pulleys - Industrial Handling Systems

600 - 1400 mm

BELT WIDTHS

EN-8

SHAFT MATERIAL

Sealed

BALL BEARINGS



Ravindra Kr. Agarwal, Proprietor

Dhanbad, Jharkhand, India | +91 9430707348

www.manualtoolsco.com

Conveyor Components

Idlers, Rollers & Pulleys - Industrial Handling Systems

AT A GLANCE

Components for belt conveyors in coke oven plants, coal washeries and power plants: carrying idlers, return rollers, rubber-ringed impact rollers, and head and tail pulleys in plain steel or with rubber lagging. Rollers use seamless pipe on bright steel (EN-8) shafts with sealed ball bearings to keep dust out.



KEY SPECIFICATIONS



BELT WIDTHS
600 - 1400 mm



BEARINGS
Sealed



MATERIAL
Seamless Pipe



APPLICATION
Heavy Duty

SPECIFICATIONS

Belt Width Compatibility	600 - 1400 mm
Shaft Material	Bright Steel Bar (EN-8)
Bearings	Ball Bearings (6204, 6205, 6305)
Roller Pipe	Heavy Gauge Seamless Steel
Pulley Lagging	Diamond Groove or Plain
Idler Frames	With Rollers or as Spares

DESIGN & DURABILITY

- ✓ Carrying idlers in 30 degree troughing sets
- ✓ Return rollers with a smooth surface to prevent belt wear
- ✓ Impact rollers with shock-absorbing rubber rings
- ✓ Head and tail pulleys with key-based locking assemblies
- ✓ Coupling pair available for the head pulley
- ✓ Bulk orders taken for plant-wide replacement

BUYING INFORMATION

Lead time	Standard sizes (800 mm and 1000 mm rollers) are often in stock. Custom pulleys usually take 2 - 3 weeks.
Warranty	1 year, as on all our machinery.
Bulk orders	Taken for plant-wide replacement of idlers, rollers and pulleys.
Custom builds	Sizes and lagging matched to your plant and drawings.

HOW IT WORKS

01 Loading Point

Material drops onto the belt over impact rollers, whose rubber rings absorb the shock and stop falling lumps damaging the belt.

02 Carrying Run

Carrying idlers in 30 degree troughing sets shape the belt into a trough so it holds its load, running on sealed bearings that keep dust out.

03 Return Run and Drive

Return rollers support the empty underside of the belt with a smooth face, while the head pulley drives the belt and the tail pulley keeps it tensioned.

APPLICATIONS

Coke Oven Plants	Belt conveyors carrying coal to the ovens and coke away from them.
Coal Washeries	Abrasive, wet duty where sealed bearings and lagged pulleys hold up.
Power Plants	Continuous fuel handling from the yard to the bunkers.

COMMON QUESTIONS

What belt sizes do you support?

We manufacture components for all standard belt widths: 600 mm, 750 mm, 800 mm, 900 mm, 1000 mm, 1200 mm and 1400 mm.

Are the impact rollers rubberized?

Yes. Our impact rollers have robust rubber rings designed to absorb the shock of falling material at hopper loading points.

Do pulleys come with lagging?

We offer both plain steel face pulleys and rubber-lagged pulleys (diamond groove or plain) for better traction in wet conditions.

Can you supply brackets?

Yes. We can supply the idler frames (brackets) along with the rollers or separately as spares.

What is the delivery time?

Standard sizes such as 800 mm and 1000 mm rollers are often in stock. Custom pulleys typically take 2 - 3 weeks.

PRODUCT GALLERY



ALSO FROM MANUAL TOOLS COMPANY

Coal Crusher (5 No.)

Single Disc - Coal Disintegrator

Coal Crusher (5 No.)

Double Disc - High Capacity Disintegrator

Coke Cutter Machine

Double Drive, Drum Type - Industrial Series

Ring Type Coke Cutter

Double Drive - Segmented Manganese Steel Rings

Haulage Machine

10 HP / 10 Ton - Coke Oven Extraction Series

Door Lifting Power Winch

Coke Oven Gate Lifting Equipment

Vibrator Screen Machine

Multi-Deck Series - Industrial Grading & Sorting

Pusher Machine

With Roller Stamping Arrangement

Coal Charging Car

Top Feed - Coke Oven Machinery Series

REQUEST A QUOTATION

+91 9430707348

Custom sizes and capacities built to order.
www.manualtoolsco.com | Dhanbad, Jharkhand, India