



MANUAL TOOLS COMPANY

Manufacturer of Coke Oven Machinery



30+ YEARS OF
EXCELLENCE

Ravindra Kr. Agarwal, Prop.

Dhanbad, Jharkhand | manualtoolsco.com



COAL CRUSHER (5 NO.)

DOUBLE DISC - HIGH CAPACITY DISINTEGRATOR



KEY CAPABILITY:

A double disc coal crusher for high-volume plants: up to 25 TPH, with 12 manganese steel hammers that reduce coal lumps up to 150 mm to below 2 mm.


PERFORMANCE

- ✓ Capacity: 20 - 25 Tons / Hour
- ✓ Motor: 160 - 200 HP
- ✓ Input Feed Size: below 150 mm
- ✓ Output Size: below 2 mm

DURABILITY & DESIGN

- ✓ Double Disc Rotor, 12 Manganese Hammers
- ✓ Individually Replaceable Hammers
- ✓ 12 mm Fabricated Steel Housing
- ✓ Handles moisture up to 10 - 12%

PRODUCT GALLERY



REQUEST A QUOTATION: +91 9430707348



HOW IT WORKS

1. Large Feed Intake

Accepts lumps up to 150 mm; the wide hopper spreads material across both discs.

2. Dual Rotor Impact

Two discs carrying 12 manganese hammers create a dense impact zone.

3. High Volume Discharge

Crushed coal passes the calibrated grate bars at up to 25 TPH, below 2 mm.

APPLICATIONS

Large Coke Ovens	High-capacity recovery ovens needing continuous feed.
Thermal Power	Consistent fuel for larger FBC boilers.
Briquetting Plants	High volumes of fines for fuel briquettes.

COMMON QUESTIONS

Q. How does it differ from the Single Disc?

A. Two rotors and 12 hammers give 20 - 25 TPH and accept 150 mm feed, versus 8 - 10 TPH for the Single Disc.

Q. What motor is required?

A. A slip-ring or squirrel cage motor between 160 HP and 200 HP.

Q. Can it handle wet coal?

A. Up to 10 - 12% moisture; clean the grate bars more often for sticky coal.

Q. Are the hammers replaceable individually?

A. Yes, each hammer can be replaced or reversed without dismantling the rotor.

Q. What is the delivery timeline?

A. Made to order; fabrication usually takes 4 - 5 weeks depending on the production queue.

REQUEST A QUOTATION: +91 9430707348