




MANUAL TOOLS COMPANY

Manufacturer of Coke Oven Machinery

PRODUCT BROCHURE



DOOR LIFTING POWER WINCH

Coke Oven Gate Lifting Equipment

2.5 - 5 T

LIFTING CAPACITY

5 - 7.5 HP

MOTOR

2 - 4 m/min

LIFTING SPEED



Ravindra Kr. Agarwal, Proprietor

Dhanbad, Jharkhand, India | +91 9430707348


www.manualtoolsco.com

Door Lifting Power Winch

Coke Oven Gate Lifting Equipment

AT A GLANCE

A power winch for lifting heavy coke oven doors. Its self-locking worm reducer gearbox holds the load steady even during a power failure. 5 - 7.5 HP motor, up to 5 tons.



2.5 - 5 T

LIFTING CAPACITY

5 - 7.5 HP

MOTOR

2 - 4 m/min

LIFTING SPEED

SPECIFICATIONS

Lifting Capacity	2.5 - 5 Tons
Motor	5 - 7.5 H.P. (3-Phase)
Operation	Vertical Lift
Lifting Speed	Approx. 2 - 4 m / min
Gearbox	Self-Locking Worm Reducer
Drum	Grooved Steel

DESIGN & DURABILITY

- ✓ Self-locking worm reducer gearbox
- ✓ Cast steel and phosphor bronze gears
- ✓ Grooved steel drum for wire rope
- ✓ Electro-magnetic motor brake available

BUYING INFORMATION

Lead time	Made to order. Ask us for the current lead time.
Warranty	1 year, as on all our machinery.
Installation	Installation supervision and commissioning available.
Custom builds	Capacity, motor power and dimensions matched to your plant and drawings.

REQUEST A QUOTATION

+91 9430707348

Custom sizes and capacities built to order.
www.manualtoolsco.com | Dhanbad, Jharkhand, India

HOW IT WORKS

01 Drive Activation

The electric motor engages and drives the worm gearbox input shaft through a coupling.

02 Torque Multiplication

The worm shaft drives the worm wheel, cutting speed and multiplying torque for a smooth, non-jerky lift.

03 Vertical Lift

The output shaft turns the grooved drum, winding the wire rope and lifting the oven door to the required height.

APPLICATIONS

Coke Oven Doors	Lifting and positioning heavy oven doors during charging.
Heavy Dampers	Lifting isolation dampers in flue gas ducts in power plants and steel mills.
Maintenance Bays	General vertical lifting where overhead cranes are not available.

COMMON QUESTIONS

Why a worm gearbox instead of helical?

Worm gearboxes are self-locking: if power fails, the door's weight cannot drive the motor backwards.

What is the lifting speed?

Slow and controlled, approximately 2 - 4 metres/minute, for safety.

Does it come with a brake?

We recommend and supply an electro-magnetic brake on the motor shaft for double safety.



What capacity do I need for a coke oven?

Standard coke oven doors usually need 2.5 to 5 tons, depending on battery height and door weight.

Is the wire rope included?

Yes, a standard length is included; rope length and diameter can be customised.

PRODUCT GALLERY



ALSO FROM MANUAL TOOLS COMPANY

Coal Crusher (5 No.)

Single Disc - Fine Coal Disintegrator

Coal Crusher (5 No.)

Double Disc - High Capacity Disintegrator

Coke Cutter Machine

Double Drive, Drum Type - Industrial Series

Ring Type Coke Cutter

Double Drive - Segmented Manganese Steel Rings

Haulage Machine

10 HP / 10 Ton - Coke Oven Extraction Series

Vibrator Screen Machine

Multi-Deck Series - Industrial Grading & Sorting

Pusher Machine

With Roller Stamping Arrangement

Coal Charging Car

Top Feed - Coke Oven Machinery Series

Conveyor Components

Idlers, Rollers & Pulleys - Industrial Handling Systems

REQUEST A QUOTATION

+91 9430707348

Custom sizes and capacities built to order.
www.manualtoolsco.com | Dhanbad, Jharkhand, India