




MANUAL TOOLS COMPANY
Manufacturer of Coke Oven Machinery



PRODUCT BROCHURE

COAL CRUSHER (5 NO.)

Double Disc – High Capacity Disintegrator

20 – 25 TPH

CRUSHING CAPACITY

150 – 180 HP

MOTOR RANGE

< 2 mm

OUTPUT SIZE

COAL CRUSHER (5 NO.)

A double disc coal crusher for high-volume plants: up to 25 TPH, with 12 mild steel hammers that reduce coal lumps up to 200 mm to below 2 mm.



20 – 25 TPH
CAPACITY



150 – 180 HP
MOTOR POWER



< 2 mm
OUTPUT SIZE



Up to 200mm
MAX FEED SIZE

SPECIFICATIONS

Crushing Capacity	20 – 25 Tons / Hour
Motor	150 – 180 H.P.
Input Feed Size	Below 200 mm
Output Size	Below 2 mm
Hammers	12 Nos., Mild Steel
Body Thickness	16 mm Fabricated Steel

DESIGN & DURABILITY

- Double disc rotor fitted with 12 mild steel hammers
- Individually replaceable hammers
- 16 mm fabricated steel housing
- Manganese steel top and side liner jaw plates

BUYING INFORMATION

Lead time: Made to order. Fabrication usually takes 4–5 weeks.

Warranty: 1 year, as on all our machinery.

Installation: Installation supervision and commissioning available.

Custom builds: Capacity, motor power and dimensions can be matched to your plant and drawings.

Brochure: Download PDF

HOW IT WORKS

01 Large Feed Intake

Accepts lumps up to 200 mm; the wide hopper spreads material across both discs.

02 Dual Rotor Impact

Two discs fitted with 12 mild steel hammers create a dense impact zone.

03 High Volume Discharge

Crushed coal passes the calibrated grate bars at up to 25 TPH, below 2 mm.

APPLICATIONS

Large Coke Ovens	High-capacity recovery ovens needing continuous feed.
Thermal Power	Consistent fuel for larger FBC boilers.
Briquetting Plants	High volumes of fines for fuel briquettes.

COMMON QUESTIONS

How does it differ from the Single Disc?

Two rotors and 12 hammers give 20 – 25 TPH and accept 200 mm feed, versus 8 – 12 TPH for the Single Disc.

What motor is required?

A slip-ring or squirrel cage motor between 150 HP and 180 HP.

Can it handle wet coal?

Up to 8 – 10% moisture; clean the grate bars more often for sticky coal.

Are the hammers replaceable individually?

Yes, each hammer can be replaced or reversed.

What is the delivery timeline?

Made to order; fabrication usually takes 4 – 5 weeks depending on the production queue.

SPARE AND WEAR PARTS



Crusher hammers

Fits: 12 per machine, 6 per disc




Twin disc rotor

Fits: Double disc, 5 No.



Manganese Steel Top Liner Jaw Plate

Fits: Double disc, 5 No.




Driving arrangement

Fits: 150 – 180 HP drives

Also made to order: side liner plates, bearing housings, V-belt drives and hopper sections. Tell us the machine and we will quote the part.

PRODUCT GALLERY



ALSO FROM MANUAL TOOLS COMPANY

Coal Crusher (5 No.)

Single Disc – Coal Disintegrator

Ring Type Coke Cutter

Double Drive – Segmented Manganese Steel Rings

Door Lifting Power Winch

Coke Oven Gate Lifting Equipment

Pusher Machine

With Roller Stamping Arrangement

Conveyor Components

Idlers, Rollers & Pulleys – Industrial Handling Systems

Coke Cutter Machine

Double Drive, Drum Type – Industrial Series

Haulage Machine

10 HP / 10 Ton – Coke Oven Extraction Series

Vibrator Screen Machine

Multi-Deck Series – Industrial Grading & Sorting

Coal Charging Car

Top Feed – Coke Oven Machinery Series

REQUEST A QUOTATION

+91 9430707348

Custom sizes and capacities built to order.

manualtoolsco.dhn@gmail.com

www.manualtoolsco.com | Dhanbad, Jharkhand, India