

PYTHON PROGRAMMING: INTRODUCTION & INSTALLATION

❖ General Purpose Language:

- ☐ Machine Learning AI
- ☐ GUI, Web, Software Dev

❖ Python Features:


- ☐ Interpreted
- ☐ Object oriented
- ☐ High Level
- ☐ Current version 3.x

❖ Download Install & Run:

- ☐ <https://www.python.org>
- ☐ Start > Python IDLE
- ☐ Write a line of code
e.g. 2+3 OR print("Hello World")

❖ Community version of PyCharm IDE:

- ☐ <https://www.jetbrains.com/pycharm/download>
- ☐ Install 64 bit (depending on system)
- ☐ Start > PyCharm > Create New Project > filename.py
- ☐ print("Hello World")
- ☐ Run the file



❖ Types:

- ❑ **int** e.g. 4, 1000, -34 etc.
- ❑ **float** e.g. 33.4, -0.0005
- ❑ **string** e.g. 'My friend Tom', 'cricket' etc.

❖ Assignment:

- ❑ `x = 2`
- ❑ `name = 'Rupa'`

❖ Strings:

A	n	o	d	i	a	m		R	o	c	k	s	
0	1	2	3	4	5	6	7	8	9	10	11	12	→index
-13	-12	-11	-10	-9	-8	-7	-6	-5	-4	-3	-2	-1	

Strings are immutable:

```
str1 = "My Name"
```

```
str1[3] = 'n'      # Error
```

❖ Lists: []

- ☐ Mutable
- ☐ E.g.: myList = [23, 91, 9, 507]
- ☐ Functions used in List:
 - append()
 - insert()
 - remove()
 - pop()
 - clear()
 - extend()
 - max(list)
 - min(list)
 - sum(list)
 - sort()
 - sort(reverse=True)

❖ Tuples: ()

- ☐ Immutable
- ☐ Iteration is faster than list
- ☐ E.g.: myTuple = (23, 91, 9, 507)

❖ Sets: { }

- ☐ Like mathematical sets: do not consider repetition
- ☐ E.g.: mySet = {23, 91, 9, 507, 91}
- ☐ Uses hashing for performance
- ☐ No index for sets
- ☐ Mutable
- ☐ Functions used in Set:
 - add()
 - remove()
 - set1.update(set2)

	Mutable	Ordered	Indexing / Slicing	Duplicate Elements
List	✓	✓	✓	✓
Tuple	✗	✓	✓	✓
Set	✓	✗	✗	✗

PYTHON PROGRAMMING: DICTIONARIES

Student [List of Dictionaries]					
Rupa {List of Dictionaries}	Eng 87	Math 96	Science 94	SST 84	AI 99
Sangita {List of Dictionaries}	Eng 93	Math 100	Science 85	SST 79	AI 98
Thomas {List of Dictionaries}	Eng 81	Math 98	Science 78	SST 82	AI 100
Sanjay {List of Dictionaries}	Eng 82	Math 99	Science 95	SST 95	AI 91

❖ Dictionaries: { key : value }

- ☐ Key must be unique and immutable
- ☐ Key can be numeric or non-numeric
- ☐ Access values through key/get() function
- ☐ Can zip 2 lists (key-list & value-list) to form a dictionary
- ☐ Real Life dictionaries can have nested lists, tuples, sets & other dictionaries inside

PYTHON PROGRAMMING: VARIABLES

❖ Variables Trivia:

Value	Address
	2567912
3	2567913
	2567914
Rupa	2567915
	2567916
5	2567917
	2567918
	2567919
	2567920
	2567921

❑ num = 3

❑ id(num)

❑ name = 'Rupa'

❑ id(name)

❑ Two variables assigned same values: a = 5, b=5

❑ id(a) will therefore point to the same memory as id(b)


❖ Constants:

Actually variables with names in CAPS e.g. PI = 3.14

❖ Garbage Collection:

Unused objects and variables are garbage collected by Python

PYTHON PROGRAMMING: DATA TYPES & OPERATORS



❖ Data Types:


- ❑ **None:** var not assigned (null)
- ❑ **Numeric:**
 - **Int**
 - **Float**
 - **Complex** e.g. 6+4.5j
 - **Bool** True, False

- Sequence
↑
↓
- ❑ **List**
 - ❑ **Tuple**
 - ❑ **Set**
 - ❑ **String**
 - ❑ **Range**
 - ❑ **Dictionary**

** Character data type absent in Python

❖ Types of Operators :

- ❑ **Arithmetic** e.g. + - * / % etc.
- ❑ **Assignment** assigning values (=)
- ❑ **Relational** compare two variables (">" "<" "==" ">=" "<=" "!=")
- ❑ **Logical** "AND" "OR" "NOT"
- ❑ **Unary** negating a value
- ❑ **Bitwise** "XOR" "<<" ">>" etc.



NUMBER SYSTEM

SYSTEM	DIGITS	BASE	PYTHON LITERALS
Binary	0, 1	2	0b
Octal	0, 1, 2, 3, 4, 5, 6, 7	8	0o
Decimal	0, 1, 2, 3, 4, 5, 6, 7, 8, 9	10	None
HexaDecimal	0, 1, 2, 3, 4, 5, 6, 7, 8, 9, A, B, C, D, E, F	16	0x




- ❖ `print(num)` Decimal to Binary
- ❖ `print(bin(num))` Binary to Decimal
- ❖ `print(oct(num))` Decimal to Octal
- ❖ `print(hex(num))` Decimal to HexaDecimal




PYTHON PROGRAMMING: USER INPUT

- ❖ **input():** Delays the execution of program and asks user for input
 - ❑ Strings, Integers, Floats, Characters and Expressions can be asked from the user by passing proper functions inside input()
- ❖ **eval():** Evaluates any mathematical expression



PYTHON PROGRAMMING: IF ELSE STATEMENT



- ❖ **If Statement:** Uses if keyword followed by condition
- ❖ **If-Else Statement:** Used to execute both the true part and the false part of a condition. If true, the if block code is executed. If false, the else block code is executed
- ❖ **Nested If:** One or more statements present inside another if statement. Used when a variable has to be processed multiple times
- ❖ **If-Elif-Else:** It checks the if statement condition. If false, the elif statement is executed. If elif is false, the else statement is executed

PYTHON PROGRAMMING: FOR & WHILE LOOPS



- ❖ **For:** Definite iteration. Iterates predefined number of times
- ❖ **While:** Indefinite Iteration. Keeps iterating until the condition is false
- ❖ **The Else Clause:** Python exclusive
 - ☐ For Else
 - ☐ While Else
- ❖ **Loop Control Statements:**
 - ☐ **Break** – Terminates the loop
 - ☐ **Continue** – Forces to execute the next iteration of loop
 - ☐ **Pass** – Null operation

PYTHON PROGRAMMING: ARRAY

TYPECODE	CHARACTER TYPE	PYTHON TYPE	MINIMUM SIZE IN BYTES
b	Signed Char	int	1
B	Unsigned Char	int	1
u	Py_UNICODE	unicode character	2
h	Signed Short	int	2
H	Unsigned Short	int	2
i	Signed int	int	2
I	Unsigned int	int	2
l	Signed Long	int	4
L	Unsigned Long	int	4
f	Float	float	4
d	Double	float	8

❖ Array:

- ❑ Array can be one dimensional or multi dimensional
- ❑ Import array module to work with arrays
- ❑ All elements of an array should be of same type
- ❑ Can take inputs from user to form an array

❖ Functions:

- ❑ `typecode()`
- ❑ `buffer_info()`
- ❑ `array()`
- ❑ `extend()`
- ❑ `append()`
- ❑ `pop()`

PYTHON PROGRAMMING: NUMPY


❖ Numpy:

- ❑ general purpose array-processing package
- ❑ Used mainly for multidimensional arrays
- ❑ Efficient even with 1D array. For e.g.- mentioning typecode is not necessary

❖ Array Creation:

- ❑ `array()` – array with given data
- ❑ `linspace()` – array of range divided in specified number of parts
- ❑ `logspace()` – array of range divided in parts but log values
- ❑ `arange()` – like `linspace` but breaks the range in a progressive series
- ❑ `Zeros()` – array of 0's
- ❑ `Ones()` – array of 1's





❖ Array Addition:

- ❑ Any variable can be added with each element
- ❑ **sum()**: Sum of all the array elements
- ❑ Arrays support various types of mathematical operations

❖ Copying Array:

- ❑ **Aliasing**: Assigning an existing array to a new one stored at same address
- ❑ **Shallow Copy**: `view()` function copies the array to form a new but dependent one at different address
- ❑ **Deep Copy**: `copy()` function does the same but the arrays stay independent

PYTHON PROGRAMMING: MATRICES

❖ Array Addition:


- ☐ Any variable can be added with each element
- ☐ **sum()**: Sum of all the array elements
- ☐ **Vectorized Operation**: Adds elements of two arrays to form a new array

PYTHON PROGRAMMING: VECTORIZED OPERATION

❖ Array Addition:

- ☐ Any variable can be added with each element
- ☐ **sum()**: Sum of all the array elements
- ☐ **Vectorized Operation**: Adds elements of two arrays to form a new array

PYTHON PROGRAMMING: FUNCTIONS



❖ **Function** is a block of code which only runs when called

❖ **Creating New Function:**


- ❑ **def** keyword creates a new function
- ❑ Can assign many functions/statements
- ❑ Can be called anywhere and anytime
- ❑ Saves time and space in coding
- ❑ Nested functions

❖ **Return Statement:** Used inside a function or method to send the result back to caller

❖ **Parameters** are variables inside the parentheses in a defined function. e.g. fn(x, y)

❖ **Arguments** are values sent to the function when it is called. e.g. fn(2, 3)

****Python's argument passing is neither "pass by value" nor "pass by reference" but "pass by object reference"**



❖ **Formal** arguments are parameters passed while defining a function

❖ **Actual** arguments are the values passed to the function when called

❑ **Default** arguments are the values assigned while defining a function

❑ **Positional** arguments must be specified in the proper order

❑ **Keyworded** arguments use keys to assign values even if they are not sorted in order

❑ **Variable Length** arguments are used when the number of values is unknown

e.g. `input()` where user might give multiple values

***args** used for passing a variable number of arguments to a function


****kwargs** used for the same as ***args** but with keys assigned to each of them

PYTHON PROGRAMMING: GLOBAL KEYWORD & RECURSION



- ❖ **Global** variables have a global scope and assigned outside functions
- ❖ **Local** variables have a local scope only inside the function they are assigned to
- ❖ **Global Keyword** lets access and modify the global variable even inside a function
- ❖ **globals():** function returns the dictionary of current global symbol table
 - ❑ Changes a global variable without affecting local ones if called inside a function
- ❖ **Recursion** is a process where a function calls itself
 - e.g. Program to find factorial of a number
 - ❑ **sys.getrecursionlimit():** default limit of recursion is 1000
 - ❑ **sys.setrecursionlimit(n):** changes the limit of recursion to desired value "n"

PYTHON PROGRAMMING: ANONYMOUS FUNCTIONS




❖ **Lambda** aka anonymous functions are functions without names

- ❑ Used when a small, one-time-use function is required
- ❑ Initiated with the keyword "**lambda**" instead of "def"

❖ **Limitations:**

- ❑ Limited to a single expression.
- ❑ They are often less readable than named functions
- ❑ No proper names or docstrings make it harder to understand their purpose

PYTHON PROGRAMMING: FILTER MAP & REDUCE



❖ **filter()** is an in built function used for fetching elements from a collection (e.g. list or array) based on a set condition

```
filter(function, iterable)
```

❖ **map()** function transforms each element in a collection using a given function by applying it to each element

```
map(function, iterable)
```

❖ **reduce()** aggregates elements in a collection to produce a single result by repeatedly applying a binary function to them

```
from functools import reduce  
reduce(function, sequence, initial)
```

** initial can be assigned with a value to be aggregated with the passed sequence

PYTHON PROGRAMMING: DECORATORS



- ❖ **Decorators** can modify functions (or methods) and classes without changing the source code
- ❖ Functions are **first-class citizens** in python, which means they can be:
 - ☐ passed as arguments to other functions
 - ☐ returned as values to other functions
 - ☐ defined within other functions
- ❖ The above properties validate decorators
- ❖ Example – “@timeit” decorator measures execution time of a code




PYTHON PROGRAMMING: SPECIAL VARIABLES

❖ **Special Variables** can provide details on the context, behavior or state of a code in Python

- ❑ Always defined using double underscores (e.g. "`__name__`")
- ❑ They are also known as dunder or magic methods

❖ **Examples:**

- ❑ `__name__` contains the name of current module
 - `__name__` shows '`__main__`' if the current script is running
 - If imported as a module into another script, `__name__` shows the module's name
- ❑ `__init__` is called when an object is created from a class and used to initialize the object's attributes
- ❑ `__del__` is called for destroying an object and sending it for garbage collection
- ❑ `__str__` is called by the `str()` function to generate a string that represents the object's state
- ❑ `__call__` allows instances of a class to be called like functions
- ❑ `__iter__` and `__next__` are used to define iterators for custom objects



❖ **OOPs** is a programming prototype that enables problem solving in a real world approach

- ❑ Shows how versatile Python is, based on programming spectrum
- ❑ Strings, Integers, Floats, Lists, Sets etc. are examples of built-in objects
- ❑ To define an object, declaring a class is necessary
- ❑ Classes contain **attributes** and **behaviors** of objects



❖ **Class** offers a blueprint for user-defined objects


- ❑ Contains attributes(variables) and behaviors(methods) for the objects
- ❑ Provides a way to organize code by grouping related data and behavior together
- ❑ Keyword for creation is **class**
- ❑ By convention class name should be typed in camel-case

❖ **Object** is an entity with **attributes** and **behaviors**

- ❑ For example, an object **Parrot** has
 - **attributes** - age, color
 - **behavior** - flying, singing

which belongs to the **class** "**Parrot**"

- ❑ Objects are instances created from the class



❖ **Constructors** initialize objects and allocate memory (in Heap Memory) to them

- ❑ `__init__` method lets the class assign attributes for objects
- ❑ `self` keyword (by convention) represents an instance (object) of the given class
- ❑ Constructors are generally of two types
 - **Default** (Non-parameterized) does not accept any arguments except from `self`
 - **Parameterized** accepts arguments aside from `self`

❖ **Encapsulation** is a OOPs concept that ensures a conventional restriction of data

- ❑ Wraps the variables and the methods together as a single unit
- ❑ The idea is ensuring the variables can be accessed only through the methods of their current class
- ❑ Constructors can be used for achieving encapsulation

PYTHON PROGRAMMING: OOPS VARIABLE TYPES



- ❖ **Instance Variables (Attributes)** are specific to an instance of a class
 - ❑ Stores unique data to each object created from the class
 - ❑ Object level
- ❖ **Class Variables (Static Variables)** are shared by all instances of a class
 - ❑ Defined within the class but outside of any instance methods
 - ❑ Same for all instances of the class (Class level)
 - ❑ Can be accessed using the class name or any instance of the class
- ❖ **Local Variables** are defined within methods or functions (Method level)
 - ❑ Only accessible within those
 - ❑ They have no connection to the class or its instances



❖ **Instance Methods** are meant to access the instance attributes

- ❑ Takes **self** as parameter
- ❑ The most commonly used method
- ❑ **Accessors** fetch (get) the value and **Mutators** modify (set) the value

❖ **Class Methods** are usually used to access class variables

- ❑ Can be called using the class name itself
- ❑ Takes **cls** as parameter
- ❑ Declared by **@classmethod** decorator

❖ **Static Methods** are not associated with either of the class or instance variables


- ❑ Takes no parameters
- ❑ Declared by **@staticmethod** decorator
- ❑ Can be accessed using the class name as well as class objects

```
class OuterClass:
    def __init__(self, outer_var):
        self.outer_var = outer_var

    class InnerClass:
        def __init__(self, inner_var):
            self.inner_var = inner_var
```

❖ **Inner Classes** or nested classes are basically one defined inside the other


- ❑ Useful for grouping two related classes
- ❑ Better privacy of code
- ❑ Inner classes are of two types, as follows
 - **Multiple:** The class contains one or more variables
 - **Multilevel:** The class contains an inner class which contains another inner class




❖ **Inheritance** is a OOPs concept that allows a class to inherit attributes and behaviors from another class

- ❑ Provides reusability of the code and increases its performance
- ❑ **Parent Class (Super Class)** is the class whose properties are inherited by the new one
- ❑ **Child Class (Sub Class)** derives its properties from its parent class aside from having its own


SINGLE LEVEL




MULTIPLE




HIERARCHICAL



MULTILEVEL




HYBRID





PYTHON PROGRAMMING: METHOD RESOLUTION ORDER

- ❖ **MRO** is an order in which classes are searched when looking for a method or attribute in an inheritance hierarchy
 - ❑ Modern Python uses C3 Linearization algorithm over the old school DLR
 - ❑ **Example:** In Case of A(B,C) – MRO dictates that the code will first search A itself, then go to B and then C
 - ❑ **Left to Right**
- ❖ **Super()** is a built-in function which allows access to the parent's methods and attributes in the child class
 - ❑ Follows MRO



transport()



❖ **Polymorphism** means having multiple forms in general

- ❑ Provides code flexibility and reusability
- ❑ **len()** is an in-built polymorphic function
- ❑ Functions or methods with same name make different objects behave in similar pattern

"If it looks like a duck, swims like a duck and quacks like a duck, then it probably is a duck"



❖ **Duck Typing** is an idea of assigning types to classes based on similar methods

❑ Python is a dynamically typed language which dictates:

- The type or class of an object is determined by its behavior
- Declaring the type of an object explicitly is unnecessary




❖ **Operator Overloading** lets us define how operators behave for objects of custom classes

❑ Operators in python actually calls certain special methods behind the scene


- " + " calls `__add__`
- " - " calls `__sub__`
- " * " calls `__mul__`

❑ Custom operations can be defined by modifying those special methods

- For e.g. adding two objects by inducing new addition logic to `__add__`



OVERLOADING




OVERRIDING

❖ **Method Overloading** defines multiple methods with the same name but different parameters

- ❑ **Compile time** Polymorphism
- ❑ Is implemented within the same class
- ❑ Python does not support this by default which makes the latest definition valid for the overloaded method

❖ **Method Overriding** defines a new implementation for a method in a subclass that already exists in the parent class

- ❑ **Run time** Polymorphism
- ❑ Works within at least two classes (or more) related via inheritance
- ❑ Methods must have same name and parameters



- ❖ **Abstract Methods** are declared but not implemented
 - ❑ Defined using `@abstractmethod` decorator
 - ❑ Need to import **ABC** (Abstract Base Classes) module
 - ❑ Python does not support this by default
- ❖ **Abstract Classes** are classes that contain at least one abstract method
 - ❑ Used for building **API** (Application Program Interface)
 - ❑ Serves as a blueprint for other classes
 - ❑ Objects can not be created from them