

DETAILS

SPECIFICATION	
Plank Size	7.13" x 48.03"
Wear Layer	0.3mm
Thickness	4mm
Attached underlayment	Additional underlay to be added
Edge proof	Micro bevel edge

DESCRIPTION	STANDARD TEST
Lighth stability for color fastness	ASTM F1515
Dimensional stability	ASTM F2199
Curling	180 23999
Short term indentation	ASTM F1914
Product thickness	ASTM F386
Wear layer thickness	ASTM F410
Size and squareness	ASTM F2055
Smoke density flaming	ASTM E662
Static of coefficient friction	C1028
Resistance to impact	ASTM F1265
Stain cleanability	NALFA 34
Abrasion resistance	ASTM D4060
Critical radiant flux	ASTM E648

Get professional installation and a 10-year warranty.



intertek
Total Quality. Assured.

SAMARO
FLOORING

Address: 5th Floor, Vilco Centre,
Subhash Road, Opp. Garware,
Vile Parle East, Mumbai-400057



✉ info@samaro.in
📞 +91 22 69310 600/606



FLOORING
SAMARO

Tuscan Collection



RAW HONEY

SAM0031

ASH WOOD

SAM0025

COPPER SAND

SAM0030

ROSEWOOD

SAM0529

CASPER GREY

SAM0501

PEBBLE

SAM0029



RAVEN
SAM0013

Low Maintenance

Termite Proof

GINGER GOLD
SAM0017

Scratch Resistant

ASH GREY
SAM0024

Dust-free Installation

VINTAGE OAK
SAM0504

1-Day Installation*

100% WaterProof

