

SETUP GUIDE

Ox Alpha in OpenCode (macOS Setup)

Complete configuration guide for running Ox Alpha free on macOS via OpenCode & OpenRouter

MODEL TARGET

stealth/ox-alpha (1M Context)

PRICING STATUS

\$0 / Free (Temporary Preview)

SUPPORTED PLATFORM

macOS (Terminal / Desktop)

Method 1: OpenCode → OpenRouter Pipeline

1 Install OpenCode on macOS

Install OpenCode CLI using Homebrew or the official curl script:

```
brew install opencode
# Verify installation:
opencode --version
```

2 Generate OpenRouter API Key

Go to openrouter.ai, sign in or create an account, open **API Keys**, and click **Create Key**. Copy your key (starts with `sk-or-v1-...`). No deposit required for free-tier models.

3 Connect OpenRouter to OpenCode

Launch OpenCode and run the interactive provider connector:

```
opencode
/connect
```

Select **OpenRouter** from the list and paste your API key when prompted.

4 Select or Register Ox Alpha Model

Type `/models` and choose `stealth/ox-alpha`. If not automatically listed, add it to your OpenCode configuration:

```
mkdir -p ~/.config/opencode
nano ~/.config/opencode/opencode.json
```

```
{
  "$schema": "https://opencode.ai/config.json",
  "provider": {
    "openrouter": {
      "models": {
        "stealth/ox-alpha": {}
      }
    }
  }
}
```

Configuration Tip

Save the JSON file (Ctrl+O → Enter → Ctrl+X) and restart OpenCode. Select `openrouter/stealth/ox-alpha` from the picker.

Method 2: Direct OpenCode Zen Route

Ox Alpha is also integrated directly into OpenCode's preview ecosystem. This bypasses OpenRouter API keys for immediate development access:

1 Open Project in OpenCode

Navigate to your codebase repository:

```
cd ~/your-project
opencode
```

2 Select Direct Free Model

Open the model picker via `/models` and select the built-in free Ox Alpha / Zen preview directly without configuring external credentials.

3 Execute Agentic Tasks

Start with repository exploration before executing broad edits:

```
# Test 1: Architecture overview
Analyze this repository and explain the architecture.

# Test 2: Multi-file agent refactoring
Find the authentication bug, investigate relevant files, fix it, and run tests.
```

Setup Comparison

Setup Route	Current Cost	Setup Complexity	Best Used For
OpenCode → Direct (Zen)	\$0 Free	Easiest (Zero setup)	Quick evaluation, coding agent tasks
OpenCode → OpenRouter	\$0 Free (Preview)	Moderate (Requires API key)	Provider control, rate limit management
Browser Playground	\$0 Free	Web Only	General Q&A and prompt testing

Temporary Preview Notice

Ox Alpha is offered at \$0 during its initial anonymous evaluation period. Pricing and availability may change as the preview matures.

Preserving Existing Configs

If you have OmniRoute or other custom endpoints in `opencode.json`, keep existing provider keys intact and append `openrouter` alongside them.