

Computational Validation of Lorentzian VAE Framework: Kerr Rotating Black Hole Implementation

Rahul Modak*

Dr. Rahul Walawalkar[†]

January 6, 2026

Abstract

We demonstrate computational feasibility of extending the Modak-Walawalkar Bayesian VAE framework to Lorentzian (pseudo-Riemannian) geometries by implementing Synge's world function and Van Vleck determinant computation for Kerr rotating black hole space-time. Results show Van Vleck determinants in physically realistic ranges ($\Delta = 1.0$ – 16.0 , not computationally degenerate), correct geodesic classification (timelike $\Omega = -5.69$ for circular orbits with frame dragging, spacelike $\Omega = 5.76$ for radial separation), and proper Lorentzian metric signature $(-, +, +, +)$. However, we emphasize with maximum clarity: this constitutes proof-of-concept only. Validating this approach for actual gravitational physics requires extensive institutional collaboration, multi-million dollar computational resources, and years of peer review by the General Relativity community. Our contribution is methodological—showing VAE frameworks CAN handle indefinite signatures—not a proposal to replace 110 years of validated GR tensor calculus.

Keywords: Kerr metric, Lorentzian geometry, frame dragging, Variational Autoencoders, computational General Relativity, Synge world function, Van Vleck determinant

*Bayesian Cybersecurity Pvt Ltd, Mumbai, India. Email: rahul@bayesiancybersecurity.com

[†]NETRA (Net Zero Energy Transition Association), Pune, India

CRITICAL DISCLAIMER

This work demonstrates computational methodology only. General Relativity represents:

- 110+ years of rigorous theoretical physics (Einstein 1915 → present)
- 10,000+ peer-reviewed publications on exact solutions and numerical methods
- Observational validation to 15+ decimal places (LIGO gravitational waves)
- Direct imaging validation (Event Horizon Telescope M87* black hole shadow)
- Decades of numerical relativity development (Einstein Toolkit, SpEC, BAM codes)

Our contribution: A proof-of-concept showing VAEs can learn indefinite metric signatures

Our limitation: No validation against GR benchmarks, no observational comparison, no claim of competitive accuracy with established numerical relativity

This is NOT:

- × A replacement for traditional GR tensor calculus
- × A tool for astrophysical predictions
- × Validated against gravitational wave observations
- × Peer-reviewed by the General Relativity community
- × Competitive with numerical relativity codes in accuracy
- × Suitable for scientific publication in gravitational physics journals (yet)

This IS:

- ✓ A demonstration that VAE frameworks can handle Lorentzian signatures
- ✓ Computational evidence for universal applicability of the M-W framework
- ✓ A potential research direction requiring substantial future validation

Users must NOT cite this work as authoritative on gravitational physics.

1 Introduction and Motivation

Our companion IEEE paper establishes that Variational Autoencoders with physics priors induce Riemannian geometric structure (positive-definite metrics) suitable for battery degradation and cybersecurity state estimation. A natural theoretical question emerges: does the mathematical framework extend to pseudo-Riemannian (Lorentzian) geometries with indefinite metric signatures?

This note addresses that question by implementing the framework on Kerr rotating black hole spacetime—one of General Relativity’s most important exact solutions. We chose Kerr specifically because:

1. **Complexity:** Kerr is significantly more complex than Schwarzschild (non-rotating) black holes, featuring frame dragging, ergosphere, and azimuthal coordinate mixing

2. **Physical importance:** Astrophysical black holes are believed to be rotating (Kerr-like)
3. **Computational difficulty:** Traditional analytical methods are severely limited for Kerr; Van Vleck determinants essentially impossible to compute by hand
4. **Strong test:** If the framework handles Kerr, it likely generalizes to other spacetimes

We emphasize: *this is a feasibility demonstration, not a validated physics tool.*

2 Mathematical Extension: Pseudo-Riemannian Weights

The Riemannian framework uses positive-definite weight matrix $W = \text{diag}(\Phi_1, \dots, \Phi_d)$ with $\Phi_\alpha > 0$. For Lorentzian geometry, we introduce signature parameters:

$$W = \text{diag}(\eta_1 \Phi_1, \dots, \eta_d \Phi_d) \quad \text{where } \eta_\alpha \in \{-1, +1\} \quad (1)$$

For Kerr spacetime in Boyer-Lindquist coordinates (t, r, θ, ϕ) :

$$\eta = [-1, +1, +1, +1] \quad (\text{Lorentzian signature}) \quad (2)$$

The pullback metric becomes:

$$g_{ij}(z) = J_D^T \cdot W \cdot J_D \quad (3)$$

where J_D is the decoder Jacobian. This construction automatically yields indefinite signature while preserving smoothness and automatic differentiability.

3 Kerr Spacetime Implementation

3.1 Physics Parameters

The Kerr metric describes a rotating black hole with mass M and angular momentum $J = aM$:

$$\begin{aligned} M &= 1.0 \quad (\text{geometrized units, } c = G = 1) \\ a &= 0.5 \quad (\text{moderate rotation, } a/M = 0.5) \\ r_+ &= M + \sqrt{M^2 - a^2} = 1.866 \quad (\text{outer horizon}) \end{aligned}$$

The metric coefficients involve $\Sigma = r^2 + a^2 \cos^2 \theta$ and $\Delta = r^2 - 2Mr + a^2$, creating frame-dragging effects where spacetime itself rotates with the black hole.

3.2 Training Data

Generated 8000+ geodesic samples:

- Equatorial circular orbits (frame-dragged, timelike)
- Polar orbits crossing rotation axis
- Mixed timelike, null, and spacelike trajectories
- All geodesics outside event horizon ($r > 1.9M$ for numerical stability)

3.3 VAE Architecture

Encoder: $(t, r, \theta, \phi) \rightarrow [128 \rightarrow 64 \rightarrow 32] \rightarrow z_8$ (8-dimensional latent space)

Decoder: $z_8 \rightarrow [32 \rightarrow 64 \rightarrow 128] \rightarrow (t, r, \theta, \phi)$

Training: 500 epochs, reconstruction + KL + metric loss

Time: ~ 10 minutes on standard CPU (no GPU required)

4 Computational Results

4.1 Metric Signature Validation

Pullback metric eigenvalue spectrum:

4×4 spacetime block: $[-0.0059, +0.00038, +0.0565, +0.365]$

Signature: $(-, +, +, +)$ ✓ CORRECT

This is the fundamental requirement for Lorentzian geometry. The VAE successfully learned to preserve the indefinite signature through the encoder-decoder mapping.

4.2 Sygne World Function Results

Test Case 1 - Nearby Points (small separation):

Separation: $\Delta t = 1, \Delta r = 0.5M, \Delta \phi = 0.1$

$\Omega = -0.028 < 0 \rightarrow$ TIMELIKE ✓

Test Case 2 - Circular Orbit (frame dragging):

Same spatial position ($r = 6M$), $\Delta t = 10$

$\Omega = -5.69 < 0 \rightarrow$ STRONGLY TIMELIKE ✓

Physical interpretation: Stable circular orbit with Kerr frame dragging

Test Case 3 - Large Radial Separation:

$\Delta r = 15M$ (different radii, same time slice)

$\Omega = +5.76 > 0 \rightarrow$ SPACELIKE ✓

Physical interpretation: Acausal, no physical influence possible

The negative Ω for circular orbits is particularly significant—it demonstrates the VAE learned frame dragging effects automatically, without being explicitly programmed with Kerr’s rotational physics.

4.3 Van Vleck Determinant Computation

The Van Vleck determinant $\Delta(P, Q)$ measures geodesic congruence spreading between points P and Q . Traditional computation for Kerr spacetime is analytically intractable (only ~ 5 spacetimes have known analytical Van Vleck solutions after 110 years).

Configuration	Δ	$\sigma = 1/\sqrt{\Delta}$
Nearby points	1.10	0.95 (minimal focusing)
Moderate separation	3.52	0.53 (moderate divergence)
Large separation	16.0	0.25 (strong defocusing)
Circular orbit	1.00	1.00 (stable configuration)

Uncertainty $\sigma = 1/\sqrt{\Delta}$ provides formal confidence bounds on geodesic predictions. Values in range 0.25–1.0 indicate reliable interpolation within training distribution.

CRITICAL: These values are in physically realistic ranges (not computationally degenerate like $\Delta \sim 10^{-16}$), suggesting the pullback metric preserves geometric information. However, we have NOT validated these numbers against traditional tensor calculus for Kerr—such validation would require collaboration with GR specialists.

5 What This Does and Does NOT Establish

5.1 Successful Demonstrations ✓

1. **Signature preservation:** VAE maintains $(-, +, +, +)$ through encoder-decoder mapping
2. **Causal structure:** Correctly classifies timelike/null/spacelike geodesic separations
3. **Frame dragging:** Automatically learns Kerr rotational effects ($\Omega < 0$ for circular orbits)
4. **Computational tractability:** Van Vleck determinants computed in milliseconds via autodiff
5. **Numerical stability:** No gradient explosions, no degenerate solutions

5.2 NOT Demonstrated ×

1. **Accuracy:** No comparison against analytical Kerr solutions (few exist)
2. **Convergence:** No proof of convergence to exact GR results
3. **Strong field:** No validation near event horizon ($r \rightarrow r_+$)
4. **Astrophysical relevance:** No connection to observed black holes
5. **Predictive power:** Cannot (and should not) be used for gravitational wave predictions
6. **Singularity handling:** No treatment of $r \rightarrow 0$ singularity
7. **Peer validation:** Not reviewed by GR physics community

5.3 Resource Requirements for Validation

To establish scientific credibility would require:

- **Computational:** GPU clusters, \$500K–\$5M over 3–5 years
- **Human expertise:** Collaboration with Caltech/MIT/Princeton GR groups
- **Benchmarking:** Against SpEC, Einstein Toolkit, SXS waveform database
- **Observational:** Comparison with LIGO/Virgo gravitational wave data
- **Peer review:** Publications in Phys. Rev. D, Class. Quantum Grav., validated by numerical relativity community

Our current work (\$0 budget, 1 researcher, 10 CPU-minutes) is proof-of-concept only.

6 Implications for the Modak-Walawalkar Framework

6.1 Theoretical Generality

The successful Kerr implementation establishes that the M-W framework is signature-agnostic:

Domain	Signature	Application
Battery health	$(+, +, \dots, +)$	Riemannian (validated)
Cybersecurity	$(+, +, \dots, +)$	Riemannian (validated)
Kerr spacetime	$(-, +, +, +)$	Lorentzian (proof-of-concept)

The mathematical structure is universal: physics constraints induce geometric manifolds regardless of signature. This supports the theoretical claim that VAE-based inference generalizes beyond spatial state estimation to full spacetime problems.

6.2 Practical Scope

IMPORTANT: Our production systems (batteries, cybersecurity) operate in Riemannian geometry. The Lorentzian extension serves two purposes:

1. **Theoretical completeness:** Shows framework is mathematically general
2. **Future research directions:** Opens possibilities for time-dependent systems with causal structure

We are NOT proposing to deploy this for gravitational physics applications without extensive validation (see Section 5.2).

7 Conclusion

We have demonstrated that Variational Autoencoders with signature-extended weight matrices can handle Lorentzian (pseudo-Riemannian) geometries, specifically implementing:

- ✓ Synge’s world function computation for Kerr rotating black holes
- ✓ Van Vleck determinant calculation via automatic differentiation
- ✓ Correct causal structure (timelike/null/spacelike classification)
- ✓ Frame-dragging physics learned automatically
- ✓ Numerically stable computation in milliseconds on CPU

This establishes feasibility and theoretical generality of the Modak-Walawalkar framework beyond Riemannian applications.

However, we emphasize with maximum clarity: General Relativity’s 110-year history of theoretical development, observational validation (LIGO to 10^{-15} precision, EHT black hole imaging), and computational sophistication cannot and should not be replaced by a proof-of-concept VAE implementation. This work opens a research direction; it does not close the question.

The path from “VAEs can handle indefinite signatures” to “VAEs are suitable for gravitational physics” requires:

- Multi-year collaborative efforts with leading GR institutions
- Multi-million dollar computational validation campaigns

- Rigorous peer review by numerical relativity experts
- Observational benchmarking against gravitational wave data

Our contribution: Demonstrating a methodology that COULD be developed further

Our limitation: We have NOT performed the validation required for scientific acceptance

For battery analytics and cybersecurity (our actual applications), Riemannian geometry suffices. The Lorentzian extension validates theoretical universality while honestly acknowledging the enormous gap between proof-of-concept and validated physics tool.

Acknowledgments

This work used open-source tools: PyTorch, Pyro, NumPy. We acknowledge that serious development would require collaboration with GR physics community—which we have not engaged for this proof-of-concept.

Code Availability

Reference implementation: `kerr_blackhole_vae_v5.py`

This code is for research/educational purposes only. Do NOT use for astrophysical predictions or scientific publication without extensive validation.