

---

---

---

# Introduction to Machine Learning and Pattern Recognition

David Brady<sup>1</sup>

<sup>1</sup>ECE Department  
Northeastern University

Fall 2018

---

Higher Dimensional Features Are Good   Lower Dimensional Features Are Good   Principal Component Analysis   Fisher L  
oo  
oo  
oo

---

---

Next:

Higher Dimensional Features Are Good

Lower Dimensional Features Are Good

Principal Component Analysis

- Linear PCA

- Adaptive PCA

- Nonlinear PCA (after neural net lectures)

- Kernel PCA

Fisher Linear Discriminant Analysis

Kernel LDA

Multiple Discriminant Analysis


Independent Component Analysis

## Independent Gaussian Shift in Mean

- ▶  $p(\mathbf{x}|\omega_i) = \mathcal{N}(\mu_i, \Sigma)$ ,  $P[\omega_i] = 0.5$
- ▶ Bayes Classifier:  

$$P[\text{error}] = 1/\sqrt{2\pi} \int_{r/2}^{\infty} e^{-u^2/2} du$$
- ▶  $r = \sqrt{(\mu_1 - \mu_2)^t \Sigma^{-1} (\mu_1 - \mu_2)}$   
 Mahalanobis distance
- ▶ Independence  $\Rightarrow r^2 = \sum_{i=1}^d \frac{(\mu_{i1} - \mu_{i2})^2}{\sigma_i^2}$  **squared!**

**r grows with d, P[error] drops with d**




- ▶ (non-Gaussian distributions in figure)
- ▶ more data is better (?)  $\Rightarrow$  higher  $d$


Higher Dimensional Features Are Good   Lower Dimensional Features Are Good   Principal Component Analysis   Fisher L

○○  
○○  
○○

## Reality: Independence Disappears for High Dimensions



- ▶ in-class scatter clouds are “flat” for high  $d$
- ▶ marginal return on feature dimension
- ▶ newer dimensions become predictable (**dependent**)



- ▶ height, weight, width, length, color, lightness...
- ▶ what else provides additional discrimination?

---

Higher Dimensional Features Are Good   **Lower Dimensional Features Are Good**   Principal Component Analysis   Fisher L

oo  
oo  
oo

---

Next:

Higher Dimensional Features Are Good

**Lower Dimensional Features Are Good**

Principal Component Analysis

- Linear PCA

- Adaptive PCA

- Nonlinear PCA (after neural net lectures)

- Kernel PCA

Fisher Linear Discriminant Analysis

Kernel LDA

Multiple Discriminant Analysis

Independent Component Analysis

◀ ◻ ▶   ◀ ◻ ▶   ◀ ≡ ▶   ◀ ≡ ▶   ≡   ↺ 🔍 ↻

## Training, Parameter Estimation, Computational Complexity

- ▶ determine Gaussian discriminant for class  $i$
- ▶  $n$  training feature vectors (fixed  $n$ )
- ▶ feature dimension  $d$  (growing  $d$ )
- ▶  $d + \frac{d(d-1)}{2} \approx \frac{d^2}{2}$  scalar parameters (large  $d$ )
- ▶  $nd$  scalar training samples
- ▶  $2n/d$  samples per parameter  $\rightarrow 0$  !
- ▶ parameter estimator error grows with  $d$
- ▶  $g(\mathbf{x})$  computational complexity is  $\mathcal{O}(nd^3) \rightarrow \infty$


this complexity. For each of the  $d(d+1)/2$  independent components of the sample covariance matrix  $\hat{\Sigma}$  there are  $n$  multiplications and additions (Eq. 19), giving a complexity of  $\mathcal{O}(d^2n)$ . Once  $\hat{\Sigma}$  has been computed, its determinant is an  $\mathcal{O}(d^3)$  calculation, as we can easily verify by counting the number of operations in matrix inversion methods. The inverse can be calculated in  $\mathcal{O}(d^3)$  calculations, for instance by Gaussian elimination.\* The complexity of estimating  $P(\omega)$  is of course  $\mathcal{O}(nd)$ . Equation 74 illustrates these individual complexities for the problem of setting parameters of normal distributions via maximum-likelihood:

$$g(\mathbf{x}) = -\frac{1}{2}(\mathbf{x} - \hat{\boldsymbol{\mu}})^T \hat{\Sigma}^{-1}(\mathbf{x} - \hat{\boldsymbol{\mu}}) - \frac{d}{2} \ln 2\pi - \frac{1}{2} \ln |\hat{\Sigma}| + \ln P(\omega).$$

$\begin{matrix} \mathcal{O}(dn) & \mathcal{O}(nd^2) & \mathcal{O}(1) & \mathcal{O}(d^3) & \mathcal{O}(n) \\ \uparrow & \uparrow & \uparrow & \uparrow & \uparrow \\ \mathbf{x} & \hat{\boldsymbol{\mu}} & \hat{\Sigma}^{-1} & \hat{\Sigma} & P(\omega) \end{matrix}$

## Model Overfitting

- ▶ features are corrupted by noise (ex., additive)
- ▶ small  $d \rightarrow$  model does not follow signal
- ▶ large  $d \rightarrow$  model follows signal and noise
- ▶ Goldilocks  $d$  ?



- ▶ Information Criteria: AIC, BIC (later)
- ▶ Component Analysis (here)

---

Higher Dimensional Features Are Good   Lower Dimensional Features Are Good   **Principal Component Analysis**   Fisher L

○○  
○○  
○○

---

Next:

Higher Dimensional Features Are Good

Lower Dimensional Features Are Good

**Principal Component Analysis**

- Linear PCA

- Adaptive PCA

- Nonlinear PCA (after neural net lectures)

- Kernel PCA

Fisher Linear Discriminant Analysis

Kernel LDA

Multiple Discriminant Analysis

Independent Component Analysis

◀ ◻ ▶   ◀ ◻ ▶   ◀ ≡ ▶   ◀ ≡ ▶   ≡   ↺ 🔍 ↻




**Linear PCA**

## Linear PCA

- ▶ sample  $\mathbf{x}_1, \dots, \mathbf{x}_n$ . Find best representative vector  $\mathbf{x}_0$ .
- ▶  $\mathbf{x}_0 = \arg \min_{\mu} \sum_{k=1}^n \|\mu - \mathbf{x}_k\|^2 \rightarrow \mathbf{x}_0 = \mathbf{m} = \sum \mathbf{x}_k / n$
- ▶ sample mean best represents data
- ▶ but is there something better?
- ▶ let  $\mathbf{x}_k \approx \mathbf{m} + a_k \mathbf{e}$ . Find  $\{a_k\}, \mathbf{e}$ !
- ▶  $\{\mathbf{a}, \mathbf{e}\} = \arg \min_{\|\mathbf{e}\|=1} \sum_{j=1}^n \|\mathbf{x}_k - a_k \mathbf{e} - \mathbf{m}\|^2 \Rightarrow a_k = \mathbf{e}^t (\mathbf{x}_k - \mathbf{m})$
- ▶ scatter matrix  $\mathbf{S} = \sum_{k=1}^n (\mathbf{x}_k - \mathbf{m})(\mathbf{x}_k - \mathbf{m})^t$
- ▶ substitution yields:  $\mathbf{e} = \arg \min_{\|\mathbf{v}\|=1} -\mathbf{v}^t \mathbf{S} \mathbf{v} + \sum_{k=1}^n \|\mathbf{x}_k - \mathbf{m}\|^2$
- ▶  $\mathbf{e} = \arg \max_{\|\mathbf{v}\|=1} \mathbf{v}^t \mathbf{S} \mathbf{v} \rightarrow \text{Appendix A.3} \rightarrow \mathbf{S} \mathbf{e} = \lambda \mathbf{e}$
- ▶  $\mathbf{e}$  is the dominant eigenvector of  $\mathbf{S}$  (principal component)
- ▶  $a_k$  is the projection of  $\mathbf{x}_k - \mathbf{m}$  onto  $\mathbf{e}$
- ▶  $\lambda = \mathbf{e}^t \mathbf{S} \mathbf{e}$  is the principal value

## Linear PCA

## Linear PCA (2)




- ▶ 2 dimensions here, 2 principal components (no reduction)
- ▶ also,  $[\mathbf{E}, \mathbf{D}] = \text{eig}(\mathbf{S})$

Recursively find other principal components:

- ▶ initialize  
 $\mathbf{S}_1 = \mathbf{S}, \mathbf{e}_1 = \mathbf{e}, \lambda_1 = \lambda$
- ▶  $\mathbf{S}_{i+1} = \mathbf{S}_i - \lambda_i \mathbf{e}_i \mathbf{e}_i^t$
- ▶ Linear  
 $\text{PCA}(\mathbf{S}_{i+1}) \rightarrow \lambda_{i+1}, \mathbf{e}_{i+1}$
- ▶ stop when  
 $\lambda_1 / \lambda_{K+1} - \lambda_1 / \lambda_K < \varepsilon$
- ▶  $\{\lambda_i, \mathbf{e}_i\}_{i=1}^K$  are the principal values, components

## On-line Version of PCA

- ▶ left neurons, activation  $\mathbf{x}(n) \in \mathcal{R}^m$
- ▶ right neuron connected by weights  $\mathbf{w}(n) \in \mathcal{R}^m$
- ▶ right neuron activation  $y(n) = \mathbf{w}^t(n)\mathbf{x}(n) \in \mathcal{R}$
- ▶ find sequence  $\{\mathbf{w}(n)\} \rightarrow \mathbf{w}_{opt} = \mathbf{e}$



- ▶ let  $\mathbf{S}(n) = \mathbf{x}(n)\mathbf{x}^t(n)$  be a single-step estimate of  $\mathbf{S}$

## Adaptive PCA

## Adaptive PCA (2)

- ▶  $J_0(\mathbf{v}) = \frac{\mathbf{v}^T \mathbf{S}(n) \mathbf{v}}{\|\mathbf{v}\|^2}$
- ▶  $y^2(n) = \mathbf{v}^T(n) \mathbf{S}(n) \mathbf{v}(n)$
- ▶  $J_0(\mathbf{v}) = \frac{y^2(n)}{\|\mathbf{v}\|^2}$
- ▶  $\mathbf{w}_{opt} = \arg \max_{\mathbf{v}(n)} J_0(\mathbf{v}(n))$
- ▶ consider the stochastic ascent:
- ▶  $\mathbf{w}(n+1) - \mathbf{w}(n) = \eta \mathbf{D}(n)$ , where
- ▶  $\mathbf{D}(n)$  approximates  $\nabla J_0$


two steps:

1.  $\hat{\mathbf{w}}(n+1) = \mathbf{w}(n) + \eta y(n) \mathbf{w}(n)$
  2.  $\mathbf{w}(n+1) = \hat{\mathbf{w}}(n+1) / \|\hat{\mathbf{w}}(n+1)\|$
- ▶ for small  $\eta$ , single-step approximation
1.  $\mathbf{w}(n+1) - \mathbf{w}(n) = \eta (\mathbf{x}(n) - y(n) \mathbf{w}(n)) y(n) + \mathcal{O}(\eta^2)$

## Kernel PCA

### Dimensionality Reduction

- Data representation  
Inputs are real-valued vectors in a high dimensional space.
- Linear structure  
Does the data live in a low dimensional subspace?
- Nonlinear structure  
Does the data live on a low dimensional submanifold?



Higher Dimensional Features Are Good Lower Dimensional Features Are Good **Principal Component Analysis** Fisher L

○ ○  
○ ○

○ ●

**Kernel PCA**

KPCA hyperlink

[L08]KPCA

---

Higher Dimensional Features Are Good   Lower Dimensional Features Are Good   Principal Component Analysis   Fisher L

oo  
oo  
oo

---

Next:

Higher Dimensional Features Are Good

Lower Dimensional Features Are Good

Principal Component Analysis

Linear PCA

Adaptive PCA

Nonlinear PCA (after neural net lectures)

Kernel PCA

Fisher Linear Discriminant Analysis

Kernel LDA

Multiple Discriminant Analysis


Independent Component Analysis

◀ ◻ ▶   ◀ ☰ ▶   ◀ ≡ ▶   ◀ ≡ ▶   ≡   ↺ 🔍 ↻

## LDA

- ▶ 2-classes  $\omega_1, \omega_2$
- ▶ observe  $\mathbf{x}_i, i = 1 \dots n$ .
- ▶ form  $y_i = \mathbf{w}^t \mathbf{x}_i$  to separate classes
- ▶ let  $\mathbf{m}_i = \sum_{j \in \mathcal{D}_i} \mathbf{x}_j / n_i$
- ▶ class scatter matrix  

$$\mathbf{S}_i = \sum_{\mathbf{x} \in \mathcal{D}_i} (\mathbf{x} - \mathbf{m}_i)(\mathbf{x} - \mathbf{m}_i)^t$$
- ▶ want  $|\mathbf{w}^t (\mathbf{m}_1 - \mathbf{m}_2)|$  large  
 $\rightarrow \|\mathbf{w}\| = \infty$




- ▶ better:  $J(\mathbf{w}) = \frac{|\mathbf{w}^t (\mathbf{m}_1 - \mathbf{m}_2)|^2}{\mathbf{w}^t (\mathbf{S}_1 + \mathbf{S}_2) \mathbf{w}}$  large



## LDA (2)

- ▶  $J(\mathbf{w}) = \mathbf{w}^t \mathbf{S}_B \mathbf{w} / \mathbf{w}^t \mathbf{S}_W \mathbf{w}$   
(generalized Rayleigh quotient)
- ▶  $\mathbf{S}_B = (\mathbf{m}_1 - \mathbf{m}_2)(\mathbf{m}_1 - \mathbf{m}_2)^t$   
(between-class scatter matrix)
- ▶  $\mathbf{S}_W = \mathbf{S}_1 + \mathbf{S}_2$  (within-class scatter matrix)
- ▶ calculus of variations:  
 $\delta / \delta \varepsilon \ J(\mathbf{w}_o + \varepsilon \mathbf{v})|_{\varepsilon=0} = 0 \forall \mathbf{v}$




- ▶ generalized eigenvector:  
 $\mathbf{S}_B \mathbf{w}_o = \lambda \mathbf{S}_W \mathbf{w}_o$
- ▶  $\mathbf{S}_W^{-1} \mathbf{S}_B \mathbf{w}_o = \lambda \mathbf{w}_o$ , if  $\mathbf{S}_W^{-1}$  exists
- ▶  $\mathbf{w}_o = \mathbf{S}_W^{-1} (\mathbf{m}_1 - \mathbf{m}_2)$ , since  
 $\mathbf{m}_1 - \mathbf{m}_2 \propto \mathbf{S}_B^{-1} \mathbf{w}_o$
- ▶  $\mathbf{w}_o$  is canonical variate

## LDA Example

# LDA ... Two Classes - Example

- Compute the Linear Discriminant projection for the following two-dimensional dataset.
  - Samples for class  $\omega_1$  :  $\mathbf{X}_1=(x_1,x_2)=\{(4,2),(2,4),(2,3),(3,6),(4,4)\}$
  - Sample for class  $\omega_2$  :  $\mathbf{X}_2=(x_1,x_2)=\{(9,10),(6,8),(9,5),(8,7),(10,8)\}$



```
% samples for class 1
X1 = [4,2;
      2,4;
      2,3;
      3,6;
      4,4];

% samples for class 2
X2 = [9,10;
      6,8;
      9,5;
      8,7;
      10,8];
```

LDA hyperlink

[L09]Elhabian\_LDA09

---

Higher Dimensional Features Are Good   Lower Dimensional Features Are Good   Principal Component Analysis   Fisher L

oo  
oo  
oo

---

Next:

Higher Dimensional Features Are Good

Lower Dimensional Features Are Good

Principal Component Analysis

- Linear PCA

- Adaptive PCA

- Nonlinear PCA (after neural net lectures)

- Kernel PCA

Fisher Linear Discriminant Analysis

**Kernel LDA**

Multiple Discriminant Analysis

Independent Component Analysis

---

Higher Dimensional Features Are Good   Lower Dimensional Features Are Good   Principal Component Analysis   Fisher L

oo  
oo  
oo

---

Next:

Higher Dimensional Features Are Good

Lower Dimensional Features Are Good

Principal Component Analysis

- Linear PCA

- Adaptive PCA

- Nonlinear PCA (after neural net lectures)

- Kernel PCA


Fisher Linear Discriminant Analysis

Kernel LDA

**Multiple Discriminant Analysis**

Independent Component Analysis

## MDA



- ▶  $c$  classes &  $c-1$  discriminants
- ▶  $n_i$  features in class  $\omega_i$
- ▶ total mean  $\mathbf{m} = \sum_{i=1}^c \mathbf{m}_i n_i / n$
- ▶ total scatter matrix  

$$\mathbf{S}_T = \sum_{\mathbf{x}} (\mathbf{x} - \mathbf{m})(\mathbf{x} - \mathbf{m})^t$$

- ▶  $\mathbf{S}_T = \mathbf{S}_B + \mathbf{S}_W$ ,  

$$\mathbf{S}_B = \sum_{i=1}^c n_i (\mathbf{m}_i - \mathbf{m})(\mathbf{m}_i - \mathbf{m})^t$$
- ▶ we seek  $\mathbf{W} \in \mathcal{R}^{d \times (c-1)}$  to yield  $\mathbf{y} = \mathbf{W}^t \mathbf{x}$
- ▶ good  $\mathbf{W} \iff$  large between-class scatter, small within-class scatter
- ▶  $J(\mathbf{W}) = |\mathbf{W}^t \mathbf{S}_B \mathbf{W}| / |\mathbf{W}^t \mathbf{S}_W \mathbf{W}|$
- ▶ solution  $\rightarrow$  ith column of  $\mathbf{W}$ :  

$$\mathbf{S}_B \mathbf{w}_i = \lambda_i \mathbf{S}_W \mathbf{w}_i$$
- ▶ implementation: roots of char poly  $|\mathbf{S}_B - \lambda_i \mathbf{S}_W| = 0$
- ▶ then solve:  $(\mathbf{S}_B - \lambda_i \mathbf{S}_W) \mathbf{w}_i = 0$
- ▶  $\mathbf{S}_B$  has rank  $\leq c-1 \implies$  at most  $c-1$  positive eigenvalues

## MDA

## LDA ... C-Classes

- Now, we have  $C$ -classes instead of just two.
- We are now seeking  $(C-1)$  projections  $[y_1, y_2, \dots, y_{C-1}]$  by means of  $(C-1)$  projection vectors  $\mathbf{w}_i$ .
- $\mathbf{w}_i$  can be arranged by *columns* into a projection matrix  $\mathbf{W} = [\mathbf{w}_1 | \mathbf{w}_2 | \dots | \mathbf{w}_{C-1}]$  such that:

$$y_i = \mathbf{w}_i^T \mathbf{x} \quad \Rightarrow \quad \mathbf{y} = \mathbf{W}^T \mathbf{x}$$

$$\text{where } \mathbf{x}_{m \times 1} = \begin{bmatrix} x_1 \\ \cdot \\ \cdot \\ x_m \end{bmatrix}, \quad \mathbf{y}_{(C-1) \times 1} = \begin{bmatrix} y_1 \\ \cdot \\ \cdot \\ y_{C-1} \end{bmatrix}$$

$$\text{and } \mathbf{W}_{m \times (C-1)} = [\mathbf{w}_1 | \mathbf{w}_2 | \dots | \mathbf{w}_{C-1}]$$

---

Higher Dimensional Features Are Good   Lower Dimensional Features Are Good   Principal Component Analysis   Fisher L

oo  
oo  
oo

---

---

MDA hyperlink

Elhabian\_LDA09.pdf



---

Higher Dimensional Features Are Good   Lower Dimensional Features Are Good   Principal Component Analysis   Fisher L  
oo  
oo  
oo

---

---

Next:

Higher Dimensional Features Are Good

Lower Dimensional Features Are Good

Principal Component Analysis

- Linear PCA

- Adaptive PCA

- Nonlinear PCA (after neural net lectures)

- Kernel PCA

Fisher Linear Discriminant Analysis

Kernel LDA

Multiple Discriminant Analysis

Independent Component Analysis

---

Higher Dimensional Features Are Good   Lower Dimensional Features Are Good   Principal Component Analysis   Fisher L

oo

oo

oo

---

## 2-Column Template