

BORNFIRE

LOCAL SETUP & DEVELOPER ONBOARDING GUIDE



VERSION 1.0 AUTHOR: BORNFIRE ENGINEERING TARGET AUDIENCE: ONBOARDING DEVELOPERS

1. SYSTEM PREREQUISITES

Before attempting to run the Bornfire workspace locally, you must ensure that your system has the following tools installed and active:

- **Node.js:** Version 18.x or higher (LTS recommended).
- **NPM / Bun:** Version manager to run scripts.
- **Docker Desktop:** Essential for launching the local PostgreSQL database service.
- **Git:** For version control.
- **DBeaver Community Edition:** Recommended database management client.

2. LOCAL ENVIRONMENT SETUP STEPS

Follow these steps sequentially to configure the workspace environment on your local machine:

1. Install Node Dependencies

Navigate to the frontend folder inside your repository and install dependencies:

```
cd frontend  
npm install
```

2. Configure Environment Variables (.env)

Duplicate the example env file inside the frontend directory and rename it to .env:

```
cp .env.example .env
```

Ensure the following keys are populated in your local .env:

```
VITE_SUPABASE_URL=your_supabase_project_url  
VITE_SUPABASE_ANON_KEY=your_supabase_anon_key
```

3. Launch Database Service (Docker Container)

Launch the PostgreSQL container using Docker Compose from the root workspace directory:

```
npm run docker:up
```

To verify the database is running successfully, execute:

```
docker ps
```

You should see a container named bornfire-db running on port 5435.

4. Connect DBeaver & Execute Migrations

Launch DBeaver and connect using the following credential structure:

- **Host:** localhost
- **Port:** 5435
- **Database:** bornfire
- **Username:** postgres
- **Password:** Panda@1501.1

Once connected, open an SQL script sheet, copy the content from `backend/schema.sql`, and run it to create database tables, indices, and triggers.

5. Run Frontend Development Server

Run the local Vite dev server from the project root directory:

```
npm run dev
```

The application will launch on port 3000: **`http://localhost:3000/`**.

3. SETUP TROUBLESHOOTING

3.1 DATABASE PORT 5435 ALREADY IN USE

If the container fails to start, verify if another local PostgreSQL server is using port 5435. You can stop conflicting local tasks or change the host port inside backend/docker-compose.yml.

3.2 ENV VARIABLES MISMATCH

If the client fails to connect to the database or authorization fails on mount, ensure that the Supabase keys in frontend/.env do not contain extra quotation marks or spaces.

DEVELOPER ONBOARDING SUPPORT

If you encounter problems that are not covered in this guide, reach out to the Bornfire engineering channel or check the docker container logs via: `docker logs bornfire-db`.