

About CIFAR-10 Dataset

19 October 2024 20:10

CIFAR-10 dataset is one of the well-known datasets in deep learning.

↓
image classification tasks

It is often used as a benchmark dataset for testing and evaluating algorithms, especially in the context of CNNs.

Overview of CIFAR-10 Dataset

Dataset Size

60,000 color images




Image Size:

all images are of size 32×32 pixels $\rightarrow 1024$ pixels

images are colored

↓
(RGB) \rightarrow meaning each image has 3 channels.

$$32 \times 32 =$$

↓
x's vector having that many neurons.

Number of categories (classes):

CIFAR-10 dataset has 10 classes


↓
representing objects or scenes or living things.

dataset is balanced

meaning there are 6000 images per class.

1 \rightarrow 6000
2 \rightarrow 6000
3 \rightarrow 6000
⋮
10 \rightarrow 6000

6000 \times 10 \rightarrow 60,000



→ Multi-class classification task

The CIFAR-100 dataset

This dataset is just like the CIFAR-10, except it has 100 classes containing 600 images each. There are 50 superclasses. Here is the list of classes in the CIFAR-100:

Superclass

aquatic mammals
fish
flowers
food containers
fruit and vegetables
household electrical devices
household furniture
insects
large carnivores
large man-made outdoor things
large natural outdoor scenes
large omnivores and herbivores
medium-sized mammals
non-insect invertebrates
people
reptiles
small mammals
trees
vehicles 1
vehicles 2

Classes

beaver, dolphin, otter, seal, whale
aquarium fish, flatfish, ray, shark, trout
orchids, poppies, roses, sunflowers, tulips
bottles, bowls, cans, cups, plates
apples, mushrooms, oranges, pears, sweet peppers
clock, computer keyboard, lamp, telephone, television
bed, chair, couch, table, wardrobe
bee, beetle, butterfly, caterpillar, cockroach
bear, leopard, lion, tiger, wolf
bridge, castle, house, road, skyscraper
cloud, forest, mountain, plain, sea
camel, cattle, chimpanzee, elephant, kangaroo
fox, porcupine, possum, raccoon, skunk
crab, lobster, snail, spider, worm
baby, boy, girl, man, woman
crocodile, dinosaur, lizard, snake, turtle
hamster, mouse, rabbit, shrew, squirrel
maple, oak, palm, pine, willow
bicycle, bus, motorcycle, pickup truck, train
lawn-mower, rocket, streetcar, tank, tractor

Yes, I know mushrooms aren't really fruit or vegetables and bears aren't really carnivores.

Concept of dimensions

Array → ndim
n-dimensions

1-D




line
x axis

2-D

∞ times

Height

∞ times



```
model = models.Sequential()
model.add(layers.Conv2D(32, (3,3), activation = 'relu', input_shape = (32,32,3))) ## added a 2D convolutional layer with 32 filters, each of size: 3 x 3, activation function is 'ReLU'
model.add(layers.MaxPooling2D((2,2))) ### adds a max pooling layer with pool size of 2 x 2, to reduce the spatial dimension -- by half
model.add(layers.Conv2D(64, (3,3), activation = 'relu')) ### added a 2D convolutional layer with 64 filters, each of size: 3x3, activation function is 'ReLU'
model.add(layers.MaxPooling2D((2,2))) ### Adds another max pooling layer of similar size 2x2
model.add(layers.Conv2D(64, (3,3), activation='relu')) #added a 2D convolutional layer with 64 filters, each of size, 3x3, activation function is 'ReLU'
```


Model: "sequential_2"

| Layer (type) | Output shape | Param # |
|--------------------------------|--------------------|---------|
| ✓ conv2d_4 (Conv2D) | (None, 30, 30, 32) | 896 |
| max_pooling2d_2 (MaxPooling2D) | (None, 15, 15, 32) | 0 |
| conv2d_5 (Conv2D) | (None, 13, 13, 64) | 18,496 |
| max_pooling2d_3 (MaxPooling2D) | (None, 6, 6, 64) | 0 |
| conv2d_6 (Conv2D) | (None, 4, 4, 64) | 36,928 |

Total params: 56,320 (220.00 KB)
 Trainable params: 56,320 (220.00 KB)
 Non-trainable params: 0 (0.00 B)

First layer: Conv2D

Input shape: (32, 32, 3)



Number of parameters

Formula for the number of parameters in a conv 2D layer is:

(kernel height \times kernel width \times input channels + 1) \times no. of filters

$= ((3 \times 3 \times 3) + 1) \times 32$

bias

$= 28 \times 32 = 28 \times 32 = 896$

Note: The additional '1' accounts for the bias term.

Second Layer: Max Pooling 2D

Input shape: (30, 30, 32)

output shape: (15, 15, 32)

of kernels/filters

spatial dimensions are reduced by half because of 2x2 max pooling operation with stride = 2

No parameters are learnt in the Max Pooling layer, so param # = 0.