

```
No.      Time                Source                Destination            Protocol Length Info
 4894 2024-01-15 23:28:01.766245 10.240.17.102         23.58.95.138          HTTP      208      GET /connecttest.txt HTTP/1.1
Frame 4894: 208 bytes on wire (1664 bits), 208 bytes captured (1664 bits) on interface \Device\NPF_{8F3B6709-9739-4955-9F08-FBF0EC1F870B}, id
0
Ethernet II, Src: ASUSTekCOMPU_02:43:cf (04:42:1a:02:43:cf), Dst: Cisco_0a:9a:e1 (44:b6:be:0a:9a:e1)
Internet Protocol Version 4, Src: 10.240.17.102, Dst: 23.58.95.138
Transmission Control Protocol, Src Port: 4594, Dst Port: 80, Seq: 1, Ack: 1, Len: 154
Hypertext Transfer Protocol

No.      Time                Source                Destination            Protocol Length Info
 4897 2024-01-15 23:28:01.817567 23.58.95.138          10.240.17.102          HTTP      241      HTTP/1.1 200 OK (text/plain)
Frame 4897: 241 bytes on wire (1928 bits), 241 bytes captured (1928 bits) on interface \Device\NPF_{8F3B6709-9739-4955-9F08-FBF0EC1F870B}, id
0
Ethernet II, Src: Cisco_13:2a:c2 (f8:7a:41:13:2a:c2), Dst: ASUSTekCOMPU_02:43:cf (04:42:1a:02:43:cf)
Internet Protocol Version 4, Src: 23.58.95.138, Dst: 10.240.17.102
Transmission Control Protocol, Src Port: 80, Dst Port: 4594, Seq: 1, Ack: 155, Len: 187
Hypertext Transfer Protocol
Line-based text data: text/plain (1 lines)
```