

```
No.      Time                Source                Destination            Protocol Length Info
 1327 2024-01-15 23:40:06.072400 10.240.17.102         34.107.221.82         HTTP      357      GET /canonical.html HTTP/1.1
Frame 1327: 357 bytes on wire (2856 bits), 357 bytes captured (2856 bits) on interface \Device\NPF_{8F3B6709-9739-4955-9F08-FBF0EC1F870B}, id
0
Ethernet II, Src: ASUSTekCOMPU_02:43:cf (04:42:1a:02:43:cf), Dst: Cisco_0a:9a:e1 (44:b6:be:0a:9a:e1)
Internet Protocol Version 4, Src: 10.240.17.102, Dst: 34.107.221.82
Transmission Control Protocol, Src Port: 3389, Dst Port: 80, Seq: 1, Ack: 1, Len: 303
Hypertext Transfer Protocol

No.      Time                Source                Destination            Protocol Length Info
 1329 2024-01-15 23:40:06.092821 34.107.221.82         10.240.17.102         HTTP      352      HTTP/1.1 200 OK (text/html)
Frame 1329: 352 bytes on wire (2816 bits), 352 bytes captured (2816 bits) on interface \Device\NPF_{8F3B6709-9739-4955-9F08-FBF0EC1F870B}, id
0
Ethernet II, Src: Cisco_13:2a:c2 (f8:7a:41:13:2a:c2), Dst: ASUSTekCOMPU_02:43:cf (04:42:1a:02:43:cf)
Internet Protocol Version 4, Src: 34.107.221.82, Dst: 10.240.17.102
Transmission Control Protocol, Src Port: 80, Dst Port: 3389, Seq: 1, Ack: 304, Len: 298
Hypertext Transfer Protocol
Line-based text data: text/html (1 lines)
```