Lecture 6

Jan 15, 2024

Process Execution

- OS creates a process entry for the process in a process list
- Allocates memory and creates memory image
- –Code and data (from executable)
- –Stack and heap
- Points CPU program counter to current instruction
- Other registers may store operands, return values etc.
- After setup, OS is out of the way and process executes directly on CPU

A simple function call

- A function call translates to a jump instruction
- A new stack frame pushed to stack and stack pointer (SP)updated
- Old value of PC (return value) pushed to stack and PC updated
- Stack frame contains return value, function arguments etc.

How is a system call different?

- CPU hardware has multiple privilege levels
 - -One to run user code: user mode
 - -One to run OS code like system calls: kernel mode
 - -Some instructions execute only in kernel mode
- Kernel does not trust user stack
 - -Uses a separate kernel stack when in kernel mode
- Kernel does not trust user provided addresses to jump to
 - -Kernel sets up Interrupt Descriptor Table (IDT) at boot time
- -IDT has addresses of kernel functions to run for system calls and other events

Mechanism of system call: trap instruction

- When system call must be made, a special trap instruction is run(usually hidden from user by libc)
- Trap instruction execution
 - -Move CPU to higher privilege level
 - -Switch to kernel stack
 - -Save context (old PC, registers) on kernel stack
- Look up address in IDT and jump to trap handler function in OS code

More on trap instruction

- Trap instruction is executed on hardware in following cases:
 - –System call (program needs OS service)
- -Program fault (program does something illegal, e.g., access memory it doesn't have access to)
- -Interrupt (external device needs attention of OS, e.g., a network packet has arrived on network card)
- Across all cases, the mechanism is: save context on kernel stack and switch to OS address in IDT
- IDT has many entries: which to use?
- -System calls/interrupts store a number in a CPU register before calling trap, to identify which IDT entry to use

Return from trap

- When OS is done handling syscall or interrupt, it calls a special instruction return-from-trap
 - Restore context of CPU registers from kernel stack
 - -Change CPU privilege from kernel mode to user mode
 - Restore PC and jump to user code after trap
- User process unaware that it was suspended, resumes execution as always
- Must you always return to the same user process from kernel mode? No
- Before returning to user mode, OS checks if it must switch to another process

Why switch between processes?

- Sometimes when OS is in kernel mode, it cannot return back to the same process it left
 - -Process has exited or must be terminated (e.g., segfault)
 - -Process has made a blocking system call
- Sometimes, the OS does not want to return back to the same process
 - -The process has run for too long
 - -Must timeshare CPU with other processes
- In such cases, OS performs a context switch to switch from one process to another

Mechanism to implement Process API

- A Process lifecycle Who does What ?
- Good to think terms of three layers
 - OS
 - Hardware
 - Process

Operating System	Hardware	User – Space Process
	BOOT UP	
Setup trap table	Save Syscall address	
Create 1st Process		
Assign pid to Proc Allocate Memory Load Program Setup stack with argv Setup Kernel Stack Return from trap	Restore regs from kernel stack Switch to user mode	Create Process
	Jump to PC (main)	Run main() in user s

Operating System	Hardware	User – Space Process
		Running Program Call syscall (int 0x80)
	Save regs to kernel stack, switch to kernel mode, jump to trap handler	
Handle trap, run syscall Update kernel stack, user stack Return from trap		
·	Restore regs from kernel stack, switch to user mode, jump to PC after trap	Continue execution exit() - trap
Free Memory, delete pid, manage child pids		

The OS scheduler

- OS scheduler has two parts
 - —Policy to pick which process to run
 - –Mechanism to switch to that process
- Non preemptive (cooperative) schedulers are polite
 - -Switch only if process blocked or terminated
- Preemptive (non-cooperative) schedulers can switch even when process is ready to continue
 - -CPU generates periodic timer interrupt
- After servicing interrupt, OS checks if the current process has run for too long

Context Switch Mechanism

- Example: process A has moved from user to kernel mode, OS decides it must switch from A to B
- Save context (PC, registers, kernel stack pointer) of A on kernel stack
- Switch SP to kernel stack of B
- Restore context from B's kernel stack
- Who has saved registers on B's kernel stack?—OS did, when it switched out B in the past
- Now, CPU is running B in kernel mode, return-from-trap to switch to user mode of B

A subtlety on saving context

- Context (PC and other CPU registers) saved on the kernel stack in two different scenarios
- When going from user mode to kernel mode, user context (e.g., which instruction of user code you stopped at) is saved on kernel stack by the trap instruction
 - -Restored by return-from-trap
- During a context switch, kernel context (e.g., where you stopped in the OS code) of process A is saved on the kernel stack of A by the context switching code
 - -Restores kernel context of process B

Operating System	Hardware	User – Space Process
Setup trap table	Save Syscall, timer interrupt address	
Start Interrupt Timer	Start timer Interrupt CPU in X ms	
Handle the trap Decide process to run by scheduling policy	Timer Interrupt Save regs (A) to kernel stack (A) Switch to kernel mode Jump to trap handler	Run Process A
Call switch(): Save proc-state of A Switch to kernel-stack of B Return from trap	Restore regs from kernel stack (B) Switch to user mode Jump to PC of B	Run Process B

```
# void swtch(struct context **old, struct context *new);
# Save current register context in old
# and then load register context from new.
.qlobl swtch
swtch:
  # Save old registers
 mov1 4(%esp), %eax # put old ptr into eax
 popl 0(%eax)
                 # save the old IP
 movl %esp, 4(%eax) # and stack
 movl %ebx, 8(%eax) # and other registers
 movl %ecx, 12(%eax)
 movl %edx, 16(%eax)
 movl %esi, 20(%eax)
 movl %edi, 24(%eax)
 movl %ebp, 28(%eax)
  # Load new registers
 mov1 4(%esp), %eax # put new ptr into eax
 mov1 28(%eax), %ebp # restore other registers
 movl 24(%eax), %edi
 movl 20(%eax), %esi
 movl 16(%eax), %edx
 movl 12(%eax), %ecx
 movl 8(%eax), %ebx
 movl 4(%eax), %esp # stack is switched here
                  # return addr put in place
  pushl 0(%eax)
                      # finally return into new ctxt
 ret
```

Homework -2

- What is the kernel stack of a process used for?
- When a process goes from user mode to kernel mode due to a trap occurring (system call / interrupt / program fault), who saves the context of the process? What exactly happens?
- What happens on a trap?
- Who saves user's CPU context when moving from user mode to kernel mode?
- Are different types of contexts saved on the kernel stack?

Scheduling is a vital OS role

- Many processes with differing roles run together
- Deciding which one runs next is a vital role of the OS

What is a scheduling policy?

- On context switch, which process to run next, from set of ready processes?
- OS scheduler schedules the CPU requests (bursts) of processes
- CPU burst = the CPU time used by a process in a continuous stretch
- If a process comes back after I/O wait, it counts as a fresh
 CPU burst

Policy and Mechanism


Dispatcher

- Main responsibility is context switch
- Low level hardware-software handling
- Mechanism

Scheduler

- Main responsibility is deciding which process to run
- High level algorithmic view
- Policy

Execution Phases



Types of Processes


I/O bound

- Has small bursts of CPU activity and then waits for I/O
- eg. Word processor
- Affects user interaction (we want these processes to have highest priority)
 cpu usage

CPU bound

- Hardly any I/O, mostly CPU activity (eg. gcc, scientific modeling, 3D rendering, etc)
 - Useful to have long CPU bursts
- Could do with lower priorities idle execute cpu usage time

CPU Scheduler



Scheduler triggered to run when timer interrupt occurs or when running process is blocked on I/O or exits

Scheduler picks another process from the ready queue

Performs a context switch

Schedulers

- Decides which process should run next.
- Objectives:
 - Minimize waiting time
 - · Process should not wait long in the ready queue
 - Maximize CPU utilization
 - CPU should not be idle
 - Maximize throughput
 - · Complete as many processes as possible per unit time
 - Minimize response time
 - CPU should respond immediately
 - Fairness
 - · Give each process a fair share of CPU

- Make gaming the scheduler hard

- Keep overheads of scheduling small

What are we trying to optimize?

- Maximize (utilization = fraction of time CPU is used)
- Minimize average (turnaround time = time from process arrival to completion)
- Minimize average (response time = time from process arrival to first scheduling)
- Fairness: all processes must be treated equally
- Minimize overhead: run process long enough to amortize cost of context switch (~1 microsecond)

When studying scheduling...


- Careful abstractions
- Workload Set of abstracted job descriptions
- Scheduler The policy/logic that decides what runs
- Metric Measurements/ analysis on scheduling quality

When studying scheduling...

- Theoretical analysis
- Workload (W), Scheduler (S), Metric (M)
- f(W, S) = M
- Scheduling problems are of different flavours:
- Given any two of these quantities, compute the third

Abstraction setup

• A job has an arrival time (a) and an execution time/burst time (c)




Turnaround time (t) = Completion time – arrival time

$$t_1 = 30 - 0 = 30$$

 $t_2 = 50 - 10 = 40$

Abstraction setup

• A job has an arrival time (a) and an execution time/burst time (c)



Response time (r) = first execution – arrival time

$$t_1 = 0 - 0 = 0$$

 $t_2 = 30 - 10 = 20$