PULSE

ACCURACY
YOU CAN TRUST,
RESULTS
YOU CAN RELY ON.

ZT Smart
SAA Biochemistry

High Performance
Reliable Results.



A complete solution for accurate and efficient biochemistry testing.

Trusted by **Labs.** Proven by **Results.**

ACCURATE RESULTS
Achieve highest accuracy

COST SAVING
Minimize reagent consumption

USER FRIENDLY
Easy to use with intuitive interface

RELIABLE PERFORMANCE
Advanced technology for consistent results

COMPACT. POWERFUL. PRECISE.

Compatible with all biochemistry reagents

7" RESISTIVE COLOUR TOUCH SCREEN
Display

25,000 TEST STORAGE
With QC Results

HALOGEN LAMP
Long life & high intensity

10 INCUBATOR POSITIONS
Built-in

BUILT-IN THERMAL PRINTER
(Optional)

MAKE IN INDIA

CE

Description :

ZT Smart Advance is a clinical chemistry analyzer with powerful features in a compact Unit For Biochemistry...


MAIN MENU

ZT Smart Advance is analyzer with a variety of features and performance levels to fit any application. 7" Resisistive color display gives you true convenience in operation and minimizes errors while entering data User friendly software with interactive Graphical user interface Shortcut keys for Menus to ease the operation




CALIBRATION

Availability of various Calibration types like K-factor, Linear and Non Linear calibration curves like Cubic Spline, Logit- log, Point to point enable the ZT Smart Advance to run variety of biochemical and immuno - turbidity assays.



SEARCH RESULTS

Easy to Access and Search Patient results for 3 different ways- View Record By ID,View Record By Date and View Record By Test.



Technical Specification :

Assay Types	End Point, Fixed Time, Rate A, Two Point Non Linear, Sample Blank, Multi-standard, Coagulation, Absorbency
Wavelengths	Automatic by 8 positions filter wheel Standard Filters: 340nm, 405nm, 505nm, 546nm, 578nm, 630nm, ± 10nm Two position free for optional filter Half bandwidth < 8nm Stray Light: < 0.3 at 340nm.
Photometer range	0.1-3.000Abs
Aspiration Volume	300ul to 1000uL
Flow Cell	Stainless steel with Quartz window measuring volume 32µL, optical path 1mm.
Inbuilt Incubator	Inbuilt with 10 incubator position.
Storage Capacity	120 Programs, 25000 Test records with reaction curve, QC Results
Light Source	12V/20W, Tungsten Halogen Lamp
Temperature Control	25, 30, 37C by Peltier Effect
Display	7"TFT colour LCD Display with resistive touch screen, Resolution-800X480Pixels
Printer	Built-in Thermal Printer (can be switched ON/OFF, when desired)
Power supply	External Universal Adaptor (15V,8A) 100 - 240VAC ±10%, 50/60 Hz, 60W
Operating Conditions	Temperature:15Cto40C, Relative Humidity: upto85%
Net Weight	5.5 Kgs Approx.

Zuvio Technologies Private Limited
1st Floor, Plot No. 646. 27th MainRoad, HSR Layout,
Sec-1, Bengaluru 560102.
+91 9071 101 108 www.pulseio.in info@pulseio.in

PULSE