Parameters

WBC, LYM#, MID#, GRAN#, LYM%, MID%, GRAN%,
RBC, HGB, HCT, MCV, MCH, MCHC, RDW–CV, RDW–SD,
PLT, MPV, PDW–SD, PDW–CV, PCT, P–LCR, P–LCC
3–part differentiation of WBC, 22 parameters and 3 histograms

Principles of operation

WBC/RBC/PLT: electrical impedance
HGB: photoelectric colorimetry

Aspiration volume

Whole blood 8.5 μL, pre–diluted 20 μL

Aperture diameter

WBC 100 μm, RBC/PLT 68 μm

Throughput

72 T/H

Data storage

Up to 1,000,000 sample results with histograms

Alarms

Error messages

Dilution ratio

	Whole blood	Capillary blood
WBC/HGB	1:232	1:400
RBC/PLT	1:40000	1:45000

Display

10.4–inch color LCD, resolution 800 × 600, touch screen

Control and calibration

L–J, X, X–R, X–B four control modes, manual and auto–calibration

Input/output

Support RS232, 6 USB (mouse, keyboard, HP printer, barcode reader and flash disk),
Internal 57mm thermal printer

Power

AC 100–240V, 50/60Hz, 180VA

Dimension & weight

380mm (L) × 305mm (W) × 395mm (H), about 18kg

PULSE



Marketed & Distributed By:
Zuvio Technologies Pvt. Ltd
1st Floor ' Plot no 646 , 27th Main Road
HSR Layout , sec -1 ,Bengaluru 560102
+91 9071101108 info@pulseio.in

PULSE



ZT370

3-Part-Diff Hematology Analyzer

Never Compromise Thirst for Speed, Faster to be First


72 tests/hour of double chambers
Compact and minimized size
2 reagents system (Diluent & Lyse)
RFID reagent close system optional



- 22 parameters with P–LCC, P–LCR and RBC, WBC, PLT histograms
- Throughput up to 72 tests per hour with double chamber design
- Impedance method for WBC, RBC and PLT
- Photoelectric colorimetry method for HGB with cyanide free reagent
- Micro sample volume at 8.5 μL for whole blood mode and 20 μL for pre-dilute mode
- On board storage capacity of 1,000,000 samples results
- RFID reagent close system optional
- Four kinds of QC modes: L–J, X, X–R and X–B
- Support USB data backup & system upgrade
- Built–in thermal printer
- LIS and HIS available with HL7 protocol







Accurate and Precise Results

- Proven impedance measurement technology
- Auto internal & external cleaning for aspiration probe
- High precision syringes
- Internal preheating for diluent for every test
- 68μm and 100μm ruby apertures



Easy to Use

- Large color LCD with high resolution
- Working status indicator light
- Mouse and keyboard connection by USB
- Internal storage of lyse



Cost-effective

- Tidy fluid system with low reagent consumption
- Only 2 reagents for sample testing
- Flexible reagent packaging from original manufacturer
- 30+ reagent joint venture manufacturers worldwide



Low and Easy Maintenance

- Special self-checking function during initialization
- Auto clog removing by aperture cauterizing and flushing
- Error messages
- Openable front panel and side door



Nearly Perfect Software Function

- Friendly interface and illustrate icons
- On board storage up to 1,000,000
- L-J, X, X-R and X-B QC methods
- Support LIS and HIS
- Tailor-made multi-language operation system



Reliable Spare Parts Quality

- Well-known global spare parts suppliers
- High performance PCB board from fully automatic assembly line
- Individual quality control management for each single component



International Standard Certificate and Registration Documents

- ISO9001 & ISO13485
- CE, FSC, clinical test report, risk analysis report
- Others



Professional Technical Support

- 24 x 7 around-the-clock response
- Entire life cycle service solution
- Door-to-door service for complicated problems
- Provide qualification certificate to skilled engineer

