KajiAI: Auditable Claim Verification with Bounded Research and Selective Evidence Gates

Anonymous review draft

***Abstract*—KajiAI is a LangGraph workflow that separates proposed factual labels from evidence acceptance. It records retrieved text versions, checks quotation provenance and citation support, and repeats research within explicit budgets. Across 500 AVeriTeC development claims, retaining 13 execution failures, the workflow achieved 67.4% label accuracy against 53.8% for a same-model control. The paired difference was 13.6 percentage points (95% bootstrap interval 8.6–18.6). The gate accepted 44 verdicts (8.8% coverage), of which 42 matched the dataset labels. Additional rounds corrected 18 predictions and changed 25 correct predictions to incorrect labels. In a separate challenge with 12 paired live continuations on fixed synthetic evidence, a query-exhaustion rule bypassed six reassessments and forfeited two correct gate acceptances, crossing the study's zero-loss guard. The findings distinguish label accuracy, acceptance coverage and the cost of reassessing unchanged evidence. Contemporary web access, development-set reuse and the absence of independent human citation validation constrain generalization.**

***Index Terms*—automated fact-checking, retrieval-augmented generation, LangGraph, citation provenance, selective prediction, AVeriTeC**

I. Introduction

Automated fact-checking requires more than assigning a plausibly correct label. A system should identify evidence, connect that evidence to the claim, disclose uncertainty and preserve enough provenance for inspection. FEVER established an evidence-oriented task using claims derived from Wikipedia [1]. AVeriTeC extends this setting to real-world claims and web evidence [2]. Its shared-task score combines verdict correctness with evidence quality [3], emphasizing that label agreement alone is an incomplete account of verification.

Retrieval-augmented generation provides external information to a language model [4], but retrieved documents, citations and repeated reasoning do not themselves guarantee an evidence-supported verdict. Citation evaluation distinguishes answer correctness from citation quality [5]. This distinction motivates an architecture in which prediction and acceptance are observable, separate decisions.

We present KajiAI, an auditable workflow implemented with LangGraph. A model proposes a factual label and an evidence assessment. A gate checks retrieved citations, exact quotations, assertion coverage, source-host diversity and domain requirements, followed by automated semantic citation review. Failed checks preserve the prediction while withholding an accepted verdict. Unresolved gaps can trigger further research, subject to limits on rounds, searches, page fetches, elapsed time and reported tokens.

We examine three questions. **RQ1** compares label prediction with a same-model, model-only control. **RQ2** asks which outputs fixed evidence policies select and what label agreement accompanies their coverage. **RQ3** examines how predictions, acceptance and resource use change across saved trajectories and under a query-exhaustion rule with fixed evidence.

We contribute a failure-inclusive comparison on 500 development claims, a fixed-evidence replay of acceptance rules and a paired challenge of query-exhaustion stopping. In the challenge, correct labels and supporting quotes can survive a stop even when stopping forfeits correct gate acceptance. Versioned sources and saved assessments make these outcomes separately auditable.

II. Related Work

A. Evidence-Based Fact-Checking

FEVER pairs supported and refuted claims with annotated evidence sentences [1]. AVeriTeC uses real-world claims, question–answer evidence and textual justifications from web sources [2]. The AVeriTeC shared task evaluates evidence retrieval and veracity prediction jointly [3]. We use its development labels for a local four-class study; our scores are not official AVeriTeC scores and cannot be directly compared with shared-task rankings.

The 2025 AVeriTeC shared task instead specifies open-weight models, a precompiled evidence store, a single-GPU resource constraint and a one-minute processing limit [6]. Our cloud-assisted, contemporary-web protocol does not reproduce those conditions.

B. Retrieval and Citation Evaluation

RAG combines parametric generation with external document memory [4]; Self-RAG learns retrieval and critique through reflection tokens [7]. KajiAI instead uses structured assessments, query templates and explicit routing rules, allowing inspection of query generation and stopping behavior.

FIRE integrates retrieval and verification iteratively, choosing a final judgment or another search query using confidence [8]. EMULATE distributes search-result ranking and webpage-content assessment across agents [9]. Iterative research and role separation therefore precede KajiAI. Our empirical focus is preserving source versions, separating provisional prediction from rule-based acceptance, and measuring changes across frozen trajectories.

ALCE evaluates generated answers along fluency, correctness and citation quality dimensions [5]. Our literal-quote check addresses a narrower property: whether a quoted string occurs in stored text for its cited URL. A separate model reviews whether that quotation supports its attached finding.




Fig. 1. Explicit stateful workflow. Remaining gaps can trigger retrieval; failures, stagnation and budgets stop research. Finalization independently rechecks acceptance conditions.

Neither mechanism independently establishes the truth of the overall verdict.

C. Selective Prediction

Selective classification trades coverage for accuracy through rejection [10]. KajiAI selects outputs through evidence requirements; its confidence categories and citation-review scores lack independent calibration, so the reported coverage and conditional label accuracy carry no statistical risk guarantee.

III. System Design

A. Stateful Graph and Execution

LangGraph supports stateful workflows combining deterministic operations and model calls [11]. Eight nodes execute KajiAI's process in Fig. 1. The shared state includes the original claim, optional reference date, domain, assertions, retrieval ledger, research history, proposed assessment, evidence gaps, budgets and stop reason. Individual claims follow a sequential graph; the study runner processes up to three claims concurrently.

The evaluated model is `gemma4:31b-cloud`, accessed through a local Ollama endpoint. The cloud model and TinyFish and TypeSafe services make this a network-dependent implementation. Successfully fetched pages are reused within a claim. The study runner resumes at completed claim boundaries; the graph has no persistent checkpoint store.

Jev, accessed through the TypeSafe SDK, supplies the workflow's domain, search-ranking, source-review and citation-support judgments. Domain classification uses Jev when its confidence is at least 0.6, with an Ollama classifier and then keyword scoring as fallbacks. The profiles are general, scientific, political and health/medical. Decomposition is a deterministic conjunction heuristic, limited to six fragments; the original claim is always retained. Fragments are coverage obligations within one assessment, rather than independently executed agents or a weighted verdict ensemble.

B. Query Construction and Retrieval

At round t, retrieval constructs an ordered list from (i) follow-up queries proposed in the previous assessment, (ii) the claim plus "evidence," (iii) the claim plus "counterevidence," (iv) each assertion plus "evidence," and (v) each assertion plus "original source fact check." It trims and deduplicates strings, excludes previously used queries and selects the first two remaining candidates when the budget permits.

Candidate construction therefore combines model suggestions with hardcoded templates. No learned optimizer chooses the best query. Jev ranks returned URLs for fetching, a separate decision from choosing a query. TinyFish supplies up to five results per search and up to two full-page fetch attempts per search. Failed fetches leave available snippets in the ledger.

A source record stores the URL, query, provider, retrieval time, snippet or page text, content hash and review scores. Full-page text is preferred to a snippet for the same URL, truncated to 20,000 characters and hashed after truncation. The canonical record used in an assessment is retained by URL and hash, permitting replay against the same text version. Jev source review estimates relevance, evidence value, counterevidence value and injection risk. Reviewed records with injection score at least 0.9, or all three relevance/evidence scores below 0.1, are excluded from usable evidence. Unreviewed records retain permissive defaults; this filter is not a demonstrated injection defense.

C. Prediction and Acceptance

The analyzer returns a structured assessment containing a verdict, confidence category, findings, cited URLs, quotations, assertion resolutions, contradictions, gaps and next queries. It also reports source independence, counterevidence search and, where required, peer-reviewed support. These model-reported flags are policy inputs rather than independently verified facts.

Let $\hat{y}_i$ be the proposed label for claim i, and $G_{s,i}$ and $G_{m,i}$ its structural and semantic gap sets. Acceptance is

$$a_i = \mathbf{1}\{G_{s,i} = \varnothing,\ G_{m,i} = \varnothing,\ F_i = 0\}, \tag{1}$$

where F_i indicates execution failure. The accepted output is

$$\tilde{y}_i = \begin{cases} \hat{y}_i, & a_i = 1, \\ \perp, & a_i = 0, \end{cases} \tag{2}$$

where $\perp$ is operational abstention, not the factual NEI class.

Structural acceptance requires a decisive verdict and High confidence; nonempty retrieved citations for every finding; literal quotations in canonical source text; complete assertion coverage; at least two cited hosts; no flagged duplicate lineage among cited sources; and no unresolved gaps or contradictions. A token-set Jaccard threshold of 0.85 flags substantially

similar source text. Counterevidence and independence flags must be positive. Scientific claims require HTTPS citations; health/medical claims require the peer-review flag. A conflicting verdict additionally requires supporting and refuting findings. Established disagreement belongs in those findings and the summary; the contradictions field instead records unresolved objections to the proposed verdict. Distinct hosts, text dissimilarity and model flags do not prove actual independence.

For each eligible finding–URL–quotation triple, Jev reviews the quotation and up to 1,200 surrounding characters on each side. Semantic acceptance requires a "supports" relation with confidence at least 0.8 for every citation. Missing or failed citation checks block acceptance. Review identity includes finding, URL, quotation and content hash; finalization repeats structural checks and confirms review coverage. This tests quotation support for an attached finding, not the entire inferential chain from documents to verdict.

D. Bounded Research and Auditability

When gaps remain, routing allows further research if execution has not failed and resource and stagnation limits permit it. Two consecutive rounds with no new ledger records trigger a stagnation stop. A new record can be a changed snippet for an already fetched URL, so ledger growth is not equivalent to new usable evidence.

Each round retains its raw assessment, exact usable source versions, gaps, budget snapshot, elapsed time and stop decision. Reported token usage is aggregated, with a completeness flag when accounting is unavailable. Time and token limits govern scheduling; an in-flight request can finish after the soft deadline or exceed the reported-token threshold. Missing usage prevents a guaranteed spend cap. The report preserves proposed and accepted verdicts separately and distinguishes insufficient evidence from execution errors.

IV. Evaluation Protocol

A. Dataset and Frozen Conditions

The completed study assesses all 500 AVeriTeC development claims in two conditions. The split contains 122 Supported, 305 Refuted, 35 Not Enough Evidence and 38 Conflicting Evidence/Cherrypicking labels. Only claim text and claim date are supplied as dataset inputs to inference. Gold labels, justifications and annotated evidence are reserved for scoring and post hoc audit. Both conditions use the same model, temperature and structured-output adapter.

The *model-only control* produces one verdict from existing model knowledge without search, domain routing or an evidence gate. The *full workflow* applies the architecture above. Their comparison measures the combined workflow, including its different prompt and evidence context; it does not isolate retrieval, Jev or LangGraph individually. The *first-round analysis* truncates saved full-workflow trajectories rather than constituting a separately executed system.

Table I summarizes the protocol. Claim-condition tasks were shuffled with a fixed seed, but contemporary search and cloud-model responses remain externally variable. Source, configuration, package versions, dataset bytes and hashes are archived. Earlier exploratory runs used different source versions and are excluded. Resume checks reject changes to the frozen inference configuration.

TABLE I
Frozen Evaluation Configuration

Setting	Value
Main model / temperature	`gemma4:31b-cloud` / 0
Review model / threshold	`jev-1.13.0` / 0.8
Research limits per claim	3 rounds; 300 s soft deadline
Search / fetch ceilings	20 logical searches; 20 fetches
Budgeted reported tokens	250,000 aggregate reported tokens
Per-round retrieval	Up to 2 queries; 2 fetches/query
Study scheduling	3 workers; seed 20261009
Installed libraries	LangGraph 1.2.11; Pydantic 2.13.5; TypeSafe SDK 0.7.1

The local reproducibility bundle, `study-20261009-v3`, contains the run manifest, source archive, dataset snapshot, raw JSONL records and per-claim replay results. Source and dataset SHA-256 prefixes are `624a8d2fa125` and `499793726b4a`, respectively; the manifest retains their complete hashes. The plotting script reads saved metrics, without issuing additional service calls.

The study retains all 1,000 planned claim-condition attempts, including 8 workflow and 5 control execution failures. A monthly quota limit interrupted execution after 302 workflow and 283 control attempts; seven quota failures remain recorded. Later concurrent-slot timeouts and a local Ollama restart interrupted two pending control requests. Only unattempted tasks were resumed, with the original model, source, dataset and settings; recorded failures were never retried or replaced. Full incident details accompany the reproducibility bundle.

B. Metrics and Uncertainty

The evaluation schema maps TRUE, FALSE, NOT_ENOUGH_EVIDENCE and CONFLICTING to the four dataset labels. Generic MISLEADING predictions are not equated with the conflicting-evidence class. The evidence gate accepts decisive labels only, excluding NEI by design. Accepted NEI recall is therefore zero even when raw predictions are correct.

For n attempted claims and gold labels y_i, raw accuracy, coverage and selective accuracy are

$$A = \frac{1}{n}\sum_{i=1}^{n} \mathbf{1}\{\hat{y}_i = y_i\}, \tag{3}$$

$$C = \frac{1}{n}\sum_{i=1}^{n} a_i, \tag{4}$$

$$A_{\text{sel}} = \frac{\sum_{i=1}^{n} a_i \mathbf{1}\{\hat{y}_i = y_i\}}{\sum_{i=1}^{n} a_i}. \tag{5}$$

Selective accuracy is undefined when no output is accepted. Macro F1 averages F1 across the four gold classes; abstentions

TABLE II
PREDICTION RESULTS ON ALL 500 CLAIMS

Condition	Accuracy (%)	95% CI	Macro F1
Always Refuted	61.0	56.7–65.2	0.189
Model only	53.8	49.4–58.1	0.417
First round†	68.8	64.6–72.7	0.530
Final workflow	67.4	63.2–71.4	0.500

†Saved-trajectory truncation, not a separate live one-round condition. Wilson intervals; local label metrics, not official AVeriTeC evidence scores.

TABLE III
ACCEPTANCE REPLAY ON 500 FINAL ASSESSMENTS

Policy	Accepted	Coverage (%)	Correct / accepted
Structural only	50	10.0	45/50 (90.0%)
Structural + Jev	44	8.8	42/44 (95.5%)

Conditional accuracy 95% CI: 78.6–95.7% for structural-only replay; 84.9–98.7% for the full gate.

contribute missed predictions without becoming a fifth gold class. End-to-end accepted-label accuracy is CA_{sel}, preventing conditional accuracy from obscuring low coverage.

Fatal errors remain in the denominator. Failure-inclusive scoring treats them as abstentions; raw scoring can preserve an earlier prediction if a later service fails. Raw and failure-inclusive accuracies coincide. We report 95% Wilson intervals for proportions, a paired accuracy bootstrap with 2,000 claim-level resamples and seed 20261009, and an exact two-sided McNemar test. These intervals treat claims as sampling units; they do not capture correlated topics, shared-source effects, model drift, service availability or web changes.

C. Offline Policy Replay and Citation Audit

Policy replay applies alternative acceptance rules to the same saved final assessments and source versions. We compare structural-only acceptance with the full gate and semantic thresholds from 0.5 to 0.95. Replay cannot show how changing a gate would alter later retrieval or reasoning. Removing exact-quote requirements also changes eligibility for semantic review, so it is not an isolated semantic ablation.

Citation measurements count finding–URL occurrences in final assessments, including repeated URLs across findings. A blinded human-audit worksheet contains 454 citation rows from 44 accepted and 50 sampled rejected claims; labels and acceptance status are stored separately. Human annotation fields remain blank. Automated Jev judgments are measurements rather than independent human ground truth.

V. RESULTS

A. Paired Label Prediction

Both conditions assess the same 500 claims: 122 Supported, 305 Refuted, 35 NEI and 38 Conflicting labels. Table II reports the paired label results, including failed attempts.

Full predictions are correct on 337 claims, compared with 269 for the control. The workflow is correct on 117 claims missed by the control, while the control is correct on 49 missed by the workflow; both are correct on 220 and both are wrong on 114. The paired accuracy difference is 13.60 percentage points (bootstrap 95% CI: 8.60–18.60); exact McNemar $p = 1.35 \times 10^{-7}$.

The majority baseline achieves 61.0% accuracy because Refuted dominates the split, but its macro F1 is only 0.189. The workflow improves accuracy and macro F1 over the model-only control. It predicts the conflicting class 98 times, compared with 38 gold conflicting labels. Its NEI recall is 17.1%, compared with 40.0% for the control. Improvement is therefore not uniform across classes.

B. Selective Acceptance

Table III compares acceptance rules on all 500 saved final assessments. Raw prediction accuracy and accepted-label accuracy represent different outcomes.

The full gate withholds 6 outputs accepted by structural-only replay: 3 wrong labels and 3 correct labels. It accepts 35 Refuted and 9 Supported. Its coverage interval is 6.6–11.6%, and end-to-end accepted-label accuracy is 8.4%. The gate leaves 295 correct predictions and 161 other attempts unaccepted. Its 95.5% conditional accuracy describes a small selected subset.

The selected gold labels are 33 Refuted, 9 Supported and 2 Conflicting; the 35 Refuted and 9 Supported counts above describe predictions. On these same 44 IDs, the model-only control matches 30 labels (68.2%), while the workflow matches 42. This is a descriptive comparison on a workflow-selected subset, not an independent test of the gate's causal benefit. Selecting only High-confidence assessments instead retains 429 claims with 326 matching labels (76.0%); these differently selected cohorts do not establish a calibrated risk guarantee.

Both accepted errors, IDs 353 and 404, have gold conflicting-evidence labels but receive Refuted predictions. In ID 353, the saved assessment uses findings about compensation and legal action to adjudicate a claim specifically about unlicensed vaccines. In ID 404, it combines official denials of complete railway privatization and job losses with reporting about employees' future job-security fears. These illustrative records expose a gap between supporting individual findings and resolving the claim's qualifications and temporal scope. They are case inspections rather than completed human citation annotations.

Figure 2 shows descriptive threshold replay. Stricter thresholds reduce coverage, while lower thresholds can admit additional outputs. Selecting a threshold from this development analysis would require separate validation.

C. Changes Across Saved Research Rounds

First-round accuracy is 68.8%, compared with 67.4% for final predictions. Additional rounds change 62 predictions: 18 wrong-to-correct, 25 correct-to-wrong and 19 between incorrect labels. The final-minus-first difference is -1.40 percentage points (bootstrap 95% CI: -4.00 to 1.20). Excluding




Fig. 2. Semantic-threshold replay on 500 final assessments, holding evidence and structural rules fixed. Accepted counts at thresholds 0.50, 0.60, 0.70, 0.80, 0.90 and 0.95 are 46, 45, 44, 44, 30 and 24. The curve does not establish an optimal threshold.

8 fatal attempts yields -0.81 points on 492 nonfatal attempts, with an interval of -3.25 to 1.63.

These saved trajectories quantify within-run changes across later rounds; a separately deployed one-round system can behave differently because timing and search responses can change. Of the attempted workflows, 452 use 3 rounds, 30 use 2 rounds, 18 use 1 round. The prevalence of the round limit warrants evaluating stopping behavior.

Acceptance also changes across the saved trajectories: the first round accepts 14 labels, all matching gold, whereas the final outputs accept 44, with 42 matching gold. Higher final acceptance therefore accompanies lower raw label accuracy in this run. The paired accuracy intervals include zero, so the negative point estimate does not establish an average harmful effect of iteration.

A post hoc query-exhaustion audit identifies 252 third rounds with no additional searches, empty prior follow-up queries and unchanged usable-source versions. These repeated assessments consume 4,154,865 observed tokens. They correct two labels, change one correct label to an incorrect one, and add two acceptances. Truncating those saved rounds would lose one net correct prediction and two acceptances. This motivates testing an explicit stopping policy, while preserving reassessment as a potentially useful operation; it does not demonstrate a cost-only improvement.

D. Citation Diagnostics and Resource Use

Final assessments contain 2,611 citation occurrences. Of these, 1,914 have literal quotes present in canonical text and 1,914 have Jev reviews. 34 reviewed quotes receive a relation other than "supports," and 158 receive supporting confidence below 0.8. The remaining 697 occurrences fail literal provenance matching. They are not automatically counted as hallucinations: a quotation can refer to a snippet differing from the preferred full-page text, or exhibit another provenance mismatch.

TABLE IV
OPERATIONAL MEASUREMENTS ON 500 TASKS PER CONDITION

Measurement	Full workflow	Model only
Attempted tasks	500	500
Fatal execution errors	8	5
Mean elapsed time (s)	79.2	7.7
Median elapsed time (s)	72.1	3.4
90th percentile time (s)	120.1	9.0
Logical search calls	2,049	0
Page-fetch attempts	3,953	0
Observed model tokens	34,452,832	183,416

Same 500 claim inputs; tokens aggregate providers and accounting is incomplete. Concurrent task durations are not study wall-clock time.

Final structural gaps include missing exact quotations on 353 claims and insufficient independence flags on 357; these categories overlap. A host-exposure audit unwraps Wayback Machine URLs before comparison. On 208 of 500 claims, a cited host matches the host of the dataset's fact-check article. Host equality does not prove exact-article exposure, and an unmatched host does not exclude other exposure routes.

In the post hoc host-match group, workflow and control accuracies are 77.9% and 50.5% (208 claims); in the unmatched group they are 59.9% and 56.2% (292 claims). Groups depend on workflow citations and differ in class composition. This is a descriptive exposure audit, not a causal comparison or contamination-free score.

Table IV reports operational totals. There are 551 recorded fetch failures and 2 Jev ranking failures, distinct from fatal execution errors. The 934 rounds after the first consume 1,049 searches, 2,013 fetch attempts and 23,546,637 observed tokens; 263 add no new ledger records. Incomplete provider-level accounting prevents an exact monetary-cost estimate. Iteration cost and the saved accuracy changes support investigating evidence novelty and stopping rules.

E. Separate Runtime Development Pilot

After freezing the historical study, we implemented an opt-in query-exhaustion stop that retains the prior assessment and leaves acceptance rules unchanged. Pending source review or semantic citation gaps preserve reassessment. Focused fixtures reduce provider invocations from three to two (six to four with a repair per assessment), while also demonstrating a possible lost acceptance. The baseline remains the default.

A live development pilot paired both policies on claims 17 and 246 with tighter output limits and service retries disabled. The 75 requests comprised 11 Ollama, 31 Jev, 11 search and 22 fetch requests, including a smoke check and the retained baseline failure caused by local UTF-8 logging. Transport records contain 190,142 Ollama and 79,658 Jev tokens. Three workflows completed, all proposed Refuted and none passed the gate. Both candidate trajectories exhausted queries after round two, but semantic citation gaps kept reassessment active. The only complete pair used three model assessments per policy. The live pilot therefore exercised no early stop.

F. Controlled Stopping Challenge

We froze eight synthetic cases and exercised both policies through the production graph with identical scripted retrieval and first two assessments. All exhausted their queries after round two. The candidate stopped in all four cases with completed citation review, preserved the preceding proposal and two literal citations in each, and used two assessments against three for the baseline. All four unresolved-review cases continued and matched the baseline under shared scripted continuations. Among the four early stops, the designed third-round outcomes included two correct gate acceptances that stopping forfeited, one wrong verdict that stopping avoided, and one unchanged decision. A wrong verdict also passed both policies in one unresolved case under the permissive scripted final review. These are controlled reachability results. The scripts specify the outcomes, so the counts do not estimate model behavior or real-world event rates.

An exploratory eligibility screen reuses the 252 historical no-search rounds. Round-two semantic gaps would block stopping in 77, including both recovered correct acceptances. The remaining 175 contain two label corrections, one degradation and no new acceptances. Round-two pending source review is unavailable for reconstruction. Even if stopping only affects this latter stratum, the compatible change in correct predictions in the saved subset ranges from losing two to gaining one, depending on which transitions were eligible. This is a descriptive bound on saved outcomes. The synthetic counterexamples establish that completed citation review can coexist with useful reassessment.

We froze two four-case batches before live inference. Each included two completed-review and two unresolved-review cases. The scripted prefixes held a correct, Medium-confidence proposal after round two, below the gate's High requirement. Each baseline received a live third assessment at temperature zero with a 2,048-token requested generation cap and up to one schema repair. If the candidate continued, it reused the assessment after an exact match of continuation inputs. Scripted retrieval and citation review required zero search, fetch or Jev requests. The final reviewer stub permitted literal quotes, so we separately adjudicated each gate acceptance against the authored finding, stance and source text. The predeclared zero-loss guard was evaluated at the batch boundary.

The first batch completed all 12 model–case pairs and passed every trace check. Each model's candidate stopped on both completed-review cases, preserving the exact proposal and two literal quotes in each. Both unresolved cases per model continued and matched their coupled baselines. Table V reports the within-model outcomes.

In case e01, a firsthand account and a committee record both place the inaugural lantern fair on Thursday. Gemma's reassessment accepted the correct verdict with both exact quotes, while the stopped candidate retained the proposal and quotes but abstained. In e02, an August 2 public-opening record and an independent diary of the August opening ceremony refute a June opening under the authored case's single-event interpretation. The diary corroborates the month without establishing the exact day. Both acceptances were lost under stopping. The e01 loss alone crossed the guard. Batch two was therefore left unrun and reassessment remains the default.

TABLE V
CONTROLLED LIVE CONTINUATIONS, FOUR PAIRED CASES PER MODEL

Model	Correct labels B / C	Correct accepts B / C	Sends skipped	Tokens skipped
Gemma 4 31B	4 / 4	3 / 1	2	4,446
GLM 5.3 Flash	1 / 2	0 / 0	3	9,086
DeepSeek V4.1 Flash	4 / 4	0 / 0	2	7,461

B is the baseline and C is the candidate. Skipped costs are observed on baseline continuations bypassed by C.

The requested tags were `gemma4:31b-cloud`, `glm-5.3-flash:cloud` and `deepseek-v4.1-flash:cloud`. Responses identified the corresponding models without the cloud tag suffix. The batch used 15 actual sends and 42,447 observed tokens, including three GLM schema repairs. Four GLM replies and one DeepSeek reply reached the output cap. GLM's candidate retained four literal quotes across the four cases, while its baseline retained zero. Gemma and DeepSeek each retained eight under either policy. Each model had only two eligible cases and the Flash baselines accepted none. The shared synthetic cases and scripted correct prefixes limit interpretation to the tested continuations. Harm rates and net savings under live web deployment remain undetermined.

VI. DISCUSSION AND LIMITATIONS

A. What the Results Support

The paired comparison shows higher label accuracy for this combined workflow than for its control. Semantic replay withholds both correct and incorrect labels; saved trajectories expose costly reassessment with mixed prediction changes. Prediction, acceptance and resource use therefore warrant separate measurement.

The study includes no independently executed retrieval-only, Jev-disabled or alternative-framework comparison. Its evidence supports neither framework superiority, a hallucination-reduction percentage nor benchmark-leading performance.

B. Threats to Validity

Service availability: Quota and concurrent-slot interruptions required resumption across time. A post hoc sensitivity analysis on 487 pairs without fatal errors gives a workflow-minus-control difference of 14.37 points (bootstrap 95% CI: 9.45–19.10). Remote responses and current web results can drift.

Temporal and verdict exposure: Retrieval uses the contemporary web without a historical publication cutoff. Later reports and published verdicts can help predict older claims. Original AVeriTeC annotations address temporal evidence concerns [2], but our protocol does not reproduce that constraint. Pretraining exposure is unknown, and the repeatedly used development split is not a pristine held-out test.

Evidence validity: Literal checks verify provenance only. Jev support judgments lack independent calibration and human entailment labels. Model-reported independence and peer-review flags can be wrong. Text similarity can miss paraphrased copying or flag legitimate overlap; snippets can omit qualifying context. The prepared human audit has not been performed.

Task and control scope: Different prompts make the model-only comparison a combined-workflow effect. Heuristic decomposition can create incomplete fragments. Excluding NEI from acceptance restricts task coverage. Multilingual, multimodal, adversarial and user-facing behavior has not been evaluated.

Reproducibility: Hosted model revisions and complete provider-specific usage are unavailable for the historical study. Soft deadlines, quotas and web changes limit repeatability. The companion artifact documents the historical records and includes the controlled protocol, authored cases, assessment harness, saved traces and request ledgers. Both sets of reported results can be checked from saved records without calling live services.

C. Next Evaluation Steps

Independent human review should assess citation support and source credibility, retaining separate annotations and adjudication for the accepted and rejected strata. An independent, temporally constrained evaluation could measure naturally occurring stopping eligibility. Executed retrieval-only and Jev-disabled conditions would help isolate the contribution of each mechanism.

VII. Conclusion

KajiAI makes proposed verdicts, evidence acceptance and research history independently inspectable. In a completed 500-claim AVeriTeC development evaluation, the workflow improves paired label accuracy over a model-only control, while a strict gate accepts few claims and later research can worsen saved predictions. In a controlled challenge with live continuations, reassessing unchanged evidence recovered correct acceptances that query-exhaustion stopping forfeited. This tradeoff supports keeping reassessment as the default under the tested guard.

Acknowledgment

OpenAI Codex assisted with drafting Sections I–VII, creating the architecture diagram and plotting code, developing the controlled evaluation harness, and auditing scripts and results. Numerical results were computed from saved execution records.

References

[1] J. Thorne, A. Vlachos, C. Christodoulopoulos, and A. Mittal, "FEVER: A large-scale dataset for fact extraction and verification," in *Proc. NAACL-HLT*, vol. 1, 2018, pp. 809–819, doi: 10.18653/v1/N18-1074.

[2] M. Schlichtkrull, Z. Guo, and A. Vlachos, "AVeriTeC: A dataset for real-world claim verification with evidence from the web," in *Advances in Neural Information Processing Systems*, vol. 36, 2023. [Online]. Available: https://arxiv.org/abs/2305.13117

[3] M. Schlichtkrull et al., "The Automated Verification of Textual Claims (AVeriTeC) shared task," in *Proc. Seventh Fact Extraction and VERification Workshop*, 2024, pp. 1–26, doi: 10.18653/v1/2024.fever-1.1.

[4] P. Lewis et al., "Retrieval-augmented generation for knowledge-intensive NLP tasks," in *Advances in Neural Information Processing Systems*, vol. 33, 2020. [Online]. Available: https://arxiv.org/abs/2005.11401

[5] T. Gao, H. Yen, J. Yu, and D. Chen, "Enabling large language models to generate text with citations," in *Proc. EMNLP*, 2023, pp. 6465–6488, doi: 10.18653/v1/2023.emnlp-main.398.

[6] M. Akhtar et al., "The 2nd Automated Verification of Textual Claims (AVeriTeC) shared task: Open-weights, reproducible and efficient systems," in *Proc. Eighth Fact Extraction and VERification Workshop*, 2025, pp. 201–223, doi: 10.18653/v1/2025.fever-1.15.

[7] A. Asai, Z. Wu, Y. Wang, A. Sil, and H. Hajishirzi, "Self-RAG: Learning to retrieve, generate, and critique through self-reflection," in *Proc. International Conference on Learning Representations*, 2024. [Online]. Available: https://arxiv.org/abs/2310.11511

[8] Z. Xie et al., "FIRE: Fact-checking with iterative retrieval and verification," in *Findings of the Association for Computational Linguistics: NAACL 2025*, 2025, pp. 2901–2914, doi: 10.18653/v1/2025.findings-naacl.158.

[9] S. Hong, M. Luo, and X. Wan, "EMULATE: A multi-agent framework for determining the veracity of atomic claims by emulating human actions," in *Proc. Eighth Fact Extraction and VERification Workshop*, 2025, pp. 179–183, doi: 10.18653/v1/2025.fever-1.13.

[10] Y. Geifman and R. El-Yaniv, "Selective classification for deep neural networks," in *Advances in Neural Information Processing Systems*, vol. 30, 2017. [Online]. Available: https://arxiv.org/abs/1705.08500

[11] LangChain, "LangGraph overview." Accessed: Oct. 10, 2026. [Online]. Available: https://docs.langchain.com/oss/python/langgraph/overview