Revision Comparison

The number stays. The claim changes.

COMPARE MODE / SYNTHETIC ML EXCERPT

The revision shortens the method, moves the reporting protocol, and broadens a timing claim. Both supplied versions are preserved.

In this report: C1 / concise method C2 / moved and merged protocol C3 / timing scope

C3 / Broaden the timing claim

The Summary's claim depends on a measurement boundary in another section.

Source context / After, Evaluation Protocol, paragraph 2, sentence 2

Timing starts after feature precomputation and excludes that cost.

Retained from Before, Results, paragraph 3, sentence 2; moved by C2. The adapter and baseline use the same cached embeddings and fixed split.

C3 / BEFORE — **Summary, paragraph 1**

The adapter reduces optimization time by 38%.

C3 / AFTER — **Summary, paragraph 1**

The adapter reduces end-to-end training time by 38%.

C3 / Explanation / inferred; author intent unknown

The value stays at 38%, but the stated timing scope expands. The supplied protocol excludes feature precomputation and does not substantiate end-to-end time.

Review / substantive scope change. Author review needed. The wording and timing boundary were checked; the number is not shown to be false. Additional measurements may exist. The supplied After is not repaired.

Sources. `before.md` and `after.md`; SHA-256 identities in `identity.json`. Paragraphs count prose blocks under each heading. Both complete files are compared. No experimental records or author explanations were supplied.

Useful edits, traced

The same revision also improves wording and organization

C1 / Make the training description more concise

C1 / BEFORE — **Method, paragraph 1**

We keep the encoder fixed. We compute one embedding per image and store it. A small adapter is trained on these stored embeddings.

C1 / AFTER — **Method, paragraph 1**

We cache one embedding per image from a frozen encoder and train a small adapter on the cached embeddings.

Inferred benefit. One sentence connects feature computation, storage, and adapter training. The original wording is grammatical. **Review / exposition-only.** The fixed encoder, one embedding per image, storage, and training on those embeddings are preserved. Author intent is unknown.

C2 / Move and merge the reporting protocol

C2 / BEFORE / 1 — **Results, paragraph 2**

We report mean test accuracy across five seeds.

C2 / BEFORE / 2 — **Results, paragraph 3**

We report mean optimization time across five seeds. Timing starts after feature precomputation and excludes that cost.

C2 / AFTER / merged — **Evaluation Protocol, paragraph 2**

We report mean test accuracy and mean optimization time across five seeds. Timing starts after feature precomputation and excludes that cost.

Inferred benefit. Readers meet the metrics and timing boundary together, before the result. **Review / equivalent reporting description.** Both five-seed means and the timing boundary are preserved. The context used by C3 was moved, not deleted. Author intent is unknown.

Coverage. C1–C3 cover the changed passages. The title, headings, baseline definition, evaluation setup, and accuracy result are retained; no mapping is unresolved. No edits are applied. Measurement validity and statistical significance are not independently verified. See `comparison.md` for the full setup quotation and source anchors.