Revision Comparison

The number stays. The claim changes.

COMPARE MODE / SYNTHETIC ML EXCERPT

The revision shortens the method, moves the reporting protocol, and broadens a timing claim. Both supplied versions are preserved.

In this report: C1 / concise method C2 / moved and merged protocol C3 / timing scope

C3 / Broaden the timing claim

To read the Summary's timing claim, check what the timer includes.

Source context / After, Evaluation Protocol, paragraph 2, sentence 2

Timing starts after feature precomputation and excludes that cost.

Retained from Before, Results, paragraph 3, sentence 2; moved by C2. The adapter and baseline use the same cached embeddings and fixed split.

C3 / BEFORE — **Summary, paragraph 1**

The adapter reduces optimization time by 38%.

C3 / AFTER — **Summary, paragraph 1**

The adapter reduces end-to-end training time by 38%.

C3 / Review note / inferred

The reported 38% reduction is for optimization time only: feature precomputation is excluded. The revision calls this an end-to-end reduction.

Review / substantive scope change. Author review needed. The wording was checked against both drafts. The underlying timings remain unverified; check which timing measurement the 38% refers to.

Sources. `before.md` and `after.md`; SHA-256 identities in `identity.json`. Paragraphs count prose blocks under each heading. Both complete files are compared. No experimental records or author explanations were supplied.

Useful edits, traced

The same revision also improves wording and organization

C1 / Make the training description more concise

C1 / BEFORE — **Method, paragraph 1**

We keep the encoder fixed. We compute one embedding per image and store it. A small adapter is trained on these stored embeddings.

C1 / AFTER — **Method, paragraph 1**

We cache one embedding per image from a frozen encoder and train a small adapter on the cached embeddings.

Inferred benefit. The revision describes caching the features and training the adapter in one sentence. The original wording is grammatical. **Review / exposition-only.** The fixed encoder, one embedding per image, storage, and training on those embeddings are preserved. Author intent is unknown.

C2 / Move and merge the reporting protocol

C2 / BEFORE / 1 — **Results, paragraph 2**

We report mean test accuracy across five seeds.

C2 / BEFORE / 2 — **Results, paragraph 3**

We report mean optimization time across five seeds. Timing starts after feature precomputation and excludes that cost.

C2 / AFTER / merged — **Evaluation Protocol, paragraph 2**

We report mean test accuracy and mean optimization time across five seeds. Timing starts after feature precomputation and excludes that cost.

Inferred benefit. Readers can find both metrics, the five-seed averages, and what the timer includes together, before the accuracy result. **Review / equivalent reporting details.** Both five-seed means and the timing boundary are preserved. The context used by C3 was moved, not deleted. Author intent is unknown.

Coverage. C1–C3 cover the changed passages. The title, headings, baseline definition, evaluation setup, and accuracy result are unchanged. Every changed passage has a counterpart or is part of a merge. Neither draft is modified. See `comparison.md` for the full setup quotation and source anchors.