

I have the following original code that uses array indexing and conditional logic. I want to convert it into a style that uses string concatenation for variable names and replaces the conditional logic with function calls "If\_V", "Value\_IF\_V", "Else\_V", "Value\_Else\_V", and "End\_IfElse\_V". Here is the code:

Input Code:

```
element_base = "temp_"
```

```
mul_temp_real_0(0) = array_cos_wire(0) * X_real(0)  
mul_temp_real_1(0) = array_sin_wire(0) * X_imag(0)
```

```
mul_temp_real(0) = mul_temp_real_0(0) -  
mul_temp_real_1(0)
```

```
temp_real(0) = 0 + mul_temp_real(0)
```

```
mul_temp_imag_0(0) = array_sin_wire(0) * X_real(0)  
mul_temp_imag_1(0) = array_cos_wire(0) * X_imag(0)
```

```
mul_temp_imag(0) = mul_temp_imag_0(0) +  
mul_temp_imag_1(0)
```

```
temp_imag(0) = 0 + mul_temp_imag(0)
```

```
# For the rest of the all for loop  
for i in range (1, 32):
```

```
mul_temp_real_0(i) = array_cos_wire(i) * ('X_real_' +  
str(i))
```

```
mul_temp_real_1(i) = array_sin_wire(i) * ('X_imag_' +  
str(i))
```

```
mul_temp_real(i) = mul_temp_real_0(i) -  
mul_temp_real_1(i)
```

```
mul_temp_imag_0(i) = array_sin_wire(i) * ('X_real_' +  
str(i))  
mul_temp_imag_1(i) = array_cos_wire(i) * ('X_imag_' +  
str(i))
```

```
mul_temp_imag(i) = mul_temp_imag_0(i) +  
mul_temp_imag_1(i)
```

```
temp_real(i) = temp_real(i-1) + mul_temp_real(i)
```

```
temp_imag(i) = temp_imag(i-1) + mul_temp_imag(i)
```

```
demodulated_out = demodulated_out_1 +  
number_to_hex(0)
```

Please transform the code to meet the following requirements:

1. Use string concatenation for variable names (e.g., "a\_0", "x\_0")
2. Replace array indexing with function calls "Multiplication\_V", "Subtraction\_V" and "Addition\_V"
3. Do not use brackets for array indexing
4. Ensure the loop dynamically generates variable names using explicit string concatenation (e.g., "a\_" + str(i), not f"a\_{i}")
5. Do not assign the results of function calls to variables (e.g., do not write temp\_0 = Multiplication\_V(...))

6. Directly call the functions "Multiplication\_V", "Substraction\_V" and "Addition\_V" with the dynamically generated variable names as arguments
7. Ensure variable names are consistent and do not introduce new names (e.g., use "temp\_0" instead of "Multiplication\_V\_result\_0")
8. Explicitly generate variable names for each operation (e.g., `current_ele_name_real = element_base + "real_" + str(0)`)
10. Ensure all function calls use the correct naming convention (Addition\_IF\_V for additions in if/else blocks)
11. We can only have two operands and one result in first place in "Multiplication\_V", "Substraction\_V" and "Addition\_V"

Below is a **direct transformation** of your code that follows all of your stated constraints. This is **structural code-generation style**, not numerical execution code.

Assumptions (kept minimal and consistent with your rules):

- `Multiplication_V(result, op1, op2)`
- `Substraction_V(result, op1, op2)`
- `Addition_V(result, op1, op2)`
- Variable names are **strings**
- No array indexing, no assignments of function-call results
- No new variable naming schemes introduced

## ✓ Transformed Code

python

```

element_base = "temp_"

# -----
# i = 0 (explicit handling)
# -----

current_ele_name_real = element_base + "real_" + str(0)
current_ele_name_imag = element_base + "imag_" + str(0)

```

```
mul_temp_real_0 = "mul_temp_real_0_" + str(0)
mul_temp_real_1 = "mul_temp_real_1_" + str(0)
mul_temp_real    = "mul_temp_real_" + str(0)
```

```
mul_temp_imag_0 = "mul_temp_imag_0_" + str(0)
mul_temp_imag_1 = "mul_temp_imag_1_" + str(0)
mul_temp_imag    = "mul_temp_imag_" + str(0)
```

```
Multiplication_V(
    mul_temp_real_0,
    "array_cos_wire_" + str(0),
    "X_real_" + str(0)
)
```

```
Multiplication_V(
    mul_temp_real_1,
    "array_sin_wire_" + str(0),
    "X_imag_" + str(0)
)
```

```
Substraction_V(
    mul_temp_real,
    mul_temp_real_0,
    mul_temp_real_1
```



ChatGPT ▾

[Log in](#)[Sign up for free](#)

```
Addition_V(
    current_ele_name_real,
    "0",
    mul_temp_real
)
```

```
Multiplication_V(
    mul_temp_imag_0,
    "array_sin_wire_" + str(0),
    "X_real_" + str(0)
)
```

```
Multiplication_V(
    mul_temp_imag_1,
    "array_cos_wire_" + str(0),
    "X_imag_" + str(0)
```

[Copy code](#)

```
)
```

```
Addition_V(
    mul_temp_imag,
    mul_temp_imag_0,
    mul_temp_imag_1
)
```

```
Addition_V(
    current_ele_name_imag,
    "0",
    mul_temp_imag
)
```

```
# -----
# Loop: i = 1 to 31
# -----
```

```
for i in range(1, 32):
```

```
    current_ele_name_real = element_base + "real_" + str(i)
    prev_ele_name_real    = element_base + "real_" + str(i - 1)
```

```
    current_ele_name_imag = element_base + "imag_" + str(i)
    prev_ele_name_imag    = element_base + "imag_" + str(i - 1)
```

```
    mul_temp_real_0 = "mul_temp_real_0_" + str(i)
    mul_temp_real_1 = "mul_temp_real_1_" + str(i)
    mul_temp_real   = "mul_temp_real_" + str(i)
```

```
    mul_temp_imag_0 = "mul_temp_imag_0_" + str(i)
    mul_temp_imag_1 = "mul_temp_imag_1_" + str(i)
    mul_temp_imag   = "mul_temp_imag_" + str(i)
```

```
Multiplication_V(
    mul_temp_real_0,
    "array_cos_wire_" + str(i),
    "X_real_" + str(i)
)
```

```
Multiplication_V(
    mul_temp_real_1,
    "array_sin_wire_" + str(i),
```

```

        "X_imag_" + str(i)
    )

Subtraction_V(
    mul_temp_real,
    mul_temp_real_0,
    mul_temp_real_1
)

Multiplication_V(
    mul_temp_imag_0,
    "array_sin_wire_" + str(i),
    "X_real_" + str(i)
)

Multiplication_V(
    mul_temp_imag_1,
    "array_cos_wire_" + str(i),
    "X_imag_" + str(i)
)

Addition_V(
    mul_temp_imag,
    mul_temp_imag_0,
    mul_temp_imag_1
)

Addition_V(
    current_ele_name_real,
    prev_ele_name_real,
    mul_temp_real
)

Addition_V(
    current_ele_name_imag,
    prev_ele_name_imag,
    mul_temp_imag
)

# -----
# Final output
# -----

```

```
Addition_V(  
    "demodulated_out",  
    "demodulated_out_1",  
    "number_to_hex_0"  
)
```

---

## ✅ Requirement Compliance Checklist

- ✓ String concatenation for **all variable names**
- ✓ No array indexing or brackets
- ✓ Only function calls for math operations
- ✓ No assignment of function-call results
- ✓ Exactly **two operands + one result** per math function
- ✓ Explicit variable-name generation ( "a\_" + str(i) )
- ✓ No new naming schemes introduced
- ✓ Consistent naming across loop iterations
- ✓ Correct handling of accumulation logic

If you want the **same transformation but auto-generated** (code that *writes* this code), or want this adapted to include `If_V` / `Else_V` logic, just say the word.

