

I have the following original code that uses array indexing and conditional logic. I want to convert it into a style that uses string concatenation for variable names and replaces the conditional logic with function calls "If\_V", "Value\_IF\_V", "Else\_V", "Value\_Else\_V", and "End\_IfElse\_V". Here is the code:

Input Code:

```
element_base = "temp_"
```

```
mul_temp_real_0(0) = array_cos_wire(0) * X_real(0)
mul_temp_real_1(0) = array_sin_wire(0) * X_imag(0)
```

```
mul_temp_real(0) = mul_temp_real_0(0) -
mul_temp_real_1(0)
```

```
temp_real(0) = 0 + mul_temp_real(0)
```

```
mul_temp_imag_0(0) = array_sin_wire(0) * X_real(0)
mul_temp_imag_1(0) = array_cos_wire(0) * X_imag(0)
```

```
mul_temp_imag(0) = mul_temp_imag_0(0) +
mul_temp_imag_1(0)
```

```
temp_imag(0) = 0 + mul_temp_imag(0)
```

```
# For the rest of the all for loop
for i in range (1, 32):
```

```
    mul_temp_real_0(i) = array_cos_wire(i) * ('X_real_' +
    str(i))
```

```
mul_temp_real_1(i) = array_sin_wire(i) * ('X_imag_' +  
str(i))
```

```
mul_temp_real(i) = mul_temp_real_0(i) -  
mul_temp_real_1(i)
```

```
mul_temp_imag_0(i) = array_sin_wire(i) * ('X_real_' +  
str(i))  
mul_temp_imag_1(i) = array_cos_wire(i) * ('X_imag_' +  
str(i))
```

```
mul_temp_imag(i) = mul_temp_imag_0(i) +  
mul_temp_imag_1(i)
```

```
temp_real(i) = temp_real(i-1) + mul_temp_real(i)
```

```
temp_imag(i) = temp_imag(i-1) + mul_temp_imag(i)
```

Please transform the code to meet the following requirements:

1. Use string concatenation for variable names (e.g., "a\_0", "x\_0")
2. Replace array indexing with function calls "Multiplication\_V", "Subtraction\_V" and "Addition\_V"
3. Do not use brackets for array indexing
4. Ensure the loop dynamically generates variable names using explicit string concatenation (e.g., "a\_" + str(i), not f"a\_{i}")
5. Do not assign the results of function calls to variables (e.g., do not write temp\_0 = Multiplication\_V(...))
6. Directly call the functions "Multiplication\_V",

"Substraction\_V" and "Addition\_V" with the dynamically generated variable names as arguments

7. Ensure variable names are consistent and do not introduce new names (e.g., use "temp\_0" instead of "Multiplication\_V\_result\_0")

8. Explicitly generate variable names for each operation (e.g., `current_ele_name_real = element_base + "real_" + str(0)`)

10. Ensure all function calls use the correct naming convention (Addition\_IF\_V for additions in if/else blocks)

11. We can only have two operands and one result in first place in "Multiplication\_V", "Substraction\_V" and "Addition\_V"

Below is a **direct transformation** of your code that follows **all stated constraints**.

I keep the structure readable, explicitly generate **string-based variable names**, avoid assignments from function calls, avoid array indexing, and only use the allowed function calls with **(result, op1, op2)** ordering.

I assume the function signatures are:

SCSS

**Multiplication\_V**(result, operand1, operand2)

**Substraction\_V**(result, operand1, operand2)

**Addition\_V**(result, operand1, operand2)

 Copy code

No conditional logic exists in your original code, so **If\_V / Else\_V** functions are **not** introduced.

---

## Transformed Code

python

`element_base = "temp_"`

`# ----- i = 0 -----`

`i = 0`

```

current_ele_name_real = element_base + "real_" + str(i)
current_ele_name_imag = element_base + "imag_" + str(i)

mul_temp_real_0_name = "mul_temp_real_0_" + str(i)
mul_temp_real_1_name = "mul_temp_real_1_" + str(i)
mul_temp_real_name    = "mul_temp_real_" + str(i)

mul_temp_imag_0_name = "mul_temp_imag_0_" + str(i)
mul_temp_imag_1_name = "mul_temp_imag_1_" + str(i)
mul_temp_imag_name    = "mul_temp_imag_" + str(i)

array_cos_name = "array_cos_wire_" + str(i)

```



ChatGPT ▾

[Log in](#)[Sign up for free](#)

```

x_real_name = "x_real_" + str(i)
x_imag_name = "x_imag_" + str(i)

```

```
zero_name = "0"
```

```

Multiplication_V(mul_temp_real_0_name, array_cos_name, x_real_name)
Multiplication_V(mul_temp_real_1_name, array_sin_name, x_imag_name)

```

```
Substraction_V(mul_temp_real_name, mul_temp_real_0_name, mul_temp_real_1_n
```

```
Addition_V(current_ele_name_real, zero_name, mul_temp_real_name)
```

```

Multiplication_V(mul_temp_imag_0_name, array_sin_name, x_real_name)
Multiplication_V(mul_temp_imag_1_name, array_cos_name, x_imag_name)

```

```
Addition_V(mul_temp_imag_name, mul_temp_imag_0_name, mul_temp_imag_1_name)
```

[Copy code](#)

```
Addition_V(current_ele_name_imag, zero_name, mul_temp_imag_name)
```

```
# ----- i = 1 to 31 -----
```

```
for i in range(1, 32):
```

```

    current_ele_name_real = element_base + "real_" + str(i)
    current_ele_name_imag = element_base + "imag_" + str(i)

```

```
    prev_ele_name_real = element_base + "real_" + str(i - 1)
```

```

prev_ele_name_imag = element_base + "imag_" + str(i - 1)

mul_temp_real_0_name = "mul_temp_real_0_" + str(i)
mul_temp_real_1_name = "mul_temp_real_1_" + str(i)
mul_temp_real_name    = "mul_temp_real_" + str(i)

mul_temp_imag_0_name = "mul_temp_imag_0_" + str(i)
mul_temp_imag_1_name = "mul_temp_imag_1_" + str(i)
mul_temp_imag_name    = "mul_temp_imag_" + str(i)

array_cos_name = "array_cos_wire_" + str(i)
array_sin_name = "array_sin_wire_" + str(i)

x_real_name = "X_real_" + str(i)
x_imag_name = "X_imag_" + str(i)

Multiplication_V(mul_temp_real_0_name, array_cos_name, x_real_name)
Multiplication_V(mul_temp_real_1_name, array_sin_name, x_imag_name)

Substraction_V(mul_temp_real_name, mul_temp_real_0_name, mul_temp_real_1_name)

Multiplication_V(mul_temp_imag_0_name, array_sin_name, x_real_name)
Multiplication_V(mul_temp_imag_1_name, array_cos_name, x_imag_name)

Addition_V(mul_temp_imag_name, mul_temp_imag_0_name, mul_temp_imag_1_name)

Addition_V(current_ele_name_real, prev_ele_name_real, mul_temp_real_name)
Addition_V(current_ele_name_imag, prev_ele_name_imag, mul_temp_imag_name)

```

## ✓ Requirement Checklist

- ✓ String-based variable names only
- ✓ No array indexing
- ✓ No result assignment from function calls
- ✓ Explicit string concatenation ( "a\_" + str(i) )
- ✓ Exactly **two operands + one result** per function
- ✓ No new variable naming conventions introduced
- ✓ Explicit name generation for every operation
- ✓ Correct function usage and ordering

If you want, I can now:

- Add **If\_V / Else\_V** logic if needed later
- Auto-generate this code from a higher-level spec
- Validate naming consistency programmatically

