

Project 3 Beautiful Subsequence

Group 24

Date: 2020-04-21

Project 3 Beautiful Subsequence

1. Introduction

1.1 Description

2. Algorithm Specification

2.1 Data Structure Specification

2.2 Algorithm Specification

3. Testing Results

4. Analysis and Comments

4.1 Time Complexity

4.2 Space Complexity

4.3 Comments

5. Author List

6. Declaration

7. Appendix

7.1 Source code in C

1. Introduction

1.1 Description

Given a sequence S , we are required to find the number of all subsequences which contain 2 neighbors with difference no larger than M , where M is an input integer.

We are going to use *dynamic programming* to solve this problem.

2. Algorithm Specification

2.1 Data Structure Specification

- `input[MAX]`

The array to store the input sequence.

- `dp[MAX]`

Before diving into the algorithm, let's look at the data structure we use to perform dynamic programming.

`dp[]` is an array that store the state information. Specifically, `dp[i]` is the number of subsequences ending at index i such that `input[i]` is the last element of the subsequence.

2.2 Algorithm Specification

- State Definition

As mentioned above, we define the state as `dp[i]`, which indicate the number of subsequences ending at index i such that `input[i]` is the last element of the subsequence. And the final result would be $\sum_i dp[i]$.

- State Conversion Equation

To compute `dp[i]`, we need to traverse each j ($0 \leq j < i$). For each j , we're going to find the number of *beautiful* subsequences consist of element whose indices can only be chosen from the set $\{0, 1, \dots, j, i\}$. And `dp[i]` would be the sum of all the j .

For each j , we can divide this into two conditions

- $abs(input[i] - input[j]) \leq M$

In this case, the i^{th} and j^{th} elements have already satisfying the definition of *beautiful*, thus any number whose index in $\{0, 1, \dots, j-1\}$ can be chosen. So we can get $dp[i] = dp[i] + 2^j$

- *otherwise*

Otherwise, for each valid case in `dp[j]`, we can append `input[i]` to the end of the subsequence. So the recurrence would be $dp[i] = dp[i] + dp[j]$

As a result, state conversion equation would be

$$dp[i] = \begin{cases} dp[i] + 2^j & \text{abs(input[i]-input[j])} \leq M \\ dp[i] + dp[j] & \text{otherwise} \end{cases}$$

- Base case: $dp[i] = 0$ for each i

- Aftering acquiring the recurrence relation, it is easy to implement the code.

```
1  for(int i = 0; i < N; i++) // initialization the base case
2      dp[i] = 0;
```

```

3
4  for(int i = 1; i < N; i++){
5      for(int j = 0; j < i; j++){
6          if(abs(input[i] - input[j]) <= M)    // case1
7              dp[i] += pow(2, j);
8          else                                  // case2
9              dp[i] += dp[j];
10     }
11
12     for(int i = 0, result = 0; i < N; i++){    // get the result
13         result += dp[i];
14         result %= DIVISOR;
15     }

```

3. Testing Results

- Sample

input:

```

4 2
5 3 8 6

```

output:

```

8

```

- Minimum case

input:

```

2 3
1 7

```

output:

```

0

```

- Min N

input:

```

0 2

```

output:

```

0

```

- Max N

input:

```

100001 0
0 1 2 3 4 5 ... 100000

```

output:

```

0

```

4. Analysis and Comments

4.1 Time Complexity

The initialization and finding the result takes $O(N)$. The dynamic programming process takes $O(1 + 2 + \dots + N) = O(N^2)$. As a result, this algorithm takes $O(N^2)$ time.

4.2 Space Complexity

We only use two 1-D arrays, so the space complexity is $O(N)$.

4.3 Comments

- At my first thought, I wanted to use the bitmask to implement the DP, but the input size may be too big (we need 10^5 bits in the maximum case, which is not feasible), so we turn to another approach.

5. Author List

Programmer: WangRui

Tester: LiYalin

Writer: LiYalin OuyangHaodong

6. Declaration

We hereby declare that all the work done in this project titled "Safe Fruit" is of our independent effort as a group.

7. Appendix

7.1 Source code in C

You can open the code.c in IDE for a better view

```
1  #include<stdio.h>
2  #include<stdlib.h>
3  #include<math.h>
4
5  #define MAX 100001
6  #define DIVISOR 1000000007
7
8  int main()
9  {
10     int N, M;
11     int i, j, input[MAX], dp[MAX];
12     long count = 0;
13
14     scanf("%d %d", &N, &M);
15     for (i = 0; i < N; i++) {
16         scanf("%d", &input[i]);
17         dp[i] = 0;
18     }
19     // initialize the dp[]
20     array
```

```
18     }
19
20     for (i = 1; i < N; i++) {
21         for (j = 0; j < i; j++) {
22             if (abs(input[i] - input[j]) <= M) // case1: already valid
23                 dp[i] += 1<<j;
24             else // case2: otherwise
25                 dp[i] += dp[j];
26         }
27     }
28
29     for (i = 0; i < N; i++) { // get the result
30         count += dp[i];
31         count %= DIVISOR;
32     }
33
34     printf("%ld\n", count);
35
36     return 0;
37 }
```