Bootstrap Model Selection in Finite Samples

Resample Size, Screening, and True-Model Selection

Emre Davud Can[2] Moritz Kolbe[1] Justus Mennerich[1]
Tamara Zuhr[1]

[1] Institute of Statistics, University of Bamberg
[2] Institute of Statistics, University of Trier

Motivation

- Model selection criteria: Prediction error instead of in-sample fit (Shao, 1996)
- Bootstrap role: Data-driven approximation of prediction error and model comparison (Efron, 1983)
- Standard bootstrap ($m = n$) limitation: Asymptotic inconsistency for smallest correct model (Shao, 1996)
- Model selection: Finite-sample problem → stability perspective of model dominance under resampling (Meinshausen & Bühlmann, 2010)
- Implicit complexity controls: Training size m and candidate set size K (Bickel & Sakov, 2008)
- Research focus: Joint impact of m and K on selection stability, overfitting, and underfitting (Bickel & Sakov)

Simulation Design



Methodological Trade-offs

- Choice of K (screening level) (Spokoiny & Willrich, 2019)
  - Smaller K yields large computational gains.
  - Risk: Top-K screening may discard the true model a_0.
  - Screening is noisy (finite B_1): aggressive screening increases exclusion risk.
- Choice of m (m-out-of-n bootstrap) (Shao, 1996; Bickel & Sakov, 2008)
  - $m = n$: classical bootstrap; asymptotically inconsistent for selecting the smallest correct model.
  - Smaller m strengthens the implicit complexity penalty (complex models are unstable when trained on smaller samples).
  - Too small m inflates estimation variance and makes PE estimates noisy.
- Finite-sample tension (Shao, 1996)
  - Larger m: higher stability / lower variance.
  - Smaller m: stronger discrimination among overfitted but correct models.
  - Best-performing m is problem-dependent (signal strength, effective model space).

Accuracy–Runtime Trade-off of Bootstrap Model Selection



Solid lines: true-model selection rate $\hat{\pi}(a_0)$ under m-out-of-n bootstrap selection.
Dashed lines: mean runtime per Monte Carlo replication (right axis).
Smaller m can increase discrimination (often higher $\hat{\pi}(a_0)$ in our settings), but too small m may increase noise

Screening trade-off: reduced runtime vs. lower selection accuracy.

Runtime Decomposition Across Screening Levels



Discussion and Limitations

- **Empirical frontier.** Across our settings, screening shifts the accuracy–runtime frontier mainly via large runtime gains (see runtime decomposition), at the potential cost of lower $\hat{\pi}(a_0)$.
- **Practical tuning remains open.** While K and m control the trade-offs (see *Methodological Trade-offs*), an *ex ante* choice is difficult in real data because effective signal, sparsity, and redundancy are unknown.
- **Scope.** Finite-sample results for a linear Gaussian DGP and an enumerated model space (moderate p); we illustrate trade-offs rather than establish optimality.

References

[1] Bickel, P. J. & Sakov, A. (2008). On the choice of m in the m out of n bootstrap and confidence bounds for extrema. *Statistica Sinica*, *18*(3), 967-985. https://www.jstor.org/stable/24308525

[2] Efron, B. (1983). Estimating the Error Rate of a Prediction Rule: Improvement on Cross-Validation. *Journal of the American Association*, *78*(382), 316-331. https://doi.org/10.2307/2288636

[3] Meinshausen, N. & Bühlmann, P. (2010). Stability selection. *Journal Of The Royal Statistical Society Series B (Statistical Methodology)*, *72*(4), 417-473 https://doi.org/10.1111/j.1467-9868.2010.00740.x

[4] Kreutzmann, A.-K., Pannier, S., Rojas-Perilla, N., Schmid, T., Templ, M., and Tzavidis, N. (2019). The R package `emdi` for estimating and mapping regionally disaggregated indicators. *Journal of Statistical Software*, *91*(7), 1–33.

[5] Rabbi, F., Khalil, A., Khan, I., Almuqrin, M. A., Khalil, U. Andualem, M. (2022). Robust model selection using the out-of-bag bootstrap in linear regression *Scientific Reports*, *12*(1), 10992. https://doi.org/10.1038/s41598-022-14398-1

[6] Shao, J. (1996). Bootstrap Model Selection. *Journal of the American Statistical Association*, *91*(434), 655-665. https://doi.org/10.2307/2291661

[7] Spokoiny, V. Willrich, N. (2019). Bootstrap tuning in Gaussian ordered model selection. *The Annals Of Statistics*, *47*(2). https://doi.org/10.1214/18-aos1717

Reproduction Materials available on GitHub

Monte Carlo Simulation Methods

{moritz.kolbe; justus-lasse.mennerich; t_zuhr}@stud.uni-bamberg.de
s4emcann@uni-trier.de