



Architectural Design

Xin Feng


Software Development Life Cycle



Software Development Life Cycle




Software Development Life Cycle



Subsystems

- Decompose (分解) system into **manageable** (可管理的) parts
- Each subsystem can be assigned to a developer or a team and implemented **independently**
- The individual subsystems can be implemented **concurrently** (同时)
- A subsystem can be further divided into **simpler subsystems**
- E.g. Package in Java

System and Subsystem



Picture resource:

http://www.google.com/imgres?imgurl=http://www.stsc.hill.af.mil/crosstalk/2006/09/0609Butler_Fig2.jpg&imgrefurl=http://www.stsc.hill.af.mil/crosstalk/2006/09/0609Butler.html&h=290&w=525&sz=17&tbnid=g2H7MdlixhteM::&tbnh=73&tbnw=132&prev=/images%3Fq%3Dsystem%2Bsubsystem%2Bpicture&hl=en-GB&usq=__pFRPFiEjlZSw5Ufu2GgpxkNOSjg=&ei=5W6SSfXZGtW4kAXlo_H6Cw&sa=X&oi=image_result&resnum=4&ct=image&cd=1

Software Architectural Design

- Identify (标识) subsystems
 - What subsystems
- Establish (建立) relationships between the subsystems
 - How do they communicate

Is a Software Architecture Important



Picture resource: http://images.google.com/images?um=1&hl=en&newwindow=1&rlz=1T4GGLJ_en-GBCN276CN309&q=house+collapse+images+cartoon+structure

Is a Software Architecture Important

- A good software architecture can help
 - communication
 - Developers in different phases can understand
 - system analysis
 - Complexity （复杂度） analysis
 - large scale （规模） reuse
 - The reuse of subsystems

Architectural Design


- A software architectural design is an abstract decomposition of a system into large-grain (大粒) components (构件), each of which may be a substantial system in its own right (本身) .

Design Fundamentals

- Abstraction （抽象）
- Pattern （模板）
- Modularity （模块性）
- Information hiding （信息隐藏）
- Independence （独立）
- Refinement （精炼）
- Refactoring （重构）

Abstraction

- Many levels of abstraction can be posed




1. Browse a website
2. Search for flight info.
3. Pay the ticket

1. Passenger
2. Date
3. Time


Pattern

- A design pattern (模板) describes a design structure that solves a particular design problem within a specific context (背景)
 - Architectural patterns
 - Design patterns
 - Coding patterns



Modularity


- Modularity is the single attribute of software that allows a program to be intellectually (智力上) manageable
 - Divide and conquer strategy (分而治之)
 - Solve the complexity



PictPicture source: http://images.google.com/images?ndsp=20&um=1&hl=en&newwindow=1&rlz=1T4GGLJ_en-GBCN276CN309&q=Complexity+divide+and+conquer+picture&start=40&sa=N

Information Hiding

- Each module is characterized (刻画) by the design decisions which are invisible (不可见的) from outside the module



Independence

- Coupling (耦合)
 - The measure of the dependencies between two subsystems
 - Looser, better
- Cohesion (凝聚)
 - The measure of the dependencies within a system
 - Higher better

Cohesion

Worst

Coincidental cohesion

parts of a component are grouped arbitrarily

Logical cohesion

parts of a component are grouped because they logically are categorized to do the same thing

Temporal cohesion

parts of a component are grouped by when they are processed

Procedural cohesion

parts of a component are grouped because they follow a certain sequence of execution

Communicational cohesion

parts of a component are grouped because they operate on the same data

Sequential cohesion

parts of a component are grouped because the outputs are from one part

Informational cohesion

parts of a component are grouped they use they use the same data structure

Functional cohesion

parts of a component are grouped because they together perform exactly one function

Best

Coupling

Worst



Best

Content Coupling

A component uses/alters (改变) data in another

Control Coupling

Two components communicating with a control flag (标志)

Global-data Coupling

Two components communicate via global (总) data

Data-structure Coupling


Communicating via a data structure passed as a parameter

Data Coupling

Communicating via parameter passing


Refinement

- Stepwise (逐步) refinement (精化) is a process of elaboration (阐述). It is opposite to **abstraction**.



Refactoring

- It is a method that reorganizes (重组) the architecture to make the design better.



Picture source: http://images.google.com/imgres?imgurl=http://www.pabrant.es.net/blog/space/start/2007-12-10/1/refactoring.png&imgrefurl=http://www.pabrant.es.net/blog/space/start/2007-12-10/1&usqJZGyYh6xxJeBT2Gd7PqETejM0o8=&h=549&w=480&sz=50&hl=en&start=20&um=1&tbnid=5PopuhRVAlDaRM:&tbnh=133&tbnw=116&prev=/images%3Fq%3Drefactoring%2Bpicture%26um%3D1%26hl%3Den%26newwindow%3D1%26rlz%3D1T4GGLJ_en-GBCN276CN309%26sa%3DX

Questions to Answer in Architectural Design

1. How many processors?
2. What templates (样板) available?
3. What architectures are to be established?
4. How to decompose a system into subsystems?
5. How to decompose a subsystem into modules?
6. How are the modules controlled?
7. How good is the architecture?

Architectures from Different Perspectives(观察角度)

- Static model
 - Subsystems or components
- Dynamic model
 - Processes in run time
- Interface model
 - Services offered by each subsystem
- Relationship model
 - Calling relationships
- Distribution model
 - Distribution (分布) on different computers


System Organization

- Three models can be used to decompose a system into subsystems
 - The repository (储存库) model
 - Repository is shared by the subsystems
 - The client server model
 - The services offered by servers can be used by clients through network
 - The layered model
 - The upper layers use the lower layers through defined standard interface

System Organization

- Three models can be used to decompose a system to subsystems
 - The repository model
 - Repository is shared by the subsystems
 - The client server model
 - The services offered by servers can be used by clients through network
 - The layered model
 - The upper layers use the lower layers through defined standard interface

The Repository Model – An Example



CASE Toolset Architecture

Advantages and Disadvantages



No direct transmission (传递) between two subsystems



The subsystems must follow the data model defined by repository



Advantages and Disadvantages



The information handling is centralized




The changes in repository can affect many subsystems



Advantages and Disadvantages



The repository manager is responsible




Subsystem cannot have their own policies



Advantages and Disadvantages



It is easy to add a new system with the compatible (兼容的) data model




It is hard to distribute the repository to a number of machines



System Organization

- Three models can be used to decompose a system to subsystems
 - The repository model
 - Repository is shared by the subsystems
 - The client server model
 - The services offered by servers can be used by clients through network
 - The layered model
 - The upper layers use the lower layers through defined standard interface


The Client Server Model – An Example



Advantages and Disadvantages



Distributed processors
Easy to add new server



The shared data model
may be unavailable



System Organization

- Three models can be used to decompose a system to subsystems
 - The repository model
 - Repository is shared by the subsystems
 - The client server model
 - The services offered by servers can be used by clients through network
 - The layered model
 - The upper layers use the lower layers through the defined standard interfaces

The Layered model – An Example

Configuration (配置) management system layer

Object management system layer

Database system layer

Operating system layer

Advantages and Disadvantages



Support incremental process model

Configuration management system layer



Operating system layer

Hard to structure into layers



Advantages and Disadvantages



A layer can be replaced by another one if the interface is not changed

Configuration management system layer



Another operating system

Performance can be a problem



Component Control

- How to use a component's service
 - Centralized （集中式） control
 - One component has the overall （全面的） control of start or stop of other components
 - Event-based （基于事件的） control
 - Each component can response to the external events

Centralized Control

- The call-return models （调用-返回）
 - Tree structure diagrams
- The manager models （中间协调）
 - A component coordinates other components in a concurrent system

Event-based Control

- Broadcast models （广播）
 - An event is broadcasted to all the components
- Interrupt-driven models （中断驱动）
 - An interrupt handler detects the external interrupts and passes them to the corresponding components.