Mawlana Bhashani Science and Technology University

Lab-Report

Report No: 01

Course code: ICT-4202

Course title: Wireless and Mobile Communication Lab

Date of Performance: March, 2020

Date of Submission: 04 .09. 2020

Submitted by

Name: Raisa Jerin Sristy

ID: IT-16056

4th year 2nd semester

Session: 2015-2016

Dept. of ICT

MBSTU.

Submitted To

Nazrul Islam

Assistant Professor

Dept. of ICT

MBSTU.

LAB NO.:01

Name of Experiment: **Simple Client-Server communication (NS-3warmup)**

Objectives:

1. To create a simple topology of two nodes (Node1 and Node2) separated by a point to point link.
2. To setup a UDP client on one node (Node-1) and a UDP server on another (Node-2). Let it be of a fixed data rate 1.
3. To start the Client application and measure end to end throughput whilst varying the latency.

Source Code:

```
/* -*- Mode:C++; c-file-style:"gnu"; indent-tabs-mode:nil; -*- */
/*
 * This program is free software; you can redistribute it and/or modify
 * it under the terms of the GNU General Public License version 2 as
 * published by the Free Software Foundation;
 *
 * This program is distributed in the hope that it will be useful,
 * but WITHOUT ANY WARRANTY; without even the implied warranty of
 * MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the
 * GNU General Public License for more details.
 *
 * You should have received a copy of the GNU General Public License
 * along with this program; if not, write to the Free Software
 * Foundation, Inc., 59 Temple Place, Suite 330, Boston, MA  02111-1307  USA
 */

#include "ns3/core-module.h"
#include "ns3/network-module.h"
#include "ns3/internet-module.h"
#include "ns3/point-to-point-module.h"
#include "ns3/applications-module.h"

// Default Network Topology
//
//       10.1.1.0
// n0 -------------- n1
//    point-to-point
//
```

```
using namespace ns3;

NS_LOG_COMPONENT_DEFINE ("FirstScriptExample");

int
main (int argc, char *argv[])
{
  CommandLine cmd (__FILE__);
  cmd.Parse (argc, argv);

  Time::SetResolution (Time::NS);
  LogComponentEnable ("UdpEchoClientApplication", LOG_LEVEL_INFO);
  LogComponentEnable ("UdpEchoServerApplication", LOG_LEVEL_INFO);

  NodeContainer nodes;
  nodes.Create (2);

  PointToPointHelper pointToPoint;
  pointToPoint.SetDeviceAttribute ("DataRate", StringValue ("5Mbps"));
  pointToPoint.SetChannelAttribute ("Delay", StringValue ("2ms"));

  NetDeviceContainer devices;
  devices = pointToPoint.Install (nodes);

  InternetStackHelper stack;
  stack.Install (nodes);

  Ipv4AddressHelper address;
  address.SetBase ("10.1.1.0", "255.255.255.0");

  Ipv4InterfaceContainer interfaces = address.Assign (devices);

  UdpEchoServerHelper echoServer (9);

  ApplicationContainer serverApps = echoServer.Install (nodes.Get (1));
  serverApps.Start (Seconds (1.0));
  serverApps.Stop (Seconds (10.0));

  UdpEchoClientHelper echoClient (interfaces.GetAddress (1), 9);
  echoClient.SetAttribute ("MaxPackets", UintegerValue (1));
  echoClient.SetAttribute ("Interval", TimeValue (Seconds (1.0)));
  echoClient.SetAttribute ("PacketSize", UintegerValue (1024));

  ApplicationContainer clientApps = echoClient.Install (nodes.Get (0));
  clientApps.Start (Seconds (2.0));
```

```
clientApps.Stop (Seconds (10.0));

Simulator::Run ();
Simulator::Destroy ();
return 0;
```

Output:

Conclusion: Here in this experiment, Basic client server paradigm, reading of pcap traces are found and it's the basic of NS-3 simulation and it was successfully done.