

CampusRide

Master Engineering & System Documentation Verified Peer-to-Peer University Mobility & Transit Network

Comprehensive architectural specification, data schemas, security threat models, matching algorithms, real-time protocols, and operational blueprints.

PROJECT NAME CampusRide (COLLEGERIDE)	SYSTEM VERSION v2.4.0 (Enterprise Campus Release)
DOCUMENTATION VERSION Doc-v3.0.0-Master	RELEASE DATE October 2026
REPOSITORY & BRANCH RaisterAnmol/COLLEGERIDE (branch: main)	TARGET UNIVERSITIES Uttaranchal University (UIT/UU), Graphic Era, UPES
PRIMARY COMMIT REFERENCE c38fa18 (Fix: SPA Routing & Module MIME Compliance)	CLASSIFICATION Confidential — Proprietary University Architecture

PART 1 — PROJECT FOUNDATION

2. Document Purpose

This master engineering document serves as the canonical technical authority, reference manual, and architectural blueprint for the **CampusRide** platform. It provides exhaustive clarity on every layer of the system—from frontend React components and state machines to MongoDB schemas, real-time Socket.IO room architectures, cryptographic verification protocols, and deployment infrastructure.

Target Audience

- **Core Software Engineers & Maintainers:** Full codebase understanding, API contracts, mathematical matching formulas, and bug mitigation histories.
- **University Security & IT Administrators:** Identity verification workflows, student PII compliance, audit logging mechanisms, and SOS dispatch protocols.
- **DevOps & QA Engineers:** Automated test suites, CI/CD pipelines, containerization specs, and monitoring metrics.

How Incoming Developers Should Use This Guide

New engineers should review *Part 3 (System Architecture)*, followed by *Part 7 (Core Engineering Logic)* and *Part 8 (Authentication & Verification)*. Every API route, model schema, and state transition documented here corresponds directly to source files under `client/src/` and `server/src/`.

3. Project Overview

CampusRide is an institutional, peer-to-peer carpooling, bike-pooling, and micro-mobility network engineered exclusively for university ecosystems. Designed to solve commuter bottlenecks between campus gates and surrounding student residential hubs (e.g., Premnagar, Selaqui, Suddhowala, Vikasnagar in the Dehradun educational cluster), CampusRide enables verified students and university faculty to share daily commutes safely, legally, and at transparent, non-profit cost-sharing rates.

Key Differentiators

- **Closed Institutional Trust Ring:** Strictly restricted to verified university students with official `.edu` emails, physical student ID OCR verification, and facial biometrics.
- **Academic Affinity Engine:** Passengers are prioritized with drivers from their exact course, semester, and department (e.g., B.Tech CSE Classmates).
- **Zero-Commission Fair-Share UPI:** Drivers receive 100% of fuel-share contributions directly via native `upi://pay` deep-links without platform cuts or third-party escrow fees.
- **Dual-Layer Pickup Verification:** Cryptographically generated CSPRNG 6-digit OTPs and QR codes ensure physical presence verification before trips commence.

4. Problem Statement

University campuses across India face severe transit and safety deficiencies that impact thousands of students twice daily:

Domain	Existing Manual / Commercial Reality	CampusRide Solution
Safety & Trust	Unregulated WhatsApp / Telegram carpool groups with total anonymity; no vetting of external strangers entering campus vehicles.	Mandatory university ID verification, face biometrics, emergency contact dispatch, and in-app SOS with live GPS link.
Transit Bottlenecks	Auto-rickshaws overcharge students (₹80–₹120 for 3 km) during peak 8:30 AM and 4:30 PM university gate rushes.	Pre-scheduled peer carpools at capped fuel-split rates (₹20–₹35) between residential hubs and campus gates.
Identity Fraud	Students use fake names and temporary phone numbers on social messaging channels.	Argon2id credential security, institutional email token verification, and automated ID card OCR.
Coordination Chaos	Chat groups get flooded with spam, lost pickup messages, and unconfirmed ride promises.	Structured ride state machines, seat capacity locks, and dedicated room-scoped coordination chat.

5. Product Vision

Short-Term Horizon (Months 1–6): Achieve dominant campus adoption across Uttaranchal University (UIT, Law, Pharmacy, Management) and neighboring Dehradun colleges, onboarding 2,500+ verified daily commuters and saving over 15 metric tons of CO₂.

Long-Term Horizon (Years 1–3): Expand CampusRide as a turnkey institutional mobility infrastructure deployed across 50+ university campuses nationwide, integrating with college RFID smart-card turnstiles, EV charging points, and institutional student activity credits.

PART 2 — PRODUCT REQUIREMENTS

6. Core Features

CampusRide encapsulates 24 mission-critical feature modules spanning student commuters, drivers, and campus safety officers:

- **Student & Driver Registration:** Multi-step registration capturing academic identity (college, branch, department, semester, year).
- **Institutional Email Verification:** Single-use cryptographic tokens dispatched via email (Resend API) ensuring `.edu` authenticity.
- **Phone & WhatsApp Verification:** Direct OTP delivery through integrated WhatsApp service (Baileys engine).
- **Student ID Card OCR & Biometric Upload:** Secure multi-file document upload handling student IDs and face photos with automatic data extraction.
- **Daily Driver ID & Facial Check:** Liveness and verification challenge prior to daily ride dispatch.
- **Road-Aware Ride Offer Creation:** Driver sets origin, destination, departure time, available seats (1–6), and route summary with interactive Leaflet map dragging.
- **Recurring Weekly Commutes:** Toggle automated Monday–Friday schedules matching semester timetables.
- **Campus Landmark Quick-Picks:** One-tap selection of recognized gates (UIT Gate 1, Hostel Block A/B, Central Library Roundabout, Premnagar Chowk).
- **Intelligent Corridor Search:** Passengers search routes with distance bounding, detour minutes, and time tolerance windows.
- **Academic Affinity Engine:** Algorithmic matching calculating classmate bonuses and department prioritization.
- **Guarded Seat Requests:** Atomic seat decrement preventing concurrency race conditions.
- **Real-Time Coordination Chat:** In-app chat modal with instant quick-chips ("I've arrived at Gate 1", "Running 2 mins late").
- **CSPRNG OTP & QR Pickup Verification:** 6-digit cryptographic OTP displayed exclusively to the driver; scanned/entered by passenger to begin trip.
- **Live Telemetry & Route Tracking:** Smooth vehicle icon translation along the corridor via WebSockets.
- **Zero-Commission UPI Payment Deep Links:** Passenger taps "Pay ₹30 via GPay / PhonePe / Paytm" launching `upi://pay` with driver's UPI ID.
- **Mutual Peer Reviews & Ratings:** Two-way reviews updating composite driver reliability and passenger scores.
- **Idempotent SOS & WhatsApp Emergency Dispatch:** Panic button triggers instant WhatsApp alert with Google Maps coordinate link to family contacts.
- **Institutional Admin Command Center:** Real-time review queue, telemetry counters, safety incident logs, and university verification approvals.
- **CO₂ & Fuel Savings Impact Dashboard:** Cumulative environmental sustainability metrics.
- **Installable PWA:** Standalone web manifest and hardened Service Worker for Android/iOS home screen installation.

7. User Roles & Permission Matrix

Role	Permissions	Restrictions	Accessible Endpoints
Student (Passenger)	Search rides, request seats, join trip chats, verify OTP pickup, submit reviews, trigger SOS.	Cannot post rides as driver; cannot view other users' emergency logs or unmask driver private PII.	<code>/api/rides</code> (GET), <code>/api/requests</code> , <code>/api/trips/:id</code> , <code>/api/emergency/sos</code>
Driver	Post ride offers, set recurring schedules, accept/decline requests, receive OTP, start/complete trips.	Must maintain active verified license & student credentials; cannot accept requests exceeding seat capacity.	<code>/api/rides</code> (POST/PATCH), <code>/api/trips/:id/start</code> , <code>/api/trips/:id/regenerate-otp</code>
Campus Admin	Review verification queue, inspect uploaded student IDs/licenses, approve/reject students, manage incidents.	Cannot alter server-level cryptographic secrets or bypass audit logging.	<code>/api/admin/*</code> , <code>/api/verification/queue</code> , <code>/api/verification/requests/:id/approve</code>
Super Admin	Full institutional system control, manage university campuses, configure geofences, view system metrics.	All destructive operations tracked in immutable AuditLog collection.	<code>/api/admin/*</code> , <code>/api/metrics</code> , <code>/api/audit</code>

8. Complete User Journeys

8.1 Student Registration & Onboarding Lifecycle


[Student Registers] → Enter Institutional Email & Password (Argon2id Hash) | ▼ [Email Verification] → Dispatch Cryptographic Token URL → User Verifies Token | ▼ [Document Submission] → Upload University ID Card & Live Facial Selfie | ▼ [Admin Review Queue] → Automatic Queue Ingestion → Admin Inspects Credentials | ▼ [Account Verified] → Role-Based Campus Green Badge Granted → Unlocked for Commuting

8.2 Passenger Ride Discovery & Commute Flow

[Search Route] → Enter Origin (e.g., Premnagar) & Destination (UIT Gate 1) | ▼ [Matching Engine] → Compute Corridor, Time Window, and Classmate Affinity Score | ▼ [Inspect Driver] → View Verified Badge, Department, Vehicle Model, and Punctuality Rating | ▼ [Request Seat] → Guarded Atomic Request Submission → Driver Accepts Request | ▼ [Coordination] → Real-Time In-App Chat Modal with Arrival Quick-Chips | ▼ [Pickup & OTP] → Passenger scans Driver QR or enters Driver's CSPRNG 6-digit OTP | ▼ [Trip & Arrival] → Live Telemetry → Destination Reached → 1-Tap UPI Settlement → Mutual Review

PART 3 — SYSTEM ARCHITECTURE

9. High-Level Architecture Diagram



10. Technology Stack Matrix

Tier / Domain	Technology	Rationale & Application in CampusRide	Evaluated Alternative
Frontend	React 19 + TypeScript + Vite 6	Instant compilation, sub-second HMR, strict type safety for mission-critical transport contracts.	Next.js (Rejected: added unnecessary SSR overhead for an SPA/PWA mobile app).
Styling & Motion	Tailwind CSS + Framer Motion	Utility-first mobile styling and spring-animated modal feedback for seat booking and safety dialogs.	Bootstrap / Raw CSS (Too verbose; lacks dynamic theme consistency).
Backend Runtime	Node.js v24 + Express 4.21	Event-driven non-blocking I/O handling high concurrency during peak morning campus commute spikes.	Python Django / FastAPI (Node allows shared TypeScript schemas across layers).
Database & ORM	MongoDB Atlas + Mongoose 8.9	Native GeoJSON <code>2dsphere</code> indexing, flexible document schemas for rides and trip states.	PostgreSQL / PostGIS (MongoDB provided faster rapid iterations for dynamic commute profiles).
Real-Time Events	Socket.IO 4.8	Room-based multiplexed pub/sub for trip telemetry, coordination chat, and security room dispatch.	Raw WebSockets (Socket.IO offers built-in reconnect, room partitioning, and heartbeats).
Mapping & Tiles	Leaflet 1.9 + CARTO Voyager Tiles	Open-source map container avoiding expensive Google Maps API billing, clear campus road labels.	Mapbox GL (Expensive monthly active user limits for student projects).
Road Routing	OSRM (Open Source Routing Machine)	Precise road-aware route polylines, real road distances, and detour durations in milliseconds.	Straight-line Haversine (Unsafe for mountain hill-roads in Dehradun).
WhatsApp Messaging	@whiskeysockets/baileys	Zero-cost direct WhatsApp messaging for student OTPs and SOS coordinate broadcasts.	Twilio SMS / Meta Cloud API (Prohibitive per-message API costs for student clubs).
Security & Hashing	Argon2id + Helmet + CSP	State-of-the-art memory-hard password hashing with HTTP header baseline fortification.	bcrypt (Argon2id is superior against GPU-assisted rainbow table attacks).

PART 4 — FRONTEND ARCHITECTURE

11. Frontend Architecture

The client application is built with React 19, TypeScript, and Vite, packaged as an installable Progressive Web App. State is managed via lightweight React Context providers (`AuthContext` , `RideContext` , `ThemeContext`) to eliminate Redux boilerplate while maintaining immediate reactive state across routes.

- **Client API Layer** (`client/src/services/api.ts`): Centralized HTTP client managing JWT authorization bearer tokens, error code normalization, and automatic retries.
- **Real-Time WebSocket Client** (`client/src/services/socket.ts`): Singleton Socket.IO instance establishing authenticated socket handshakes and room subscriptions.
- **Responsive Layout Hierarchy**: Modular page shells featuring persistent mobile navigation bars, desktop header links, and translucent glassmorphism background components.

12. Frontend Folder Structure

```
client/
├── public/
│   ├── favicon.ico / favicon.png / favicon.svg
│   ├── manifest.json           # PWA manifest specifications
│   └── sw.js                   # Hardened Service Worker
├── src/
│   ├── assets/
│   │   └── illustrations/      # Compressed WebP hero & background assets
│   ├── components/
│   │   ├── common/            # Translucent backgrounds, badges, modals
│   │   ├── chat/              # ChatModal & quick commute chips
│   │   ├── maps/              # PickupAndRouteNavigationMap Leaflet component
│   │   └── safety/            # DailyDriverCheckModal & SOS triggers
│   ├── context/
│   │   ├── AuthContext.tsx    # Authentication token & verified user state
│   │   └── RideContext.tsx    # Active ride offers & search filter states
│   ├── pages/
│   │   ├── LandingPage.tsx    # Institutional public introduction & hero
│   │   ├── AuthPage.tsx       # Login / Register tabs with academic picker
│   │   ├── DashboardPage.tsx  # Student commute hub & quick stats
│   │   ├── SearchRidesPage.tsx # Corridor search, filters & matching cards
│   │   ├── PostRidePage.tsx   # Driver route creation & pin drag map
│   │   ├── RideDetailPage.tsx # Comprehensive ride information & chat trigger
│   │   ├── TripTrackingPage.tsx # Live trip telemetry, OTP entry & UPI settlement
│   │   ├── VerificationStatusPage.tsx # Student ID card & selfie upload
│   │   ├── AdminDashboardPage.tsx # Review queue & campus mobility analytics
│   │   └── SafetyPage.tsx     # Safety policies & emergency protocols
│   ├── services/
│   │   ├── api.ts             # REST API client
│   │   └── socket.ts          # Socket.IO connection manager
│   ├── App.tsx                # Route definitions & global backgrounds
│   └── main.tsx                # Root entry, React.StrictMode & PWA manager
```

13. UI/UX Design System

Design Token	Specification	Usage in CampusRide
Primary Institutional Forest	#143D32	Main navigation bars, action buttons, table headers, verified badges.
Accent Emerald	#10B981 / #D1FAE5	Match percentage badges, successful OTP checks, eco-commuter indicators.
Safety Amber & SOS Red	#F59E0B / #EF4444	Warning callouts, pending approval tags, high-priority emergency SOS trigger.
Canvas Backgrounds	#F8FAF9 / Translucent Glass	Subtle light-mode campus background illustrations with high text contrast.
Typography	Inter (UI) + JetBrains Mono (Code/OTP)	Clear legibility on low-resolution student mobile displays in sunlight.

PART 5 — BACKEND ARCHITECTURE

14. Backend Architecture

HTTP Request → Helmet / CSP / Compression / RateLimiter | ▼ Correlation ID Tracking (X-Request-Id) & Telemetry Middleware | ▼ Authentication & RBAC Middleware (requireAuth, requireRole, requireVerificationApproved) | ▼ Zod Input Validation Schemas (Safe Parsing & Coercion) | ▼ Route Controller Handlers (Atomic operations, CSPRNG calculations) | ▼ Mongoose Service Layer → MongoDB Database | ▼ Asynchronous Side Effects: Socket.IO Room Broadcasts & WhatsApp Alert Dispatch

15. Backend Folder Structure

```
server/
├── src/
│   ├── config/
│   │   └── env.ts                # Validated environment configuration (Zod)
│   ├── middleware/
│   │   ├── auth.ts              # JWT verification, RBAC & approval checks
│   │   ├── correlationId.ts     # Distributed tracing request IDs
│   │   ├── errorHandler.ts     # Centralized error mapping & status codes
│   │   └── telemetry.ts        # Prometheus duration metrics
│   ├── models/
│   │   ├── User.ts             # Academic identity, ratings, biometrics
│   │   ├── Ride.ts             # Commute offers, routes, recurring schedules
│   │   ├── RideRequest.ts      # Booking requests with compound indexing
│   │   ├── Trip.ts             # In-progress trips, salted OTP hashes, distance
│   │   ├── Vehicle.ts          # Registered vehicles & plate numbers
│   │   ├── VerificationRequest.ts # Student ID cards & review statuses
│   │   ├── Conversation.ts     # Group chats & messages
│   │   ├── EmergencyIncident.ts # SOS incident logs & dispatch records
│   │   └── Review.ts           # Mutual ratings & comments
│   ├── routes/
│   │   ├── authRoutes.ts       # Registration, Login, Google OAuth, Profile
│   │   ├── rideRoutes.ts       # Search, Matching, Ride Creation
│   │   ├── requestRoutes.ts    # Seat booking, atomic acceptance
│   │   ├── tripRoutes.ts       # Trip start, OTP verify, Completion
│   │   ├── verificationRoutes.ts # Queue, document upload, admin approvals
│   │   └── emergencyRoutes.ts  # SOS trigger, incident resolution
│   ├── services/
│   │   ├── matchingEngine.ts    # Corridor matching & academic affinity
│   │   ├── emergencyService.ts  # Idempotent SOS & alert dispatch
│   │   └── whatsappService.ts   # Baileys WhatsApp bot connection
│   ├── sockets/
│   │   └── socketHandler.ts     # Socket.IO connection & room multiplexing
│   ├── utils/
│   │   ├── db.ts               # MongoDB connection & in-memory fallback
│   │   ├── logger.ts           # Pino structured JSON logging
│   └── app.ts                  # Express server assembly & static serving
```

16. API Architecture & Endpoint Specification

Method & Path	Auth & Role	Request Summary	Success Response & Status
POST /api/auth/register	Public	Name, email, password, college, department, year, phone, accountType.	201 Created : User object + verification token.
POST /api/auth/login	Public	Email, password (or Google credential).	200 OK : JWT token + user profile.
POST /api/auth/google	Public	Google credential ID token.	200 OK : Google-authenticated user session.
GET /api/rides	Student / Driver	Query: originLat, originLng, destLat, destLng, date, seats.	200 OK : Ranked rides with matchScore and affinity breakdown.
POST /api/rides	Verified Driver	Origin, destination, departureTime, availableSeats, pricePerSeat, routePolyline.	201 Created : Active ride offer document.
POST /api/rides/:id/request	Verified Student	Requested seats, pickup location notes.	201 Created : Pending ride request.
PATCH /api/requests/:reqId	Ride Driver	Status: "accepted" "declined" "cancelled".	200 OK : Request updated; atomically decrements availableSeats.
POST /api/trips/:id/start	Ride Driver	Trip initiation command.	201 Created : Trip in_progress; CSPRNG OTP returned to driver.
POST /api/trips/:id/verify-otp	Trip Passenger	6-digit numeric OTP.	200 OK : Timing-safe match verified; lockout cleared.
POST /api/emergency/sos	Any User	Latitude, longitude, accuracy, address, emergency notes.	201 Created : Idempotent incident created; WhatsApp alerts dispatched.
GET /api/verification/queue	Campus Admin	Status query filter.	200 OK : List of pending student credential submissions.
POST /api/verification/requests/:id/approve	Campus Admin	Admin review decision notes.	200 OK : User verificationStatus set to "verified".

PART 6 — DATABASE ARCHITECTURE

17. Database Architecture

CampusRide utilizes MongoDB with Mongoose ODM, leveraging document-oriented schemas with embedded sub-documents for geographical coordinates and nested academic profiles. In local development and unit tests, the server transparently deploys an isolated in-memory MongoDB instance (`mongodb-memory-server`), guaranteeing that tests execute hermetically without external dependencies.

18. Complete Database Schema Definitions

18.1 User Schema

```
name: { type: String, required: true, trim: true },
email: { type: String, required: true, unique: true, lowercase: true },
passwordHash: { type: String, required: true },
college: { type: String, required: true },
department: { type: String, required: true },
course: { type: String, required: true },
year: { type: Number, required: true, min: 1, max: 5 },
semester: { type: Number, default: 1 },
role: { type: String, enum: ['student', 'driver', 'campus_admin', 'super_admin'], default: 'student' },
verificationStatus: { type: String, enum: ['unverified', 'pending', 'verified', 'rejected'], default: 'unverified' },
rating: { type: Number, default: 5.0, min: 1.0, max: 5.0 },
totalRides: { type: Number, default: 0 },
phone: { type: String, trim: true },
upiId: { type: String, trim: true },
avatarURL: { type: String },
enrolledIdCardUrl: { type: String },
emergencyContacts: [{
  name: String,
  phone: String,
  relationship: String
}]
```


18.2 Ride Schema

```
creator: { type: Schema.Types.ObjectId, ref: 'User', required: true, index: true },
origin: {
  text: { type: String, required: true },
  lat: { type: Number, required: true },
  lng: { type: Number, required: true }
},
destination: {
  text: { type: String, required: true },
  lat: { type: Number, required: true },
  lng: { type: Number, required: true }
},
departureTime: { type: Date, required: true, index: true },
availableSeats: { type: Number, required: true, min: 0, max: 8 },
pricePerSeat: { type: Number, required: true, min: 0 },
status: { type: String, enum: ['active', 'in_progress', 'completed', 'cancelled'], default: 'active', index: true },
recurring: { type: Boolean, default: false },
recurringSchedule: {
  daysOfWeek: [Number], // 1=Mon, 2=Tue...
  time: String
},
routePolyline: { type: String },
routeDistanceMeters: { type: Number },
routeDurationSeconds: { type: Number }
```

18.3 Trip Schema

```
rideId: { type: Schema.Types.ObjectId, ref: 'Ride', required: true, index: true },
driverId: { type: Schema.Types.ObjectId, ref: 'User', required: true, index: true },
passengerIds: [{ type: Schema.Types.ObjectId, ref: 'User', index: true }],
startTime: { type: Date, default: Date.now },
endTime: { type: Date },
distance: { type: Number, default: 0 },
status: { type: String, enum: ['scheduled', 'in_progress', 'completed', 'cancelled'], default: 'scheduled' },
otpHash: { type: String, select: false }, // Hidden by default from projections
otpSalt: { type: String, select: false },
otpExpiresAt: { type: Date },
otpAttempts: { type: Number, default: 0 },
isLocked: { type: Boolean, default: false }
```

19. Entity Relationship Architecture



20. Database Indexing Strategy

Collection	Index Keys	Type	Engineering Purpose
User	{ email: 1 }	Unique	Guarantees zero duplicate accounts during registration.
User	{ verificationStatus: 1, role: 1 }	Compound	Powers high-performance admin verification queue queries.
Ride	{ status: 1, departureTime: 1 }	Compound	Filters upcoming active commute offers within milliseconds.
RideRequest	{ rideId: 1, passengerId: 1 }	Compound Unique	Strictly prevents duplicate simultaneous requests from the same student for the same ride offer.
Review	{ tripId: 1, fromUserId: 1, toUserId: 1 }	Compound Unique	Guarantees participants can only review each other once per trip.
EmergencyIncident	{ triggeredBy: 1, status: 1 }	Compound	Enforces idempotent panic button activation checks.

PART 7 — CORE ENGINEERING LOGIC

21. Ride Creation Logic

1. **Driver Authentication & Approval Gate:** Verifies active JWT token and validates that `isVerificationApproved(user)` returns `true`. Unverified drivers receive `403 Forbidden`.
2. **Vehicle Linkage:** Queries `vehicle` collection for driver's registered car or bike. If missing, dynamically provisions a verified vehicle record from submitted payload.
3. **Geospatial Sanitization:** Validates origin and destination coordinates are within latitude `[-90, 90]` and longitude `[-180, 180]`.
4. **Road Polyline Ingestion:** Connects to OSRM engine to capture real turn-by-turn road geometry, road distance in meters, and estimated transit duration in seconds.
5. **Fair-Share Fuel Cap:** Enforces minimum price (₹10) and checks price per seat against campus fuel-share standards (preventing commercial gouging).
6. **Recurring Weekly Scheduling:** If `recurring: true`, generates timetable matrix matching selected days of the week (e.g. Mon–Fri at 8:30 AM).

22. Ride Search Logic

1. **Coordinate Extraction:** Accepts passenger pickup (originLat, originLng) and optional destination coordinates.
2. **Active Candidate Filtering:** Queries `Ride` collection for `status: 'active'` and `availableSeats >= requestedSeats` with departure times `>=` current time.
3. **Corridor Bounding:** Calculates passenger proximity to driver's route polyline. Pickup must fall within acceptable walking tolerance (default 1.5 km).
4. **Directional Alignment Check:** Evaluates vector cosine similarity between passenger journey and driver route to ensure trips travel in the same physical direction.
5. **Scoring & Priority Sorting:** Computes comprehensive match score (0–100%) and sorts results by academic affinity rank, match score, and departure time.

23. Matching Engine Architecture

The matching engine evaluates 10 multidimensional criteria across geographical, temporal, academic, and behavioral vectors:

- **Route Corridor Distance:** Measures perpendicular distance from passenger pickup to driver's road trajectory.
- **Directional Vector Alignment:** Disqualifies reverse commutes (e.g., driver heading toward campus vs passenger heading away).
- **Time Gap Clamping:** Penalizes departures diverging from passenger requested time. Time difference `> 15 mins` clamps to 0 time match score.
- **Detour Penalty:** Computes additional kilometers the driver must divert to pick up the passenger.
- **Academic Affinity Tiering:** Awards major priority multipliers for shared courses, departments, and semesters.
- **Driver Reliability Score:** Factors driver punctuality, completed rides, and peer rating (1.0–5.0 scale).
- **Gender Preference Hard Gates:** Strictly eliminates male drivers when a female passenger selects women-only carpools.

24. Mathematical Matching Score Formula

$$\text{MatchScore} = (W_{\text{geo}} \times S_{\text{geo}}) + (W_{\text{time}} \times S_{\text{time}}) + (W_{\text{academic}} \times S_{\text{academic}}) + (W_{\text{rating}} \times S_{\text{rating}}) - \text{DetourPenalty}$$

Where: - $W_{\text{geo}} = 0.40$ (Geographic Corridor Proximity) $S_{\text{geo}} = \max(0, 1 - (\text{PickupDistanceKm} / \text{MaxCorridorRadiusKm}))$ - $W_{\text{time}} = 0.25$ (Temporal Synchronization) $S_{\text{time}} = \max(0, 1 - (|\text{DepartureTime} - \text{TargetTime}| \text{ in minutes} / \text{MaxWaitMinutes}))$ - $W_{\text{academic}} = 0.25$ (Institutional Affinity Tier) S_{academic} : * 1.00 = Classmate (Exact Same Course & Semester, e.g. B.Tech CSE Sem 6) * 0.75 = Department Peer (Same Department, Different Semester) * 0.50 = Campus Peer (Same University, Different Department) * 0.00 = Different Institution - $W_{\text{rating}} = 0.10$ (Driver Reliability) $S_{\text{rating}} = (\text{DriverRating} - 1.0) / 4.0$

25. Ride Offer State Machine

[DRAFT] → Driver inputs route & seats | ▼ [PUBLISHED] → Active on Search Feed (availableSeats > 0) | |→ [FULL] (availableSeats == 0, waitlisted) | ▼ [IN_PROGRESS] → Driver initiates trip; OTP issued | |→ [COMPLETED] → All passengers dropped; ratings unlocked | |→ [CANCELLED] → Driver cancels prior to start; seats released

26. Request State Machine & Race-Condition Prevention

[PENDING] → Passenger requests seat (atomic compound index guard) | |→ [DECLINED] → Driver rejects; no seats deducted | |→ [CANCELLED] → Passenger cancels before acceptance | ▼ [ACCEPTED] → Atomically decrements availableSeats (\$gte: 1, \$inc: -1) | Adds passenger to real-time chat group | |→ [CANCELLED_AFTER_ACCEPT] → Atomically restores seat (\$inc: +1) | ▼ [TRIP_STARTED] → Included in trip passengerIds | ▼ [COMPLETED] → Reached destination; prompts UPI deep link & review

27. Trip Lifecycle Walkthrough

1. **Ride Scheduled:** Passengers booked; countdown timer active.
2. **Driver Departure:** Driver taps "Start Commute". Server transitions trip state to `in_progress`.
3. **Cryptographic OTP Dispatch:** Server generates 6-digit random CSPRNG OTP, salted and hashed into MongoDB. Plaintext OTP sent strictly to Driver.
4. **Physical Pickup:** Passenger enters Driver's car, asks for OTP or scans QR. Passenger submits OTP to `/api/trips/:id/verify-otp`.
5. **Constant-Time Verification:** Server executes timing-safe check. On match, emits `tripUpdate` via Socket.IO.
6. **En-Route Telemetry:** Vehicle location streamed every 5 seconds.
7. **Trip Completion:** Driver taps "Finish Trip". Ride marked completed; driver total rides incremented; review modals trigger on passenger screens.

PART 8 — AUTHENTICATION & VERIFICATION

28. Authentication Architecture

CampusRide implements enterprise-grade authentication utilizing **Argon2id** (RFC 9106) for password hashing, with memory cost of 64MB and 3 time iterations. Sessions are authenticated via stateless HMAC SHA-256 JSON Web Tokens (JWT) containing cryptographically signed user claims, roles, and a `tokenVersion` counter enabling instant revocation across all devices upon password reset or security compromise.

29. Role-Based Access Control (RBAC) Specification

Role Name	System Token Role	Administrative Scope	Guardrail Middleware
Student	student	Personal profile, ride searches, seat requests, trip chats, reviews.	requireAuth
Driver	driver	Ride offers, trip management, vehicle registrations, OTP regeneration.	requireAuth, requireRole('driver')
Campus Administrator	campus_admin	Student credential review queue, document approval, SOS incident management.	requireAuth, requireRole('campus_admin')
Super Administrator	super_admin	Global institutional control, geofence management, audit log access.	requireAuth, requireRole('super_admin')

30. Academic Verification Engine

To guarantee 100% campus safety, accounts progress through dual-tier institutional verification:

- **Email Domain Verification:** Whitelisted university top-level domains (e.g., `@uttaranchaluniversity.ac.in`, `@geu.ac.in`, `@upes.ac.in`). Single-use tokens expire after 24 hours.
- **Student ID Card OCR & Document Review:** Client-side optical character recognition extracts roll number, course, and expiry year. Documents are queued for administrative review.
- **Administrative Decisioning:** Institutional admins inspect ID card photos against submitted profiles. Approvals immediately update `verificationStatus: 'verified'`.

31. Driver Verification & Daily Liveness Checks

In addition to student ID verification, drivers must submit their Government Driving License number and vehicle registration documents. Prior to morning commutes, the platform presents a **Daily Driver ID & Liveness Check** modal prompting the driver to verify physical possession of vehicle keys and physical license, mitigating vehicle-loaning hazards.

32. Trust Badges & Reputation System

Badge	Visual Indicator	Criteria Required
Verified Classmate	 Green Academic Shield	Same Course, Branch, and Semester as passenger.
Department Peer	 Teal Building Icon	Enrolled in same faculty/department.
Top Punctual Driver	 Gold Lightning Badge	Maintains 4.8+ rating over 10+ completed campus trips.
Eco Commuter	 Emerald Leaf Badge	Prevented > 50 kg of CO ₂ emissions through shared carpools.

PART 9 — SAFETY & EMERGENCY SYSTEMS

33. Safety Architecture Overview

Safety is CampusRide's core design pillar. The architecture blends proactive identity gates (preventing unauthorized passengers/drivers) with reactive emergency dispatch pipelines (protecting students in transit).

34. Idempotent SOS System Specification

```
[Student Taps SOS Button] → Client captures high-precision GPS coordinates | ▼ [POST /api/emergency/sos] → Idempotency Check (Active incident already open?) | |→ (If Active): Appends latest coordinate ping without duplicating alerts | ▼ (If New Incident) [Database Record First] → Creates EmergencyIncident (INC-YYYYMMDD-XXXX) | |→ [WhatsApp Service]: Dispatches emergency alert to registered contacts | Format: "EMERGENCY: {Student} triggered SOS! Live GPS: https://maps.google.com/?q={lat},{lng}" | |→ [Security Room WebSocket]: Broadcasts audio-visual alarm to security console | |→ [Audit Log]: Immutable security record created with correlation ID
```

35. Emergency Contact System

During registration, commuters designate 1–3 primary emergency contacts (parents, guardians, hostel wardens) with phone numbers and relationships. In an SOS event, the system iterates through all registered contacts, logging delivery receipts (SENT / FAILED) in the incident document.

36. Live Location Tracking Protocols

While a trip is `in_progress`, driver coordinates are transmitted via the `trip:location:update` Socket.IO event. The server validates that the transmitting socket belongs to the authenticated driver before rebroadcasting exclusively to the trip's passenger room, preventing unauthorized telemetry interception.

37. Women-Safety Controls

Female students can enable the **Women-Only Driver Filter**. When active, all query projections strictly eliminate male drivers, surfacing only female-verified drivers traveling along the route.

38. Reporting & Blocking System

Students can submit confidential incident reports regarding inappropriate driving, route deviation, or discourteous behavior. Three valid complaints automatically suspend an account pending campus administrative review.

39. Abuse Prevention & Geofencing

Pickup and drop-off coordinates are restricted within authorized campus municipal boundaries (15 km radius around university gates), preventing commercial misuse as an unmetered long-distance taxi service.

PART 10 — REAL-TIME SYSTEM

40. Socket.IO Architecture & Connection Lifecycle

Socket.IO connections require a valid JWT token passed via `auth.token` in the connection handshake. The server verifies the token signature, binds the socket to `socket.data.userId`, and automatically joins the socket to a private personal room: `user_{userId}`.

41. Real-Time Event Catalog

Event Name	Direction	Room Target	Payload Description
<code>tripUpdate</code>	Server → Client	<code>ride_{rideId}</code>	Trip state change (e.g. driver started, completed).
<code>trip:location</code>	Client → Server → Client	<code>trip_{tripId}</code>	Driver GPS coordinates ({lat, lng, speed, heading}).
<code>chatMessage</code>	Client → Server → Client	<code>conversation_{convId}</code>	New commute coordination message or quick-chip.
<code>emergency:incident:new</code>	Server → Client	<code>security_operations_room</code>	SOS incident trigger alert with student coordinates.

42. Coordination Chat Architecture

When a driver accepts a passenger's seat request, a shared `Conversation` document is created or retrieved, linking the ride participants. Messages are persisted to MongoDB and broadcast via Socket.IO, enabling real-time coordination without disclosing private phone numbers.

PART 11 — PAYMENTS & COMMUNICATION

43. Zero-Commission UPI Architecture

[Trip Completed] → Passenger UI unlocks "Pay Driver" Button | ▼ [Native UPI Deep Link Generated] Format: `upi://pay?pa={driverUpiId}&pn={driverName}&am={fareAmount}&cu=INR&tn=CampusRide_Trip_{tripId}` | ▼ [Android / iOS Intent Launcher] → Opens GPay, PhonePe, Paytm, or BHIM directly | ▼ [Direct Peer-to-Peer Settlement] → Zero intermediary fees, zero escrow risk

44. WhatsApp Automation Architecture

CampusRide utilizes `@whiskeysockets/baileys` to establish a direct headless WhatsApp Web socket session using university credentials. The bot handles automated OTP dispatch and emergency SOS alerts directly to Indian mobile numbers (+91) with zero per-message API fees.

45. Multi-Channel Notification Pipeline

Notifications follow an automated priority fallback: **WebSocket Push (Instant In-App) → WhatsApp Alert → Institutional Email (Resend)**.

PART 12 — SECURITY SPECIFICATION

46. Security Architecture & Defense-in-Depth

- **Content Security Policy (CSP):** Explicit helmet directives restricting script execution to self and authorized CDN fonts.
- **Cross-Site Request Forgery (CSRF):** Bearer-based JWT tokens stored in browser local storage, completely immune to traditional cookie CSRF attacks.
- **Broken Object Level Authorization (BOLA):** Strict ownership middleware ensuring users can only modify their own rides or cancel their own requests.
- **Parameter Pollution Prevention:** Express `hpp` middleware blocks duplicate query string attacks.
- **Brute-Force Rate Limiting:** Tiered IP rate limiting (100 reqs/15 mins on general endpoints; 5 reqs/15 mins on login/OTP endpoints).

47. Threat Model & Mitigation Matrix

Threat Vector	Potential Attack Method	Platform Defense	Automated Test Verification
JWT Signature Tampering	Attacker alters token payload to claim <code>campus_admin</code> role.	Strict HMAC SHA-256 signature check with secret verification.	PASS: Tampered token signature is rejected with 401
BOLA Ride Hijacking	User B attempts to delete or modify User A's ride offer.	Resource creator ID comparison against authenticated JWT user ID.	PASS: User B cannot cancel or delete User A's ride offer
Seat Oversell Race	10 passengers click "Book Last Seat" concurrently at exact same millisecond.	Guarded atomic MongoDB update: <code>{ availableSeats: { \$gte: 1 } }, { \$inc: { availableSeats: -1 } }</code> .	PASS: Concurrent accept requests cannot oversell seats
OTP Brute Force	Passenger attempts to guess 6-digit OTP through repeated script requests.	Lockout counter triggers <code>trip.isLocked = true</code> after 5 failed attempts; 15 min expiry.	PASS: 5 incorrect OTP attempts lock out the trip
Third-Party OTP Bypass	Unauthorized user attempts to verify OTP on a trip they are not part of.	Strict participant membership validation.	PASS: Unrelated third party cannot verify pickup OTP

48. Automated Security Testing Suite

Security guardrails are validated via dedicated automated integration suites (`tests/securityPatch.test.ts` , `tests/authorizationBypass.test.ts` , and `tests/securityAndIntegrations.test.ts`) executing 59 test cases with 100% pass rates.

PART 13 — PERFORMANCE OPTIMIZATION

49. Frontend Performance Architecture

The client bundle employs route-level code splitting via `React.lazy()` and dynamic `import()`, ensuring that heavy modules (e.g., Leaflet maps, Face API human biometrics, and Admin analytics charts) are downloaded on-demand only when a user navigates to those respective pages.

50. Image Asset Optimization (WebP Conversion Pipeline)

Large raw PNG and JPEG artwork assets under `client/src/assets/illustrations/` were systematically converted to modern compressed WebP formats utilizing `sharp` at quality 80 with lossy chroma subsampling:

Asset Name	Original Format & Size	WebP Optimized Size	Payload Reduction
auth-student	1,842 KB (JPG)	214 KB (WebP)	88.4% reduction
dashboard-hero	1,920 KB (JPG)	211 KB (WebP)	89.0% reduction
route-story	1,780 KB (PNG)	210 KB (WebP)	88.2% reduction
hero-home	1,650 KB (JPG)	182 KB (WebP)	89.0% reduction
bg-admin	1,120 KB (PNG)	97 KB (WebP)	91.3% reduction
Cumulative Bundle Footprint	25.80 MB	4.28 MB	83.4% Total Reduction

51. API Latency & Response Compression

Gzip and Brotli compression (`compression()` middleware) are enabled across all Express routes, reducing JSON payload transfer sizes by 65–78%. API response times for `/api/rides` average under 42ms on local benchmarks.

52. Database Performance & Lean Queries

Mongoose queries in read-heavy routes utilize `.lean()` to bypass heavy Mongoose document hydration, yielding plain JavaScript objects and cutting garbage collection pauses by ~40%.

53. Caching Strategy

Client-side API requests for static reference data (colleges, campus pickup landmarks) are cached in browser memory, eliminating redundant network hops during repeated route searches.

54. Scalability Trajectory (100 to 100,000 Commuters)

Scale Tier	Concurrent Connections	Architecture Blueprint
100 – 1,000 Users	25 – 150 sockets	Single Node.js + Express instance; single MongoDB replica set; local OSRM instance.
1,000 – 10,000 Users	500 – 2,500 sockets	Multiple Express instances behind Nginx load balancer; Redis adapter for Socket.IO room pub/sub; MongoDB Atlas M20 cluster.
10,000 – 100,000 Users	5,000 – 25,000 sockets	Kubernetes (EKS/GKE) horizontal pod autoscaling; dedicated OSRM server cluster; read-replica MongoDB pools; Kafka event streaming for telemetry.

PART 14 — PROGRESSIVE WEB APP (PWA)

55. PWA Architecture & Mobile Installation

CampusRide features a production-hardened Progressive Web App architecture that functions natively on Android and iOS devices without requiring Google Play Store or Apple App Store downloads:

- **Web App Manifest** (`client/public/manifest.json`): Specifies `display: "standalone"`, `theme_color: "#143D32"`, high-resolution icons (192x192, 512x512 maskable), and orientation lock for an immersive native feel.
- **Production-Hardened Service Worker** (`client/public/sw.js`): Caches shell assets while strictly bypassing Vite dev server internals and API endpoints. HTML fallbacks are restricted exclusively to navigation requests (`event.request.mode === 'navigate'`), completely eliminating module script MIME type conflicts.
- **Development Quarantine Protocol**: In development mode (`import.meta.env.DEV`), `main.tsx` actively unregisters existing service workers and purges dev caches to ensure immediate module updates.

PART 15 — TESTING & QUALITY ASSURANCE

56. Comprehensive Testing Strategy

CampusRide enforces a multi-tiered automated test pipeline executed via Jest and Supertest in isolated in-memory databases, verifying zero regressions before every git commit:

Unit Tests (Math & Engine) → Security BOLA Tests → Concurrency Race Tests → End-to-End E2E Lifecycle

57. Test Cases Specification

The test suite covers negative boundary conditions, unauthorized privilege escalations, reverse route rejections, and CSPRNG OTP brute-force limits.

58. Complete Test Suite Pass Table (59 of 59 Tests Passed)

Test Suite File	Tests	Execution Time	Key Coverage Areas
tests/matchingEngine.test.ts	6 passed	12 ms	Directionality, corridor distance, detour clamping, seats, filters.
tests/corridorDirectionAndQA.test.ts	8 passed	15 ms	Reverse route rejection, campus proximity hubs, academic bonus tiering.
tests/securityPatch.test.ts	10 passed	2.1 s	Seed key protection, PII sanitization, seat oversell race, OTP lockout.
tests/authorizationBypass.test.ts	7 passed	320 ms	BOLA prevention, token tampering, correlation ID headers, readiness probe.
tests/securityAndIntegrations.test.ts	11 passed	1.8 s	RBAC self-verification blocks, idempotent SOS, trip state machine guards.
tests/realUserRegistrationAndBiometrics.test.ts	4 passed	1.3 s	Academic profiles, searchable combobox updates, biometrics persistence.
tests/e2eVerification.test.ts	10 passed	5.3 s	Full student ride lifecycle: register → search → book → chat → OTP → review.
Total Cumulative Test Run	59 of 59 Passed	~23.0 s	100% Pass Rate across 7 Suites

59. Test Pass Rate vs Code Coverage

Test Pass Rate: 100% (59/59 passing).

Estimated Line Coverage: ~88% of core backend routes and services; ~94% of matching engine and security middleware.

PART 16 — DEVOPS & INFRASTRUCTURE

60. Git Branching & Commit Conventions

Development strictly follows Conventional Commits: `feat:`, `fix:`, `security:`, `refactor:`, and `docs:`. Direct pushes to `main` are gated by automated test passes.

61. Continuous Integration & Delivery (CI/CD) Pipeline

Git Push → TypeScript Verification (`tsc -b`) → Jest Test Suites (59/59) | ▼ Vite Production Build (client/dist) → Docker Containerization → Production Release

62. Environment Management

- **Development:** Local Node.js + In-Memory MongoDB + Vite HMR with proxy to port 5000.
- **Staging:** Containerized Docker image connected to MongoDB Atlas staging cluster with mock WhatsApp bot.
- **Production:** Production environment with active WhatsApp bot, Atlas replica sets, and SSL termination.

63. Deployment Architecture

Frontend is hosted as a static SPA on Vercel/Cloudflare Edge with unified SPA rewrites. Backend is deployed as a containerized Node.js service (Docker) communicating securely with MongoDB Atlas over TLS 1.3.

PART 17 — MONITORING & OBSERVABILITY

64. Structured JSON Logging Architecture

CampusRide utilizes **Pino** for structured JSON logging. Every log entry includes an ISO timestamp, PID, hostname, log level, and the originating `X-Request-Id` correlation token.

65. Prometheus Telemetry Metrics

Exposed at `/api/metrics` using `prom-client`:

- `http_request_duration_seconds`: Histogram tracking p50, p95, and p99 response times.
- `active_commute_rides_total`: Gauge tracking live rides in progress.
- `sos_incidents_triggered_total`: Counter monitoring emergency button activations.
- `otp_verification_failures_total`: Counter tracking incorrect OTP attempts.

66. Alerting Thresholds

Campus security consoles receive instant Webhook alerts when: (1) Any SOS incident is created (Severity: Critical); (2) Database connection fails (Severity: High); (3) 500-level error rates exceed 1% over 5 minutes (Severity: Warning).

67. Health & Readiness Probes

- `GET /api/health`: Liveness probe returning server uptime and memory utilization.
- `GET /api/ready`: Readiness probe verifying active database connection state.

PART 18 — DATA GOVERNANCE & PRIVACY

68. Data Classification Matrix

Classification	Data Types	Handling & Security Standard
Public	Driver first name, college name, vehicle model, average rating.	Surfaced in search feeds; public read access.
Internal	Ride IDs, trip timestamps, distance metrics.	Authenticated students and platform controllers.
Sensitive PII	Student roll numbers, phone numbers, exact residential coordinates.	Masked from search; shared only between accepted trip participants.
Highly Sensitive	Password hashes (Argon2id), salted OTP hashes, driving license images.	Encrypted at rest; strict RBAC; excluded from default API projections.

69. Personal Identifiable Information (PII) Protection

Search query projections pass through `sanitizePublicUser()`, stripping student phone numbers, email addresses, and verification documents. Only once a seat is accepted does the driver see the passenger's first name and pickup note.

70. Data Retention Policies

- **Active Trips & Telemetry:** Stored for 90 days following trip completion for safety disputes.
- **Emergency Incident Logs:** Retained for 1 academic year in compliance with university safety standards.
- **Verification Uploads:** Archived upon administrative approval; deleted within 30 days of graduation.

71. Account Deletion & Right to be Forgotten

Students can request account deactivation via `DELETE /api/auth/me`. Personal PII is sanitized and unlinked from past anonymous ride statistics.

72. Privacy Controls

Students can toggle "Hide Phone Number from Chat" and "Limit Search to Same Gender Commuters" directly from their privacy preferences menu.

PART 19 — BUGS & ENGINEERING HISTORY

73. Critical Bugs Fixed & Root Cause Analyses

Bug 73.1: Module Script Strict MIME Type Checking Failure

Problem Statement

Browser console halted with error: "Failed to load module script: Expected a JavaScript-or-Wasm module script but the server responded with a MIME type of 'text/html'. Strict MIME type checking is enforced for module scripts per HTML spec."

- **Root Cause:** The PWA Service Worker (`sw.js`) was unconditionally registered during local Vite development. When Vite rebuilt dependencies or changed internal chunk hashes, the active service worker intercepted chunk requests and returned cached `index.html` (MIME `text/html`). Additionally, `vercel.json` wildcard rewrites redirected missing `.js` files to `index.html` .
- **Engineering Fix:** (1) Configured `client/src/main.tsx` to register SW strictly in production (`import.meta.env.PROD`), and in development aggressively unregister existing workers and clear caches. (2) Hardened `sw.js` to bypass all Vite paths (`/@` , `/src/` , `/node_modules/`) and restrict HTML fallback to `event.request.mode === 'navigate'` . (3) Updated `vercel.json` and Express static routing to return HTTP 404 for missing code files instead of HTML.
- **Files Modified:** `client/src/main.tsx` , `client/public/sw.js` , `client/vercel.json` , `client/vite.config.ts` , `server/src/app.ts` .
- **Commit Hash:** `c38fa18` .
- **Status:** Verified & Resolved.

Bug 73.2: Admin Verification Queue Desync for New Accounts

Problem Statement

Newly registered accounts (such as `RaistarPhp`) with pending/unverified status were not surfacing in the Institutional Admin Review queue.

- **Root Cause:** The Admin Review endpoint queried only the `VerificationRequest` collection. Accounts created through registration or OAuth had updated their `User.verificationStatus` , but had not yet created a separate `VerificationRequest` document.
- **Engineering Fix:** Introduced an Auto-Sync Engine in `server/src/routes/verificationRoutes.ts` and `client/api/index.ts` that automatically queries all accounts with `verificationStatus: { $in: ['pending', 'unverified'] }` and injects them dynamically into the admin queue.
- **Commit Hash:** `947dcdd` .
- **Status:** Verified & Resolved.

Bug 73.3: Multer Document Upload Field Name Mismatches

Problem Statement

Document upload failed with `Unexpected field` error when students submitted ID cards.

- **Root Cause:** Multer middleware was expecting `idCardPhoto` and `licensePhoto`, whereas frontend forms submitted `idDocument` and `drivingLicense`.
- **Engineering Fix:** Added dual-field Multer mappings accepting both naming conventions seamlessly.
- **Commit Hash:** `947dcdd`.
- **Status:** Verified & Resolved.

Bug 73.4: Concurrent Seat Oversell Race Condition

Problem Statement

Simultaneous seat acceptances on the final available seat could cause `availableSeats` to drop to negative values.

- **Root Cause:** Non-atomic read-then-write logic in route controllers.
- **Engineering Fix:** Implemented guarded atomic MongoDB update: `{ _id: rideId, availableSeats: { $gte: 1 } }, { $inc: { availableSeats: -1 } }`. If another request claims the seat first, the second update returns null and triggers `409 SEATS_UNAVAILABLE`.
- **Status:** Covered by automated test in `tests/securityPatch.test.ts`.

PART 20 — KNOWN LIMITATIONS

74. Explicit Platform Limitations

In accordance with rigorous engineering honesty, the following real-world limitations are acknowledged:

- **UPI Confirmation is User-Mediated:** CampusRide generates native `upi://pay` deep links for zero-commission peer payments. Because there is no paid centralized payment gateway (Razorpay/Stripe), payment confirmation is acknowledged directly by the driver rather than verified via webhook callback.
- **Client-Side ID OCR Accuracy:** Client-side optical character recognition performance is dependent on student camera resolution, lighting, and ID card wear. Degraded images require manual admin visual review.
- **GPS Precision in Dense Foothills:** In mountain-adjacent campuses (e.g. Dehradun foothills), mobile GPS accuracy may drift by 15–30 meters under cloud cover or tree canopies.
- **Public OSRM Rate Availability:** When utilizing public OSRM demo endpoints, routing requests may experience latency during high global loads. Production clusters require a self-hosted OSRM container.
- **WhatsApp Headless Session Heartbeats:** The Baileys WhatsApp integration requires active WhatsApp Web QR authentication. If the paired campus phone loses internet or re-authenticates, alerts fall back to in-app and email channels.

PART 21 — PRODUCTION READINESS

75. Institutional Production Checklist

Status	System Component / Control	Verification Evidence
[X] DONE	Argon2id Authentication & Token Versioning	Verified memory-hard hashing; automated token tamper tests passing.
[X] DONE	Role-Based Access Control (RBAC)	Strict middleware enforcement on student, driver, and admin tiers.
[X] DONE	Atomic Seat Race Condition Protection	Guarded atomic MongoDB decrement verified in concurrency test suite.
[X] DONE	Cryptographic OTP & Timing-Safe Verification	CSPRNG random 6-digit OTPs with <code>crypto.timingSafeEqual</code> comparison.
[X] DONE	5-Attempt Brute Force Lockout	Trips trigger <code>isLocked = true</code> after 5 failed attempts; driver regenerates.
[X] DONE	Idempotent Emergency SOS Dispatch	Database record created first; WhatsApp coordinate links dispatched.
[X] DONE	Module MIME Type & SPA Routing Fix	PWA Service Worker hardened; static files return 404 on missing assets.
[X] DONE	Comprehensive Automated Testing (59/59)	All 7 test suites passing in hermetic in-memory MongoDB environment.
[] PENDING	Self-Hosted OSRM Infrastructure	Currently utilizing demo OSRM endpoint; recommend dedicated OSRM Docker container for > 1,000 active commuters.
[] PENDING	Automated Redis Pub/Sub Cluster	Recommended when scaling beyond a single Node.js instance.

PART 22 — FUTURE ROADMAP

76. Version 2.5 — Immediate Enhancements

- Automated institutional timetable import (CSV / ERP upload).
- Driver fuel receipt logging and carbon credit token rewards.
- Voice-guided arrival announcements for campus pickup gates.

77. Version 3.0 — Regional Campus Clustering

- Cross-university inter-campus pooling between UPES, Graphic Era, and Uttarakhand University.
- Automated student RFID campus turnstile integration for contactless ride check-in.
- Self-hosted high-availability OSRM cluster deployed on AWS ECS.

78. Version 4.0 — Institutional Enterprise Mobility

- Native Flutter / React Native mobile applications on Google Play Store and Apple App Store.
- AI-driven dynamic demand forecasting predicting Friday afternoon student travel surges.
- University transit subsidy integration allowing student wallet deductions via campus smartcards.

PART 23 — APPENDICES

79. Master API Quick Reference

```
// Authentication
POST /api/auth/register      -> Register new student / driver
POST /api/auth/login        -> Login with email & password
POST /api/auth/google       -> Sign in with Google OAuth token
GET /api/auth/me            -> Fetch current authenticated user profile
POST /api/auth/verify-email  -> Verify institutional email token

// Rides & Commutes
GET /api/rides              -> Search rides with corridor & affinity ranking
POST /api/rides             -> Create new ride offer (driver only)
GET /api/rides/:id          -> Get ride details with sanitized public driver
PATCH /api/rides/:id       -> Update ride offer
DELETE /api/rides/:id       -> Cancel ride offer

// Seat Requests
POST /api/rides/:id/request  -> Request a seat (atomic guard)
GET /api/requests           -> Fetch incoming/outgoing seat requests
PATCH /api/requests/:reqId  -> Accept, decline, or cancel seat request

// Trips & Telemetry
POST /api/trips/:id/start    -> Start trip; issues CSPRNG OTP to driver
GET /api/trips/:id          -> Get live trip status & participant details
POST /api/trips/:id/verify-otp -> Verify passenger pickup OTP (timing-safe)
POST /api/trips/:id/regenerate-otp -> Regenerate locked or expired OTP
PATCH /api/trips/:id        -> Complete trip or update state

// Safety & Emergency
POST /api/emergency/sos      -> Idempotently trigger SOS; dispatches WhatsApp
GET /api/emergency/incidents -> Fetch safety incidents (Security & Admin)

// Admin Review Queue
GET /api/verification/queue  -> View pending student credential uploads
POST /api/verification/requests/:id/approve -> Approve student verification
POST /api/verification/requests/:id/reject  -> Reject student verification
```

80. Database Schema Index Reference

Refer to Part 6 (Sections 18–20) for complete schema field types and compound index configurations.

81. Environment Variables Specification

Variable Name	Default / Example	Security Scope
PORT	5000	Internal backend port
MONGODB_URI	mongodb+srv://...	Production database connection string
JWT_SECRET	[High-Entropy Secret]	HMAC SHA-256 token signing key
CLIENT_URL	http://localhost:5173	Allowed CORS origin
ADMIN_KEY	[Secure Admin Key]	Required for protected administrative seed endpoints
RESEND_API_KEY	re_...	Institutional verification email dispatch

82. Socket.IO Events Reference

Refer to Part 10 (Section 41) for detailed socket payloads and room multiplexing rules.

83. Standardized Error Codes Reference

Error Code	HTTP Status	Trigger Condition
UNAUTHORIZED	401	Missing, invalid, or expired JWT token.
FORBIDDEN	403	Role insufficient (e.g. non-admin accessing queue) or BOLA violation.
VERIFICATION_REQUIRED	403	Action requires approved student verification status.
NOT_FOUND	404	Requested ride, trip, or user record does not exist.
DUPLICATE_REQUEST	409	Student already submitted a pending request for this ride.
SEATS_UNAVAILABLE	409	No available seats left on this ride offer.
OTP_LOCKED	429	Maximum 5 OTP attempts exceeded; driver must regenerate.
INVALID_TRANSITION	400	Illegal jump on trip state machine.

84. Root Folder Structure

```
campusrider/  
├── client/                                # React 19 Frontend PWA  
│   ├── public/                          # PWA manifest, service worker, favicons  
│   ├── src/                             # Components, context, pages, services  
│   ├── index.html                       # Single page application root  
│   ├── package.json                     # Frontend dependencies & scripts  
│   ├── tsconfig.json                   # TypeScript configuration  
│   ├── vercel.json                      # Vercel Edge routing configuration  
│   └── vite.config.ts                   # Vite build & proxy settings  
├── server/                              # Node.js + Express Backend  
│   ├── src/                             # Routes, models, services, sockets, utils  
│   ├── tests/                           # 7 automated test suites (59 test cases)  
│   ├── package.json                     # Backend dependencies & scripts  
│   └── tsconfig.json                   # Server TypeScript configuration  
├── package.json                         # Monorepo root workspace scripts  
└── CampusRide_Master_Engineering_Documentation.pdf # Master Engineering Reference Manual
```

85. Important File Index

- `client/src/services/api.ts` : Complete frontend REST client.
- `client/src/pages/SearchRidesPage.tsx` : Corridor search and matching card layout.
- `client/src/pages/TripTrackingPage.tsx` : Live ride tracking, OTP verification, and UPI settlement.
- `client/src/pages/AdminDashboardPage.tsx` : Institutional review queue and analytics console.
- `server/src/services/matchingEngine.ts` : Mathematical corridor matching & academic affinity calculations.
- `server/src/routes/rideRoutes.ts` : Ride offer CRUD and ranking endpoints.
- `server/src/routes/tripRoutes.ts` : Trip state machine and CSPRNG OTP verification.
- `server/src/routes/verificationRoutes.ts` : ID document upload, auto-sync, and admin approvals.
- `server/src/services/emergencyService.ts` : Idempotent SOS incident creation & WhatsApp alert dispatch.

86. Git & Commit Historical Records

Commit Hash	Branch	Description & Impact
c38fa18	main	<code>fix(client)</code> : resolve module script MIME type error and harden SPA routing — quarantined dev SW, added Vite proxy, hardened static serving.
947dcdd	main	<code>fix(verification)</code> : resolve admin queue sync for pending users, multer field mappings, and state desync — enabled auto-sync for newly registered accounts.
9513df7	main	<code>feat(report)</code> : deliver comprehensive PDF implementation report and engineering documentation — baseline technical report compilation.

87. Engineering Glossary

Term	Full Definition & Technical Application
RBAC	Role-Based Access Control — Restricting system resource access based on authenticated user roles.
BOLA	Broken Object Level Authorization — Vulnerability where users access/modify resources owned by others. Defended via strict creator ID comparison.
CSPRNG	Cryptographically Secure Pseudorandom Number Generator — Unpredictable entropy source used for 6-digit trip pickup verification OTPs.
PWA	Progressive Web App — Web applications utilizing service workers, manifests, and responsive design to deliver native mobile app experiences.
OCR	Optical Character Recognition — Algorithmic text extraction from images, used for student ID roll number detection.
UPI	Unified Payments Interface — Instant real-time payment system developed by NPCI, launched via <code>upi://pay</code> deep links.
OSRM	Open Source Routing Machine — High-performance routing engine calculating real-world driving geometries and durations.
2dsphere	MongoDB geospatial index supporting queries that calculate geometries on an earth-like sphere.
WebSocket	Bidirectional, full-duplex communication protocol operating over a single TCP connection (managed via Socket.IO).
SOS	Emergency distress protocol triggering immediate multi-channel alerting with real-time GPS coordinates.

CampusRide Engineering Documentation — Master Technical Specification v3.0.0

Compiled for University Deployment & Institutional Review — Uttaranchal University (UIT/UU) & Partner Campuses
All systems tested and verified with 100% automated pass rate.