

Instructor Notes:

Add instructor notes here.



Instructor Notes:

Add instructor notes here.

Lesson Objectives



- Working with jQuery Plugins



June 21, 2018

<small>Proprietary and Confidential</small>	<small>- 2 -</small>
---	----------------------

Instructor Notes:

Add instructor notes here.

4.1: Bootstrap Plugins

Bootstrap jQuery Plugins



- Bootstrap comes bundled with 12 jQuery plugins that extend the features and can add more interaction to your site.
- Plugins can be included individually (using Bootstrap's individual *.js files) or all at once (using bootstrap.js or the minified bootstrap.min.js).
- Both bootstrap.js and bootstrap.min.js contain all plugins in a single file.
- We can use all Bootstrap plugins either through the markup API using data-* attributes without writing a single line of JavaScript or purely through the JavaScript API.
- To disable data attribute API and access plug-ins through JavaScript API.
 - Disable all plugins : **`$(document).off('.data-api')`**
 - Disable a specific plugin: **`$(document).off('.alert.data-api')`**

June 21, 2018Proprietary and Confidential- 3 -

Mobile first approach uses the grid system in particular is to layout designs first on small screens, such as those that come on a mobile phone and then it can be scaled up the size of those designs to larger and larger environments.

Prior to Bootstrap 3 It doesn't support mobile first approach and as a optional feature it supports Responsive web design.

Instructor Notes:

Add instructor notes here.

4.1: Bootstrap Plugins

Working with Methods



- All JavaScript API methods can accept an optional options object, a string which targets a particular method, or nothing (which initiates plugin with default behavior)
- To initialize with defaults
 - `$(selector).ApiMethod()`
- To initialize with Options
 - `$(selector).ApiMethod({options})`
- To initialize with methods to be invoked
 - `$(selector).ApiMethod('methodName')`

June 21, 2018

Proprietary and Confidential

- 4 -

Mobile first approach uses the grid system in particular is to layout designs first on small screens, such as those that come on a mobile phone and then it can be scaled up the size of those designs to larger and larger environments.

Prior to Bootstrap 3 It doesn't support mobile first approach and as a optional feature it supports Responsive web design.

Instructor Notes:

Add instructor notes here.

4.1: Bootstrap Plugins Working with Events



- Bootstrap provides custom events for most plugins' unique actions.
- All Bootstrap events are namespaced i.e. `<event>.bs.<component>`
 - **eg:** `show.bs.modal`
- If (show) is triggered at the start of an event, its past participle form (shown) is triggered on the completion of an action.

June 21, 2018 Proprietary and Confidential - 5 -

Mobile first approach uses the grid system in particular is to layout designs first on small screens, such as those that come on a mobile phone and then it can be scaled up the size of those designs to larger and larger environments.

Prior to Bootstrap 3 It doesn't support mobile first approach and as a optional feature it supports Responsive web design.

Instructor Notes:

Add instructor notes here.

4.1: Bootstrap Plug-ins Transition Plug-in



- Transition plugin provides simple transition effects.
- We can apply transitions on Modal, Tab, Alerts and Carousel plugins
- These are the classes for the different transitions:
 - .fade (fade out)
 - .fade.in (fade in)
 - .collapse (collapse out)
 - .collapse.in (collapse in)
- If you use the modal then the fade class adds animation to the modal
 - .fade (fade out to top 0)
 - .fade.in (fade in from top to 50% height)

June 21, 2018

Proprietary and Confidential

- 6 -

Mobile first approach uses the grid system in particular is to layout designs first on small screens, such as those that come on a mobile phone and then it can be scaled up the size of those designs to larger and larger environments.

Prior to Bootstrap 3 It doesn't support mobile first approach and as a optional feature it supports Responsive web design.

Instructor Notes:

Add instructor notes here.

4.1: Bootstrap Plug-ins Modal Plug-in



- A Modal dialog is a dialog that overlays the rest of the web page and take the control of page.
- A modal is a child window that is layered over its parent window.
- To invoke the modal window, we can use a button or a link with data-toggle = "modal" along with a data-target = "#identifier" or href = "#identifier" to target a specific modal
- There are 3 distinct parts inside a Modal: header, body and footer
- To include this plugin functionality individually we need to use modal.js

June 21, 2018 Proprietary and Confidential - 7 -

Mobile first approach uses the grid system in particular is to layout designs first on small screens, such as those that come on a mobile phone and then it can be scaled up the size of those designs to larger and larger environments.

Prior to Bootstrap 3 It doesn't support mobile first approach and as a optional feature it supports Responsive web design.

Instructor Notes:

Add instructor notes here.

4.1: Bootstrap Plug-ins

Modal Plug-in options

Options	Default Value	Data attribute	Description
	boolean or the string 'static'		
backdrop	Default: true	data-backdrop	specify static for a backdrop, if you don't want the modal to be closed when the user clicks outside of the modal.
	boolean		
keyboard	Default: true	data-keyboard	Closes the modal when escape key is pressed; set to false to disable.
	boolean		
show	Default: true	data-show	Shows the modal when initialized.
	path		
			Using the jQuery .load method, inject content into the modal body. If an href with a valid URL is added, it will load that content. An example of this is shown below:
remote	Default: false	data-remote	<pre><a data-toggle="modal" href="remote.html" data-target="#modal">Click me</pre>

June 21, 2008

Proprietary and Confidential

- 8 -

Mobile first approach uses the grid system in particular is to layout designs first on small screens, such as those that come on a mobile phone and then it can be scaled up the size of those designs to larger and larger environments.

Prior to Bootstrap 3 It doesn't support mobile first approach and as a optional feature it supports Responsive web design.

Instructor Notes:

Add instructor notes here.

4.1: Bootstrap Plug-ins Modal Plug-in methods		
Method	Description	Example
<code>.modal(options)</code>	Activates your content as a modal. Accepts an optional options object.	<code>\$('#identifier').modal({ keyboard: false })</code>
<code>.modal('toggle')</code>	Manually toggles a modal	<code>\$('#identifier').modal('toggle')</code>
<code>.modal('show')</code>	Manually opens a modal	<code>\$('#identifier').modal('show')</code>
<code>.modal('hide')</code>	Manually hides a modal	<code>\$('#identifier').modal('hide')</code>

June 21, 2018 Proprietary and Confidential - 9 -

Mobile first approach uses the grid system in particular is to layout designs first on small screens, such as those that come on a mobile phone and then it can be scaled up the size of those designs to larger and larger environments.

Prior to Bootstrap 3 It doesn't support mobile first approach and as a optional feature it supports Responsive web design.

Instructor Notes:

Add instructor notes here.

4.1: Bootstrap Plug-ins Modal Plug-in Events		
Event	Description	Example
show.bs.modal	Fired after the show method is called.	<pre>\$('#identifier').on('show.bs.modal', function () { // do something... })</pre>
shown.bs.modal	Fired when the modal has been made visible to the user (will wait for CSS transitions to complete).	<pre>\$('#identifier').on('shown.bs.modal', function () { // do something... })</pre>
hide.bs.modal	Fired when the hide instance method has been called.	<pre>\$('#identifier').on('hide.bs.modal', function () { // do something... })</pre>
hidden.bs.modal	Fired when the modal has finished being hidden from the user.	<pre>\$('#identifier').on('hidden.bs.modal', function () { // do something... })</pre>

June 21, 2018 Proprietary and Confidential - 10 -


Mobile first approach uses the grid system in particular is to layout designs first on small screens, such as those that come on a mobile phone and then it can be scaled up the size of those designs to larger and larger environments.

Prior to Bootstrap 3 It doesn't support mobile first approach and as a optional feature it supports Responsive web design.


Instructor Notes:

Add instructor notes here.

Demo



➤Modal-Plugin



June 21, 2018

Proprietary and Confidential

- 11 -

Instructor Notes:

Add instructor notes here.

4.1: Bootstrap Plug-ins Carousel Plug-in



- A Carousel gives you a picture Carousel that can cycle through a series of images.
- Carousel works best when all of the images have the same resolution
- Carousel can also have a caption inside of each item that typically consists of some header text and some additional text
- We can set the interval to how frequently to swap the pictures
- We can also control the carousel using user pause, previous and next buttons.
- To include this plugin functionality individually we need carousel.js

June 21, 2018 Proprietary and Confidential - 12 -

Mobile first approach uses the grid system in particular is to layout designs first on small screens, such as those that come on a mobile phone and then it can be scaled up the size of those designs to larger and larger environments.

Prior to Bootstrap 3 It doesn't support mobile first approach and as a optional feature it supports Responsive web design.

Instructor Notes:

Add instructor notes here.

4.1: Bootstrap Plug-ins Carousel Plug-in options			
Option Name	Default Value	Data attribute	Description
interval	number	data-interval	The amount of time to delay between automatically cycling an item. If false, carousel will not automatically cycle.
	Default: 5000		
pause	string	data-pause	Pauses the cycling of the carousel on mouseenter and resumes the cycling of the carousel on mouseleave.
	Default: "hover"		
wrap	boolean	data-wrap	Whether the carousel should cycle continuously or have hard stops.
	Default: true		

June 21, 2018 Proprietary and Confidential - 13 -

Mobile first approach uses the grid system in particular is to layout designs first on small screens, such as those that come on a mobile phone and then it can be scaled up the size of those designs to larger and larger environments.


Prior to Bootstrap 3 It doesn't support mobile first approach and as a optional feature it supports Responsive web design.

Instructor Notes:

Add instructor notes here.

4.1: Bootstrap Plug-ins

Carousel Plug-in methods



Method	Description	Example
<code>.carousel(options)</code>	Initializes the carousel with an optional options object and starts cycling through items.	<code>\$('#identifier').carousel({ interval: 2000 })</code>
<code>.carousel('cycle')</code>	Cycles through the carousel items from left to right.	<code>\$('#identifier').carousel('cycle')</code>
<code>.carousel('pause')</code>	Stops the carousel from cycling through items.	<code>\$('#identifier').carousel('pause')</code>
<code>.carousel(number)</code>	Cycles the carousel to a particular frame (0 based, similar to an array).	<code>\$('#identifier').carousel(number)</code>
<code>.carousel('prev')</code>	Cycles to the previous item.	<code>\$('#identifier').carousel('prev')</code>
<code>.carousel('next')</code>	Cycles to the next item..	<code>\$('#identifier').carousel('next')</code>

June 21, 2018

Proprietary and Confidential

- 14 -

Mobile first approach uses the grid system in particular is to layout designs first on small screens, such as those that come on a mobile phone and then it can be scaled up the size of those designs to larger and larger environments.

Prior to Bootstrap 3 It doesn't support mobile first approach and as a optional feature it supports Responsive web design.

Instructor Notes:

Add instructor notes here.

4.1: Bootstrap Plug-ins Carousel Plug-in Events		
Event	Description	Example
slide.bs.carousel	This event fires immediately when the slide instance method is invoked..	<pre>\$('#identifier').on('slide.bs.carousel', function () { // do something... })</pre>
slid.bs.carousel	This event is fired when the carousel has completed its slide transition.	<pre>\$('#identifier').on('slid.bs.carousel', function () { // do something... })</pre>

June 21, 2018 Proprietary and Confidential - 15 -


Mobile first approach uses the grid system in particular is to layout designs first on small screens, such as those that come on a mobile phone and then it can be scaled up the size of those designs to larger and larger environments.

Prior to Bootstrap 3 It doesn't support mobile first approach and as a optional feature it supports Responsive web design.

Instructor Notes:

Add instructor notes here.

Demo



➤ Carousel Plug-in

June 21, 2018 | Proprietary and Confidential | - 16 -

Instructor Notes:

Add instructor notes here.

4.1: Bootstrap Plug-ins Collapse Plug-in



- Collapse plugin makes it easy to make collapsing divisions of the page.
- It is used to create collapsible groups or accordion
 - **data-toggle="collapse"** is added to the link on which we click to expand or collapse the component.
 - **href** or a **data-target attribute** is added to the parent component, whose value is id of the child component.
 - **data-parent** attribute is added to is added for creating accordion like effect.
 - **.collapse** class is used to hide the content and **.collapse.in** class is used to show the content
- To include this plugin functionality individually we need to use collapse.js

June 21, 2018

Proprietary and Confidential

- 17 -

Mobile first approach uses the grid system in particular is to layout designs first on small screens, such as those that come on a mobile phone and then it can be scaled up the size of those designs to larger and larger environments.

Prior to Bootstrap 3 It doesn't support mobile first approach and as a optional feature it supports Responsive web design.

Instructor Notes:

Add instructor notes here.

4.1: Bootstrap Plug-ins CollapsePlug-in options			
Option	Default Value	Data attribute	Description
parent	selector		If selector then all collapsible elements under the specified parent will be closed when this collapsible item is shown. (similar to traditional accordion behavior - this dependent on the accordion-group class)
	Default: false		
toggle	boolean	data-toggle	Toggles the collapsible element on invocation.
	Default: true		

June 21, 2018

Proprietary and Confidential

- 18 -

Mobile first approach uses the grid system in particular is to layout designs first on small screens, such as those that come on a mobile phone and then it can be scaled up the size of those designs to larger and larger environments.

Prior to Bootstrap 3 It doesn't support mobile first approach and as a optional feature it supports Responsive web design.

Instructor Notes:

Add instructor notes here.

4.1: Bootstrap Plug-ins CollapsePlug-in methods		
Method	Description	Example
Options: <code>.collapse(options)</code>	Activates your content as a collapsible element. Accepts an optional options object.	<code>\$('#identifier').collapse({toggle: false})</code>
Toggle: <code>.collapse('toggle')</code>	Toggles a collapsible element to shown or hidden.	<code>\$('#identifier').collapse('toggle')</code>
Show: <code>.collapse('show')</code>	Shows a collapsible element.	<code>\$('#identifier').collapse('show')</code>
Hide: <code>.collapse('hide')</code>	Hides a collapsible element.	<code>\$('#identifier').collapse('hide')</code>

June 21, 2018 Proprietary and Confidential - 19 -

Mobile first approach uses the grid system in particular is to layout designs first on small screens, such as those that come on a mobile phone and then it can be scaled up the size of those designs to larger and larger environments.

Prior to Bootstrap 3 It doesn't support mobile first approach and as a optional feature it supports Responsive web design.

Instructor Notes:

Add instructor notes here.

4.1: Bootstrap Plug-ins Collapse Plug-in Events		
Event	Description	Example
show.bs.collapse	Fired after the show method is called.	<pre>\$('#identifier').on('show.bs.collapse', function () { // do something... })</pre>
shown.bs.collapse	This event is fired when a collapse element has been made visible to the user (will wait for CSS transitions to complete).	<pre>\$('#identifier').on('shown.bs.collapse', function () { // do something... })</pre>
hide.bs.collapse	Fired when the hide instance method has been called.	<pre>\$('#identifier').on('hide.bs.collapse', function () { // do something... })</pre>
hidden.bs.collapse	This event is fired when a collapse element has been hidden from the user (will wait for CSS transitions to complete).	<pre>\$('#identifier').on('hidden.bs.collapse', function () { // do something... })</pre>

June 21, 2018 Proprietary and Confidential - 30 -


Mobile first approach uses the grid system in particular is to layout designs first on small screens, such as those that come on a mobile phone and then it can be scaled up the size of those designs to larger and larger environments.

Prior to Bootstrap 3 It doesn't support mobile first approach and as a optional feature it supports Responsive web design.


Instructor Notes:

Add instructor notes here.

Demo



➤Collapsible-Plugin



June 21, 2018

Proprietary and Confidential

- 21 -

Instructor Notes:

Add instructor notes here.

4.1: Bootstrap Plug-ins Tab Plug-in



- Tabs are used to arrange a navigational menu with links to other pages or sections of the site.
- Using Tab plugin, we can transition through panes of local content in tabs or pills
- Adding the `.nav` and `.nav-tabs` classes to the tab ul will apply the Bootstrap tab styling, while adding the `.nav` and `.nav-pills` classes will apply pill styling.
- `.tab()` method activates a tab element and content container. Tab should have either a `data-target` or an `href` targeting a container node in the DOM.
- To include this plugin functionality individually we need `tab.js`

June 21, 2018

Proprietary and Confidential

- 22 -

Mobile first approach uses the grid system in particular is to layout designs first on small screens, such as those that come on a mobile phone and then it can be scaled up the size of those designs to larger and larger environments.

Prior to Bootstrap 3 It doesn't support mobile first approach and as a optional feature it supports Responsive web design.

Instructor Notes:

Add instructor notes here.

4.1: Bootstrap Plug-ins Tab Plug-in Events		
Event	Description	Example
show.bs.tab	This event fires on tab show, but before the new tab has been shown. Use event.target and event.relatedTarget to target the active tab and the previous active tab (if available) respectively.	<pre>\$('a[data-toggle="tab"]').on('show.bs.tab', function (e) { e.target // activated tab e.relatedTarget // previous tab })</pre>
shown.bs.tab	This event fires on tab show after a tab has been shown. Use event.target and event.relatedTarget to target the active tab and the previous active tab (if available) respectively.	<pre>\$('a[data-toggle="tab"]').on('shown.bs.tab', function (e) { e.target // activated tab e.relatedTarget // previous tab })</pre>

June 21, 2008 Proprietary and Confidential - 23 -


Mobile first approach uses the grid system in particular is to layout designs first on small screens, such as those that come on a mobile phone and then it can be scaled up the size of those designs to larger and larger environments.

Prior to Bootstrap 3 It doesn't support mobile first approach and as a optional feature it supports Responsive web design.


Instructor Notes:

Add instructor notes here.

Demo



➤ Tab-Plugin



June 21, 2018

Proprietary and Confidential

- 34 -

Instructor Notes:

Add instructor notes here.

**4.1: Bootstrap Plug-ins
Tooltip Plug-in**

- Tabs are used to arrange a navigational menu with links to other pages or sections of the site.
- Using Tab plugin, we can transition through panes of local content in tabs or pills
- Adding the `.nav` and `.nav-tabs` classes to the tab ul will apply the Bootstrap tab styling, while adding the `.nav` and `.nav-pills` classes will apply pill styling.
- `.tab()` method activates a tab element and content container. Tab should have either a `data-target` or an `href` targeting a container node in the DOM.
- To include this plugin functionality individually we need `tab.js`

June 21, 2018 Proprietary and Confidential - 35 -

Mobile first approach uses the grid system in particular is to layout designs first on small screens, such as those that come on a mobile phone and then it can be scaled up the size of those designs to larger and larger environments.

Prior to Bootstrap 3 It doesn't support mobile first approach and as a optional feature it supports Responsive web design.

Instructor Notes:

Add instructor notes here.

4.1: Bootstrap Plug-ins Tab Plug-in Events		
Event	Description	Example
show.bs.tab	This event fires on tab show, but before the new tab has been shown. Use event.target and event.relatedTarget to target the active tab and the previous active tab (if available) respectively.	<pre>\$('a[data-toggle="tab"]').on('show.bs.tab', function (e) { e.target // activated tab e.relatedTarget // previous tab })</pre>
shown.bs.tab	This event fires on tab show after a tab has been shown. Use event.target and event.relatedTarget to target the active tab and the previous active tab (if available) respectively.	<pre>\$('a[data-toggle="tab"]').on('shown.bs.tab', function (e) { e.target // activated tab e.relatedTarget // previous tab })</pre>

June 21, 2008 Proprietary and Confidential - 26 -


Mobile first approach uses the grid system in particular is to layout designs first on small screens, such as those that come on a mobile phone and then it can be scaled up the size of those designs to larger and larger environments.

Prior to Bootstrap 3 It doesn't support mobile first approach and as a optional feature it supports Responsive web design.


Instructor Notes:

Add instructor notes here.

Demo



➤Tooltip-Plugin



June 21, 2018

Proprietary and Confidential

- 27 -