

# Numerical Simulation Methods And Their Applications


*Monte Carlo Methods and Applications in Particle-based Systems*

Ridhwaan Amin

32005096

**Department of Mathematics and Statistics**

*University of Reading*



May 14, 2026

## **Plain language summary**

This project concerns working with a computer simulation of a particle-based system, particularly using numerical techniques known as Monte Carlo simulations.

It starts with an introduction to the history of these methods, touching upon the Manhattan Project, then focusing on pseudo-random number generators, sampling methodologies, and their applications in statistical mechanics. The project also explores the Metropolis method and its application to a Lennard-Jones liquid. Finally, it concludes with findings of a simulation created from individually developed C++ code.

These findings consist of elements such as total energy within the system, and values derived from numerical analysis of the particles, such as (but not limited to) the radial distribution and diffusion coefficients.

## Declaration

I certify that this is my own work and that use of material from other sources has been properly and fully acknowledged in the text. I have read the University's definition of plagiarism and the department's advice on good academic practice. I understand that the consequence of committing plagiarism, if proven and in the absence of mitigating circumstances may include failure in the Year or Part or removal from the membership of the University. I also certify that neither this piece of work, nor any part of it, has been submitted in connection with another assessment.

In submitting this work I can confirm that I **[have/have not]** used Generative AI Tools to prepare and complete my assignment.

to prepare and complete work, please one select the following statements:

~~/a./I acknowledge the use of AI to generate materials to support my research and understanding on the topic when drafting this assignment, but none of the outputs are included in the final version./~~

~~/b./I acknowledge the use of AI to generate materials that were included within my final assessment in modified form./I have taken responsibility to ensure that where generated materials are included, these have been referenced appropriately, in accordance with the requirements of the assignment brief./~~

# Contents

|                                                          |           |
|----------------------------------------------------------|-----------|
| <b>List of Tables</b>                                    | <b>v</b>  |
| <b>List of Figures</b>                                   | <b>v</b>  |
| <b>1 Development Of Computer Simulation Methods</b>      | <b>1</b>  |
| 1.1 The Manhattan Project . . . . .                      | 1         |
| 1.1.1 Background Context . . . . .                       | 1         |
| 1.1.2 Stanisław Ulam . . . . .                           | 1         |
| 1.1.3 Subsequent Developments . . . . .                  | 1         |
| <b>2 Monte Carlo Methods</b>                             | <b>2</b>  |
| 2.1 Pseudo-Random Number Generators . . . . .            | 2         |
| 2.1.1 The Linear Congruential Generator (LCG) . . . . .  | 2         |
| 2.1.2 Linear Congruential Generator Example . . . . .    | 3         |
| 2.1.3 The Mersenne Twister . . . . .                     | 3         |
| 2.2 Sampling Methodology . . . . .                       | 4         |
| 2.2.1 Simple Sampling . . . . .                          | 4         |
| 2.2.2 Importance . . . . .                               | 4         |
| 2.3 Statistical Mechanics . . . . .                      | 5         |
| 2.4 The Metropolis Method . . . . .                      | 5         |
| <b>3 The Lennard-Jones Potential</b>                     | <b>6</b>  |
| 3.1 A Description . . . . .                              | 6         |
| 3.1.1 Displaying The Potential Visually . . . . .        | 6         |
| 3.1.2 Applications in Modelling Simple Liquids . . . . . | 7         |
| 3.2 Periodic Boundary Conditions . . . . .               | 8         |
| <b>4 Monte Carlo Simulation: Code And Development</b>    | <b>9</b>  |
| 4.1 Steps Toward Implementation . . . . .                | 9         |
| 4.1.1 Drawing Together The Theory . . . . .              | 9         |
| 4.1.2 Initial Configuration . . . . .                    | 9         |
| 4.1.3 Trajectory Generation Loops . . . . .              | 9         |
| 4.1.4 Post-Simulation Data Analysis . . . . .            | 9         |
| 4.2 Code Origin and Inspiration . . . . .                | 9         |
| <b>5 Application of Code to a Lennard-Jones liquid</b>   | <b>10</b> |
| 5.1 Total Energy in Plots . . . . .                      | 10        |

|          |                                                                    |           |
|----------|--------------------------------------------------------------------|-----------|
| 5.2      | Numerical Analysis . . . . .                                       | 10        |
| 5.2.1    | Radial Distribution Function . . . . .                             | 10        |
| 5.2.2    | Mean-Squared Displacements . . . . .                               | 10        |
| 5.2.3    | Diffusion Coefficients . . . . .                                   | 10        |
| <b>6</b> | <b>Conclusions, Findings, Prospectives</b>                         | <b>11</b> |
| <b>7</b> | <b>Bibliography</b>                                                | <b>12</b> |
| <b>A</b> | <b>Approximation of Pi in Python, Using Monte Carlo Techniques</b> | <b>14</b> |
| <b>B</b> | <b>Approximation of Pi in Python, Code Outputs</b>                 | <b>16</b> |
| <b>C</b> | <b>Lennard-Jones Potential, Simple Plot in Python</b>              | <b>17</b> |
| <b>D</b> | <b>Jensen's Inequality</b>                                         | <b>18</b> |
| <b>E</b> | <b>Monte Carlo C++ Code</b>                                        | <b>19</b> |
| <b>F</b> | <b>Data Analysis R Code</b>                                        | <b>24</b> |
| <b>G</b> | <b>Particle Energy Data</b>                                        | <b>25</b> |
| <b>H</b> | <b>Coordinate Data for Radial Distribution Function</b>            | <b>34</b> |

## List of Tables

|   |                                                        |   |
|---|--------------------------------------------------------|---|
| 1 | <b>Linear Congruential Generator Example</b> . . . . . | 3 |
|---|--------------------------------------------------------|---|

## List of Figures

|   |                                                 |    |
|---|-------------------------------------------------|----|
| 1 | <b>Lennard-Jones Potential Plot</b> . . . . .   | 6  |
| 2 | <b>Lennard-Jones Potential Sketch</b> . . . . . | 7  |
| 3 | <b>Periodic Boundary Conditions</b> . . . . .   | 8  |
| 4 | <b>Total Energy of Simulation</b> . . . . .     | 10 |

# 1 Development Of Computer Simulation Methods

The first concepts of Monte Carlo simulations can be found in the 18th century, contained within a report found in the 1733 edition of 'Histoire de L'Académie Royale des Sciences'. This report - created by Georges Louis Leclerc, Comte de Buffon - makes mention of an approximation of  $\pi$  by throwing needles or rods atop a floor of boards, measuring the fractions that fell on a single board. Of course, this can be recreated in the modern day by a simulation of approximating  $\pi$  using many points (see Appendices A and B). When initially proposed in this report, the field of Monte Carlo methods had not been distinctly named or partitioned (Landau & Binder 2021).

## 1.1 The Manhattan Project

### 1.1.1 Background Context

Before understanding Monte Carlo Methods we are bound to mention **The Manhattan Project**. The top-secret research and development program was the first to produce Nuclear Weapons, and was a key playing card in the context of the greater geopolitical climate: World War II.

Funded by nations such as the UK, Canada and, majorly, the USA, the Manhattan Project is often cited as a turning point in human history. One of the sites of the project was Los Alamos, New Mexico - tied intimately with the birth of Monte Carlo methods. Disregarding moral arguments concerning atomic weaponry, a large factor in the awe of the project was the pure advancement in scientific knowledge - building upon previous discoveries of fission.

### 1.1.2 Stanisław Ulam

Stanisław Ulam was prominent in contributing to the founding of Monte Carlo Methods as a designated methodology, during and after his involvement in The Manhattan Project. Famously, Ulam thought up the concept while recovering in a hospital from surgery. He had been playing solitaire to pass the time and wondered whether the probability of success could be estimated statistically. Rather than approaching the problem from a combinatorial approach (which he had already tried and found unsuccessful) he began to think more 'abstractly' - he had realised that he could simply observe successive games and note outcomes. Crucially for Stanisław Ulam, this could be extended to many simulated trials with the recent advent of computers - which would yield increasingly accurate estimates (Eckhardt 1987).

### 1.1.3 Subsequent Developments

The link between Ulam's proposed ideas and the following adoption of the statistical approach was a man named John Von Neumann. Perhaps most well-known for his invention of the aptly named Von Neumann architecture (in which programs are stored within a computer much like the data these programs use), he provided the link to the ENIAC - the world's first programmable, electronic digital computer. Von Neumann's computations, refined together with colleagues at Los Alamos laboratory, became the first calculations run on the ENIAC after it had been upgraded to a stored-program paradigm. Nowadays, the computer industry has grown exponentially, and though statistical sampling had already been used in the past, Ulam's thoughts paved the way for the Monte Carlo method to dominate complex statistical problems (Summerscales 2023).

## 2 Monte Carlo Methods

Having mentioned the basic, essential history, what are Monte Carlo methods, really?

To boil the concept down to its fundamentals, they are simulations and experiments that use randomness in order to solve complex problems. These problems can manifest in different ways, from integrals to systems of equations. Although numerical solutions and standard approximations may yield more exact or precise answers, Monte Carlo methods offer a viable alternative for large dimensionality of integrals and sparse systems of equations, which can often be solved more effectively in terms of cost and time.

### 2.1 Pseudo-Random Number Generators

Random number generation is an important part of Monte Carlo methods. There are multiple different methods to obtaining random numbers, but the algorithms we are focusing on within this report are called **Pseudo-Random Number Generators** (PRNGs). While they do not generate 'actual' random numbers, what they generate is sufficient enough in variability that it can be used in scenarios where random numbers are needed.

The way that they achieve this is through the use of mathematical formulae, varying in levels of complexity. The algorithms can get increasingly elaborate, yet the simplest can consist of only a few lines of code utilising basic mathematical arithmetic. Sequences are generated which attempt to approximate random numbers, based on an initial starting *seed*, and these sequences will eventually repeat after their *period*. For satisfactory generators, these periods will be sufficiently long enough that the repetitions are often unreachable by realistic samples (Gentle 2003).

While humans can not predict the next number in the sequences that are generated, this is not perfectly computationally secure. This is because if the initial *seed state* is known, an identical sequence can be reproduced. Therefore, the sequences are deterministic and not as unpredictable as systems with true chaos built into them - such as radioactive atom decay, or, famously, *Cloudflare's* wall of lava lamps (Liebow-Feeser 2017).

#### 2.1.1 The Linear Congruential Generator (LCG)

One such example of a PRNG, albeit possibly the simplest one, is the Linear Congruential Generator given in the following form:

$$x_i \equiv (ax_{i-1} + c) \bmod m$$

As can be seen, the equation consists of a simple linear function followed by a modular reduction. Although this may not produce sufficiently long streams of random numbers, and the numbers may not appear to be very random themselves, the Linear Congruential Generator and its alternative forms create the basis of many more powerful PRNGs. These alternative forms are built by modifying certain elements, for example setting  $c = 0$  (yielding something known as the Multiplicative Congruential Generator)

Here,

- $a$  is called the 'multiplier'
- $c$  is called the 'increment'

- $m$  is called the ‘modulus’.

The seed for this generator is the initial value supplied, which is to say  $x_0$ . Due to the modular reduction that occurs, there can only be  $m$  possible values that  $x$  can take; The maximum period of the LCG is, by definition,  $m$  (Gentle 2003).

### 2.1.2 Linear Congruential Generator Example

Following is an example of a LCG displayed in a ‘truth table’, allowing the process to be broken down into small, simple, and visible steps. Traditionally, values of  $m$  are usually a power of 2 as this is easier for the computer to use during calculation. Due to this, I have chosen  $m = 2^5 = 32$  which is smaller than a typical usecase. The other values that this LCG will take are  $a = 5$ ,  $c = 7$ ,  $X_0 = 19$ , which have been arbitrarily selected.

Table 1: Linear Congruential Generator Example

| $aX_n$           | $+ c$             | $(\text{mod } m)$      | $= X_{n+1}$ |
|------------------|-------------------|------------------------|-------------|
| $(5 * 19) = 95$  | $(95 + 7) = 102$  | $102 (\text{mod } 32)$ | $= 6$       |
| $(5 * 6) = 30$   | $(30 + 7) = 37$   | $37 (\text{mod } 32)$  | $= 5$       |
| $(5 * 5) = 25$   | $(25 + 7) = 32$   | $32 (\text{mod } 32)$  | $= 0$       |
| $(5 * 0) = 0$    | $(0 + 7) = 7$     | $7 (\text{mod } 32)$   | $= 7$       |
| $(5 * 7) = 35$   | $(35 + 7) = 42$   | $42 (\text{mod } 32)$  | $= 10$      |
| $(5 * 10) = 50$  | $(50 + 7) = 57$   | $57 (\text{mod } 32)$  | $= 25$      |
| $(5 * 25) = 125$ | $(125 + 7) = 132$ | $132 (\text{mod } 32)$ | $= 4$       |

From the table, we can see that for the Linear Congruential Generator  $5X_n + 7 \pmod{32}$ , the starting seed of  $X_0 = 19$  provides a sequence of: 6, 5, 0, 7, 10, 25, 4, ...

Following this, the sequence continues until it starts to repeat, having a period of 32 (the value of  $m$ , as stated earlier). The full sequence in its entirety is:

19, 6, 5, 0, 7, 10, 25, 4, 27, 14, 13, 8, 15, 18, 1, 12, 3, 22, 21, 16, 23, 26, 9, 20, 11, 30, 29, 24, 31, 2, 17, 28, 19, ...

### 2.1.3 The Mersenne Twister

The Mersenne Twister is a more complex, modern PRNG family, developed initially in 1997 (Matsumoto & Nishimura 1998).

It derives its name from a prime number known as a Mersenne Prime, which contributes to its period. As its period is sufficiently large, the algorithm is highly optimised, and the numbers generated have low correlations, the Mersenne Twister is a prominent PRNG that is used across industry. Most notably, it is used in scientific simulations (Monte Carlo methods, as discussed) but also within Machine Learning, statistical sampling and also video game graphics (Samadov 2024).

As, arguably, the most widely used PRNG in the modern day, the Mersenne Twister can be found in many software libraries for standard random generation. These include, but are not limited to, Python, Ruby, and R. One of its multiple variant forms can be used in C++ through `std::mt19937` in the standard library. Due to these occurrences, it is highly likely that within code used in this report (found in the Appendices), the Mersenne Twister is the PRNG that has contributed random elements. For this reason, my C++ simulation (see Appendix E) has employed the use of the mentioned Mersenne Twister.

## 2.2 Sampling Methodology

By 'Sampling Methodology', we refer to the way in which Monte Carlo methods are used to sample data points (selections to be resampled within subsequent analysis). Depending on the context and scenario, different qualities may be prioritised, and this is reflected in the different ways that sampling can occur (Brownlee 2019).

The 'Law of Large Numbers' plays a significant part in these simulations as that allows the sampling that occurs to form a relevant distribution, despite the initial data being random.

### 2.2.1 Simple Sampling

Simple sampling, also called a 'crude monte carlo', is the most direct and rudimentary method of using monte carlo sampling techniques. This entails the collection of completely random observations of a random variable. The aforementioned reliance on the law of large numbers leads to a large enough sample size so that an estimate of the expected value ( $E[X]$ ) can be found (Simple Sampling 2010).

To see the way that simple sampling works, we can base an example upon the integral of a collected distribution. If a one-dimensional integral  $I$ , where  $I = \int_a^b dx f(x)$ , were to be re-written as:

$$I = (b - a) \langle f(x) \rangle,$$

this would represent the unweighted average of  $f(x)$  over the interval  $[a, b]$ . As this average is evaluated, larger and larger distributions, tending to infinity, yield a correct value of  $I$  (Frenkel & Smit 1996).

An example of this 'crude monte carlo' method can be found in the approximation of Pi mentioned earlier (see Appendices A and B), where uniform and random coordinates are generated within the given square. This results in a calculated average for the value of Pi. This sampling methodology can fall short due to its reliance on randomness; If random values fell unusually within negligible or heavily influencing areas, the final results of a monte carlo sample can be inaccurate - rendering the process inefficient.

### 2.2.2 Importance

Like Simple sampling, Importance sampling is a method of sampling for data values over an interval, however what sets Importance sampling apart is the addition of weighted 'importance' to certain selected values (hence the name given to the technique). This is achieved through the introduction of a new weight term which we will designate as  $p(x)$ . This function is commonly known as the '*importance function*'.

Fulfilling a key objective of sampling in the first place, this leads to the variation being reduced to either insignificant levels or, at best, zero in areas where the distribution may not be relevant to draw samples from.

Representing the probability density over a dimension,  $D$ , this importance function can be introduced into our earlier estimated integral, making sure  $p(x)$  is carefully chosen to minimise variance:

$$\int_D \frac{f(x)}{p(x)} p(x) dx$$

Variation, with respect to the distribution of  $X$  with density  $p(x)$ , is, hence, given by:

$$V\left(\frac{f(X)}{p(X)}\right) = \left[E\left(\frac{f^2(X)}{p^2(X)}\right)\right] - \left[E\left(\frac{f(X)}{p(X)}\right)\right]^2$$

where  $\left[E\left(\frac{f(X)}{p(X)}\right)\right]^2$  is actually equal to  $\left(\int_D f(x) dx\right)^2$ , suggesting that only the first expression in the Variance formula has any significant effect on the importance sample.

By Jensen's inequality (see Appendix D for theorem and proof via (Wasserman 2004)), there is a lower bound on this first term. This looks like:

$$\begin{aligned} E\left(\frac{f^2(X)}{p^2(X)}\right) &\geq \left(E\left(\frac{|f(X)|}{p(X)}\right)\right)^2 \\ &= \left(\int_D |f(x)| dx\right)^2 \end{aligned}$$

This is where it is important to select a correct  $p(x)$ . This bound we have shown is achieved when

$$p(x) = \frac{|f(x)|}{\int_D |f(x)| dx},$$

but this is futile when we're considering a monte carlo estimate (and do not know the integral necessarily) - therefore we seek to choose  $p$  nearly proportional to  $|f|$ . Ultimately, it is preferable for  $\frac{|f(x)|}{p(x)}$  to be nearly constant (Gentle 2003) as this allows variance to, as stated previous, "vanish altogether" (Frenkel & Smit 1996).

## 2.3 Statistical Mechanics

In order to understand working with particles, and simulations of them, statistical mechanics plays a pivotal part. Within this field, matters of concern include '**macrostates**' and '**microstates**'. Statistical mechanics serves as the bridge connecting microscopic particle behaviour to observable macroscopic properties. A microstate represents a specific, highly detailed configuration of the system at a frozen point in time, such as the exact spatial coordinates of all particles in a liquid simulation. By contrast, a macrostate describes the overall thermodynamic condition of the system, defined by fixed properties (Greiner et al. 1995).

A system at thermal equilibrium would not visit every possible microstate with equal probability. Instead, the probability  $P(x)$  of finding the system in a specific microstate  $x$  with energy  $E(x)$  is proportional to its Boltzmann weight:

$$P(\mathbf{x}) \propto \exp(-\beta E(\mathbf{x}))$$

where  $\beta = 1/k_B T$ , and  $k_B$  is the Boltzmann constant. By generating a sample of microstates that follow this distribution, we can accurately calculate macroscopic thermodynamic averages without needing to evaluate the complex, and often computationally impossible, partition function (Saxena 2016).

## 2.4 The Metropolis Method

The Metropolis method is an application of importance sampling of system states. Rather than picking completely random configurations, which would likely result in particle overlaps and infinite energies, the algorithm targets configurations with high Boltzmann probabilities.

To ensure the simulation produces a true representation of thermal equilibrium without systematic bias, the transition between states must satisfy the condition of detailed balance. This principle states that the rate of transitioning from an old state  $i$  to a new state  $j$  must exactly equal the reverse transition rate:

$$P_i W_{i \rightarrow j} = P_j W_{j \rightarrow i}$$

where  $P_i$  is the Boltzmann probability of state  $i$ , and  $W_{i \rightarrow j}$  is the underlying transition probability.

We can split this transition probability into two components: the probability of proposing the move,  $q_{i \rightarrow j}$ , and the probability of accepting it,  $A_{i \rightarrow j}$ . Substituting this into the detailed balance equation gives:

$$P_i q_{i \rightarrow j} A_{i \rightarrow j} = P_j q_{j \rightarrow i} A_{j \rightarrow i}$$

By choosing a symmetric proposal distribution—meaning the chance of proposing a random spatial shift from  $i$  to  $j$  is the same as proposing a shift from  $j$  to  $i$  ( $q_{i \rightarrow j} = q_{j \rightarrow i}$ )—the proposal probabilities cancel out. Rearranging the remaining terms yields the ratio of acceptance probabilities:

$$\frac{A_{i \rightarrow j}}{A_{j \rightarrow i}} = \frac{P_j}{P_i} = \exp(-\beta(E_j - E_i))$$

To satisfy this ratio, the Metropolis choice for the acceptance probability is defined as:

$$A_{i \rightarrow j} = \min(1, \exp(-\beta(E_j - E_i)))$$

(Frenkel & Smit 1996, Landau & Binder 2021).

### 3 The Lennard-Jones Potential

#### 3.1 A Description

The Lennard-Jones potential describes the potential energy of two non-bonded particles based on their distance of separation. The equation accounts for both attractive forces and repulsive forces.

The equation is given as follows

$$V(r) = 4\varepsilon \left[ \left( \frac{\sigma}{r} \right)^{12} - \left( \frac{\sigma}{r} \right)^6 \right]$$

where:

- $V$  indicates the intermolecular potential between particles,
- $\varepsilon$  is the well depth: the maximum strength of attractive force and minimum energy value
- $\sigma$  is referred to as the '**van der Waals**' radius, and is a measure of how close two nonbonding particles can get. It measures the distance at which the intermolecular potential between the two particles is zero.
- $r$  indicates distance of separation between both particles, measured from the center of each.

The  $\sigma/r^{12}$  term models strong, short-range repulsion and the  $\sigma/r^6$  term models long-range van der Waals attraction.

Sometimes the potential can be rearranged and expressed alternatively as

$$V(r) = \frac{A}{r^{12}} - \frac{B}{r^6}$$

in which  $A, B$  are equal to  $4\varepsilon\sigma^{12}, 4\varepsilon\sigma^6$  respectively (*Lennard-Jones Potential* 2025).

##### 3.1.1 Displaying The Potential Visually

The Lennard-Jones plot can be shown in a graphical manner, representing the various elements of the equation, as described earlier. Setting  $\sigma, \varepsilon = 0$ , for simplicities sake, generates the following graph, programmed in python (see Appendix C) using, primarily, the matplotlib library (Hunter 2007).




Figure 1: **Lennard-Jones Potential Plot**

In order to facilitate the showcasing of more details on certain parts of the graph, there is also a physical sketch included below. This highlights where certain variables come into play in different parts of the plot, such as  $\sigma$  and  $\epsilon$ , alongside the repulsion and attraction aspects.




Figure 2: Lennard-Jones Potential Sketch

### 3.1.2 Applications in Modelling Simple Liquids

A 'Simple liquid' within statistical mechanics refers to

When modelling simple liquid simulations, the Lennard-Jones potential is relevant because

### 3.2 Periodic Boundary Conditions

Boundary conditions help to define how a simulation may handle particles within a system. Periodic boundary conditions, in particular, aid in abstracting a small simulation of particles so that it seems like they are interacting within an infinite system. This is done by letting particles cross over the boundaries of the simulation and into identical neighbouring 'cells', i.e cells are tiled infinitely and particles leaving the cell re-enter through the opposite face which can be seen in **Figure 3** (Katiyar & Jha 2018). This allows a much larger system to be simulated with a smaller computational load (as the simulation only really has fewer particles that are replicated and extrapolated).




Figure 3: **Periodic Boundary Conditions**

When calculating the interaction energy between a Particle A and Particle B, program code would not just look at a single simple distance. Rather, Particle B and all of its infinite '**periodic images**' (the clones in the adjacent cells) would be considered. The simulation would then calculate the distance to whichever image is physically closest to Particle A. This ensures that particles near the boundary of the primary box correctly interact with the fluid surrounding them.

## 4 Monte Carlo Simulation: Code And Development

### 4.1 Steps Toward Implementation

#### 4.1.1 Drawing Together The Theory

In order for correct implementation of the code, all of this theory needs to be drawn together appropriately.

Some of these concepts are built into the software that I am programming with, such as PRNGs, they are very commonly present in random functions that are found in code libraries. As such is the case, I will be using an inbuilt Mersenne Twister within my program code.

The Lennard-Jones potential, previously mentioned, will be used within the code in order for calculations to be taken on particle distances and repulsions. This will be hard-coded in.

#### 4.1.2 Initial Configuration

Mersenne Twister seed is 32005096

#### 4.1.3 Trajectory Generation Loops

Regarding the Metropolis method, the derivation found in 2.4 (on page 5) translates into a straightforward algorithmic loop. A particle is randomly selected and given a small trial displacement. The change in energy,  $\Delta E = E_j - E_i$ , is calculated. If  $\Delta E < 0$ , the acceptance probability evaluates to 1, and the move is automatically accepted. If  $\Delta E > 0$ , the move is accepted conditionally by comparing the Boltzmann weight  $\exp(-\Delta E/T)$  (using reduced units where  $k_B = 1$ ) against a generated pseudo-random number. This occasional acceptance of uphill energy moves allows the system to escape local energy minima and accurately sample the phase space.

#### 4.1.4 Post-Simulation Data Analysis

### 4.2 Code Origin and Inspiration

My code was built on a framework of **Fortran** code from 'Understanding Molecular Simulation' by Daan Frenkel and Berend Smit (Frenkel & Smit 1996). Another Monte Carlo simulation of the Lennard-Jones model (Kelter et al. 2015), packaged within a library known as NetLogo (Wilensky 1999), also provided much guidance and inspiration. These were adapted and rewritten from scratch, by me, into **C++**. My program can be found in the appendix of this report (see Appendix E).

## 5 Application of Code to a Lennard-Jones liquid

### 5.1 Total Energy in Plots

A placeholder for a plot showing the total energy of the simulation. The plot area is currently blank.

Figure 4: Total Energy of Simulation

### 5.2 Numerical Analysis

#### 5.2.1 Radial Distribution Function

#### 5.2.2 Mean-Squared Displacements

#### 5.2.3 Diffusion Coefficients

## **6 Conclusions, Findings, Prospectives**

## 7 Bibliography

- Brownlee, J. (2019), 'A gentle introduction to monte carlo sampling for probability', <https://machinelearningmastery.com/monte-carlo-sampling-for-probability/>.
- Eckhardt, R. (1987), 'Stan Ulam, John von Neumann, and the Monte Carlo Method', *Los Alamos Science* (15), 131–141. Also: Los Alamos National Laboratory Tech. Report LA-UR-88-9068.  
**URL:** <https://permalink.lanl.gov/object/tr?what=info:lanl-repo/lareport/LA-UR-88-9068>
- Frenkel, D. & Smit, B. (1996), *Understanding Molecular Simulation: From Algorithms to Applications*, Academic Press.
- Gentle, J. E. (2003), *Random Number Generation and Monte Carlo Methods*, second edn, Springer.
- Greiner, W., Neise, L. & Stöcker, H. (1995), *Thermodynamics and Statistical Mechanics*, Springer. Translated from the German by Dirk Rischke.
- Hunter, J. D. (2007), 'Matplotlib: A 2d graphics environment', *Computing in Science & Engineering* **9**(3), 90–95.
- Katiyar, R. & Jha, P. (2018), 'Molecular simulations in drug delivery: Opportunities and challenges', *Wiley Interdisciplinary Reviews: Computational Molecular Science* **8**, e1358.
- Kelter, J., Luijten, E. & Wilensky, U. (2015), 'Netlogo monte carlo lennard-jones model', <http://ccl.northwestern.edu/netlogo/models/MonteCarloLennard-Jones>.
- Kopka, H. & Daly, P. W. (1999), *A Guide to LaTeX*, third edn, Pearson Education.
- Landau, D. P. & Binder, K. (2021), *A Guide to Monte Carlo Simulations in Statistical Physics*, fifth edn, Cambridge University Press.
- Lennard-Jones Potential* (2025). [Online; accessed 2026-04-22].
- Liebow-Feaser, J. (2017), 'Randomness 101: Lavarand in production', <https://blog.cloudflare.com/randomness-101-lavarand-in-production/>.
- Matsumoto, M. & Nishimura, T. (1998), 'Mersenne twister: a 623-dimensionally equidistributed uniform pseudo-random number generator', **8**(1).  
**URL:** <https://doi.org/10.1145/272991.272995>
- Metcalfe, T. (2023), 'What was the manhattan project?', *Scientific American*.
- Samadov, I. (2024), 'The mersenne twister algorithm. a deep dive into a pseudo-random number generator', *Medium*.
- Saxena, A. K. (2016), *An Introduction to Thermodynamics and Statistical Mechanics*, second edn, Alpha Science International, Limited, 2016.
- Sharma, V. (2023), 'Estimating pi using monte carlo methods', <https://medium.com/the-modern-scientist/estimating-pi-using-monte-carlo-methods-dbf26c888d6>.
- Simple Sampling* (2010), Lecture Slides for EG2080 Monte Carlo Methods in Engineering.  
**URL:** <https://www.kth.se/social/upload/50bf16b7f276547633d8a01b/Theme%203%20-%20Simple%20Sampling.pdf>
- Summerscales, O. (2023), 'Hitting the jackpot: The birth of the monte carlo method', <https://www.lanl.gov/media/publications/actinide-research-quarterly/1123-hitting-the-jackpot-the-birth-of-the-monte-carlo-method>.

Wang, C. (2018), Applications of Monte Carlo Methods in Studying Polymer Dynamics, PhD thesis, University of Reading.

Wasserman, L. A. (2004), *All of Statistics: A Concise Course in Statistical Inference. Springer Texts in Statistics*, Springer.

Wilensky, U. (1999), 'Netlogo', <http://ccl.northwestern.edu/netlogo/>.

## A Approximation of Pi in Python, Using Monte Carlo Techniques

ApproximationOfPi/src/python/SimpleImplementation.py

```
#!/ python3
"""
Simple implementation of approximation of pi.

Steps:
Generate random x, y inside centre of square of side 2
Repeat steps for a large number of points
Calculate ratio of points
Multiply by 4 (pi / 4)
"""

import numpy as np

def estimatePi(samples):
    insideCircle = 0
    for i in range(samples):
        x = np.random.uniform(-1, 1)
        y = np.random.uniform(-1, 1)

        if (x**2 + y**2) <= 1:
            insideCircle += 1
    ratio = insideCircle / samples
    return (ratio * 4)

if __name__ == "__main__":
    print(f"Estimate with 1 Sample:\n{estimatePi(1)}\n")
    print(f"Estimate with 10 Sample:\n{estimatePi(10)}\n")
    print(f"Estimate with 50 Sample:\n{estimatePi(50)}\n")
    print(f"Estimate with 100 Sample:\n{estimatePi(100)}\n")
    print(f"Estimate with 1000 Sample:\n{estimatePi(1_000)}\n")
    print(f"Estimate with 10,000 Sample:\n{estimatePi(10_000)}\n")
    print(f"Estimate with 1,000,000 Sample:\n{estimatePi(1_000_000)}\n")
```

ApproximationOfPi/src/python/GraphicalRepresentation.py

```
#!/ python3
"""
Graphical representation of approximation of Pi using Monte Carlo methods.
"""

import matplotlib.pyplot as plt
import numpy as np

from SimpleImplementation import estimatePi

def main():
    samples = int(input("Enter Intended Samples:\n"))

    x = np.random.uniform(-1, 1, samples)
    y = np.random.uniform(-1, 1, samples)

    plt.plot(x, y, ".k", markersize = 1)
```

```
t = np.linspace(0, 2 * np.pi, 400)
xc = np.cos(t)
yc = np.sin(t)
plt.plot(xc, yc, 'r-', linewidth=1)
plt.gca().set_aspect('equal', adjustable='box')

plt.xlim(-1.1, 1.1)
plt.ylim(-1.1, 1.1)
plt.xlabel("x")
plt.ylabel("y")

plt.suptitle(f"Estimate of Pi: {estimatePi(samples)}", fontsize = 18)
plt.title("Graphical Representation Is Independent To Estimate Calculation",
          fontsize = 10)
plt.show()


if __name__ == "__main__":
    main()
```

## B Approximation of Pi in Python, Code Outputs

```
Estimate with 1 Sample:  
4.0  
  
Estimate with 10 Sample:  
3.2  
  
Estimate with 50 Sample:  
2.96  
  
Estimate with 100 Sample:  
3.04  
  
Estimate with 1000 Sample:  
3.104  
  
Estimate with 10,000 Sample:  
3.1376  
  
Estimate with 1,000,000 Sample:  
3.143152
```

**Estimate of Pi: 3.152**

Graphical Representation Is Independent To Estimate Calculation



## C Lennard-Jones Potential, Simple Plot in Python

LennardJonesPotential/src/LennardJonesPotential.py

```
#!/ Python3
"""
Lennard-Jones potential plotted in Matplotlib
"""
import numpy as np
import matplotlib.pyplot as plt
from typing import final

def main():
    r = np.linspace(0, 3.0, 1000)
    SIGMA: final = 1.0
    EPSILON: final = 1.0
    V = 4 * EPSILON * ((SIGMA/r)**12 - (SIGMA/r)**6)

    plt.plot(r, V)

    plt.ylim(-1.2, 2)
    plt.xlim(0.9, 3)
    plt.grid(True)
    plt.ylabel("Potential Energy (V)")
    plt.xlabel("Particle Distance (r)")

    plt.show()

if __name__ == "__main__":
    main()
```

## D Jensen's Inequality

**4.9 Theorem** (Jensen's inequality). *If  $g$  is convex, then*

$$\mathbb{E}g(X) \geq g(\mathbb{E}X). \quad (4.6)$$

*If  $g$  is concave, then*

$$\mathbb{E}g(X) \leq g(\mathbb{E}X). \quad (4.7)$$

PROOF. Let  $L(x) = a + bx$  be a line, tangent to  $g(x)$  at the point  $\mathbb{E}(X)$ . Since  $g$  is convex, it lies above the line  $L(x)$ . So,

$$\mathbb{E}g(X) \geq \mathbb{E}L(X) = \mathbb{E}(a + bX) = a + b\mathbb{E}(X) = L(\mathbb{E}(X)) = g(\mathbb{E}X). \quad \blacksquare$$

From Jensen's inequality we see that  $\mathbb{E}(X^2) \geq (\mathbb{E}X)^2$  and if  $X$  is positive, then  $\mathbb{E}(1/X) \geq 1/\mathbb{E}(X)$ . Since  $\log$  is concave,  $\mathbb{E}(\log X) \leq \log \mathbb{E}(X)$ .

via (Wasserman 2004)

## E Monte Carlo C++ Code

ParticleSimulation/src/main.cpp

```
#include <iostream>
#include <vector>
#include <cmath>
#include <cstdlib>
#include <string>
#include <random>
#include <fstream>

// To simulate position of particles
struct Position {
    double x, y;
};

const std::string csvTracking_FilePath = "C:\\Users\\rajam\\OneDrive - University of Reading\\THIRD YEAR\\PPR\\Numerical-simulation-methods-and-their-applications\\ParticleSimulation\\data\\energy_data.csv";
const std::string rdfTracking_FilePath = "C:\\Users\\rajam\\OneDrive - University of Reading\\THIRD YEAR\\PPR\\Numerical-simulation-methods-and-their-applications\\ParticleSimulation\\data\\rdf_histogram.csv";

// Random Number Generation (Mersenne Twister)
// Using a seed of "32005096" for reproducibility

// std::random_device rd; // Random seed used during programming and testing
std::mt19937 gen(32005096);
std::uniform_real_distribution<double> uniform_dist(0.0, 1.0);

int initialisation(int NumParticles, double Density, std::vector<Position>& particles, double& box_length) {

    // Calculation of the simulation box length
    // Density ( $\rho$ ) =  $N / \text{Area}$ . Therefore,  $\text{Area} = N / \text{Density}$ .
    // The length of one side of a square is the square root of its area.
    box_length = std::sqrt(NumParticles / Density);

    // Determining lattice size and spacing
    int n_cells = std::ceil(std::sqrt(NumParticles));
    double spacing = box_length / n_cells;

    // Looping through the grid and place particles
    int p = 0; // Particle counter

    for (int x = 0; x < n_cells; ++x) {
        for (int y = 0; y < n_cells; ++y) {

            // Only place a particle if NumParticles not yet reached
            if (p < NumParticles) {
                Position new_pos;
                new_pos.x = (x + 0.5) * spacing;
                new_pos.y = (y + 0.5) * spacing;

                particles.push_back(new_pos);
                p++;
            }
        }
    }
}
```

```

    }
}

std::cout << "Initialization complete. Placed " << particles.size() << "
particles.\n";
return 0;
}

double calc_energy(int idx, const std::vector<Position>& particles, double
box_length) {
    // Calculation of a Particle's Energy
    double energy = 0.0;
    double rc2 = 6.25; // Cutoff radius squared (2.5 * 2.5)

    for (int i = 0; i < particles.size(); ++i) {
        if (i == idx) continue; // prevent self-interaction of a particle

        // Calculate 2D distance components
        double dx = particles[idx].x - particles[i].x;
        double dy = particles[idx].y - particles[i].y;

        // Periodic Boundary Conditions (Minimum Image Convention)
        dx -= box_length * std::round(dx / box_length);
        dy -= box_length * std::round(dy / box_length);

        double r2 = dx*dx + dy*dy;

        // Lennard-Jones Potential Calculation (only if within cutoff)
        if (r2 < rc2) {
            double r6_inv = 1.0 / (r2 * r2 * r2);
            energy += 4.0 * (r6_inv * r6_inv - r6_inv);
        }
    }
    return energy;
}

// Test initial energy
double calc_total_energy(const std::vector<Position>& particles, double
box_length) {
    double total_energy = 0.0;
    for (int i = 0; i < particles.size(); ++i) {
        total_energy += calc_energy(i, particles, box_length);
    }
    // Divide by 2 to account for pairs
    return total_energy / 2.0;
}

void mcmove(std::vector<Position>& particles, double box_length, double Temp,
double max_disp, int& accepted_moves) {

    // Picking a random particle uniformly
    std::uniform_int_distribution<int> particle_dist(0, particles.size() - 1);
    int idx = particle_dist(gen);

    // Calculation of particle energy in current state
    double e_old = calc_energy(idx, particles, box_length);

```

```

    // Saving old position in case of rejection
    Position old_pos = particles[idx];

    // Random displacement proposition
    particles[idx].x += (uniform_dist(gen) - 0.5) * max_disp;
    particles[idx].y += (uniform_dist(gen) - 0.5) * max_disp;

    // PBC
    particles[idx].x -= box_length * std::floor(particles[idx].x / box_length);
    particles[idx].y -= box_length * std::floor(particles[idx].y / box_length);

    // Energy calculation in proposed new state
    double e_new = calc_energy(idx, particles, box_length);
    double delta_e = e_new - e_old;

    // Metropolis Acceptance Criteria
    // If delta_e negative, condition is true, accepted
    // If delta_e positive, Boltzmann probability checked
    if (delta_e < 0.0 || uniform_dist(gen) < std::exp(-delta_e / Temp)) {
        accepted_moves++; // Move accepted, particle stays
    } else {
        particles[idx] = old_pos; // Move rejected, og position restored
    }
}

void simulate_withTracking(int Cycles, int NumParticles, std::vector<Position>&
particles, double box_length, double Temp, double max_disp, int&
accepted_moves) {

    std::ofstream outfile(csvTracking_FilePath);
    outfile << "Cycle,TotalEnergy\n";

    // Setup for RDF Histogram variables
    int num_bins = 100;
    double max_r = box_length / 2.0; // Max radius to measure is half the box
    double bin_width = max_r / num_bins;
    std::vector<double> rdf_histogram(num_bins, 0.0);
    int rdf_samples = 0;

    std::cout << "Running " << Cycles << " MC cycles and writing data files...\n";

    for (int c = 0; c < Cycles; ++c) {
        for (int i = 0; i < NumParticles; ++i) {
            mcmmove(particles, box_length, Temp, max_disp, accepted_moves);
        }

        // Data Sampling (Every 10 cycles)
        if (c % 10 == 0) {
            double current_energy = calc_total_energy(particles, box_length);
            outfile << c << "," << current_energy << "\n";

            // RDF Sampling
            rdf_samples++;
            for (int i = 0; i < NumParticles - 1; ++i) {
                for (int j = i + 1; j < NumParticles; ++j) {

                    double dx = particles[i].x - particles[j].x;

```

```

        double dy = particles[i].y - particles[j].y;

        // PBC for distance measurement
        dx -= box_length * std::round(dx / box_length);
        dy -= box_length * std::round(dy / box_length);

        double r = std::sqrt(dx*dx + dy*dy);

        if (r < max_r) {
            int bin = static_cast<int>(r / bin_width);
            rdf_histogram[bin] += 2.0; // +2 doubled pairs
        }
    }
}

outfile.close();

// Write to csv
std::ofstream rdf_file(rdfTracking_FilePath);
rdf_file << "Distance,Count\n";
for (int b = 0; b < num_bins; ++b) {
    double r_center = (b + 0.5) * bin_width;
    double average_count = rdf_histogram[b] / rdf_samples;
    rdf_file << r_center << "," << average_count << "\n";
}
rdf_file.close();

std::cout << "Data collection complete. Files closed successfully.\n";
}

int main() {
    // Variables
    double Temp = 1.0;
    int NumParticles = 150;
    double Density = 0.8;
    int Cycles = 5000;
    double max_disp = 0.25; // Maximum allowed distance a particle can jump in
                           // one step

    std::vector<Position> particles;
    double box_length = 0.0;

    // Initialisation
    initialisation(NumParticles, Density, particles, box_length);
    std::cout << "Initial System Energy: " << calc_total_energy(particles,
        box_length) << "\n\n";

    // Simulation running
    int accepted_moves = 0;
    int total_moves_attempted = NumParticles * Cycles;

    simulate_withTracking(Cycles, NumParticles, particles, box_length, Temp,
        max_disp, accepted_moves);

    // Final Output
    std::cout << "\nFinal System Energy: " << calc_total_energy(particles,

```

```
        box_length) << "\n";
    std::cout << "Acceptance Ratio: " << (double)accepted_moves /
        total_moves_attempted * 100.0 << "%\n";

    return 0;
}
```

## F Data Analysis R Code

ParticleSimulation/src/DataAnalysis.R

```
# Libraries
library(ggplot2)

# Setting Up Files

particle.Energy.file <- "ParticleSimulation/data/energy_data.csv"
particle.Energy <- read.csv(particle.Energy.file, header = T)
attach(particle.Energy)

plot()
```

## G Particle Energy Data

Cycle, TotalEnergy

```
0, -309.863
10, -250.463
20, -276.888
30, -266.705
40, -275.963
50, -286.343
60, -280.128
70, -286.2
80, -288.988
90, -300.878
100, -299.956
110, -303.117
120, -307.052
130, -323.478
140, -312.36
150, -318.273
160, -319.792
170, -308.859
180, -316.692
190, -317.261
200, -316.745
210, -309.549
220, -304.221
230, -321.301
240, -296.909
250, -324.022
260, -321.785
270, -311.376
280, -307.957
290, -309.199
300, -317.012
310, -305.181
320, -312.712
330, -315.21
340, -329.324
350, -321.849
360, -320.864
370, -302.365
380, -322.465
390, -329.645
400, -308.939
410, -307.363
420, -310.869
430, -315.431
440, -320.306
450, -321.074
460, -328.196
470, -330.333
480, -317.936
490, -313.588
500, -325.466
510, -320.619
520, -307.063
530, -317.328
```

540 , -296.76  
550 , -309.517  
560 , -302.638  
570 , -312.572  
580 , -293.174  
590 , -304.974  
600 , -304.327  
610 , -330.468  
620 , -315.034  
630 , -325.513  
640 , -305.149  
650 , -310.837  
660 , -324.098  
670 , -311.052  
680 , -302.015  
690 , -319.562  
700 , -335.832  
710 , -320.368  
720 , -310.707  
730 , -327.621  
740 , -313.159  
750 , -328.421  
760 , -319.265  
770 , -309.178  
780 , -328.638  
790 , -318.87  
800 , -322.21  
810 , -304.31  
820 , -313.333  
830 , -307.513  
840 , -313.908  
850 , -302.142  
860 , -314.494  
870 , -298.726  
880 , -320.295  
890 , -320.822  
900 , -332.109  
910 , -318.716  
920 , -314.697  
930 , -316.565  
940 , -313.842  
950 , -318.016  
960 , -316.259  
970 , -315.558  
980 , -319.875  
990 , -317.393  
1000 , -309.063  
1010 , -311.472  
1020 , -324.197  
1030 , -319.269  
1040 , -314.596  
1050 , -302.005  
1060 , -317.128  
1070 , -315.833  
1080 , -318.394  
1090 , -318.508  
1100 , -306.596  
1110 , -306.659

1120 , -331.974  
1130 , -329.031  
1140 , -324.626  
1150 , -299.916  
1160 , -298.273  
1170 , -312.958  
1180 , -313.553  
1190 , -329.846  
1200 , -338.984  
1210 , -320.508  
1220 , -331.609  
1230 , -319.349  
1240 , -317.006  
1250 , -324.334  
1260 , -320.881  
1270 , -313.739  
1280 , -325.287  
1290 , -327.587  
1300 , -317.702  
1310 , -321.26  
1320 , -323.917  
1330 , -331.188  
1340 , -327.117  
1350 , -312.976  
1360 , -318.256  
1370 , -319.052  
1380 , -311.245  
1390 , -322.148  
1400 , -327.235  
1410 , -324.689  
1420 , -336.015  
1430 , -317.947  
1440 , -321.573  
1450 , -321.723  
1460 , -323.086  
1470 , -304.707  
1480 , -319.432  
1490 , -299.354  
1500 , -319.962  
1510 , -327.366  
1520 , -315.366  
1530 , -317.398  
1540 , -326.445  
1550 , -315.802  
1560 , -319.74  
1570 , -321.106  
1580 , -317.094  
1590 , -308.931  
1600 , -311.079  
1610 , -305.941  
1620 , -323.453  
1630 , -316.195  
1640 , -323.535  
1650 , -328.689  
1660 , -323.818  
1670 , -326.871  
1680 , -321.967  
1690 , -329.877

1700 , -312.148  
1710 , -308.011  
1720 , -298.255  
1730 , -312.662  
1740 , -316.256  
1750 , -304.723  
1760 , -316.622  
1770 , -336.023  
1780 , -322.12  
1790 , -331.807  
1800 , -318.758  
1810 , -315.368  
1820 , -292.501  
1830 , -315.971  
1840 , -322.34  
1850 , -317.506  
1860 , -320.607  
1870 , -324.687  
1880 , -342.735  
1890 , -331.502  
1900 , -324.776  
1910 , -324.062  
1920 , -311.015  
1930 , -303.993  
1940 , -313.87  
1950 , -316.359  
1960 , -315.929  
1970 , -317.475  
1980 , -295.941  
1990 , -308.923  
2000 , -297.306  
2010 , -309.734  
2020 , -323.162  
2030 , -315.408  
2040 , -318.381  
2050 , -336.949  
2060 , -335.802  
2070 , -328.246  
2080 , -323.083  
2090 , -323.454  
2100 , -328.8  
2110 , -331.694  
2120 , -320.508  
2130 , -325.063  
2140 , -326.895  
2150 , -320.799  
2160 , -327.703  
2170 , -316.911  
2180 , -326.608  
2190 , -310.338  
2200 , -319.836  
2210 , -326.191  
2220 , -320.158  
2230 , -315.967  
2240 , -309.925  
2250 , -318.098  
2260 , -305.041  
2270 , -299.464

2280 , -331.416  
2290 , -331.392  
2300 , -317.243  
2310 , -327.297  
2320 , -323.094  
2330 , -330.132  
2340 , -302.836  
2350 , -317.668  
2360 , -321.584  
2370 , -310.991  
2380 , -310.848  
2390 , -313.787  
2400 , -327.081  
2410 , -299.219  
2420 , -310.098  
2430 , -318.669  
2440 , -326.369  
2450 , -324.172  
2460 , -312.708  
2470 , -322.238  
2480 , -301.415  
2490 , -314.715  
2500 , -301.305  
2510 , -313.547  
2520 , -310.881  
2530 , -320.661  
2540 , -311.7  
2550 , -308.41  
2560 , -314.527  
2570 , -318.09  
2580 , -316.161  
2590 , -323.155  
2600 , -311.717  
2610 , -316.676  
2620 , -329.388  
2630 , -320.669  
2640 , -331.389  
2650 , -307.671  
2660 , -307.439  
2670 , -321.606  
2680 , -313.992  
2690 , -308.618  
2700 , -322.725  
2710 , -304.091  
2720 , -314.403  
2730 , -305.576  
2740 , -303.511  
2750 , -307.99  
2760 , -300.635  
2770 , -322.913  
2780 , -328.805  
2790 , -316.923  
2800 , -320.393  
2810 , -320.515  
2820 , -311.524  
2830 , -310.39  
2840 , -296.771  
2850 , -323.386

2860 , -316.104  
2870 , -320.149  
2880 , -322.688  
2890 , -323.101  
2900 , -315.508  
2910 , -313.108  
2920 , -322.14  
2930 , -314.646  
2940 , -318.73  
2950 , -325.029  
2960 , -314.624  
2970 , -310.574  
2980 , -338.409  
2990 , -311.866  
3000 , -317.351  
3010 , -335.889  
3020 , -317.839  
3030 , -315.905  
3040 , -326.589  
3050 , -324.4  
3060 , -315.97  
3070 , -304.327  
3080 , -321.983  
3090 , -319.24  
3100 , -320.629  
3110 , -332.467  
3120 , -308.932  
3130 , -305.233  
3140 , -320.249  
3150 , -317.65  
3160 , -317.171  
3170 , -318.345  
3180 , -334.619  
3190 , -327.493  
3200 , -313.68  
3210 , -317.33  
3220 , -314.403  
3230 , -310.166  
3240 , -316.053  
3250 , -322.502  
3260 , -305.647  
3270 , -315.102  
3280 , -302.505  
3290 , -300.154  
3300 , -309.191  
3310 , -310.933  
3320 , -315.481  
3330 , -307.926  
3340 , -317.278  
3350 , -320.54  
3360 , -324.861  
3370 , -315.789  
3380 , -330.47  
3390 , -291.9  
3400 , -317.204  
3410 , -322.939  
3420 , -323.211  
3430 , -314.452

3440 , -314.715  
3450 , -318.16  
3460 , -317.704  
3470 , -312.159  
3480 , -314.835  
3490 , -332.331  
3500 , -313.702  
3510 , -323.622  
3520 , -326.591  
3530 , -322.356  
3540 , -307.168  
3550 , -330.914  
3560 , -321.649  
3570 , -336.089  
3580 , -316.466  
3590 , -310.182  
3600 , -315.277  
3610 , -327.437  
3620 , -313.87  
3630 , -329.137  
3640 , -315.723  
3650 , -326.567  
3660 , -318.393  
3670 , -335.543  
3680 , -327.214  
3690 , -304.879  
3700 , -307.926  
3710 , -319.007  
3720 , -328.946  
3730 , -299.473  
3740 , -329.565  
3750 , -326.425  
3760 , -316.243  
3770 , -328.38  
3780 , -309.189  
3790 , -321.845  
3800 , -323.453  
3810 , -336.454  
3820 , -332.319  
3830 , -322.471  
3840 , -300.823  
3850 , -319.282  
3860 , -335.776  
3870 , -328.51  
3880 , -328.618  
3890 , -318.295  
3900 , -319.672  
3910 , -316.68  
3920 , -324.384  
3930 , -337.475  
3940 , -315.955  
3950 , -322.078  
3960 , -322.97  
3970 , -325.329  
3980 , -325.232  
3990 , -328.381  
4000 , -325.541  
4010 , -319.714

4020 , -344.659  
4030 , -305.291  
4040 , -300.314  
4050 , -319.423  
4060 , -319.036  
4070 , -330.795  
4080 , -331.805  
4090 , -326.79  
4100 , -333.333  
4110 , -337.282  
4120 , -326.15  
4130 , -319.593  
4140 , -318.215  
4150 , -325.76  
4160 , -338.8  
4170 , -332.345  
4180 , -324.666  
4190 , -328.845  
4200 , -320.157  
4210 , -324.262  
4220 , -326.772  
4230 , -324.725  
4240 , -327.169  
4250 , -330.597  
4260 , -325.662  
4270 , -297.312  
4280 , -328.975  
4290 , -315.936  
4300 , -311.373  
4310 , -318.131  
4320 , -327.414  
4330 , -312.516  
4340 , -319.251  
4350 , -311.909  
4360 , -300.236  
4370 , -315.466  
4380 , -310.613  
4390 , -321.84  
4400 , -318.761  
4410 , -339.195  
4420 , -324.277  
4430 , -309.889  
4440 , -340.492  
4450 , -322.756  
4460 , -326.658  
4470 , -317.318  
4480 , -331.035  
4490 , -310.402  
4500 , -312.141  
4510 , -313.321  
4520 , -327.241  
4530 , -298.877  
4540 , -320.385  
4550 , -324.146  
4560 , -311.752  
4570 , -322.426  
4580 , -326.462  
4590 , -321.805

4600 , -321.311  
4610 , -306.519  
4620 , -312.769  
4630 , -310.266  
4640 , -313.355  
4650 , -308.741  
4660 , -316.299  
4670 , -338.852  
4680 , -324.007  
4690 , -320.777  
4700 , -313.165  
4710 , -322.947  
4720 , -310.734  
4730 , -336.596  
4740 , -322.296  
4750 , -324.317  
4760 , -309.447  
4770 , -322.352  
4780 , -316.689  
4790 , -309.386  
4800 , -323.088  
4810 , -326.757  
4820 , -327.324  
4830 , -331.247  
4840 , -322.676  
4850 , -320.505  
4860 , -323.335  
4870 , -312.847  
4880 , -331.581  
4890 , -323.574  
4900 , -317.768  
4910 , -316.373  
4920 , -330.117  
4930 , -311.988  
4940 , -313.174  
4950 , -323.659  
4960 , -309.58  
4970 , -319.506  
4980 , -310.046  
4990 , -320.015

## H Coordinate Data for Radial Distribution Function

```
Distance, Count
0.0342327,0
0.102698,0
0.171163,0
0.239629,0
0.308094,0
0.376559,0
0.445025,0
0.51349,0
0.581955,0
0.650421,0
0.718886,0
0.787351,0
0.855816,0.008
0.924282,5.976
0.992747,84.584
1.06121,176.592
1.12968,165.996
1.19814,124.368
1.26661,87.8
1.33507,64.512
1.40354,50.896
1.472,42.992
1.54047,37.944
1.60894,36.672
1.6774,38.844
1.74587,46.748
1.81433,62.52
1.8828,83.492
1.95126,107.344
2.01973,136.276
2.08819,161.74
2.15666,170.66
2.22512,166.336
2.29359,151.356
2.36205,135.208
2.43052,118.532
2.49898,104.54
2.56745,95.904
2.63591,93.412
2.70438,96.076
2.77285,106.436
2.84131,124.2
2.90978,144.912
2.97824,167.456
3.04671,184.116
3.11517,197.428
3.18364,201.716
3.2521,200.108
3.32057,196.276
3.38903,185.492
3.4575,176.668
3.52596,166.036
3.59443,158.572
3.66289,158.156
```

3.73136,162.052  
3.79983,171.988  
3.86829,184.216  
3.93676,199.156  
4.00522,214.02  
4.07369,227.796  
4.14215,237.984  
4.21062,243.44  
4.27908,242.64  
4.34755,243.044  
4.41601,236.32  
4.48448,229.684  
4.55294,225.824  
4.62141,221.632  
4.68987,223.368  
4.75834,224.688  
4.82681,231.296  
4.89527,238.796  
4.96374,252.164  
5.0322,261.592  
5.10067,273.54  
5.16913,281.856  
5.2376,289.836  
5.30606,293.288  
5.37453,290.768  
5.44299,287.42  
5.51146,283.296  
5.57992,282.252  
5.64839,281.572  
5.71685,283.084  
5.78532,284.688  
5.85378,287.992  
5.92225,295.82  
5.99072,306.308  
6.05918,313.044  
6.12765,322.408  
6.19611,327.804  
6.26458,332.32  
6.33304,337.744  
6.40151,342.128  
6.46997,340.144  
6.53844,339.692  
6.6069,337.132  
6.67537,341.34  
6.74383,343.184  
6.8123,343.836