

```
In [1]: # K-Nearest Neighbors (K-NN)

# Importing the libraries
import numpy as np
import matplotlib.pyplot as plt
import pandas as pd
```

```
In [4]: # Importing the dataset
dataset = pd.read_csv('Social_Network_Ads.csv')
X = dataset.iloc[:, [2, 3]].values
y = dataset.iloc[:, 4].values
```

```
In [6]: # Splitting the dataset into the Training set and Test set
from sklearn.model_selection import train_test_split

# Your code here...

X_train, X_test, y_train, y_test = train_test_split(X, y, test_size = 0.25, random_sta
```

```
In [7]: # Feature Scaling
from sklearn.preprocessing import StandardScaler
sc = StandardScaler()
X_train = sc.fit_transform(X_train)
X_test = sc.transform(X_test)
```

```
In [8]: # Fitting K-NN to the Training set
from sklearn.neighbors import KNeighborsClassifier
classifier = KNeighborsClassifier(n_neighbors = 5, metric = 'minkowski', p = 2)
classifier.fit(X_train, y_train)
```

```
Out[8]: KNeighborsClassifier()
```

```
In [11]: # Predicting the Test set results
import warnings
from sklearn.neighbors import KNeighborsClassifier
warnings.filterwarnings('ignore')

y_pred = classifier.predict(X_test)
```

```
In [12]: # Making the Confusion Matrix
from sklearn.metrics import confusion_matrix
cm = confusion_matrix(y_test, y_pred)
```

```
In [15]: # Visualising the Training set results

from matplotlib.colors import ListedColormap
X_set, y_set = X_train, y_train
X1, X2 = np.meshgrid(np.arange(start = X_set[:, 0].min() - 1, stop = X_set[:, 0].max() + 1,
                             step = 0.5),
                     np.arange(start = X_set[:, 1].min() - 1, stop = X_set[:, 1].max() + 1,
                             step = 0.5))
plt.contourf(X1, X2, classifier.predict(np.array([X1.ravel(), X2.ravel()]).T).reshape(X1.shape),
             alpha = 0.75, cmap = ListedColormap(('red', 'green')))
plt.xlim(X1.min(), X1.max())
plt.ylim(X2.min(), X2.max())
for i, j in enumerate(np.unique(y_set)):
    plt.scatter(X_set[y_set == j, 0], X_set[y_set == j, 1],
```


```

        c = ListedColormap(('red', 'green'))(i), label = j)
plt.title('K-NN (Training set)')
plt.xlabel('Age')
plt.ylabel('Estimated Salary')
plt.legend()
plt.show()

```

\*c\* argument looks like a single numeric RGB or RGBA sequence, which should be avoided as value-mapping will have precedence in case its length matches with \*x\* & \*y\*. Please use the \*color\* keyword-argument or provide a 2D array with a single row if you intend to specify the same RGB or RGBA value for all points.

\*c\* argument looks like a single numeric RGB or RGBA sequence, which should be avoided as value-mapping will have precedence in case its length matches with \*x\* & \*y\*. Please use the \*color\* keyword-argument or provide a 2D array with a single row if you intend to specify the same RGB or RGBA value for all points.



```


In [16]: # Visualising the Test set results
from matplotlib.colors import ListedColormap
X_set, y_set = X_test, y_test
X1, X2 = np.meshgrid(np.arange(start = X_set[:, 0].min() - 1, stop = X_set[:, 0].max() + 1,
                             step = 0.5),
                     np.arange(start = X_set[:, 1].min() - 1, stop = X_set[:, 1].max() + 1,
                             step = 0.5))
plt.contourf(X1, X2, classifier.predict(np.array([X1.ravel(), X2.ravel()]).T).reshape(X1.shape),
             alpha = 0.75, cmap = ListedColormap(('red', 'green')))
plt.xlim(X1.min(), X1.max())
plt.ylim(X2.min(), X2.max())
for i, j in enumerate(np.unique(y_set)):
    plt.scatter(X_set[y_set == j, 0], X_set[y_set == j, 1],
                c = ListedColormap(('red', 'green'))(i), label = j)
plt.title('K-NN (Test set)')
plt.xlabel('Age')
plt.ylabel('Estimated Salary')

```

```
plt.legend()  
plt.show()
```

\*c\* argument looks like a single numeric RGB or RGBA sequence, which should be avoided as value-mapping will have precedence in case its length matches with \*x\* & \*y\*. Please use the \*color\* keyword-argument or provide a 2D array with a single row if you intend to specify the same RGB or RGBA value for all points.

\*c\* argument looks like a single numeric RGB or RGBA sequence, which should be avoided as value-mapping will have precedence in case its length matches with \*x\* & \*y\*. Please use the \*color\* keyword-argument or provide a 2D array with a single row if you intend to specify the same RGB or RGBA value for all points.



In [ ]: