

Product Overview :

Ceramic fiber paper is a lightweight, flexible, and high-performance insulation material. Designed to withstand extremely high temperatures, ceramic fiber paper provides excellent thermal insulation and is particularly suitable for applications where space constraints require thin insulation layers. It is used across various industries, including aerospace, automotive, and industrial manufacturing, for its outstanding thermal properties and ease of use.



Key Points :

High-Temperature Resistance: Ceramic fiber paper can withstand temperatures up to 1427°C (2600°F), making it ideal for extreme heat environments.

Low Thermal Conductivity: The paper's low thermal conductivity ensures efficient insulation, minimizing heat loss and enhancing energy efficiency in industrial applications.

Flexibility and Ease of Use: Its flexible nature allows for easy installation, cutting, and shaping, making it suitable for wrapping and gasketing in tight or irregular spaces.

Lightweight: Despite its robust thermal properties, ceramic fiber paper is lightweight, facilitating easy handling and installation.

Applications:

Gasketing and Sealing: Ideal for creating seals in heating equipment, offering both flexibility and durability in high-temperature environments.

Electrical Insulation: Serves as an insulating layer in electrical appliances, protecting against heat and ensuring operational safety.

Automotive Exhaust Systems: Used in exhaust wraps and heat shields, offering thermal protection and preventing heat transfer to sensitive parts.

Aerospace: Used to wrap sensitive components, protecting them from heat in extreme environments.



Advantages:

Energy Efficiency: Reduces heat loss significantly, contributing to lower energy consumption in high-temperature processes.

Durability: Withstands repeated thermal cycling and chemical exposure, ensuring long service life.

Safety and Environmental Compliance: Manufactured without harmful substances, making it safe for use in diverse industrial settings.

Technical Specifications:

Temperature : 1260°C(2300°F) and 1425°C(2597°F)

Width: Standard widths include 500mm for sheet and 1000mm for roll, with custom sizes available upon request.

Thickness: Available in thicknesses ranging from 1mm to 6mm, accommodating various application needs.

TECHNICAL SPECIFICATIONS :

<i>Chemical Analysis</i>	<i>1425°C</i>	<i>1260°C</i>
Al ₂ O ₃ (%)	30 - 34	42 - 46
SiO ₂ (%)	50 - 55	54 - 58
ZrO ₂ (%)	14 -18	-
Fe ₂ O ₃ +TiO ₂ (%)	< 0.5	< 0.5
Loss On Ignition (Wt. %)	< 10	< 10

<i>Physical Properties</i>		
Color	White	White
Classification Temperature (°C)	1425	1260
Density (kg/m ³)	150 - 250	150 - 250
Paper Type	DS	DS
Melting Point (°C)	> 1760	> 1760
Tensile Strength (kPa)	> 300	> 300

<i>Thermal Conductivity , ASTM C-177 (W/MK)</i>		
400°C	0.06	0.06
600°C	0.08	0.08
800°C	0.11	0.11
1000°C	0.17	0.17

Thermal Conductivity figures are empirical values (average) based on experience.

<i>Linear Shrinkage (%) For 24 Hrs</i>		
1250°C	-	< 4.0
1400°C	< 4.0	-

For Specification Add 0.5% To Above Shrinkage Value.

Classification temperature refers to the maximum short term temperature limit. The maximum continuous use limit depends upon application conditions. For certain applications continuous use temperature limits may be significantly reduced. For assistance or clarification please contact us at email or office.

AVAILABILITY :

Thickness (mm)	Sheet Size (mm)	Sheet Size (mm)	Sheets Per Carton
2	30000 x 1000	1000 x 500	70
3	20000 x 1000	1000 x 500	50
5	12000 x 1000	1000 x 500	30

Other thicknesses / sizes may be available on request subject to minimum order requirement.

HANDLING INFORMATION

A Material Safety Data Sheet Has Been Issued Describing The Health, Safety And Environmental Properties Of This Product, Identifying The Potential Hazards And Giving Advice On Handling Precautions And Emergency Procedures. This Must Be Consulted And Fully Understood Before Handling, Storage Or Use.

Supplied by :

All data represents typical result of standard tests conducted under controlled condition. As Such, the information is intended only as a general guide for specifications and design estimates.

Information contained in this publication is for illustrative purposes only and is not intended to create any contractual obligation. Further information and advice on specific details of the products described should be obtained in writing from a Orient company. Orient maintains a continuous programme of product development and reserves the right to change product specifications without prior notice. Therefore, it maintains at all times the responsibility of the customer to ensure that Orient materials are suitable for the particular purpose intended. Similarly, insofar as materials not manufactured nor supplied by Orient are used in conjunction with or instead of Orient materials, the customer should ensure that all technical data and other information relating to such materials has been obtained from the manufacturer or supplier. Orient accepts no liability arising from the use of such materials. All sales made by a Orient company are subject to that company's Terms and Conditions of Sale, copies of which are available on request.