

Product Overview :

Ceramic fiber bulk is a versatile insulation material composed of high-purity aluminosilicate fibers. Produced through a fiberization process, this material provides exceptional thermal resistance, making it ideal for a wide range of high-temperature applications. Ceramic fiber bulk is commonly used as a raw material for the production of other ceramic fiber products like blankets, boards, and paper. Its lightweight nature, combined with low thermal conductivity and excellent resistance to thermal shock, makes it a crucial component in industries requiring efficient heat management.



Key Points :

Customizable Insulation: Due to its loose and fluffy nature, ceramic fiber bulk can be easily packed or layered to provide precise thermal insulation, conforming to complex geometries.

Excellent Acoustic Dampening: Beyond thermal insulation, ceramic fiber bulk effectively reduces sound transmission, making it suitable for environments requiring both thermal and acoustic control.

Non-Combustible: Offers superior fire resistance, making it a safe choice for high-risk areas where fire safety is a concern.

Versatile Application: Ideal for filling expansion joints, insulating around pipes, or as a loose fill in high-temperature areas where traditional rigid insulations are not suitable.

Applications:

Furnace Expansion Joints: Used to fill and insulate gaps in expansion joints, accommodating thermal expansion while preventing heat loss.

Pipe Insulation: Suitable for insulating around complex piping systems, especially in high-temperature environments where traditional insulation is difficult to apply.

Flexible Moldable Insulation: Can be used to form flexible, moldable insulation pads or wraps for components that experience temperature fluctuations.



Advantages:

Highly Flexible: Unlike rigid insulation materials, ceramic fiber bulk can be easily shaped and packed into irregular spaces, providing tailored insulation solutions.

Cost-Effective: Offers a cost-efficient solution for filling large spaces or gaps where precision insulation is required.

Lightweight: Easy to handle and apply, reducing labor costs and installation time.

Non-Toxic and Environmentally Safe: Free from asbestos and other harmful substances, ensuring a safe working environment and compliance with environmental regulations.

Technical Specifications:

Temperature : 1260°C(2300°F) and 1425°C(2597°F)

TECHNICAL SPECIFICATIONS :

<i>Chemical Analysis</i>	<i>1260°C</i>	<i>1425°C</i>
Al ₂ O ₃ (%)	42 - 47	30 - 34
SiO ₂ (%)	53 - 58	50 - 54
ZrO ₂ (%)	-	14 - 18
Fe ₂ O ₃ (%)	< 0.1	< 0.1
TiO ₂ (%)	< 0.3	< 0.3
Leachable Chlorides, ppm	< 10	< 10
<i>Physical Properties</i>		
Color	White	White
Classification Temperature (°C)	1260	1425
Melting Point (°C)	1760	1760
Shot Content By Wt. (%)	8 - 14	10 - 15
Specific Gravity	2.65	2.65
Mean Fiber Dia (M)	2.6 to 3.4	2.6 to 3.4
Fiber Index (%)	48 min	48 min

Classification temperature refers to the maximum short term temperature limit. The maximum continuous use limit depends upon application conditions. For certain applications continuous use temperature limits may be significantly reduced. For assistance or clarification please contact us at email or office.

AVAILABILITY :

Orwool® Bulk Fibers Are Available As Standard In 20kg HDPE Bags. Other Sizes Available On Request Subject To Minimum Order Requirements

HANDLING INFORMATION

A Material Safety Data Sheet Has Been Issued Describing The Health, Safety And Environmental Properties Of This Product, Identifying The Potential Hazards And Giving Advice On Handling Precautions And Emergency Procedures. This Must Be Consulted And Fully Understood Before Handling, Storage Or Use.

Supplied by :

All data represents typical result of standard tests conducted under controlled condition. As Such, the information is intended only as a general guide for specifications and design estimates.

Information contained in this publication is for illustrative purposes only and is not intended to create any contractual obligation.

Further information and advice on specific details of the products described should be obtained in writing from a Orient company. Orient maintains a continuous programme of product development and reserves the right to change product specifications without prior notice. Therefore, it maintains at all times the responsibility of the customer to ensure that Orient materials are suitable for the particular purpose intended. Similarly, insofar as materials not manufactured nor supplied by Orient are used in conjunction with or instead of Orient materials, the customer should ensure that all technical data and other information relating to such materials has been obtained from the manufacturer or supplier. Orient accepts no liability arising from the use of such materials. All sales made by a Orient company are subject to that company's Terms and Conditions of Sale, copies of which are available on request.