

## Question 2 [5 Marks]

A relational schema for a train reservation database is given below.

Passenger (pid, pname, age)

Reservation (pid, class, tid)

**Table: Passenger**

pid	pname	age
-----	-------	-----

-----		
-------	--	--

0	Sachin	65
---	--------	----

1	Rahul	66
---	-------	----

2	Sourav	67
---	--------	----

3	Anil	69
---	------	----

**Table : Reservation**

pid	class	tid
-----	-------	-----

-----		
-------	--	--

0	AC	8200
---	----	------

1	AC	8201
---	----	------

2	SC	8201
---	----	------

5	AC	8203
---	----	------

1	SC	8204
---	----	------

3	AC	8202
---	----	------

What pids are returned by the following SQL query for the above instance of the tables?

```
SELECT pid
```

```
FROM Reservation ,
```

```
WHERE class 'AC' AND
```

```
EXISTS (SELECT *
```

```
FROM Passenger
```

```
WHERE age > 65 AND
```

```
Passenger. pid = Reservation.pid)
```

- ☐ A 1, 0
- ☐ B 1, 2
- ☒ C 1, 3
- ☐ D 1, 5

#### Explanation

When a subquery uses values from outer query, the subquery is called correlated subquery. The correlated subquery is evaluated once for each row processed by the outer query.

The outer query selects 4 entries (with pids as 0, 1, 5, 3) from Reservation table. Out of these selected entries, the subquery returns Non-Null values only for 1 and 3.