

SET

Recruitment Entrance Test for Scientist/Engineer 'SC' 2017

1. If A is a skew symmetric matrix, then A^t

(a) diagonal matrix

(b) *A*

(c) (

(d) -A

2. If *A* and *B* be two arbitrary events, then

- (a) $P(A \cap B) = P(A)P(B)$
- (b) $P(A \cup B) = P(A) + P(B)$
- (c) $P(A/B) = P(A \cap B) + P(B)$
- (d) $P(A \cup B) \le P(A) + P(B)$

3. Using Newton-Raphson method, a root correct to 3 decimal places of the equation $x^3 - 3x - 5 = 0$

(a) 2.222

(b) 2.275

(c) 2.279

(d) None of the above

4. What does the data dictionary identify?

(a) Field names

(b) Field formats

(c) Field Types

(d) All of these

5. Which of the following concurrency control protocol ensures both conflict serializability and free from deadlock?

- (a) Time stamp ordering
- (b) 2 Phase locking

(c) Both (a) and (b)

(d) None of the above

6. ACID properties of a transactions are

- (a) Atomicity, consistency, isolation, database
- (b) Atomicity, consistency, isolation, durability
- (c) Atomicity, consistency, integrity, durability
- (d) Atomicity, consistency, integrity, database
- 7. Database table by name Overtime_allowance is given below:



SET A

Recruitment Entrance Test for Scientist/Engineer 'SC' 2017

Employee	Department	OT_allowance
RAMA	Mechanical	5000
GOPI	Electrical	2000
SINDHU Computer		4000
MAHESH	Civil	1500

What is the output of the following SQL query?

select count(*) from ((select Employee, Department from Overtime_allowance) as S natural join (select Department, OT_allowance from Overtime_allowance) as T);

(a) 16

(b) 4

(c) 8

(d) None of the above

8. Which symbol denote derived attributes in ER Model?

- (a) Double ellipse
- (b) Dashed ellipse
- (c) Squared ellipse
- (d) Ellipse with attribute name underlined

9. The symmetric difference of sets $A = \{1, 2, 3, 4, 5, 6, 7, 8\}$ and $B = \{1, 3, 5, 6, 7, 8, 9\}$ is

(a) $\{1, 3, 5, 6, 7, 8\}$

(b) $\{2, 4, 9\}$

(c) {2, 4}

 $(d) \quad \{1,\,2,\,3,\,4,\,5,\,6,\,7,\,8,\,9\}$

10. The problems 3-SAT and 2-SAT are

- (a) Both NP-complete
- (b) Both in P
- (c) NP-complete and in P, respectively
- (d) Undecidable and NP-complete, respectively

11. Given the following statements



SET A

Recruitment Entrance Test for Scientist/Engineer 'SC' 2017

S1: Every context-sensitive language L is recursive

S2: There exists a recursive language that is not context-sensitive

Which statements are true?

(a) Only S1 is correct

- (b) Only S2 is correct
- (c) Both S1 and S2 are not correct
- (d) Both S1 and S2 are correct
- **12.** Which one of the following is FALSE?
 - (a) There is a unique minimal DFA for every regular language
 - (b) Every NFA can be converted to an equivalent PDA
 - (c) Compliment of every context-free language is recursive
 - (d) Every non-deterministic PDA can be converted to an equivalent deterministic PDA
- 13. In some programming languages, an identifier is permitted to be a letter followed by any number of letters or digits. If L and D denotes the set of letters and digit respectively. Which of the following expression defines an identifier?
 - (a) $(L+D)^*$

(b) (L.D)*

(c) L(L+D)*

- (d) L(L.D)*
- 14. The recurrence relation that arises in relation with the complexity of binary search is
 - (a) T(n) = 2T(n/2) + k, where k is constant
 - (b) T(n) = T(n/2) + k, where k is constant
 - (c) $T(n) = T(n/2) + \log n$
 - (d) T(n) = T(n/2) + n
- **15.** Which one of the following in-place sorting algorithms needs the minimum number of swaps?
 - (a) Insertion Sort

(b) Quick Sort

(c) Heap Sort

(d) Selection Sort

16. Given two statements



SET A

Recruitment Entrance Test for Scientist/Engineer 'SC' 2017

(i) Insertion of an element should be done at the last node in a circular list

(ii) Deletion of an element should be done at the last node of the circular list

(a) Both are true

(b) Both are false

(c) First is false and second is true

(d) None of the above

17. Which of the following data structure is useful in traversing a given graph by breadth first search?

(a) Stack

(b) Queue

(c) List

(d) None of the above

18. How many 128×8 bit RAMs are required to design $32K \times 32$ bit RAM?

(a) 512

(b) 1024

(c) 128

(d) 32

19. The most appropriate matching for the following pairs:

X: Indirect Addressing

1. Loop

Y: Immediate Addressing

2. Pointers

Z : Auto Decrement Addressing

3. Constants

(a) X-3, Y-2, Z-1

(b) X-2, Y-3, Z-1

(c) X-3, Y-1, Z-2

(d) X-2, Y-1, Z-3

20. Which interrupt in 8085 Microprocessor is unmaskable?

(a) RST 5.5

(b) RST 7.5

(c) TRAP

(d) Both (a) and (b)

21. A cache memory needs an access time of 30 ns and main memory 150 ns, what is the average access time of CPU (assume hit ratio = 80%)?

(a) 60 ns

(b) 30 ns

(c) 150 ns

(d) 70 ns



SET

Recruitment Entrance Test for Scientist/Engineer 'SC' 2017

22. Which one of the following Boolean expressions is NOT a tautology?

(a)
$$((a \rightarrow b) \land (b \rightarrow c)) \rightarrow (a \rightarrow c)$$

(b)
$$(a \leftrightarrow c) \rightarrow (\sim b \rightarrow (a \land c))$$

(c)
$$(a \land b \land c) \rightarrow (c \lor a)$$

(d)
$$a \rightarrow (b \rightarrow a)$$

23. What is the minimum number of two-input NAND gates used to perform the function of two input OR gate?

(a) One

(b) Two

(c) Three

(d) Four

24. When two n-bit binary numbers are added the sum will contain at the most

(a) n bits

(b) (n+3) bits

(c) (n+2) bits

(d) (n+1) bits

25. The 2-input XOR has a high output only when the input values are

(a) low

(b) high

(c) same

(d) different

26. Advantage of synchronous sequential circuits over asynchronous one is

- (a) Lower hardware requirement
- (b) Better noise immunity

(c) Faster operation

(d) All of the above

27. Physical topology of FDDI is?

(a) Bus

(b) Ring

(c) Star

(d) None of the above

28. In networking terminology UTP means

- (a) Uniquitous teflon port
- (b) Uniformly terminating port
- (c) Unshielded twisted pair
- (d) Unshielded T-connector port

29. The default subnet mask for a class B network can be

(a) 255.255.255.0

(b) 255.0.0.0

(c) 255.255.192.0

(d) 255.255.0.0



Recruitment Entrance Test for Scientist/Engineer 'SC' 2017

30.	If there are n devices (nodes) in a network, what is the number of cable links required
	for a fully connected mesh and a star topology respectively

(a) n(n-1)/2, n-1

(b) n, n-1

(c) n-1, n

(d) n-1, n(n-1)/2

31. Which of the following protocol is used for transferring electronic mail messages from one machine to another?

(a) TELNET

(b) FTP

(c) SNMP

(d) SMTP

32. Which media access control protocol is used by IEEE 802.11 wireless LAN?

(a) CDMA

(b) CSMA/CA

(c) ALOHA

(d) None of the above

33. An Ethernet frame that is less than the IEEE 802.3 minimum length of 64 octets is called

(a) Short frame

(b) Small frame

(c) Mini frame

(d) Runt frame

34. Match with the suitable one:

List-I

List-II

(A) Multicast group membership

1. Distance vector routing

(B) Interior gateway protocol

2. IGMP

(C) Exterior gateway protocol

3. OSPF

(D) RIP

4. BGP

(a) A-2, B-3, C-4, D-1

(b) A-2, B-4, C-3, D-1

(c) A-3, B-4, C-1, D-2

(d) A-3, B-1, C-4, D-2

35. MD5 is a widely used hash function for producing hash value of

(a) 64 bits

(b) 128 bits

(c) 512 bits

(d) 1024 bits



SET

Recruitment Entrance Test for Scientist/Engineer 'SC' 2017

- **36.** Which protocol suite designed by IETF to provide security for a packet at the Internet layer?
 - (a) **IPsec**

NetSec (b)

PacketSec (c)

(d) SSL

- **37.** Pretty Good Privacy (PGP) is used in
 - Browser security

(b) FTP security

(c) **Email security** (d) None of the above

- **38.** What is WPA?
 - wired protected access (a)

wi-fi protected access (b)

(c) wired process access

- (d) wi-fi process access
- Estimation of software development effort for organic software in basic COCOMO is
 - $E = 2.0(KLOC)^{1.05}PM$

 $E = 3.4(KLOC)^{1.06}PM$ (b)

 $E = 2.4(KLOC)^{1.05}PM$ (c)

- $E = 2.4(KLOC)^{1.07}PM$ (d)
- **40.** XPath is used to navigate through elements and attributes in
 - XSL document (a)

XML document (b)

(c) XHTML document

- XQuery document (d)
- **41.** What is the output of this C++ program?

```
#include <iostream>
using namespace std:
void square (int *x)
      *_{X} = (*_{X}) + + * (*_{X});
void square (int *x, int *y)
      *_{X} = (*_{X}) * --(*_{V});
int main ()
      int number = 30;
      cout << number;</pre>
      return 0;
```

square(&number, &number);

(a) 910 (b) 920

(c) 870 (d) 900



SET A

Recruitment Entrance Test for Scientist/Engineer 'SC' 2017

- **42.** Which of the following operator(s) cannot be overloaded?
 - (a) . (Member Access or Dot operator)
 - (b) ?: (Ternary or Conditional Operator)
 - (c) :: (Scope Resolution Operator)
 - (d) All of the above
- **43.** Which of the following UML 2.0 diagrams capture behavioural aspects of a system?
 - (a) Use Case Diagram, Object Diagram, Activity Diagram, and State Machine Diagram
 - (b) Use Case Diagram, Activity Diagram, and State Machine Diagram
 - (c) Object Diagram, Communication Diagram, Timing Diagram, and Interaction diagram
 - (d) Object Diagram, Composite Structure Diagram, Package Diagram, and Deployment Diagram
- **44.** Which of the following is associated with objects?
 - (a) State

(b) Behavior

(c) Identity

- (d) All of the above
- **45.** Which one of these is characteristic of RAID 5?
 - (a) Dedicated parity

(b) Double parity

(c) Hamming code parity

- (d) Distributed parity
- **46.** SATA is the abbreviation of
 - (a) Serial Advanced Technology Attachment
 - (b) Serial Advanced Technology Architecture
 - (c) Serial Advanced Technology Adapter
 - (d) Serial Advanced Technology Array
- **47.** Capability Maturity Model (CMM) is a methodology to
 - (a) develop and refine an organization's software development process
 - (b) develop the software
 - (c) test the software
 - (d) all of the above

- 48. What problem is solved by Dijkstra banker's algorithm?
 - (a) Mutual exclusion

(b) Deadlock recovery


(c) Deadlock avoidance

- (d) Cache coherence
- **49.** The number of swappings needed to sort the numbers 8, 22, 7, 9, 31, 5, 13 in ascending order, using bubble sort is
 - (a) 11

(b) 12

(c) 13

- (d) 10
- **50.** Consider the following tree



If the post order traversal gives ab-cd*+ then the label of the nodes 1,2,3,... will be

(a) +,-,*,a,b,c,d

(b) a,-,b,+,c,*,d

(c) a,b,c,d,-,*,+

- (d) -,a,b,+,*,c,d
- **51.** What is the output of the following program?

```
main()
{
    int a = 10;
    if ((fork () == 0))
        a++;
    printf ("%d\n", a );
}
```

(a) 10 and 11

(b) 10

(c) 11

(d) 11 and 11



SET

Recruitment Entrance Test for Scientist/Engineer 'SC' 2017

52. Given reference to the following pages by a program

How many page faults will occur if the program has three page frames available to it and uses an optimal replacement?

(a) 7

(b) 8

(c) 9

- (d) None of these
- **53.** In a doubly linked list, the number of pointers affected for an insertion operation will be
 - (a) 4
 - (b) 0
 - (c) 1
 - (d) Depends upon the nodes of the doubly linked list
- **54.** Consider the following C function

```
void swap ( int x, int y )
{
  int tmp;
  tmp = x;
  x= y;
  y = tmp;
}
```

In order to exchange the values of two variables a and b:

- (a) Call swap (a, b)
- (b) Call swap (&a, &b)
- (c) swap(a, b) cannot be used as it does not return any value
- (d) swap(a, b) cannot be used as the parameters passed by value



SET A

Recruitment Entrance Test for Scientist/Engineer 'SC' 2017


55.	What does the following C-statement declare? int (*f) (int*);							
	(a)	A function that takes an integer pointer as argument and returns an integer						
	(b)	A function that takes an integer as argument and returns an integer pointer						
	(c)	A pointer to a function that takes an integer pointer as argument and returns an integer						
	(d)	A function that takes an integer pointer	ointer	as argument and returns a function				
56.	Mutual exclusion problem occurs							
	(a)	Between two disjoint processes that do not interact						
	(b)	Among processes that share resources						
	(c)	Among processes that do not use the same resource						
	(d)	Between two processes that uses different resources of different machine						
57.	(121	$(217)_8$ is equivalent to						
	(a)	$(1217)_{16}$	(b)	$(028F)_{16}$				
	(c)	$(2297)_{10}$	(d)	$(0B17)_{16}$				
58.	Wh	Which of the following is not a life cycle model?						
	(a)	Spiral model	(b)	Prototyping model				
	(c)	Waterfall model	(d)	Capability maturity model				
59.	The best data structure to check whether an arithmetic expression has balanced parenthesis is a							
	(a)	Queue	(b)	Stack				
	(c)	Tree	(d)	List				



SET

Recruitment Entrance Test for Scientist/Engineer 'SC' 2017

60. The cyclomatic complexity of each of the modules X and Y shown below is 10. What is the cyclomatic complexity of the sequential integration shown on the right hand side?



- (a) 21
- (c) 20

- (b) 19
- (d) 10
- **61.** In software maintenance tackling the changes in the hardware or software environment where the software works, is
 - (a) Corrective maintenance
- (b) Perfective maintenance
- (c) Adaptive maintenance
- (d) Preventive maintenance
- **62.** What will be the output of the following C code?

```
#include <stdio.h>
main()
{
  int i;
  for ( i=0; i<5; i++)
  {
    int i = 10;
    printf (" %d", i );
    i++;
}
return 0;
}</pre>
```

(a) 10 11 12 13 14

(b) 10 10 10 10 10

(c) 0 1 2 3 4

(d) Compilation error



SET A

Recruitment Entrance Test for Scientist/Engineer 'SC' 2017

63. What does the following program do when the input is unsigned 16-bit integer? #include <stdio.h>

```
main()
{
    unsigned int num;
    int i;
    scanf ("%u", &num);
    for ( i = 0; i<16; i++)
    {
        printf ("%d", (num << i & 1 << 15 ) ? 1:0);
     }
}</pre>
```

- (a) It prints all even bits from num
- (b) It prints all odd bits from num
- (c) It prints binary equivalent of num (d) None of the above
- **64.** What is the output of the following program?

```
#include <stdio.h>
int tmp=20;
main()
{
    printf("%d ",tmp);
    func();
    printf("%d ",tmp);
}
func()
{
    static int tmp=10;
    printf("%d ",tmp);
}
```

(a) 20 10 10

(b) 20 10 20

(c) 20 20 20

(d) 10 10 10



SET A

Recruitment Entrance Test for Scientist/Engineer 'SC' 2017

- **65.** Which product metric gives the measure of the average length of words and sentence in documents?
 - (a) SCI number

(b) Cyclomatic complexity

(c) LOC

- (d) Fog index
- **66.** Consider a disk system with 100 cylinders. The request to access the cylinders occur in the following sequences

4, 37, 10, 7, 19, 73, 2, 15, 6, 20

Assuming the head is currently at cylinder 50, what is the time taken to satisfy all requests if it takes 1 ms to move from one cylinder to adjacent one and shortest seek time first algorithm is used

(a) 95 ms

(b) 119 ms

(c) 233 ms

- (d) 276 ms
- 67. A B-Tree used as an index for a large database table has four levels including the root node. If a new key is inserted in this index, then the maximum number of nodes that could be newly created in the process are
 - (a) 5

(b) 4

(c) 1

(d) 2

- 68. A critical region
 - (a) is a piece of code which only one process executes at a time
 - (b) is a region prone to deadlock
 - (c) is a piece of code which only a finite number of processes execute
 - (d) is found only in windows NT operating system
- 69. Choose the equivalent prefix form of the following expression

$$(a + (b-c))*((d-e)/(f+g-h))$$

(a)
$$*+a-bc/-de-+fgh$$

(b)
$$*+a-bc-/de-+fgh$$

(c)
$$*+a-bc/-ed+-fgh$$

(d)
$$*+ab-c/-ed+-fgh$$



SET A

Recruitment Entrance Test for Scientist/Engineer 'SC' 2017

70.	We use malloc and calloc for						
	(a)) Dynamic memory allocation					
	(b)	Static memory allocation					
	(c)	Both dynamic and static memory allocation					
	(d)	None of the above					
71.	At p	At particular time, the value of a counting semaphore is 10, it will become 7 after					
	(a)	3 V operations	(b)	3 P operations			
	(c)	5 V operations and 2 P operations	(d)	2 V operations and 5 P operations			
72.	The	The linux command "mknod myfifo b 4 16"					
	r is root						
	er is root						
	(c) Will create a block device if the user is root						
	(d)	None of the above					
73.	3. Which of the following statement is true?						
	(a) Hard real time OS has less jitter than soft real time OS(b) Hard real time OS has more jitter than soft real time OS(c) Hard real time OS has equal jitter as soft real time OS						
	(d)	(d) None of the above					
74.	. Which of these is a super class of all errors and exceptions in the Java lang						
	(a)	RunTime Exceptions	(b)	Throwable			
	(c)	Catchable	(d)	None of the above			
75 .	Cho	Choose the most appropriate HTML tag in the following to create a numbered lists.					
	(a)	<dl></dl>	(b)	t>			
	(c)		(d)	<_0]>			



SET

Recruitment Entrance Test for Scientist/Engineer 'SC' 2017

76. Which of the following algorithm solves the all-pair shortest path problem?

- (a) Prim's algorithm
- (b) Dijikstra's algorithm
- (c) Bellman-Ford's algorithm
- (d) Floyd-Warshall's algorithm

77. If L and P are two recursively enumerable languages, then they are not closed under

- (a) Kleene Star L * of L
- (b) Intersection $L \cap P$

(c) Union $L \cup P$

(d) Set difference

78. In the context of modular software design, which one of the following combinations is desirable?

- (a) High cohesion and high coupling
- (b) High cohesion and low coupling
- (c) Low cohesion and high coupling
- (d) Low cohesion and low coupling

79. The output of a lexical analyzer is

(a) A parse tree

(b) Intermediate code

(c) Machine code

(d) A stream of tokens

80. The time complexity of computing the transitive closure of a binary relation on a set of *n* elements is known to be

(a) $O(n \log n)$

(b) $O(n^{3/2})$

(c) $O(n^3)$

(d) O(n)

~ इसरो **is**ro

INDIAN SPACE RESEARCH ORGANISATION

SET A

Recruitment Entrance Test for Scientist/Engineer 'SC' 2017

Space for rough work

-इसरो **isro**

INDIAN SPACE RESEARCH ORGANISATION

SET A

Recruitment Entrance Test for Scientist/Engineer 'SC' 2017

Space for rough work